

Analyzing the Utah Bikeways data

Comparing the bikeways by type with the highway mileage for each city

Pukar Bhandari
Wasatch Front Regional Council
pukar.bhandari@wfrc.utah.gov

2025-11-16

Table of contents

1	Introduction	1
2	Setup Environment	2
2.1	Install Packages	2
2.2	Load Packages	2
2.3	Environment Variables	2
3	Read Data from UGRC	3
3.1	Utah City Boundaries	3
3.2	Utah County Boundaries	4
3.3	Utah Roadways	5
3.4	Utah Bikeways	6
4	Road Lane Miles by Municipality	7
4.1	Add Unincorporated Areas	7
4.2	Calculate Lane Miles	8
4.3	Aggregate by Municipality	9
5	Bikeway Miles by Municipality	10
5.1	Reclassify Bikeway Types to Categories	10
5.2	Calculate Bikeway Lane Miles by Facility Type	11
6	Combine dataframes	14
6.1	Create Multimodal Summary	14
7	Export Final results	18
8	Conclusion	18

1 Introduction

This analysis examines the distribution of roadway and bikeway infrastructure across Utah municipalities. The primary objectives are to:

1. Calculate total road lane miles for each municipality

2. Calculate bikeway lane miles by facility type for each municipality
3. Compare roadway and bikeway infrastructure across municipalities

All spatial data is sourced from the Utah Geospatial Resource Center (UGRC) and processed using the R spatial ecosystem.

2 Setup Environment

2.1 Install Packages

The following packages are required for this analysis. Install them if not already available in your R environment.

```
install.packages("dplyr")
install.packages("tidyr")
install.packages("readr")
install.packages("stringr")
install.packages("forcats")
install.packages("fs")
install.packages("sf")
install.packages("arcgislayers")
install.packages("janitor")
install.packages("units")
install.packages("tmap")
```

2.2 Load Packages

```
library(dplyr) # for data manipulation
library(tidyr) # for tidy data operations (pivot functions)
library(readr) # read and write tabular data
library(stringr) # manipulate strings
library(forcats) # process categorical data
library(fs) # for file system management
library(sf) # for simple feature geometries
library(arcgislayers) # to read arcgis rest services
library(janitor) # clean column names
library(units) # set and adjust units of measurement
library(tmap) # view sf objects
```

2.3 Environment Variables

We use EPSG:3566 (NAD83(HARN) / Utah North) projection, which uses US survey feet as the base unit. This projection is appropriate for statewide analysis in Utah and ensures accurate distance calculations.

```
# Set Project CRS
PROJECT_CRS = "EPSG:3566"

# Set tmap mode to interactive
tmap::tmap_mode("view")
```

3 Read Data from UGRC

All spatial datasets are downloaded from UGRC's ArcGIS REST services. To improve performance and enable offline work, the data is cached locally as GeoDatabase files. The code checks if local copies exist before downloading.

```
# set data folder
dir_data <- "_data"
fs::dir_create(dir_data) # Create a directory if it doesnt exist
```

3.1 Utah City Boundaries

Municipal boundaries are used to aggregate roadway and bikeway data by city. These boundaries represent the legal limits of incorporated municipalities in Utah.

```
# Define paths
path_ut_cities <- file.path(dir_data, "UtahMunicipalBoundaries.gpkg")

# Download if not exists
if (!fs::file_exists(path_ut_cities)) {
  # Read data using arcgis package
  sf_ut_cities <- arcgislayers::arc_read(
    "https://services1.arcgis.com/99lidPhWCzftIe9K/ArcGIS/rest/services/UtahMunicipalBoundaries/FeatureServer/0",
    crs = PROJECT_CRS
  ) |> janitor::clean_names()
  # Write to a GeoDatabase
  sf_ut_cities |>
    sf::st_write(path_ut_cities, layer = "UtahMunicipalBoundaries", append = FALSE)
} else {
  # Read from local copy
  sf_ut_cities <- sf::st_read(path_ut_cities) |>
    sf::st_transform(PROJECT_CRS)
}
```

```

Reading layer `UtahMunicipalBoundaries' from data source
  `C:\Users\Pukar.Bhandari\Documents\GitHub\ar-puuk.github.io\posts\utah-
bikeways\_data\UtahMunicipalBoundaries.gpkg'
  using driver `GPKG'
Simple feature collection with 261 features and 18 fields
Geometry type: POLYGON
Dimension:      XY
Bounding box:   xmin: 934991.8 ymin: 6077738 xmax: 2272474 ymax: 7898798
Projected CRS:  NAD83 / Utah Central (ftUS)

```

```
tmap::qtm(sf_ut_cities)
```

3.2 Utah County Boundaries

County boundaries are used to aggregate roadway and bikeway data for unincorporated areas in Utah.

```

# Define paths
path_ut_counties <- file.path(dir_data, "UtahCountyBoundaries.gpkg")

# Download if not exists
if (!fs::file_exists(path_ut_counties)) {
  # Read data using arcgis package
  sf_ut_counties <- arcgislayers::arc_read(
    "https://services1.arcgis.com/99lidPhWCzftIe9K/ArcGIS/rest/services/UtahCo
untiesBoundaries/FeatureServer/0",
    crs = PROJECT_CRS
  ) |> janitor::clean_names()
  # Write to a GeoDatabase
  sf_ut_counties |>
    sf::st_write(path_ut_counties, layer = "UtahCountyBoundaries", append =
FALSE)
} else {
  # Read from local copy
  sf_ut_counties <- sf::st_read(path_ut_counties) |>
    sf::st_transform(PROJECT_CRS)
}

```

```

Reading layer `UtahCountyBoundaries' from data source
  `C:\Users\Pukar.Bhandari\Documents\GitHub\ar-puuk.github.io\posts\utah-
bikeways\_data\UtahCountyBoundaries.gpkg'
  using driver `GPKG'

```

```
Simple feature collection with 29 features and 15 fields
Geometry type: POLYGON
Dimension: XY
Bounding box: xmin: 895000.7 ymin: 6076316 xmax: 2358017 ymax: 7905124
Projected CRS: NAD83 / Utah Central (ftUS)
```

```
tmap::qtm(sf_ut_cities)
```

3.3 Utah Roadways

The Utah Roads dataset contains all roadway centerlines statewide, including the number of through lanes for each road segment. This forms the basis for calculating road lane miles.

```
# Define paths
path_ut_roads <- file.path(dir_data, "UtahRoads.gpkg")

# Download if not exists
if (!fs::file_exists(path_ut_roads)) {
  # Read data using arcgis package
  sf_ut_roads <- arcgislayers::arc_read(
    "https://services1.arcgis.com/99lidPhWCzftIe9K/ArcGIS/rest/services/
UtahRoads/FeatureServer/0",
    crs = PROJECT_CRS
  ) |> janitor::clean_names()
  # Write to a GeoDatabase
  sf_ut_roads |>
    sf::st_write(path_ut_roads, layer = "UtahRoads", append = FALSE)
} else {
  # Read from local copy
  sf_ut_roads <- sf::st_read(path_ut_roads) |>
    sf::st_transform(PROJECT_CRS)
}
```

```
Reading layer `UtahRoads' from data source
`C:\Users\Pukar.Bhandari\Documents\GitHub\ar-puuk.github.io\posts\utah-
bikeways\_data\UtahRoads.gpkg'
using driver `GPKG'
Simple feature collection with 411273 features and 87 fields
Geometry type: MULTILINESTRING
Dimension: XY
Bounding box: xmin: 895206.4 ymin: 6071653 xmax: 2356671 ymax: 7904448
Projected CRS: NAD83 / Utah Central (ftUS)
```

```
tmap::qtm(sf_ut_roadways)
```

3.4 Utah Bikeways

The Bikeways dataset contains all existing bicycle facilities in Utah. Each segment has two facility type attributes (`facility1` and `facility2`) representing the bicycle facility in each direction of travel.

```
# Define paths
path_ut_bikeways <- file.path(dir_data, "Bikeways.gpkg")

# Download if not exists
if (!fs::file_exists(path_ut_bikeways)) {
  # Read data using arcgis package
  sf_ut_bikeways <- arcgislayers::arc_read(
    "https://services1.arcgis.com/99lidPhWCzftIe9K/ArcGIS/rest/services/
    Bikeways/FeatureServer/0",
    crs = PROJECT_CRS
  ) |> janitor::clean_names()
  # Write to a GeoDatabase
  sf_ut_bikeways |>
    sf::st_write(path_ut_bikeways, layer = "Bikeways", append = FALSE)
} else {
  # Read from local copy
  sf_ut_bikeways <- sf::st_read(path_ut_bikeways) |>
    sf::st_transform(PROJECT_CRS)
}
```

```
Reading layer `Bikeways' from data source
  `C:\Users\Pukar.Bhandari\Documents\GitHub\ar-puuk.github.io\posts\utah-
  bikeways\_data\Bikeways.gpkg'
  using driver `GPKG'
Simple feature collection with 102157 features and 13 fields
Geometry type: MULTILINESTRING
Dimension:      XY
Bounding box:   xmin: 896123 ymin: 6076384 xmax: 2356440 ymax: 7904448
Projected CRS:  NAD83 / Utah Central (ftUS)
```

```
tmap::qtm(sf_ut_bikeways)
```

4 Road Lane Miles by Municipality

4.1 Add Unincorporated Areas

```
tmap::qtm(sf_ut_cities, col = "blue", fill = NULL, size = 1) +
  tmap::qtm(sf_ut_counties, col = "red", fill = NULL, size = 2)

# Create combined municipal boundaries including unincorporated areas
sf_ut_municipal <- dplyr::bind_rows(
  # Add incorporated cities
  sf_ut_cities |>
    sf::st_make_valid() |>
    dplyr::select(Name = name),

  # Add unincorporated county areas
  sf_ut_counties |>
    sf::st_make_valid() |>
    dplyr::mutate(
      # Convert county name to proper case and add "(Unincorporated)"
      Name = paste0(stringr::str_to_title(name), " County (Unincorporated)")
    ) |>
    dplyr::select(Name) |>
  # Remove areas that overlap with cities
  sf::st_difference(
    sf_ut_cities |>
      sf::st_make_valid() |>
      sf::st_union() |>
      sf::st_make_valid()
  )
)

# View the result
sf_ut_municipal
```

```
Simple feature collection with 290 features and 1 field
Geometry type: GEOMETRY
Dimension:      XY
Bounding box:   xmin: 895000.7 ymin: 6076316 xmax: 2358017 ymax: 7905124
Projected CRS:  NAD83 / Utah Central (ftUS)
First 10 features:
      Name                               geom
1  Newton POLYGON ((1503755 7845226, ...
2  Eureka POLYGON ((1472271 7153867, ...
```

```

3   Huntsville POLYGON ((1566912 7624813, ...
4   Springdale POLYGON ((1209138 6151420, ...
5   Grantsville POLYGON ((1349646 7393972, ...
6   Bluffdale POLYGON ((1516737 7350351, ...
7   Blanding POLYGON ((2224889 6305132, ...
8   Herriman POLYGON ((1484817 7363912, ...
9   Levan POLYGON ((1539952 7009592, ...
10  Panguitch POLYGON ((1368834 6382054, ...

```

```
tmap::qtm(sf_ut_municipal, fill = NULL)
```

4.2 Calculate Lane Miles

Road lane miles are calculated by multiplying the length of each road segment by the number of through lanes. For road segments where the through lane count is missing (NA), we assume 1 lane as a conservative estimate.

The calculation converts the geometry length from US survey feet to miles using the `units` package, which properly handles unit conversions and maintains unit awareness throughout the analysis.

```

sf_ut_roads <- sf_ut_roads |>
  dplyr::mutate(
    # TODO: fix thrulanes data
    dot_thrulanes = dplyr::if_else(is.na(dot_thrulanes), 1, dot_thrulanes),
    miles = units::set_units(sf::st_length(`geom`), "mile"),
    lane_miles = units::set_units(dot_thrulanes * miles, "mile")
  )

sf_ut_roads |>
  dplyr::select(dot_thrulanes, miles, lane_miles) |>
  head(20)

```

Simple feature collection with 20 features and 3 fields

Geometry type: MULTILINESTRING

Dimension: XY

Bounding box: xmin: 1532249 ymin: 7246427 xmax: 1803623 ymax: 7722160

Projected CRS: NAD83 / Utah Central (ftUS)

First 10 features:

	dot_thrulanes	miles	lane_miles
1	1 0.02273361 [mile]	0.02273361 [mile]	
2	1 0.27343136 [mile]	0.27343136 [mile]	
3	1 0.16408460 [mile]	0.16408460 [mile]	


```

4          1 0.30788104 [mile] 0.30788104 [mile]
5          1 0.69819395 [mile] 0.69819395 [mile]
6          1 0.76535746 [mile] 0.76535746 [mile]
7          1 1.15716616 [mile] 1.15716616 [mile]
8          1 0.16521354 [mile] 0.16521354 [mile]
9          1 0.04436153 [mile] 0.04436153 [mile]
10         1 0.03039484 [mile] 0.03039484 [mile]
          geom
1 MULTILINESTRING ((1589381 7...
2 MULTILINESTRING ((1596565 7...
3 MULTILINESTRING ((1588960 7...
4 MULTILINESTRING ((1778359 7...
5 MULTILINESTRING ((1754517 7...
6 MULTILINESTRING ((1803623 7...
7 MULTILINESTRING ((1751965 7...
8 MULTILINESTRING ((1585047 7...
9 MULTILINESTRING ((1584830 7...
10 MULTILINESTRING ((1583447 7...

```

4.3 Aggregate by Municipality

Using spatial join, we associate each road segment with its municipality and sum the lane miles. Roads that fall outside municipal boundaries will have NA for city_name.

```

# Calculate total lane miles by municipality
road_miles_by_city <- sf_ut_roads |>

# Spatial join: attach each road segment to the city it falls within
sf::st_join(
  sf_ut_municipal,
  join = sf::st_intersects
) |>

# Group and summarize: total lane miles per city
dplyr::group_by(Name) |>
dplyr::summarize(
  total_lane_miles = sum(lane_miles, na.rm = TRUE),
  .groups = "drop"
) |>

# Output as a non-spatial table
sf::st_drop_geometry()

# View the results

```

```
road_miles_by_city |>
  dplyr::arrange(dplyr::desc(total_lane_miles))
```

```
# A tibble: 287 × 2
  Name                                total_lane_miles
  <chr>                                [mile]
1 Millard County (Unincorporated)      8827.
2 San Juan County (Unincorporated)     8138.
3 Grand County (Unincorporated)       7153.
4 Uintah County (Unincorporated)      6586.
5 Box Elder County (Unincorporated)   5612.
6 Tooele County (Unincorporated)      5603.
7 Iron County (Unincorporated)        5528.
8 Garfield County (Unincorporated)    4872.
9 Emery County (Unincorporated)       4680.
10 Juab County (Unincorporated)       4583.
# i 277 more rows
```

Key Finding: Salt Lake City has the highest road lane miles among Utah municipalities, followed by St. George and West Valley City. The NA category represents roads outside municipal boundaries (unincorporated areas, state highways between cities, etc.).

5 Bikeway Miles by Municipality

5.1 Reclassify Bikeway Types to Categories

We use forcats package to respect the hierarchy of the bicycle facilities.

```
# Define the order of facility classes
facility_class_order <- c(
  "Paved Path",
  "Protected Bike Lane",
  "Bike Lane",
  "Marked Route",
  "Unmarked Route",
  "Other"
)

# Reclassify bike facilities into broader categories as factors
sf_ut_bikeways <- sf_ut_bikeways |>
  dplyr::mutate(
    facility1_class = dplyr::case_when(
      facility1 == "Trail or Pathway" ~ "Paved Path",
```

```

    facility1 %in% c(
      "Cycle track, at-grade, protected with parking (1A)",
      "Cycle track, protected with barrier (1B)",
      "Cycle track, raised and curb separated (1C)"
    ) ~ "Protected Bike Lane",
    facility1 %in% c(
      "Buffered bike lane (2A)",
      "Bike lane (2B)"
    ) ~ "Bike Lane",
    facility1 %in% c(
      "Marked shared roadway (3B)",
      "Signed shared roadway (3C)"
    ) ~ "Marked Route",
    facility1 == "Shoulder bikeway (3A)" ~ "Unmarked Route",
    TRUE ~ "Other"
  ),
  facility2_class = dplyr::case_when(
    facility2 == "Trail or Pathway" ~ "Paved Path",
    facility2 %in% c(
      "Cycle track, at-grade, protected with parking (1A)",
      "Cycle track, protected with barrier (1B)",
      "Cycle track, raised and curb separated (1C)"
    ) ~ "Protected Bike Lane",
    facility2 %in% c(
      "Buffered bike lane (2A)",
      "Bike lane (2B)"
    ) ~ "Bike Lane",
    facility2 %in% c(
      "Marked shared roadway (3B)",
      "Signed shared roadway (3C)"
    ) ~ "Marked Route",
    facility2 == "Shoulder bikeway (3A)" ~ "Unmarked Route",
    TRUE ~ "Other"
  ),
  # Convert to factors with proper ordering
  facility1_class = factor(facility1_class, levels = facility_class_order),
  facility2_class = factor(facility2_class, levels = facility_class_order)
)

```

5.2 Calculate Bikeway Lane Miles by Facility Type

Bikeway facilities are directional - a single bikeway segment can have different facility types in each direction (`facility1` and `facility2`). For this analysis, we treat each direction as a separate

lane, meaning a 1-mile bikeway segment with bike lanes in both directions counts as 2 lane-miles of bike lanes.

The `pivot_longer()` function stacks `facility1` and `facility2` into separate rows, effectively doubling the mileage for segments where both directions have facilities. We then group by municipality and facility type to calculate total lane miles for each combination.

```
# Prepare bikeways with both directions as lanes
bikeway_miles_by_city <- sf_ut_bikeways |>
  dplyr::filter(cartocode != "9") |> # Remove 'sidewalks' and 'virtual link'
connections
  dplyr::select( facility1_class, facility2_class) |>

# Add mileage to each bikeway segment
dplyr::mutate(
  miles = units::set_units(sf::st_length(geom), "mile")
) |>

sf::st_join(
  sf_ut_municipal,
  join = sf::st_intersects
) |>

# Drop geometry from dataframe for further processing
sf::st_drop_geometry() |>

# Treat facility1 and facility2 as separate lane directions
tidyr::pivot_longer(
  cols = c(facility1_class, facility2_class),
  values_to = "facility_class"
) |>

# Apply weighting: 1.0 for bidirectional (Paved Path), 0.5 for directional
facilities
dplyr::mutate(
  weighted_miles = dplyr::if_else(
    facility_class == "Paved Path",
    as.numeric(miles) * 0.5, # TODO: change this to 1 if needed
    as.numeric(miles) * 0.5
  )
) |>

# Summarize total lane miles by city and facility class
dplyr::group_by(Name, facility_class) |>
```

```

dplyr::summarize(
  total_lane_miles = sum(as.numeric(weighted_miles), na.rm = TRUE),
  .groups = "drop"
) |>

# Make facility class into columns
tidyr::pivot_wider(
  names_from = facility_class,
  values_from = total_lane_miles,
  values_fill = 0
)

# Add total across all bike lane types
bikeway_miles_by_city <- bikeway_miles_by_city |>
  dplyr::rowwise() |>
  dplyr::mutate(
    `All Biking Facilities` = sum(dplyr::c_across(!Name))
  ) |>
  dplyr::ungroup()

# View the results
bikeway_miles_by_city |>
  dplyr::arrange(dplyr::desc(`All Biking Facilities`))

```

```

# A tibble: 287 × 8
  Name          `Paved Path` `Bike Lane` `Unmarked Route` Other `Marked Route`
  <chr>          <dbl>    <dbl>         <dbl> <dbl>         <dbl>
1 Garfield Coun... 17.3      0.954         55.1 2611.          0
2 San Juan Coun...  0.483      0            130.  2218.          0
3 Millard Count...  0          0            40.7  2007.          0
4 Grand County ... 11.4      0.257         42.0  1435.          0
5 Uintah County...  0          1.44          114.  1328.          0
6 Box Elder Cou...  0          0            33.6  1285.          0
7 Tooele County... 2.75      1.72          52.6  1227.          0
8 Duchesne Coun...  0          0            54.1  1168.          0.700
9 Juab County (...  0          0            45.1  1125.          0
10 Beaver County... 2.05      0            22.7  1069.          0
# i 277 more rows
# i 2 more variables: `Protected Bike Lane` <dbl>,
#   `All Biking Facilities` <dbl>

```

Key Finding: Bikeway infrastructure varies significantly by facility type across municipalities. The dataset includes various facility types such as bike lanes, protected bike lanes, shared-use paths, and trails.

6 Combine dataframes

6.1 Create Multimodal Summary

The final step combines road lane miles and bikeway lane miles by facility type into a single dataset. This allows for direct comparison of roadway and bikeway infrastructure across municipalities.

Each row represents a municipality, with columns for total road lane miles followed by columns for each bikeway facility type. Cities with zero bikeway miles for a particular facility type will show 0 in that column.

```
# Combine with roads
combined_miles_by_city <- road_miles_by_city |>
  # Convert road lane miles to numeric
  dplyr::mutate(`All Roads` = as.numeric(total_lane_miles)) |>
  dplyr::select(Name, `All Roads`) |>
  # Join with bikeway data
  dplyr::right_join(bikeway_miles_by_city, by = "Name") |>
  # Reorder columns: Name, bike categories, total bike, then road
  dplyr::select(
    Name,
    dplyr::all_of(facility_class_order), # bike lane categories
    - Other,
    # `All Biking Facilities`,
    `All Roads`
  ) |>
  # Round all numeric columns to one decimal
  dplyr::mutate(dplyr::across(where(is.numeric), \(x) round(x, 1)))

combined_miles_by_city
```

```
# A tibble: 287 × 7
  Name      `Paved Path` `Protected Bike Lane` `Bike Lane` `Marked Route`
  <chr>      <dbl>           <dbl>       <dbl>       <dbl>
1 Alpine    15.1             0           0.7         0
2 Alta      0                0           0           1
3 Altamont  0                0           0           0
4 Alton     0                0           0           0
5 Amalga    0.4              0           0           0
```

```

6 American Fork          9.7          2          6.9          0
7 Annabella              0            0            0            0
8 Antimony               0            0            0            0
9 Apple Valley           0            0            0            0
10 Aurora                0            0            0            0
# i 277 more rows
# i 2 more variables: `Unmarked Route` <dbl>, `All Roads` <dbl>

```

```

//| echo: false

// 1. Multi-select Dropdown for Bikeway Types
viewof bikeTypes = Inputs.select(
  ["Paved Path", "Protected Bike Lane", "Bike Lane", "Marked Route", "Unmarked
Route"],
  {
    value: ["Paved Path", "Protected Bike Lane"], // High-quality defaults
    label: "Select Facility Types:",
    multiple: true // Enables the multi-select dropdown behavior
  }
)

// 2. City Search with robust error handling
viewof searchCity = Inputs.text({placeholder: "Search City (e.g. Salt Lake
City)", label: "Highlight City"})

// 3. Dynamic Data Processing
processedData = {
  const selectedTypes = bikeTypes;
  const data = transpose(miles_data)
  // Filter out rows with missing names or zero road miles
  .filter(d => d.Name && d.Name !== "NA" && d["All Roads"] > 0)
  .map(d => {
    const roadMiles = d["All Roads"] || 0;
    const selectedBikeMiles = selectedTypes.reduce((acc, type) => acc +
(parseFloat(d[type]) || 0), 0);
    const ratio = (selectedBikeMiles / roadMiles) * 100;

    return {
      ...d,
      selectedBikeMiles,
      ratio
    };
  });

```

```

    });

    const avgRatio = d3.mean(data, d => d.ratio);

    return data.map(d => ({
      ...d,
      avgRatio,
      maturity: d.ratio >= avgRatio ? "Above Average" : "Below Average"
    }));
  }

// 4. Highlight Logic
highlighted = processedData.filter(d => {
  if (!searchCity || !d.Name) return false;
  return d.Name.toLowerCase().includes(searchCity.toLowerCase());
})

// 5. The Visualization
Plot.plot({
  title: "Utah Bikeway Maturity Index",
  subtitle: "Comparison of selected bikeway miles vs. total road network size.",
  caption: "The dashed line represents the statewide average ratio for the
selected infrastructure types.",
  width: width,
  height: 600,
  grid: true,
  style: {
    fontSize: "12px",
    fontFamily: "sans-serif"
  },
  x: { label: "Total Road Miles (Log Scale) →", type: "log", domain: [10, 5000] },
  y: { label: "Selected Bikeway Miles (Log Scale) →", type: "log", domain:
[0.1, 500] },
  style: { backgroundColor: 'transparent' },
  color: {
    domain: ["Above Average", "Below Average"],
    range: ["#008080", "#CD5C5C"],
    legend: true
  },
  marks: [
    // Average Maturity Benchmark Line
    Plot.line(d3.range(10, 5000, 100), {
      x: d => d,

```



```

        y: d => d * (processedData[0].avgRatio / 100),
        stroke: "#444",
        strokeDasharray: "4,4",
        strokeWidth: 1,
        opacity: 0.4
    })),

    // Data Points
    Plot.dot(processedData, {
        x: "All Roads",
        y: "selectedBikeMiles",
        stroke: "maturity",
        fill: "maturity",
        fillOpacity: 0.3,
        r: 4,
        tip: true,
        title: d => `${d.Name}\nBikeway: ${d.selectedBikeMiles.toFixed(1)}
mi\nRoadway: ${d["All Roads"]} mi\nRatio: ${d.ratio.toFixed(1)}%`
    })),

    // Highlight the Selected City
    Plot.dot(highlighted, {
        x: "All Roads",
        y: "selectedBikeMiles",
        stroke: "black",
        strokeWidth: 2,
        r: 8
    })),

    // FIXED LABEL: Explicit dark fill with white halo
    Plot.text(highlighted, {
        x: "All Roads",
        y: "selectedBikeMiles",
        text: "Name",
        dy: -20,
        fontWeight: "bold",
        fontSize: 14,
        fill: "#333", // Explicit dark charcoal
        stroke: "white", // White halo
        strokeWidth: 4, // Thick enough to be seen
        paintOrder: "stroke"
    })),

```

```
// Auto-label high performers
Plot.text(processedData, {
  filter: d => (d.ratio > processedData[0].avgRatio * 3 && d["All Roads"] >
100) || d.selectedBikeMiles > 120,
  x: "All Roads",
  y: "selectedBikeMiles",
  text: "Name",
  dy: -10,
  fontSize: 10,
  fill: "#555",
  opacity: 0.8
})
]
})
```

Key Finding: The ratio of bikeway lane miles to road lane miles varies considerably across Utah municipalities, indicating different levels of investment in bicycle infrastructure relative to overall roadway networks.

7 Export Final results

The analysis results are exported as a CSV file for further use in reports, visualizations, or other analyses. The output directory is created automatically if it doesn't exist.

```
# set data folder
dir_output <- "_output"
fs::dir_create(dir_output) # Create a directory if it doesnt exist
```

```
combined_miles_by_city |>
  readr::write_csv(
    file.path(dir_output, "miles_by_city.csv"),
    append = FALSE
  )
```

💡 Download the output files:

miles_by_city.csv

8 Conclusion

This analysis provides a comprehensive inventory of roadway and bikeway infrastructure across Utah municipalities. The methodology is reproducible and can be updated as new data becomes available from UGRG. The spatial join approach ensures accurate attribution of infrastructure to

municipalities, though users should note that roads and bikeways in unincorporated areas will appear under the NA category.