Base Year SE Data Development

Lower Savannah Council of Governments (LSCOG) 2050 Long Range Transportation Plan

Pukar Bhandari
Metro Analytics
pbhandari@metroanalytics.com

2025-07-05

Table of contents

Set up the environment 2
Install and load packages 2
Project folder 3
Set global options and parameters 5
Set census API key 6
Define study area 6
Define state and counties 6
Load TAZ geometry 8
Fetch raw data 10
2020 Decennial census 11
2020 ACS estimates 14
2019 LEHD data 18
2020 NCES school and college enrollment data 22
Public schools 22
Private schools 26
Post-secondary institutions 29
Clean data 31
Household-weighted interpolation 32
Combine population and households 37
Employment data 41
Export raw data 42
TAZ data 42
Census blocks to TAZ conversion 43
Decennial census data at census block level 44
ACS estimates at census block level 45
LEHD data at census block level 46
Public schools to TAZ 47

Private schools to TAZ 49
Aggregate data to TAZ 50
Population, households, and employment 50
School and college enrollment 53
Combine into a single data 57
Data checks and validation 59
Household size total 59
Household income total 60
Employment categories 60
Export the final data 62

Set up the environment

This section establishes the computational environment for processing socioeconomic data inputs for the Lower Savannah Council of Governments regional travel demand model using both R and Python platforms.

Install and load packages

The package installation process incorporates essential libraries for comprehensive geospatial data analysis. The R environment includes `{tidyverse}` for data manipulation, `{sf}` for spatial data handling, `{tidycensus}` for Census Bureau data access, and `{lehdr}` for Longitudinal Employer-Household Dynamics data retrieval. The Python environment focuses on core data science libraries including `{pandas}` for data manipulation, `{geopandas}` for spatial analysis, and `{pygris}` for Census data queries. These packages form the analytical backbone for processing demographic, employment, and geographic data required for travel demand modeling.

R

```
# # Install required packages
# install.packages(c(
#   "tidyverse",
#   "vroom",
#   "sf",
#   "tidycensus",
#   "lehdr",
#   "arcgislayers",
#   "mapview",
#   "RColorBrewer",
#   "janitor",
#   "here"
# ), dependencies = TRUE)

# Load packages
library(tidyverse)    # Data manipulation and visualization
```

```r
library(vroom)        # Read rectangular data
library(sf)           # Spatial analysis
library(tidycensus)   # Accessing US Census Data
library(lehdr)        # Access LODES data
library(arcgislayers) # ArcGIS REST API access
library(mapview)      # Interactive mapping
library(RColorBrewer) # Color palettes for maps
library(janitor)      # Data cleaning and preparation
library(here)         # Filepath management
```

Python

```python
# Install required packages if not available
# pip install numpy pandas geopandas shapely folium requests pygris

# Load processing libraries & modules
import os
from pathlib import Path
import zipfile
import requests
import urllib.parse
import warnings
warnings.filterwarnings('ignore')

# Load data and visualization libraries & modules
import numpy as np
import pandas as pd
import pyproj
import geopandas as gpd
import folium
from shapely.geometry import Point

# Census data query libraries & modules
from pygris import blocks, block_groups
from pygris.helpers import validate_state, validate_county
from pygris.data import get_census, get_lodes
```

Project folder

The centralized directory structure organizes input data, processing files, and model outputs. By using the `{here}` package in R and `pathlib` in Python, we ensure that file paths work correctly regardless of the computer or operating system.

R

```r
# Define Paths relative to Project Root
# We want data in: posts/socioeconomic-demo/data
# We want output in: posts/socioeconomic-demo/output

base_dir <- here("posts", "socioeconomic-demo")
data_dir <- file.path(base_dir, "data")
output_dir <- file.path(base_dir, "output")
output_tabular <- file.path(output_dir, "tabular")
output_spatial <- file.path(output_dir, "spatial")

# Create directories if they don't exist
dir.create(data_dir, showWarnings = FALSE, recursive = TRUE)
dir.create(output_tabular, showWarnings = FALSE, recursive = TRUE)
dir.create(output_spatial, showWarnings = FALSE, recursive = TRUE)

# Verify paths
print(paste("Data Directory:", data_dir))
```

```
[1] "Data Directory: D:/GitHub/ar-puuk.github.io/posts/socioeconomic-demo/data"
```

```r
print(paste("Output Directory:", output_dir))
```

```
[1] "Output Directory: D:/GitHub/ar-puuk.github.io/posts/socioeconomic-demo/
output"
```

Python

```python
# Define Paths using pathlib
# We retrieve the base_dir from R, but define everything else in Python

# Get base_dir from R environment
base_dir = Path(r.base_dir)

# Define subdirectories relative to base_dir
data_dir = base_dir / "data"
output_dir = base_dir / "output"
output_tabular = output_dir / "tabular"
output_spatial = output_dir / "spatial"

# Create directories if they don't exist
```

```
data_dir.mkdir(parents=True, exist_ok=True)
output_tabular.mkdir(parents=True, exist_ok=True)
output_spatial.mkdir(parents=True, exist_ok=True)

# Verify paths
print(f"Data Directory: {data_dir.resolve()}")
```

```
Data Directory: D:\GitHub\ar-puuk.github.io\posts\socioeconomic-demo\data
```

```
print(f"Output Directory: {output_dir.resolve()}")
```

```
Output Directory: D:\GitHub\ar-puuk.github.io\posts\socioeconomic-demo\output
```

Set global options and parameters

Configuration settings optimize performance and establish spatial consistency. We set the `{tigris}` cache to a local folder within the project to prevent redundant downloads and ensure portability. The South Carolina State Plane coordinate system (`EPSG:3361`) serves as the standard projection for accurate GIS operations.

R

```
# Set Tigris Cache to local project folder
tigris_cache <- file.path(data_dir, "tigris")
dir.create(tigris_cache, showWarnings = FALSE)
options(tigris_use_cache = TRUE)
options(tigris_cache_dir = tigris_cache)

# set project CRS
project_crs <- "EPSG:3361"
```

Python

```
# Set project CRS
project_crs = "EPSG:3361"

# Note: pygris usually respects the tigris cache environment variable or default
locations.
# We can explicitly set cache location for pygris if needed, but here we rely
on defaults
# or the R setting if they share environment variables in the session.
```

Set census API key

API authentication enables access to detailed demographic and economic datasets from the Census Bureau. The key configuration supports both R and Python environments for automated data retrieval workflows.

> Need a Census API key?
>
> Get one for free at census.gov/developers

Put the key in a file named `_environment.local` at the project root. Quarto loads it for both the R and Python engines, and the repository's `.gitignore` already excludes `_*.local` files, so the key is stored in one place and never committed:

```
CENSUS_API_KEY=your_api_key_here
```

`tidycensus` reads `CENSUS_API_KEY` on its own, and the Python code below passes `os.getenv("CENSUS_API_KEY")` to the API.

Define study area

This section defines the geographic extent of the Lower Savannah Council of Governments region and loads the Traffic Analysis Zone (TAZ) geometry for spatial analysis.

Define state and counties

The study area encompasses six counties within South Carolina: Aiken, Allendale, Bamberg, Barnwell, Calhoun, and Orangeburg. These counties constitute the LSCOG planning region for travel demand modeling purposes.

R

```r
# Define state abbreviation and county names
state_abb <- "SC"
county_names <- c(
  "Aiken",
  "Allendale",
  "Bamberg",
  "Barnwell",
  "Calhoun",
  "Orangeburg"
)
```

Python

```
# Define state abbreviation and county names
state_abb = "SC"
county_names = [
    "Aiken",
    "Allendale",
    "Bamberg",
    "Barnwell",
    "Calhoun",
    "Orangeburg"
]
```

FIPS code conversion translates state abbreviations and county names into standardized Federal Information Processing Standard codes. These codes enable consistent data retrieval across census datasets and ensure proper geographic matching with demographic and economic data sources.

R

```
# Converting state abbreviation code to FIPS code
state_fips <- tidycensus:::validate_state(state = state_abb)
county_fips <- vapply(
  county_names,
  function(x) tidycensus:::validate_county(state = state_abb, county = x),
  character(1)
)

# Converting County Names to FIPS code
fips_codes <- paste(state_fips, county_fips, sep = "")
fips_codes
```

```
[1] "45003" "45005" "45009" "45011" "45017" "45075"
```

Python

```
# Converting state abbreviation code to FIPS code
state_fips = validate_state(state_abb)
```

```
Using FIPS code '45' for input 'SC'
```

```
# Converting County Names to FIPS code
county_fips = [
    validate_county(state_fips, county)
```

```
    for county in county_names
]
```

```
Using FIPS code '003' for input 'Aiken'
Using FIPS code '005' for input 'Allendale'
Using FIPS code '009' for input 'Bamberg'
Using FIPS code '011' for input 'Barnwell'
Using FIPS code '017' for input 'Calhoun'
Using FIPS code '075' for input 'Orangeburg'
```

```
# Converting County Names to FIPS code
fips_codes = [f"{state_fips}{county}" for county in county_fips]
fips_codes
```

```
['45003', '45005', '45009', '45011', '45017', '45075']
```

Load TAZ geometry

The TAZ shapefile provides the fundamental spatial framework for travel demand modeling. The geometry is loaded from the TDM exports geodatabase and filtered to include only zones within the six-county study area using FIPS code matching. Coordinate transformation converts the TAZ geometry to the project's standard coordinate reference system (`EPSG:3361`) for accurate spatial calculations. The attribute selection retains essential fields including TAZ identifiers, area measurements, area type classifications, and county assignments.

R

```
# Load TAZ Shapefile
# We assume the input TAZ file is in the data directory
taz_path <- file.path(data_dir, "SE_2019_AD_10_30_2023.gpkg")

lscog_taz <- sf::read_sf(
  taz_path,
  query = paste0(
    "SELECT * FROM \"SE_2019_AD_10_30_2023\" WHERE countyID IN (",
    paste0("'", fips_codes, "'", collapse = ", "),
    ")"
  )
) |>
  sf::st_transform(project_crs) |>
  dplyr::select(
    ID,
```

```
    Area,
    Acres,
    TAZ_ID = TAZ_IDs,
    AREA_TYPE,
    COUNTY,
    COUNTYID = countyID
  )

lscog_taz
```

```
Simple feature collection with 585 features and 7 fields
Geometry type: MULTIPOLYGON
Dimension:     XY
Bounding box:  xmin: 1691490 ymin: 331894 xmax: 2237471 ymax: 744679.9
Projected CRS: NAD83(HARN) / South Carolina (ft)
# A tibble: 585 × 8
   ID     Area  Acres TAZ_ID AREA_TYPE COUNTY COUNTYID                    geom
   <chr> <dbl>  <dbl> <chr>  <chr>     <chr>  <chr>       <MULTIPOLYGON [foot]>
 1 9050… 13.3   8518. 90501… RURAL     Bambe… 45009    (((2046194 478862.1, 204…
 2 9050… 39.2  25084. 90501… RURAL     Bambe… 45009    (((2012593 500179.5, 201…
 3 7505…  9.03  5778. 75050… RURAL     Orang… 45075    (((2056266 515976, 20561…
 4 7505… 15.5   9934. 75050… RURAL     Orang… 45075    (((2061827 488917.9, 206…
 5 7505… 17.5  11216. 75050… SUBURBAN  Orang… 45075    (((2154222 534929.2, 215…
 6 7505… 12.8   8191. 75050… RURAL     Orang… 45075    (((2195053 518745.9, 219…
 7 7505…  8.10  5181. 75050… SUBURBAN  Orang… 45075    (((2179620 542034.9, 217…
 8 7505… 13.4   8568. 75050… SUBURBAN  Orang… 45075    (((2179131 542424, 21770…
 9 7505…  6.00  3843. 75050… SUBURBAN  Orang… 45075    (((2184440 568297.6, 218…
10 7505…  5.06  3239. 75050… SUBURBAN  Orang… 45075    (((2204464 570787.3, 220…
# ℹ 575 more rows
```

Python

```
# Load TAZ Shapefile
taz_path = data_dir / "SE_2019_AD_10_30_2023.gpkg"

lscog_taz = gpd.read_file(
    taz_path,
    layer="SE_2019_AD_10_30_2023",
    where=f"countyID IN ({', '.join([f"'{fips}'" for fips in fips_codes])})"
)

lscog_taz = lscog_taz.to_crs(project_crs)
```

```
lscog_taz = lscog_taz.rename(
  columns={
    'TAZ_IDs': 'TAZ_ID',
    'countyID': 'COUNTYID'
})[['ID',  'Area',  'Acres',  'TAZ_ID',  'AREA_TYPE',  'COUNTY',  'COUNTYID',
'geometry']]

lscog_taz
```

```
           ID  ...                                           geometry
0     9050130  ...  MULTIPOLYGON (((2046194.08 478862.054, 2046134...
1     9050132  ...  MULTIPOLYGON (((2012593.472 500179.47, 2013190...
2    75050131  ...  MULTIPOLYGON (((2056266.071 515975.986, 205617...
3    75050045  ...  MULTIPOLYGON (((2061826.693 488917.873, 206173...
4    75050182  ...  MULTIPOLYGON (((2154221.857 534929.221, 215441...
..        ...  ...                                               ...
580   5050049  ...  MULTIPOLYGON (((1924248.136 433664.04, 1924004...
581   5050055  ...  MULTIPOLYGON (((1905461.23 427627.626, 1905456...
582   5050066  ...  MULTIPOLYGON (((1880812.362 414251.546, 188090...
583   5050054  ...  MULTIPOLYGON (((1871871.454 413403.458, 187167...
584   5050065  ...  MULTIPOLYGON (((1849074.015 398566.33, 1849218...

[585 rows x 8 columns]
```

The interactive map visualization displays the TAZ structure colored by county, providing spatial context for the analysis area and enabling quality assurance of the geometric data loading process.

R

```
# Create interactive map
mapview::mapview(lscog_taz,  zcol  =  "COUNTY",  lwd  =  1.6,  map.types  =
"CartoDB.Voyager", col.regions = RColorBrewer::brewer.pal(6, "Dark2"))
```

Python

```
# Create interactive map
lscog_taz.explore(column="COUNTY",       categorical=True,       legend=True,
tiles="CartoDB.Voyager", zoom_start=8)
```

Fetch raw data

This section retrieves demographic, economic, and employment data from multiple Census Bureau sources at the appropriate geographic scales for travel demand modeling.

2020 Decennial census

The 2020 Decennial Census provides population and housing data at the census block level, offering the finest spatial resolution for demographic analysis. Population variables include total population, group quarters population, and household population derived by subtraction. Housing variables encompass total dwelling units and household counts by size categories. Household size distributions are consolidated into four categories: 1-person, 2-person, 3-person, and 4-or-more-person households. The 4-or-more category aggregates larger household sizes to simplify model implementation while maintaining essential demographic stratification for trip generation analysis. > For more information on the Decennial Census data, refer to the Decennial Census Technical Documentation.

R

```
# Define variables to download
dec_variables <- c(
    TOTPOP = "P1_001N", # Total Population
    GQPOP = "P18_001N", # Population living in Group Quarters
    DU = "H1_001N", # Dwelling Units
    HH_1 = "H9_002N", # 1-person household
    HH_2 = "H9_003N", # 2-person household
    HH_3 = "H9_004N", # 3-person household
    # HH_4 = "H9_005N", # 4-person household
    # HH_5 = "H9_006N", # 5-person household
    # HH_6 = "H9_007N", # 6-person household
    # HH_7 = "H9_008N", # 7-or-more-person household
    HH = "H9_001N" # Total Number of Households
  )

# Load Population and Household Data
lscog_dec <- tidycensus::get_decennial(
  year = 2020,
  sumfile = "dhc",
  geography = "block",
  state = state_fips,
  county = county_fips,
  output = "wide",
  cb = FALSE,
  geometry = TRUE,
  keep_geo_vars = TRUE,
  key = Sys.getenv('CENSUS_API_KEY'),
  variables = dec_variables
) |>
  sf::st_transform(project_crs) |>
  dplyr::mutate(
```

```
    HHPOP = TOTPOP - GQPOP,
    HH_4 = HH - (HH_1 + HH_2 + HH_3)
  ) |>
  dplyr::select(GEOID, TOTPOP, GQPOP, HHPOP, HH, HH_1, HH_2, HH_3, HH_4, DU)

lscog_dec
```

```
Simple feature collection with 13961 features and 10 fields
Geometry type: MULTIPOLYGON
Dimension:     XY
Bounding box:  xmin: 1691517 ymin: 331891.7 xmax: 2237472 ymax: 744669.5
Projected CRS: NAD83(HARN) / South Carolina (ft)
# A tibble: 13,961 × 11
   GEOID           TOTPOP GQPOP HHPOP    HH  HH_1  HH_2  HH_3  HH_4    DU
   <chr>            <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
 1 450179504004051      0     0     0     0     0     0     0     0     0
 2 450179504003011      0     0     0     0     0     0     0     0     0
 3 450179502011045     54     4    50    16     3     1     3     9    18
 4 450179504001020      0     0     0     0     0     0     0     0     0
 5 450750105003029     13     0    13     4     0     3     0     1     4
 6 450750117021009     10     0    10     3     3     0     0     0     8
 7 450750117011051      0     0     0     0     0     0     0     0     0
 8 450750118021087      6     0     6     4     0     1     2     1     4
 9 450750120003020      0     0     0     0     0     0     0     0     0
10 450179501003046     18     0    18     0     0     0     0     0     1
# ℹ 13,951 more rows
# ℹ 1 more variable: geometry <MULTIPOLYGON [foot]>
```

Python

```
# Define variables to download
dec_variables = {
    'P1_001N': 'TOTPOP',     # Total Population
    'P18_001N': 'GQPOP',      # Population living in Group Quarters
    'H1_001N': 'DU',          # Dwelling Units
    'H9_002N': 'HH_1',        # 1-person household
    'H9_003N': 'HH_2',        # 2-person household
    'H9_004N': 'HH_3',        # 3-person household
    # 'H9_005N': 'HH_4',        # 4-person household
    # 'H9_006N': 'HH_5',        # 5-person household
    # 'H9_007N': 'HH_6',        # 6-person household
    # 'H9_008N': 'HH_7',        # 7-or-more-person household
    'H9_001N': 'HH'           # Total Number of Households
```

```
}

# get census block geometries
lscog_cb = blocks(
    state=state_fips,
    county=county_fips,
    year=2020,
    cache=True
)

# Download decennial census data at block level
lscog_dec = get_census(
    dataset="dec/dhc",
    year=2020,
    variables=list(dec_variables.keys()),
    params={
        "for": f"block:*",
        "key": os.getenv('CENSUS_API_KEY'),
        "in": f"state:{state_fips} county:{','.join(county_fips)}"
    },
    return_geoid=True,
    guess_dtypes=True,
)

# join data to geometry
lscog_dec  =  lscog_cb[['GEOID20',  'geometry']].merge(lscog_dec,  left_on  =
"GEOID20", right_on = "GEOID")

# Rename columns
lscog_dec = lscog_dec.rename(columns=dec_variables)

# Transform CRS
lscog_dec = lscog_dec.to_crs(project_crs)

# Calculate derived variables
lscog_dec['HHPOP'] = lscog_dec['TOTPOP'] - lscog_dec['GQPOP']
lscog_dec['HH_4'] = lscog_dec['HH'] - (
    lscog_dec['HH_1'] + lscog_dec['HH_2'] + lscog_dec['HH_3']
)

# Select final columns
lscog_dec = lscog_dec[['GEOID', 'TOTPOP', 'GQPOP', 'HHPOP',
                       'HH', 'HH_1', 'HH_2', 'HH_3', 'HH_4', 'DU', 'geometry']]
```

```
lscog_dec
```

```
                GEOID  ...                                           geometry
0      450179504004051  ...  POLYGON ((2084300.974 622308.526, 2084460.74 6...
1      450179504003011  ...  POLYGON ((2112518.54 626782.208, 2112608.778 6...
2      450179502011045  ...  POLYGON ((2067775.167 662339.483, 2068091.491 ...
3      450179504001020  ...  POLYGON ((2087947.053 684345.612, 2087992.284 ...
4      450750105003029  ...  POLYGON ((2089072.743 552687.443, 2089248.831 ...
...                ...  ...                                               ...
13956  450059705003050  ...  POLYGON ((1926607.333 409005.466, 1926609.861 ...
13957  450030203042000  ...  POLYGON ((1778751.197 641782.585, 1778797.329 ...
13958  450030218002115  ...  POLYGON ((1919787.314 648288.439, 1919913.531 ...
13959  450030206012008  ...  POLYGON ((1723756.559 630234.507, 1723784.384 ...
13960  450059705002005  ...  POLYGON ((1926817.622 432583.896, 1930423.825 ...

[13961 rows x 11 columns]
```

2020 ACS estimates

The American Community Survey 5-year estimates provide household income data at the block group level. Income categories are aggregated into three broad ranges: under $15,000, $15,000-$49,999, and $50,000 and above. This stratification aligns with travel behavior research indicating distinct mobility patterns across income levels. The block group geography represents the finest spatial resolution available for ACS income data, providing sufficient detail for socioeconomic modeling while maintaining statistical reliability through the 5-year aggregation period. > For more information on the ACS data, refer to the ACS Technical Documentation.

R

```
# Define variables to download
acs_variables <- c(
    INC_CAT_02 = "B19001_002", # Less than $10,000
    INC_CAT_03 = "B19001_003", # $10,000 to $14,999
    INC_CAT_04 = "B19001_004", # $15,000 to $19,999
    INC_CAT_05 = "B19001_005", # $20,000 to $24,999
    INC_CAT_06 = "B19001_006", # $25,000 to $29,999
    INC_CAT_07 = "B19001_007", # $30,000 to $34,999
    INC_CAT_08 = "B19001_008", # $35,000 to $39,999
    INC_CAT_09 = "B19001_009", # $40,000 to $44,999
    INC_CAT_10 = "B19001_010", # $45,000 to $49,999
    # INC_CAT_11 = "B19001_011", # $50,000 to $59,999
    # INC_CAT_12 = "B19001_012", # $60,000 to $74,999
```

```
    # INC_CAT_13 = "B19001_013", # $75,000 to $99,999
    # INC_CAT_14 = "B19001_014", # $100,000 to $124,999
    # INC_CAT_15 = "B19001_015", # $125,000 to $149,999
    # INC_CAT_16 = "B19001_016", # $150,000 to $199,999
    # INC_CAT_17 = "B19001_017", # $200,000 or more
    INC_CAT_01 = "B19001_001" # Total
  )

# Load Household Income Data
lscog_acs <- tidycensus::get_acs(
  year = 2020,
  survey = "acs5",
  geography = "block group",
  state = state_fips,
  county = county_fips,
  output = "wide",
  cb = FALSE,
  geometry = TRUE,
  key = Sys.getenv('CENSUS_API_KEY'),
  variables = acs_variables
) |>
  sf::st_transform(project_crs) |>
  dplyr::mutate(
    INC_14999 = INC_CAT_02E + INC_CAT_03E,
    INC_49999 = INC_CAT_04E +
      INC_CAT_05E +
      INC_CAT_06E +
      INC_CAT_07E +
      INC_CAT_08E +
      INC_CAT_09E +
      INC_CAT_10E,
    INC_50000 = INC_CAT_01E - (INC_14999 + INC_49999)
  ) |>
  dplyr::select(GEOID, INC_TOTAL = INC_CAT_01E, INC_14999, INC_49999, INC_50000)

lscog_acs
```

```
Simple feature collection with 262 features and 5 fields
Geometry type: MULTIPOLYGON
Dimension:     XY
Bounding box:  xmin: 1691517 ymin: 331891.7 xmax: 2237472 ymax: 744669.5
Projected CRS: NAD83(HARN) / South Carolina (ft)
```

```
First 10 features:
          GEOID INC_TOTAL INC_14999 INC_49999 INC_50000
1  450030207011       467        82       171       214
2  450030212052       949         0       256       693
3  450030212051       857        21       250       586
4  450030213001       612       103       129       380
5  450030216031      1191       176       303       712
6  450030215003       773        95       240       438
7  450030205004      1081        56       302       723
8  450030205003       937        37       158       742
9  450030212041       758        37       344       377
10 450030215004       973        77       247       649
                         geometry
1  MULTIPOLYGON (((1701402 614...
2  MULTIPOLYGON (((1776367 591...
3  MULTIPOLYGON (((1768340 598...
4  MULTIPOLYGON (((1768476 630...
5  MULTIPOLYGON (((1785900 618...
6  MULTIPOLYGON (((1782074 620...
7  MULTIPOLYGON (((1707972 630...
8  MULTIPOLYGON (((1708123 634...
9  MULTIPOLYGON (((1775528 610...
10 MULTIPOLYGON (((1779272 619...
```

Python

```python
# Define variables to download
acs_variables = {
    'B19001_002E': 'INC_CAT_02',  # Less than $10,000
    'B19001_003E': 'INC_CAT_03',  # $10,000 to $14,999
    'B19001_004E': 'INC_CAT_04',  # $15,000 to $19,999
    'B19001_005E': 'INC_CAT_05',  # $20,000 to $24,999
    'B19001_006E': 'INC_CAT_06',  # $25,000 to $29,999
    'B19001_007E': 'INC_CAT_07',  # $30,000 to $34,999
    'B19001_008E': 'INC_CAT_08',  # $35,000 to $39,999
    'B19001_009E': 'INC_CAT_09',  # $40,000 to $44,999
    'B19001_010E': 'INC_CAT_10',  # $45,000 to $49,999
    # 'B19001_011E': 'INC_CAT_11',  # $50,000 to $59,999
    # 'B19001_012E': 'INC_CAT_12',  # $60,000 to $74,999
    # 'B19001_013E': 'INC_CAT_13',  # $75,000 to $99,999
    # 'B19001_014E': 'INC_CAT_14',  # $100,000 to $124,999
    # 'B19001_015E': 'INC_CAT_15',  # $125,000 to $149,999
    # 'B19001_016E': 'INC_CAT_16',  # $150,000 to $199,999
```

```
    # 'B19001_017E': 'INC_CAT_17',  # $200,000 or more
    'B19001_001E': 'INC_CAT_01'   # Total
}

# get blockgroup geometries
lscog_bg = block_groups(
    state=state_fips,
    county=county_fips,
    year=2020,
    cache=True
)

# Download household income data at block group level
lscog_acs = get_census(
    dataset="acs/acs5",
    year=2020,
    variables=list(acs_variables.keys()),
    params={
        "for": f"block group:*",
        "key": os.getenv('CENSUS_API_KEY'),
        "in": f"state:{state_fips} county:{','.join(county_fips)}"
    },
    return_geoid=True,
    guess_dtypes=True
)

# join data to geometry
lscog_acs = lscog_bg[['GEOID', 'geometry']].merge(lscog_acs, on = "GEOID")

# Rename columns
lscog_acs = lscog_acs.rename(columns=acs_variables)

# Transform CRS
lscog_acs = lscog_acs.to_crs(project_crs)

# Calculate derived variables
lscog_acs['INC_14999'] = lscog_acs['INC_CAT_02'] + lscog_acs['INC_CAT_03']
lscog_acs['INC_49999'] = (
    lscog_acs['INC_CAT_04'] +
    lscog_acs['INC_CAT_05'] +
    lscog_acs['INC_CAT_06'] +
    lscog_acs['INC_CAT_07'] +
    lscog_acs['INC_CAT_08'] +
```

```
    lscog_acs['INC_CAT_09'] +
    lscog_acs['INC_CAT_10']
)
lscog_acs['INC_50000'] = lscog_acs['INC_CAT_01'] - (
    lscog_acs['INC_14999'] + lscog_acs['INC_49999']
)

# Select final columns
lscog_acs = lscog_acs.rename(columns={'INC_CAT_01': 'INC_TOTAL'})
lscog_acs   =   lscog_acs[['GEOID',   'INC_TOTAL',   'INC_14999',   'INC_49999',
'INC_50000', 'geometry'
]]

lscog_acs
```

```
            GEOID  ...                                           geometry
0    450030207011  ...  POLYGON ((1701402.37 614608.958, 1701441.07 61...
1    450030212052  ...  POLYGON ((1776366.684 591083.944, 1776445.37 5...
2    450030212051  ...  POLYGON ((1768340.248 598546.468, 1768482.141 ...
3    450030213001  ...  POLYGON ((1768475.931 630588.733, 1768610.076 ...
4    450030216031  ...  POLYGON ((1785900.107 618251.028, 1786047.488 ...
..            ...  ...                                               ...
257  450750119004  ...  POLYGON ((1974249.527 620700.361, 1975105.197 ...
258  450750103011  ...  POLYGON ((2142864.631 581695.327, 2142874.033 ...
259  450750109011  ...  POLYGON ((2033500.16 608479.774, 2033509.304 6...
260  450750109022  ...  POLYGON ((2013478.807 622487.426, 2013488.515 ...
261  450750109023  ...  POLYGON ((2022268.105 617836.647, 2022656.655 ...

[262 rows x 6 columns]
```

2019 LEHD data

The Longitudinal Employer-Household Dynamics Workplace Area Characteristics data provides employment counts by industry sector at the census block level. Employment categories follow the North American Industry Classification System and are aggregated into transportation-relevant sectors including retail, services, manufacturing, and public administration. The 2019 reference year represents pre-pandemic employment patterns, providing a stable baseline for long-term transportation planning. Employment data at the block level enables precise spatial allocation of work destinations within the travel demand model framework. > For more information on the LEHD data, refer to the LODES Technical Documentation.

R

```
# Download LEHD WAC data at block level
lscog_emp <- lehdr::grab_lodes(
  version = "LODES8",
  state = tolower(state_abb),
  lodes_type = "wac",
  segment = "S000",
  job_type = "JT00",
  year = 2019,
  state_part = "",
  agg_geo = "block",
  use_cache = TRUE
) |>
  dplyr::filter(grepl(
    paste("^(", paste(fips_codes, collapse = "|"), ")", sep = ""),
    w_geocode
  )) |>
  # check the documentation at: https://lehd.ces.census.gov/data/lodes/LODES8/
LODESTechDoc8.0.pdf
  dplyr::mutate(
    GEOID = as.character(w_geocode),
    TOTAL_EMP = C000, # Total Employment
    AGR_FOR_FI = CNS01, # Agricultural, forestry, and fishing employment
    MINING = CNS02, # Mining employment
    CONSTRUCTI = CNS04, # Construction employment
    MANUFACTUR = CNS05, # Manufacturing employment
    TRANSP_COM = CNS08 + CNS09, # Transportation, communication employment
    WHOLESALE = CNS06, # Wholesale employment
    RETAIL = CNS07, # Retail employment
    FIRE = CNS10 + CNS11, # Finance / Insurance / Real Estate employment
    SERVICES = CNS03 +
      CNS12 +
      CNS13 +
      CNS14 + # Service employment
      CNS15 +
      CNS16 +
      CNS17 +
      CNS18 +
      CNS19,
    PUBLIC_ADM = CNS20 # Public Administration employment
  ) |>
  dplyr::select(
    GEOID,
```

```
    TOTAL_EMP,
    AGR_FOR_FI,
    MINING,
    CONSTRUCTI,
    MANUFACTUR,
    TRANSP_COM,
    WHOLESALE,
    RETAIL,
    FIRE,
    SERVICES,
    PUBLIC_ADM
  )

lscog_emp
```

```
# A tibble: 2,450 × 12
   GEOID  TOTAL_EMP AGR_FOR_FI MINING CONSTRUCTI MANUFACTUR TRANSP_COM WHOLESALE
   <chr>      <dbl>      <dbl>  <dbl>      <dbl>      <dbl>      <dbl>     <dbl>
 1 45003…         6          6      0          0          0          0         0
 2 45003…         4          0      0          0          0          4         0
 3 45003…        12          0      0         12          0          0         0
 4 45003…         1          0      0          0          0          0         0
 5 45003…        11         11      0          0          0          0         0
 6 45003…         1          0      0          0          0          0         0
 7 45003…         9          0      0          0          0          0         0
 8 45003…        18          0      0         18          0          0         0
 9 45003…         1          0      0          1          0          0         0
10 45003…         4          4      0          0          0          0         0
# ℹ 2,440 more rows
# ℹ 4 more variables: RETAIL <dbl>, FIRE <dbl>, SERVICES <dbl>,
#   PUBLIC_ADM <dbl>
```

Python

```
# Download LEHD WAC data at block level
lscog_emp = get_lodes(
    state=state_abb,
    year=2019,
    version="LODES8",
    lodes_type="wac",
    part="main",
    segment="S000",
    job_type="JT00",
```

```
    agg_level="block",
    cache=True,
    return_geometry=False
)

# Filter for specific FIPS codes
lscog_emp
= lscog_emp[lscog_emp['w_geocode'].str.match(f"^({'|'.join(fips_codes)})")]

# Create new columns with employment categories
#  Check  documentation  at:  https://lehd.ces.census.gov/data/lodes/LODES8/
LODESTechDoc8.0.pdf
lscog_emp = lscog_emp.assign(
    GEOID=lscog_emp['w_geocode'].astype(str),
    TOTAL_EMP=lscog_emp['C000'],  # Total Employment
      AGR_FOR_FI=lscog_emp['CNS01'],  # Agricultural, forestry, and fishing
employment
    MINING=lscog_emp['CNS02'],  # Mining employment
    CONSTRUCTI=lscog_emp['CNS04'],  # Construction employment
    MANUFACTUR=lscog_emp['CNS05'],  # Manufacturing employment
      TRANSP_COM=lscog_emp['CNS08'] + lscog_emp['CNS09'],  # Transportation,
communication employment
    WHOLESALE=lscog_emp['CNS06'],  # Wholesale employment
    RETAIL=lscog_emp['CNS07'],  # Retail employment
    FIRE=lscog_emp['CNS10'] + lscog_emp['CNS11'],  # Finance / Insurance / Real
Estate employment
    SERVICES=(lscog_emp['CNS03'] +
              lscog_emp['CNS12'] +
              lscog_emp['CNS13'] +
              lscog_emp['CNS14'] +
              lscog_emp['CNS15'] +
              lscog_emp['CNS16'] +
              lscog_emp['CNS17'] +
              lscog_emp['CNS18'] +
              lscog_emp['CNS19']),  # Service employment
    PUBLIC_ADM=lscog_emp['CNS20']  # Public Administration employment
)

# Select only the desired columns
lscog_emp  =  lscog_emp[['GEOID',  'TOTAL_EMP',  'AGR_FOR_FI',  'MINING',
'CONSTRUCTI',
                     'MANUFACTUR', 'TRANSP_COM', 'WHOLESALE', 'RETAIL', 'FIRE',
                       'SERVICES', 'PUBLIC_ADM']]
```

```
# Display structure/info about the dataframe
lscog_emp
```

```
                GEOID  TOTAL_EMP  AGR_FOR_FI  ...  FIRE  SERVICES  PUBLIC_ADM
191    450030201001001          6           6  ...     0         0           0
192    450030201001017          4           0  ...     0         0           0
193    450030201001037         12           0  ...     0         0           0
194    450030201001049          1           0  ...     0         0           0
195    450030201002006         11          11  ...     0         0           0
...                ...        ...         ...  ...   ...       ...         ...
28115  450750120002099         25           0  ...     0         0           0
28116  450750120002108          8           0  ...     0         0           0
28117  450750120002118          3           0  ...     0         0           0
28118  450750120004038          3           0  ...     0         0           0
28119  450750120004071          6           0  ...     0         5           0

[2450 rows x 12 columns]
```

2020 NCES school and college enrollment data

The National Center for Education Statistics provides comprehensive educational institution data including enrollment and staffing information for transportation planning analysis.

Public schools

Public school data is made available by National Center for Education Statistics through their Common Core of Data (CCD) program. For ease of processing, we retrieve the CCD from the ArcGIS REST service for the 2019-2020 academic year. The dataset includes total student enrollment and full-time equivalent teacher counts for each institution within the six-county region. Public schools represent major trip generation sources for both student and employee travel, requiring precise spatial location data for accurate modeling. > For more information on the NCES Public School data, refer to CCD Online Documentation.

To retrieve the data, we check if a local copy exists to ensure reproducibility and offline capability. If unavailable, we query the ArcGIS REST service and save a local copy.

R

```
# Define local path for public schools
pub_sch_path <- file.path(data_dir, "lscog_pub_sch_enroll.gpkg")

if (file.exists(pub_sch_path)) {
  # Load from local if exists
  lscog_pub_sch_enroll <- sf::read_sf(pub_sch_path)
```

```
} else {
  # Public School Location data 2019-2020 via API
  lscog_pub_sch_enroll <- arcgislayers::arc_read(
    url = "https://nces.ed.gov/opengis/rest/services/K12_School_Locations/EDGE_
ADMINDATA_PUBLICSCH_1920/MapServer/0",
    where = paste0(
      "LSTATE = '",
      state_abb,
      "' AND NMCNTY IN (",
      paste0("'", paste0(county_names, " County"), "'", collapse = ", "),
      ")"
    ),
    alias = "label",
    crs = project_crs
  ) |>
    dplyr::select(
      INSTITUTION_ID = NCESSCH,
      NAME = SCH_NAME,
      STATE = LSTATE,
      STUDENT_COUNT_PUB = TOTAL,
      TEACHER_COUNT_PUB = FTE
    )

  # Save locally for future use
  sf::write_sf(lscog_pub_sch_enroll, pub_sch_path)
}

lscog_pub_sch_enroll
```

```
Simple feature collection with 98 features and 5 fields
Geometry type: POINT
Dimension:     XY
Bounding box:  xmin: 1700952 ymin: 406810.6 xmax: 2203406 ymax: 724699.4
Projected CRS: NAD83(HARN) / South Carolina (ft)
# A tibble: 98 × 6
   INSTITUTION_ID NAME                STATE STUDENT_COUNT_PUB TEACHER_COUNT_PUB
   <chr>          <chr>               <chr>             <dbl>             <dbl>
 1 450108001163   Barnwell Elementary  SC                 462              32
 2 450075000064   Allendale Fairfax H… SC                 283              28.9
 3 450075001184   Allendale Elementary SC                 245              18
 4 450075001415   Allendale-Fairfax M… SC                 268              18
 5 450093000119   Bamberg-Ehrhardt Hi… SC                 381              28.5
```

```
 6 450093000120   Bamberg-Ehrhardt Mi… SC                188             15
 7 450096000122   Denmark Olar High    SC                162             20
 8 450096000123   Denmark-Olar Middle  SC                149             10
 9 450096001426   Denmark-Olar Elemen… SC                353             25
10 450098000127   Barnwell County Car… SC                  0             12
# ℹ 88 more rows
# ℹ 1 more variable: geom <POINT [foot]>
```

Python

```python
# Create function to read ArcGIS FeatureLayer or Table
def arc_read(url, where="1=1", outFields="*", outSR=4326, **kwargs):
    """
    Read an ArcGIS FeatureLayer or Table to a GeoDataFrame.
    """

    # Ensure URL ends with /query
    if not url.endswith('/query'):
        url = url.rstrip('/') + '/query'

    # Build query parameters
    params = {
        'where': where,
        'outFields': outFields,
        'returnGeometry': 'true',
        # 'geometryType': 'esriGeometryPoint',
        'outSR': outSR,
        'f': 'geojson'
    }

    # Add any additional parameters
    params.update(kwargs)

    # Make request
    response = requests.get(url, params=params)

    # Read as GeoDataFrame
    return gpd.read_file(response.text)
```

```python
# Define local path for public schools (using pathlib)
pub_sch_path = data_dir / "lscog_pub_sch_enroll.gpkg"

if pub_sch_path.exists():
```

```
    # Load from local if exists
    lscog_pub_sch_enroll = gpd.read_file(pub_sch_path)
else:
    # Public School Enrollment data 2019-2020 via API
    lscog_pub_sch_enroll = arc_read(
          url="https://nces.ed.gov/opengis/rest/services/K12_School_Locations/
EDGE_ADMINDATA_PUBLICSCH_1920/MapServer/0",
         where=f"LSTATE = '{state_abb}' AND NMCNTY IN ('{"', '".join([f"{name}
County" for name in county_names])}')",
        outFields='NCESSCH,SCH_NAME,LSTATE,TOTAL,FTE'
    )

    # Transform CRS
    lscog_pub_sch_enroll = lscog_pub_sch_enroll.to_crs(project_crs)

    # Select and rename columns
    lscog_pub_sch_enroll = lscog_pub_sch_enroll.rename(columns={
        'NCESSCH': 'INSTITUTION_ID',
        'SCH_NAME': 'NAME',
        'LSTATE': 'STATE',
        'TOTAL': 'STUDENT_COUNT_PUB',
        'FTE': 'TEACHER_COUNT_PUB'
    })

    # Save locally
    lscog_pub_sch_enroll.to_file(pub_sch_path, driver="GPKG")

lscog_pub_sch_enroll
```

```
   INSTITUTION_ID  ...                        geometry
0    450108001163  ...   POINT (1891531.15 517378.522)
1    450075000064  ...  POINT (1913416.324 420526.584)
2    450075001184  ...  POINT (1916344.406 418212.158)
3    450075001415  ...  POINT (1913416.324 420526.584)
4    450093000119  ...  POINT (1991502.166 535259.126)
..            ...  ...                            ...
93   450391001291  ...  POINT (2048659.655 606359.394)
94   450391001370  ...   POINT (2040864.57 608978.343)
95   450391001604  ...  POINT (2050403.157 617577.875)
96   450391001693  ...  POINT (2030129.868 597634.487)
97   450391001694  ...   POINT (2043556.154 596565.29)
```

```
[98 rows x 6 columns]
```

Private schools

Private school enrollment data is accessed from the NCES Private School Universe Survey (PSS) archived dataset. The data is spatially enabled using latitude and longitude coordinates and filtered to include only institutions within the study area TAZ boundaries. Private schools contribute to the regional education trip matrix and must be incorporated alongside public institutions for comprehensive coverage. > For more information on the NCES Private Schools data, refer to PSS Online Documentation.

We download the raw ZIP file to the local data folder if it is not already present.

R

```r
# Private School Data Setup
pss_url <- "https://nces.ed.gov/surveys/pss/zip/pss1920_pu_csv.zip"
pss_folder <- file.path(data_dir, "PSS - Private")
pss_zip_path <- file.path(pss_folder, "pss1920_pu_csv.zip")

# Ensure folder exists
dir.create(pss_folder, showWarnings = FALSE, recursive = TRUE)

# Check and download
if (!file.exists(pss_zip_path)) {
  download.file(pss_url, destfile = pss_zip_path, mode = "wb")
}

# Private School Enrollment data 2019-2020
lscog_pvt_sch_enroll <- vroom::vroom(
  unz(pss_zip_path, "pss1920_pu.csv"),
  col_types = vroom::cols_only(
    PPIN        = vroom::col_character(),
    PINST       = vroom::col_character(),
    PL_STABB    = vroom::col_character(),
    PCNTNM      = vroom::col_character(),
    SIZE        = vroom::col_double(),
    NUMTEACH    = vroom::col_double(),
    LATITUDE20  = vroom::col_double(),
    LONGITUDE20 = vroom::col_double()
  )
) |>
  sf::st_as_sf(coords = c("LONGITUDE20", "LATITUDE20"), crs = "EPSG:4326") |>
  sf::st_transform(project_crs) |>
```

```r
  sf::st_filter(lscog_taz, .predicate = st_intersects) |>
  dplyr::select(
    INSTITUTION_ID = PPIN,
    NAME = PINST,
    STATE = PL_STABB,
    STUDENT_COUNT_PVT = SIZE,
    TEACHER_COUNT_PVT = NUMTEACH
  )

lscog_pvt_sch_enroll
```

```
Simple feature collection with 24 features and 5 fields
Geometry type: POINT
Dimension:     XY
Bounding box:  xmin: 1704062 ymin: 492304.2 xmax: 2179510 ymax: 720184.2
Projected CRS: NAD83(HARN) / South Carolina (ft)
# A tibble: 24 × 6
   INSTITUTION_ID NAME                STATE STUDENT_COUNT_PVT TEACHER_COUNT_PVT
   <chr>          <chr>               <chr>             <dbl>             <dbl>
 1 K9305823       AIKENS FBC PRESCHOOL SC                    1               1.3
 2 01264947       ANDREW JACKSON ACAD… SC                    3              13.3
 3 A9106158       BARNWELL CHRISTIAN … <NA>                  2               5.8
 4 01263568       CALHOUN ACADEMY      SC                    3              26.6
 5 A1771477       FIRST BAPTIST CHURC… <NA>                  1               3.1
 6 A9703151       FIRST PRESBYTERIAN … <NA>                  1               2.8
 7 BB170334       FIRST SOUTHERN METH… SC                    1               6
 8 A1102039       FOUNDATION CHRISTIA… <NA>                  1               5
 9 A0307976       GRACE CHILD DEVELOP… <NA>                  1               2.9
10 A0307978       GREATER FAITH BAPTI… <NA>                  1               1
# ℹ 14 more rows
# ℹ 1 more variable: geometry <POINT [foot]>
```

Python

```python
# Private School Data Setup
pss_url = "https://nces.ed.gov/surveys/pss/zip/pss1920_pu_csv.zip"
pss_folder = data_dir / "PSS - Private"
pss_zip_path = pss_folder / "pss1920_pu_csv.zip"

# Ensure folder exists
pss_folder.mkdir(parents=True, exist_ok=True)

# Check and download if missing
```

```
if not pss_zip_path.exists():
    response = requests.get(pss_url)
    with open(pss_zip_path, 'wb') as f:
        f.write(response.content)

# Private School Enrollment data 2019-2020
with zipfile.ZipFile(pss_zip_path, 'r') as zip_ref:
    with zip_ref.open('pss1920_pu.csv') as csv_file:
        lscog_pvt_sch_enroll = pd.read_csv(
            csv_file,
            usecols=['PPIN', 'PINST', 'PL_STABB', 'PCNTNM', 'SIZE', 'NUMTEACH',
'LATITUDE20', 'LONGITUDE20'],
            dtype={'PPIN': 'str', 'PINST': 'str', 'PL_STABB': 'str', 'PCNTNM':
'str', 'SIZE': 'float64', 'NUMTEACH': 'float64'}
        )

lscog_pvt_sch_enroll = gpd.GeoDataFrame(
    lscog_pvt_sch_enroll,
              geometry=gpd.points_from_xy(lscog_pvt_sch_enroll['LONGITUDE20'],
lscog_pvt_sch_enroll['LATITUDE20']),
    crs='EPSG:4326'
).to_crs(project_crs)

lscog_pvt_sch_enroll = gpd.sjoin(lscog_pvt_sch_enroll, lscog_taz, how='inner',
predicate='intersects')[
    ['PPIN', 'PINST', 'PL_STABB', 'SIZE', 'NUMTEACH', 'geometry']
].rename(columns={
    'PPIN': 'INSTITUTION_ID',
    'PINST': 'NAME',
    'PL_STABB': 'STATE',
    'SIZE': 'STUDENT_COUNT_PVT',
    'NUMTEACH': 'TEACHER_COUNT_PVT'
})

lscog_pvt_sch_enroll
```

```
      INSTITUTION_ID  ...                        geometry
17469       K9305823  ...  POINT (1781275.702 629440.997)
17474       01264947  ...   POINT (1993756.78 492304.247)
17476       A9106158  ...   POINT (1914982.59 524548.558)
17484       01263568  ...  POINT (2072197.427 660303.544)
17533       A1771477  ...  POINT (1704061.773 606321.234)
```

```
17537       A9703151  ...  POINT (1780623.642 630282.337)
17538       BB170334  ...   POINT (2037420.57 608741.769)
17543       A1102039  ...  POINT (2006658.982 720184.199)
17547       A0307976  ...   POINT (1704601.274 606316.17)
17550       A0307978  ...  POINT (2047302.618 604573.723)
17566       A1904026  ...  POINT (2179509.785 547981.083)
17571       01263692  ...  POINT (1918041.289 549840.623)
17599       01264754  ...  POINT (1779301.654 629488.248)
17601       A0308015  ...  POINT (1733987.726 611499.727)
17623       A1303185  ...   POINT (1853302.82 681159.161)
17637       A9903938  ...   POINT (2047246.79 597082.682)
17651       A0109147  ...  POINT (1780574.399 631607.375)
17657       01264288  ...  POINT (1778262.542 613244.891)
17658       K9305825  ...  POINT (1779510.666 617490.702)
17663       K9305640  ...   POINT (2041004.71 611841.216)
17672       A9703170  ...   POINT (1780823.53 629681.358)
17676       01262826  ...   POINT (1781344.96 628712.135)
17722       01932407  ...   POINT (2037497.91 608547.947)
17733       A9903957  ...  POINT (1875514.037 565892.953)

[24 rows x 6 columns]
```

Post-secondary institutions

Post-secondary institution locations are obtained from the NCES Integrated Postsecondary Education Data System (IPEDS), filtered by state and county FIPS codes. These institutions generate significant travel demand through student commuting, employee travel, and visitor trips, making them essential components of the regional transportation network analysis. > For more information on the NCES Post-Secondary Education data, refer to IPEDS Documentation.

R

```r
# Define local path for colleges
college_path <- file.path(data_dir, "lscog_college_loc.gpkg")

if (file.exists(college_path)) {
  # Load from local
  lscog_college_loc <- sf::read_sf(college_path)
} else {
  # Post-Secondary Location data 2019-2020 via API
  lscog_college_loc <- arcgislayers::arc_read(
       url  =  "https://nces.ed.gov/opengis/rest/services/Postsecondary_School_
Locations/EDGE_GEOCODE_POSTSECONDARYSCH_1920/MapServer/0",
    where = paste0(
```

```
      "STATE = '",
      state_abb,
      "' AND CNTY IN (",
      paste0("'", fips_codes, "'", collapse = ", "),
      ")"
    ),
    alias = "label",
    crs = project_crs
  )

  # Save locally
  sf::write_sf(lscog_college_loc, college_path)
}

lscog_college_loc
```

```
Simple feature collection with 11 features and 24 fields
Geometry type: POINT
Dimension:     XY
Bounding box:  xmin: 1708029 ymin: 429827.9 xmax: 2052011 ymax: 633710.3
Projected CRS: NAD83(HARN) / South Carolina (ft)
# A tibble: 11 × 25
   OBJECTID UNITID NAME       STREET CITY  STATE ZIP   STFIP CNTY  NMCNTY LOCALE
      <dbl> <chr>  <chr>      <chr>  <chr> <chr> <chr> <chr> <chr> <chr>  <chr>
 1     3411 217615 Aiken Tec… 2276 … Gran… SC    29829 45    45003 Aiken… 41
 2     3424 217873 Claflin U… 400 M… Oran… SC    2911… 45    45075 Orang… 32
 3     3431 217989 Denmark T… 1126 … Denm… SC    29042 45    45009 Bambe… 41
 4     3439 218159 Kenneth S… 1113 … Nort… SC    29841 45    45003 Aiken… 21
 5     3448 218487 Orangebur… 3250 … Oran… SC    2911… 45    45075 Orang… 41
 6     3451 218645 Universit… 471 U… Aiken SC    29801 45    45003 Aiken… 21
 7     3455 218681 Universit… 465 J… Alle… SC    2981… 45    45005 Allen… 41
 8     3459 218733 South Car… 300 C… Oran… SC    2911… 45    45075 Orang… 32
 9     3468 218919 Voorhees … 481 P… Denm… SC    29042 45    45009 Bambe… 32
10     5829 457998 Aiken Sch… 225 R… Aiken SC    29801 45    45003 Aiken… 21
11     6683 488022 Barber Te… 1650 … Oran… SC    2911… 45    45075 Orang… 32
# ℹ 14 more variables: LAT <dbl>, LON <dbl>, CBSA <chr>, NMCBSA <chr>,
#   CBSATYPE <chr>, CSA <chr>, NMCSA <chr>, NECTA <chr>, NMNECTA <chr>,
#   CD <chr>, SLDL <chr>, SLDU <chr>, SCHOOLYEAR <chr>, geom <POINT [foot]>
```

Python

```
# Define local path for colleges
college_path = data_dir / "lscog_college_loc.gpkg"
```

```
if college_path.exists():
    # Load from local
    lscog_college_loc = gpd.read_file(college_path)
else:
    # Post-Secondary Location data 2019-2020 via API
    lscog_college_loc = arc_read(
          url="https://nces.ed.gov/opengis/rest/services/Postsecondary_School_
Locations/EDGE_GEOCODE_POSTSECONDARYSCH_1920/MapServer/0",
        where=f"STATE = '{state_abb}' AND CNTY IN ('{"', '".join([f"{fip}" for
fip in fips_codes])}')",
        outFields='*',
        outSR=project_crs
    )

    lscog_college_loc = lscog_college_loc.to_crs(project_crs)

    # Save locally
    lscog_college_loc.to_file(college_path, driver="GPKG")

lscog_college_loc
```

```
    OBJECTID  UNITID  ... SCHOOLYEAR                       geometry
0     3411.0  217615  ...  2019-2020  POINT (1743560.226 619744.344)
1     3424.0  217873  ...  2019-2020  POINT (2044403.737 605856.318)
2     3431.0  217989  ...  2019-2020   POINT (1962235.38 538509.913)
3     3439.0  218159  ...  2019-2020  POINT (1708029.351 606866.311)
4     3448.0  218487  ...  2019-2020  POINT (2052010.971 622751.254)
5     3451.0  218645  ...  2019-2020  POINT (1766227.602 633710.252)
6     3455.0  218681  ...  2019-2020  POINT (1907482.121 429827.948)
7     3459.0  218733  ...  2019-2020  POINT (2046109.999 605685.593)
8     3468.0  218919  ...  2019-2020  POINT (1960939.294 536271.874)
9     5829.0  457998  ...  2019-2020  POINT (1781522.415 628812.761)
10    6683.0  488022  ...  2019-2020  POINT (2043606.054 603654.118)

[11 rows x 25 columns]
```

Clean data

The data cleaning process involves harmonizing multiple Census data sources to create a comprehensive socioeconomic dataset at the census block level. This requires careful interpolation and integration of American Community Survey (ACS) estimates with Decennial Census counts to maintain spatial consistency and statistical accuracy.

Household-weighted interpolation

The interpolation process transfers ACS block group data to individual census blocks using household counts as weights. This method ensures that socioeconomic characteristics are distributed proportionally based on residential density rather than simple geometric overlay. The `{tidycensus}` package provides robust interpolation functionality that preserves the extensive nature of count variables while maintaining spatial relationships. For Python, the `interpolate_pw()` function is implemented to achieve similar functionality using population-weighted interpolation.

R

```
# Interpolate ACS data to Decennial Census blocks
lscog_acs_cb <- tidycensus::interpolate_pw(
  from = lscog_acs,
  to = lscog_dec,
  to_id = "GEOID",
  extensive = TRUE,
  weights = lscog_dec,
  crs = project_crs,
  weight_column = "HH"
)

lscog_acs_cb
```

```
Simple feature collection with 13961 features and 5 fields
Geometry type: MULTIPOLYGON
Dimension:     XY
Bounding box:  xmin: 1691517 ymin: 331891.7 xmax: 2237472 ymax: 744669.5
Projected CRS: NAD83(HARN) / South Carolina (ft)
# A tibble: 13,961 × 6
   GEOID                      geometry INC_TOTAL INC_14999 INC_49999 INC_50000
   <chr>           <MULTIPOLYGON [foot]>     <dbl>     <dbl>     <dbl>     <dbl>
 1 4501795040… (((2084301 622308.5, 208…      0        0         0         0
 2 4501795040… (((2112519 626782.2, 211…      0        0         0         0
 3 4501795020… (((2067775 662339.5, 206…     20.6      4.27      7.56      8.72
 4 4501795040… (((2087947 684345.6, 208…      0        0         0         0
 5 4507501050… (((2089073 552687.4, 208…      5.78     1.94      0.924     2.92
 6 4507501170… (((2046694 542273.9, 204…      2.48     0.393     1.30      0.780
 7 4507501170… (((2056704 510850.5, 205…      0        0         0         0
 8 4507501180… (((1960896 587381.7, 196…      3.19     0.694     1.42      1.08
 9 4507501200… (((2000969 657869.3, 200…      0        0         0         0
10 4501795010… (((2016178 708106.6, 201…      0        0         0         0
# ℹ 13,951 more rows
```

Python

```python
def interpolate_pw(from_gdf, to_gdf, weights_gdf, to_id=None, extensive=True,
                   weight_column=None, weight_placement='surface', crs=None):
    """
    Population-weighted areal interpolation between geometries.
    (Full function implementation hidden for brevity)
    """

    # Input validation
    if not all(isinstance(gdf, gpd.GeoDataFrame) for gdf in [from_gdf, to_gdf,
weights_gdf]):
        raise ValueError("All inputs must be GeoDataFrames")

    # Make copies to avoid modifying originals
    from_gdf = from_gdf.copy()
    to_gdf = to_gdf.copy()
    weights_gdf = weights_gdf.copy()

    # Set CRS if provided
    if crs:
        from_gdf = from_gdf.to_crs(crs)
        to_gdf = to_gdf.to_crs(crs)
        weights_gdf = weights_gdf.to_crs(crs)

    # Check CRS consistency
    if not (from_gdf.crs == to_gdf.crs == weights_gdf.crs):
        raise ValueError("All inputs must have the same CRS")

    # Handle to_id
    if to_id is None:
        to_id = 'id'
        to_gdf[to_id] = to_gdf.index.astype(str)

    # Remove conflicting columns
    if to_id in from_gdf.columns:
        from_gdf = from_gdf.drop(columns=[to_id])

    # Create unique from_id
    from_id = 'from_id'
    from_gdf[from_id] = from_gdf.index.astype(str)

    # Handle weight column
    if weight_column is None:
```

```
        weight_column = 'interpolation_weight'
        weights_gdf[weight_column] = 1.0
    else:
        # Rename to avoid conflicts
        weights_gdf['interpolation_weight'] = weights_gdf[weight_column]
        weight_column = 'interpolation_weight'

    # Convert weights to points if needed
    if weights_gdf.geometry.geom_type.iloc[0] in ['Polygon', 'MultiPolygon']:
        if weight_placement == 'surface':
            weights_gdf = weights_gdf.copy()
            weights_gdf.geometry = weights_gdf.geometry.representative_point()
        elif weight_placement == 'centroid':
            weights_gdf = weights_gdf.copy()
            weights_gdf.geometry = weights_gdf.geometry.centroid
        else:
           raise ValueError("weight_placement must be 'surface' or 'centroid'")

    # Keep only weight column and geometry
    weight_points = weights_gdf[[weight_column, 'geometry']].copy()

    # Calculate denominators (total weights per source geometry)
    with warnings.catch_warnings():
        warnings.filterwarnings('ignore', category=UserWarning)
            source_weights = gpd.sjoin(from_gdf, weight_points, how='left',
predicate='contains')

    denominators = (source_weights.groupby(from_id)[weight_column]
                    .sum()
                    .reset_index()
                    .rename(columns={weight_column: 'weight_total'}))

    # Calculate intersections between from and to
    with warnings.catch_warnings():
        warnings.filterwarnings('ignore', category=UserWarning)
        intersections = gpd.overlay(from_gdf, to_gdf, how='intersection')

    # Filter to keep only polygon intersections

intersections = intersections[intersections.geometry.geom_type.isin(['Polygon',
'MultiPolygon', 'GeometryCollection'])]

    if len(intersections) == 0:
         raise ValueError("No valid polygon intersections found between source
```

```
and target geometries")

    # Add intersection ID
    intersections['intersection_id'] = range(len(intersections))

     # Spatial join intersections with weight points to get weights within
each intersection
    with warnings.catch_warnings():
        warnings.filterwarnings('ignore', category=UserWarning)
     intersection_weights = gpd.sjoin(intersections, weight_points, how='left',
predicate='contains')

    # Calculate intersection values (sum of weights per intersection)
       intersection_values  =  (intersection_weights.groupby('intersection_id')
[weight_column]
                         .sum()
                         .reset_index()
                        .rename(columns={weight_column: 'intersection_value'}))

    # Merge back to intersections and keep only unique intersections
                intersections    =    intersections.merge(intersection_values,
on='intersection_id', how='left')
                                    intersections['intersection_value']        =
intersections['intersection_value'].fillna(0)

    # Remove duplicates created by the spatial join
    intersections = intersections.drop_duplicates(subset='intersection_id')

    # Merge with denominators to calculate weight coefficients
    intersections = intersections.merge(denominators, on=from_id, how='left')
    intersections['weight_total'] = intersections['weight_total'].fillna(1)

   # Calculate weight coefficients (intersection weight / total weight in source)
    intersections.loc[intersections['weight_total'] > 0, 'weight_coef'] = (
        intersections['intersection_value'] / intersections['weight_total']
    )
    intersections['weight_coef'] = intersections['weight_coef'].fillna(0)

    # Get numeric columns from source data
    numeric_cols = from_gdf.select_dtypes(include=[np.number]).columns
    # Remove ID columns
    numeric_cols = [col for col in numeric_cols if col not in [from_id]]
```

```
    # Prepare intersection data for interpolation
       intersection_data = intersections[[from_id, to_id, 'weight_coef'] +
numeric_cols].copy()

    if extensive:
         # For extensive variables: multiply by weight coefficient, then sum
by target
        for col in numeric_cols:
                        intersection_data[col] = intersection_data[col] *
intersection_data['weight_coef']

        interpolated = (intersection_data.groupby(to_id)[numeric_cols]
                        .sum()
                        .reset_index())
    else:
        # For intensive variables: weighted average
        interpolated_data = []
        for target_id in intersection_data[to_id].unique():
         target_data = intersection_data[intersection_data[to_id] == target_id]
           if len(target_data) > 0 and target_data['weight_coef'].sum() > 0:
               weighted_vals = {}
               for col in numeric_cols:
                                   weighted_vals[col] = (target_data[col] *
target_data['weight_coef']).sum() / target_data['weight_coef'].sum()
               weighted_vals[to_id] = target_id
               interpolated_data.append(weighted_vals)

        interpolated = pd.DataFrame(interpolated_data)

    # Merge with target geometries
        result = to_gdf[[to_id, 'geometry']].merge(interpolated, on=to_id,
how='left')

    # Fill NaN values with 0 for missing interpolations
    for col in numeric_cols:
        if col in result.columns:
            result[col] = result[col].fillna(0)

    return result
```

```
# Interpolate ACS data to Decennial Census blocks
lscog_acs_cb = interpolate_pw(
```

```
    from_gdf=lscog_acs,
    to_gdf=lscog_dec,
    weights_gdf=lscog_dec,
    to_id='GEOID',
    extensive=True,
    weight_column='HH',
    crs=project_crs
)

lscog_acs_cb.head()
```

```
             GEOID  ... INC_50000
0  450179504004051  ...  0.000000
1  450179504003011  ...  0.000000
2  450179502011045  ...  8.723288
3  450179504001020  ...  0.000000
4  450750105003029  ...  2.916335

[5 rows x 6 columns]
```

The comparative visualization reveals the increased spatial resolution achieved through interpolation. Block-level data provides more granular detail for transportation modeling applications, enabling better representation of local variations in income distribution across the study area.

R

```
# Compare before and after interpolation
mapview::mapview(lscog_acs_cb, zcol = "INC_49999", color = NA) |
mapview::mapview(lscog_acs, zcol = "INC_49999", color = NA)
```

Python

```
# Compare before and after interpolation
lscog_acs_cb.explore(column="INC_49999",       color="blue",       legend=True,
tiles="CartoDB positron") |\
           lscog_acs.explore(column="INC_49999",   color="red",   legend=True,
tiles="CartoDB positron")
```

Combine population and households

The integration step merges the interpolated ACS socioeconomic data with the Decennial Census population and household counts. This join operation creates a unified dataset containing both demographic totals and detailed characteristics at the census block level. The left join ensures that

all census blocks retain their geographic boundaries while incorporating available socioeconomic attributes.

R

```
## Combine ACS Data to Decennial data
lscog_pop_hh <- lscog_dec |>
  dplyr::left_join(
    sf::st_drop_geometry(lscog_acs_cb),
    by = dplyr::join_by(GEOID)
  )

lscog_pop_hh
```

```
Simple feature collection with 13961 features and 14 fields
Geometry type: MULTIPOLYGON
Dimension:     XY
Bounding box:  xmin: 1691517 ymin: 331891.7 xmax: 2237472 ymax: 744669.5
Projected CRS: NAD83(HARN) / South Carolina (ft)
# A tibble: 13,961 × 15
   GEOID           TOTPOP GQPOP HHPOP    HH  HH_1  HH_2  HH_3  HH_4    DU
   <chr>            <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
 1 450179504004051      0     0     0     0     0     0     0     0     0
 2 450179504003011      0     0     0     0     0     0     0     0     0
 3 450179502011045     54     4    50    16     3     1     3     9    18
 4 450179504001020      0     0     0     0     0     0     0     0     0
 5 450750105003029     13     0    13     4     0     3     0     1     4
 6 450750117021009     10     0    10     3     3     0     0     0     8
 7 450750117011051      0     0     0     0     0     0     0     0     0
 8 450750118021087      6     0     6     4     0     1     2     1     4
 9 450750120003020      0     0     0     0     0     0     0     0     0
10 450179501003046     18     0    18     0     0     0     0     0     1
# ℹ 13,951 more rows
# ℹ 5 more variables: geometry <MULTIPOLYGON [foot]>, INC_TOTAL <dbl>,
#   INC_14999 <dbl>, INC_49999 <dbl>, INC_50000 <dbl>
```

Python

```
## Combine ACS Data to Decennial data
lscog_pop_hh = lscog_dec.merge(
    lscog_acs_cb.drop(columns=['geometry']),
    on='GEOID',
    how='left'
)
```

```
lscog_pop_hh
```

```
                GEOID  TOTPOP  GQPOP  ...  INC_14999  INC_49999  INC_50000
0      450179504004051       0      0  ...   0.000000   0.000000   0.000000
1      450179504003011       0      0  ...   0.000000   0.000000   0.000000
2      450179502011045      54      4  ...   4.273973   7.561644   8.723288
3      450179504001020       0      0  ...   0.000000   0.000000   0.000000
4      450750105003029      13      0  ...   1.944223   0.924303   2.916335
...                ...     ...    ...  ...        ...        ...        ...
13956  450059705003050       5      0  ...   0.000000   0.000000   0.000000
13957  450030203042000       0      0  ...   0.000000   0.000000   0.000000
13958  450030218002115       8      0  ...   0.101167   0.470817   0.295720
13959  450030206012008       0      0  ...   0.000000   0.000000   0.000000
13960  450059705002005       0      0  ...   0.000000   0.000000   0.000000

[13961 rows x 15 columns]
```

Income category adjustments reconcile the interpolated ACS estimates with actual household counts from the Decennial Census. The proportional allocation method redistributes income categories based on the ratio of interpolated totals to observed household counts, maintaining consistency between data sources. The three-tier income classification (under $15,000, $15,000-$49,999, and $50,000 and above) provides sufficient granularity for travel demand modeling while ensuring statistical reliability.

R

```r
## Combine adjusted HH income level to Decennial census instead of ACS
lscog_pop_hh <- lscog_pop_hh |>
  dplyr::mutate(
    INC_49999 = tidyr::replace_na(round(INC_49999 / INC_TOTAL * HH, 0), 0),
    INC_50000 = tidyr::replace_na(round(INC_50000 / INC_TOTAL * HH, 0), 0),
    INC_14999 = HH - (INC_49999 + INC_50000)
  ) |>
  dplyr::select(-INC_TOTAL)

lscog_pop_hh
```

```
Simple feature collection with 13961 features and 13 fields
Geometry type: MULTIPOLYGON
Dimension:     XY
Bounding box:  xmin: 1691517 ymin: 331891.7 xmax: 2237472 ymax: 744669.5
```

```
Projected CRS: NAD83(HARN) / South Carolina (ft)
# A tibble: 13,961 × 14
   GEOID           TOTPOP GQPOP HHPOP    HH  HH_1  HH_2  HH_3  HH_4    DU
   <chr>            <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
 1 450179504004051      0     0     0     0     0     0     0     0     0
 2 450179504003011      0     0     0     0     0     0     0     0     0
 3 450179502011045     54     4    50    16     3     1     3     9    18
 4 450179504001020      0     0     0     0     0     0     0     0     0
 5 450750105003029     13     0    13     4     0     3     0     1     4
 6 450750117021009     10     0    10     3     3     0     0     0     8
 7 450750117011051      0     0     0     0     0     0     0     0     0
 8 450750118021087      6     0     6     4     0     1     2     1     4
 9 450750120003020      0     0     0     0     0     0     0     0     0
10 450179501003046     18     0    18     0     0     0     0     0     1
# ℹ 13,951 more rows
# ℹ 4 more variables: geometry <MULTIPOLYGON [foot]>, INC_14999 <dbl>,
#   INC_49999 <dbl>, INC_50000 <dbl>
```

Python

```
## Combine adjusted HH income level to Decennial census instead of ACS
lscog_pop_hh["INC_49999"]        =        ((lscog_pop_hh["INC_49999"]        /
lscog_pop_hh["INC_TOTAL"]) * lscog_pop_hh["HH"]).round().fillna(0)
lscog_pop_hh["INC_50000"]        =        ((lscog_pop_hh["INC_50000"]        /
lscog_pop_hh["INC_TOTAL"]) * lscog_pop_hh["HH"]).round().fillna(0)
lscog_pop_hh["INC_14999"] = lscog_pop_hh["HH"] - (lscog_pop_hh["INC_49999"] +
lscog_pop_hh["INC_50000"])

lscog_pop_hh = lscog_pop_hh.drop(columns="INC_TOTAL")
lscog_pop_hh
```

```
                GEOID  TOTPOP  GQPOP  ...  INC_14999  INC_49999  INC_50000
0      450179504004051       0      0  ...        0.0        0.0        0.0
1      450179504003011       0      0  ...        0.0        0.0        0.0
2      450179502011045      54      4  ...        3.0        6.0        7.0
3      450179504001020       0      0  ...        0.0        0.0        0.0
4      450750105003029      13      0  ...        1.0        1.0        2.0
...                ...     ...    ...  ...        ...        ...        ...
13956  450059705003050       5      0  ...        0.0        0.0        0.0
13957  450030203042000       0      0  ...        0.0        0.0        0.0
13958  450030218002115       8      0  ...        0.0        1.0        0.0
13959  450030206012008       0      0  ...        0.0        0.0        0.0
13960  450059705002005       0      0  ...        0.0        0.0        0.0
```

```
[13961 rows x 14 columns]
```

Employment data

The employment integration incorporates LEHD (Longitudinal Employer-Household Dynamics) workplace area characteristics into the combined dataset. This addition provides employment counts by census block, enabling the development of trip attraction models and work-based travel pattern analysis. The merge operation maintains the geographic integrity of census blocks while adding employment variables essential for comprehensive transportation planning.

R

```r
# Join LEHD Data to the Decennial data
lscog_pop_hh_emp <- lscog_pop_hh |>
  dplyr::left_join(lscog_emp, by = dplyr::join_by(GEOID))

lscog_pop_hh_emp
```

```
Simple feature collection with 13961 features and 24 fields
Geometry type: MULTIPOLYGON
Dimension:     XY
Bounding box:  xmin: 1691517 ymin: 331891.7 xmax: 2237472 ymax: 744669.5
Projected CRS: NAD83(HARN) / South Carolina (ft)
# A tibble: 13,961 × 25
   GEOID           TOTPOP GQPOP HHPOP    HH  HH_1  HH_2  HH_3  HH_4    DU
   <chr>            <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
 1 450179504004051      0     0     0     0     0     0     0     0     0
 2 450179504003011      0     0     0     0     0     0     0     0     0
 3 450179502011045     54     4    50    16     3     1     3     9    18
 4 450179504001020      0     0     0     0     0     0     0     0     0
 5 450750105003029     13     0    13     4     0     3     0     1     4
 6 450750117021009     10     0    10     3     3     0     0     0     8
 7 450750117011051      0     0     0     0     0     0     0     0     0
 8 450750118021087      6     0     6     4     0     1     2     1     4
 9 450750120003020      0     0     0     0     0     0     0     0     0
10 450179501003046     18     0    18     0     0     0     0     0     1
# ℹ 13,951 more rows
# ℹ 15 more variables: geometry <MULTIPOLYGON [foot]>, INC_14999 <dbl>,
#   INC_49999 <dbl>, INC_50000 <dbl>, TOTAL_EMP <dbl>, AGR_FOR_FI <dbl>,
#   MINING <dbl>, CONSTRUCTI <dbl>, MANUFACTUR <dbl>, TRANSP_COM <dbl>,
#   WHOLESALE <dbl>, RETAIL <dbl>, FIRE <dbl>, SERVICES <dbl>, PUBLIC_ADM <dbl>
```

Python

```
# Join LEHD Data to the Decennial data
lscog_pop_hh_emp = lscog_pop_hh.merge(
    lscog_emp,
    on='GEOID',
    how='left'
)

lscog_pop_hh_emp
```

```
                GEOID  TOTPOP  GQPOP  ...  FIRE  SERVICES  PUBLIC_ADM
0      450179504004051       0      0  ...   NaN       NaN         NaN
1      450179504003011       0      0  ...   NaN       NaN         NaN
2      450179502011045      54      4  ...   NaN       NaN         NaN
3      450179504001020       0      0  ...   NaN       NaN         NaN
4      450750105003029      13      0  ...   NaN       NaN         NaN
...                ...     ...    ...  ...   ...       ...         ...
13956  450059705003050       5      0  ...   NaN       NaN         NaN
13957  450030203042000       0      0  ...   NaN       NaN         NaN
13958  450030218002115       8      0  ...   NaN       NaN         NaN
13959  450030206012008       0      0  ...   NaN       NaN         NaN
13960  450059705002005       0      0  ...   NaN       NaN         NaN

[13961 rows x 25 columns]
```

Export raw data

The data export process creates standardized datasets for travel demand model development, maintaining both tabular and spatial formats to support various modeling applications. All exports follow consistent file naming conventions and directory structures to facilitate model integration and data management workflows.

TAZ data

The Traffic Analysis Zone (TAZ) boundary export provides the fundamental geographic framework for the regional travel demand model. The blank TAZ file serves as a template for subsequent socioeconomic data allocation, containing only zone identification fields and geometric boundaries without attribute data.

Export as CSV flat file

R

```
# Export as CSV
lscog_taz |>
```

```r
  sf::st_drop_geometry() |>
  readr::write_csv(
    file.path(output_tabular, "lscog_taz_blank.csv"),
    append = FALSE
  )
```

Python

```python
# Export as CSV
lscog_taz.to_csv(
    output_tabular / "lscog_taz_blank.csv",
    index=False
)
```

Export as Geodatabase layer

R

```r
# Export as GDB
lscog_taz |>
  sf::write_sf(
    file.path(output_spatial, "LSCOG_2020Base_SE.gdb"),
    layer = "lscog_taz_blank",
    append = FALSE
  )
```

Python

```python
# Export as GDB
lscog_taz.to_file(
    output_spatial / "LSCOG_2020Base_SE.gdb",
    layer='lscog_taz_blank',
    driver='FileGDB'
)
```

Census blocks to TAZ conversion

The block-to-TAZ conversion table establishes the critical linkage between fine-scale Census geography and the modeling zone system. This crosswalk file enables the aggregation of block-level socioeconomic data to TAZ boundaries while maintaining traceability to source geographies.

Export as CSV flat file

R

```
# Export as CSV
lscog_cb |>
  sf::st_join(lscog_taz) |>
  dplyr::select(GEOID20, ID, TAZ_ID) |>
  sf::st_drop_geometry() |>
  readr::write_csv(
    file.path(output_tabular, "lscog_block_taz.csv"),
    append = FALSE
  )
```

Python

```
# Export as CSV
lscog_cb.merge(lscog_taz[['ID', 'TAZ_ID']], left_on='GEOID20', right_on='ID')
[['GEOID20', 'ID', 'TAZ_ID']].to_csv(
    output_tabular / "lscog_block_taz.csv",
    index=False
)
```

Decennial census data at census block level

The decennial census block export captures the foundational demographic counts used throughout the modeling process. This dataset provides the most reliable population and household totals at the finest geographic resolution, serving as the base for all subsequent data integration and validation steps.

Export as CSV flat file

R

```
# Export as CSV
lscog_dec |>
  sf::st_drop_geometry() |>
  readr::write_csv(
    file.path(output_tabular, "lscog_dec_block.csv"),
    append = FALSE
  )
```

Python

```
# Export as CSV
lscog_dec.to_csv(
    output_tabular / "lscog_dec_block.csv",
```

```
    index=False
)
```

Export as Geodatabase layer

R

```
# Export as GDB
lscog_dec |>
  sf::write_sf(
    file.path(output_spatial, "LSCOG_2020Base_SE.gdb"),
    layer = "lscog_dec_block",
    append = FALSE
  )
```

Python

```
# Export as GDB
lscog_dec.to_file(
    output_spatial / "LSCOG_2020Base_SE.gdb",
    layer='lscog_dec_block',
    driver='FileGDB'
)
```

ACS estimates at census block level

The interpolated ACS data export delivers income distribution estimates at the census block level, providing the socioeconomic stratification necessary for trip generation modeling. This processed dataset represents the final product of the household-weighted interpolation methodology, ready for direct integration into the travel demand model framework.

Export as CSV flat file

R

```
# Export as CSV
lscog_acs_cb |>
  dplyr::select(GEOID, INC_14999, INC_49999, INC_50000) |>
  sf::st_drop_geometry() |>
  readr::write_csv(
    file.path(output_tabular, "lscog_acs_block.csv"),
    append = FALSE
  )
```

Python

```
# Export as CSV
lscog_acs_cb[['GEOID', 'INC_14999', 'INC_49999', 'INC_50000']].to_csv(
    output_tabular / "lscog_acs_block.csv",
    index=False
)
```

Export as Geodatabase layer

R

```
# Export as GDB
lscog_acs_cb |>
  dplyr::select(GEOID, INC_14999, INC_49999, INC_50000) |>
  sf::write_sf(
    file.path(output_spatial, "LSCOG_2020Base_SE.gdb"),
    layer = "lscog_acs_block",
    append = FALSE
  )
```

Python

```
# Export as GDB
lscog_acs_cb[['GEOID', 'INC_14999', 'INC_49999', 'INC_50000']].to_file(
    output_spatial / "LSCOG_2020Base_SE.gdb",
    layer='lscog_acs_block',
    driver='FileGDB'
)
```

LEHD data at census block level

The employment data export provides comprehensive workplace characteristics by industry sector at the census block level. This dataset captures the spatial distribution of employment opportunities across the study region, supporting both trip attraction modeling and economic impact analysis.

Export as CSV flat file

R

```
# Export as CSV
lscog_pop_hh_emp |>
  dplyr::select(GEOID, TOTAL_EMP:PUBLIC_ADM) |>
  sf::st_drop_geometry() |>
  readr::write_csv(
```

```
    file.path(output_tabular, "lscog_emp_block.csv"),
    append = FALSE
  )
```

Python

```
# Export as CSV
lscog_pop_hh_emp[['GEOID', 'TOTAL_EMP', 'AGR_FOR_FI', 'MINING', 'CONSTRUCTI',
                  'MANUFACTUR', 'TRANSP_COM', 'WHOLESALE', 'RETAIL', 'FIRE',
                  'SERVICES', 'PUBLIC_ADM']].to_csv(
    output_tabular / "lscog_emp_block.csv",
    index=False
)
```

Export as Geodatabase layer

R

```
# Export as GDB
lscog_pop_hh_emp |>
  dplyr::select(GEOID, TOTAL_EMP:PUBLIC_ADM) |>
  sf::write_sf(
    file.path(output_spatial, "LSCOG_2020Base_SE.gdb"),
    layer = "lscog_emp_block",
    append = FALSE
  )
```

Python

```
# Export as GDB
lscog_pop_hh_emp[['GEOID', 'TOTAL_EMP', 'AGR_FOR_FI', 'MINING', 'CONSTRUCTI',
                  'MANUFACTUR', 'TRANSP_COM', 'WHOLESALE', 'RETAIL', 'FIRE',
                  'SERVICES', 'PUBLIC_ADM']].to_file(
        output_spatial / "LSCOG_2020Base_SE.gdb",
        layer='lscog_emp_block',
        driver='FileGDB'
    )
```

Public schools to TAZ

The public school location export integrates educational facility data with the TAZ system, providing essential inputs for school-related trip modeling. Student and teacher counts by facility support the development of specialized trip generation rates for educational purposes.

Export as CSV flat file

R

```r
# Export as CSV
lscog_pub_sch_enroll |>
  sf::st_join(lscog_taz |> dplyr::select(ID, TAZ_ID)) |>
  sf::st_drop_geometry() |>
  readr::write_csv(
    file.path(output_tabular, "lscog_pubsch_loc.csv"),
    append = FALSE
  )
```

Python

```python
# Export as CSV
lscog_pub_sch_enroll.sjoin(
    lscog_taz[['ID', 'TAZ_ID']],
    how='left'
)[['INSTITUTION_ID', 'NAME', 'STATE', 'STUDENT_COUNT_PUB', 'TEACHER_COUNT_PUB',
'geometry']] \
    .to_csv(
        output_tabular / "lscog_pubsch_loc.csv",
        index=False
    )
```

Export as Geodatabase layer

R

```r
# Export as GDB
lscog_pub_sch_enroll |>
  sf::st_join(lscog_taz |> dplyr::select(ID, TAZ_ID)) |>
  sf::write_sf(
    file.path(output_spatial, "LSCOG_2020Base_SE.gdb"),
    layer = "lscog_pubsch_loc",
    append = FALSE
  )
```

Python

```python
# Export as GDB
lscog_pub_sch_enroll.sjoin(
    lscog_taz[['ID', 'TAZ_ID']],
    how='left'
).to_file(
    output_spatial / "LSCOG_2020Base_SE.gdb",
```

```
    layer='lscog_pubsch_loc',
    driver='FileGDB'
)
```

Private schools to TAZ

The private school dataset complements the public education data by capturing enrollment patterns in private educational institutions. This comprehensive coverage of educational facilities ensures that all school-related travel demand is properly represented in the regional model.

Export as CSV flat file

R

```
# Export as CSV
lscog_pvt_sch_enroll |>
  sf::st_join(lscog_taz |> dplyr::select(ID, TAZ_ID)) |>
  sf::st_drop_geometry() |>
  readr::write_csv(
    file.path(output_tabular, "lscog_pvtsch_loc.csv"),
    append = FALSE
  )
```

Python

```
# Export as CSV
lscog_pvt_sch_enroll.sjoin(
    lscog_taz[['ID', 'TAZ_ID']],
    how='left'
)[['INSTITUTION_ID', 'NAME', 'STATE', 'STUDENT_COUNT_PVT', 'TEACHER_COUNT_PVT',
'geometry']] \
    .to_csv(
        output_tabular / "lscog_pvtsch_loc.csv",
        index=False
    )
```

Export as Geodatabase layer

R

```
# Export as GDB
lscog_pvt_sch_enroll |>
  sf::st_join(lscog_taz |> dplyr::select(ID, TAZ_ID)) |>
  sf::write_sf(
    file.path(output_spatial, "LSCOG_2020Base_SE.gdb"),
    layer = "lscog_pvtsch_loc",
```

```
    append = FALSE
  )
```

Python

```
# Export as GDB
lscog_pvt_sch_enroll.sjoin(
    lscog_taz[['ID', 'TAZ_ID']],
    how='left'
).to_file(
    output_spatial / "LSCOG_2020Base_SE.gdb",
    layer='lscog_pvtsch_loc',
    driver='FileGDB'
)
```

Aggregate data to TAZ

The aggregation process transforms fine-scale census block data into TAZ-level inputs suitable for travel demand modeling. This spatial aggregation preserves the total counts while organizing data according to the modeling zone structure required for trip generation and distribution analysis.

Population, households, and employment

The spatial join operation aggregates all demographic, housing, and employment variables from census blocks to their corresponding TAZs using centroid-based assignment. This process ensures that each block's socioeconomic characteristics are properly allocated to the appropriate modeling zone while maintaining data integrity through comprehensive summation of all relevant variables.

R

```
# Aggregate population, households, and employment to TAZ
lscog_taz_pop <- lscog_taz |>
  sf::st_join(
    lscog_pop_hh_emp |> sf::st_centroid(of_largest_polygon = TRUE)
  ) |>
  dplyr::group_by(
    ID,
    Area,
    TAZ_ID,
    COUNTY,
    AREA_TYPE,
    COUNTYID,
    .drop = FALSE
  ) |>
```

```
  dplyr::summarize(
    .groups = "drop",
    # Population and Household Size
    TOTPOP = sum(TOTPOP, na.rm = TRUE),
    GQPOP = sum(GQPOP, na.rm = TRUE),
    HHPOP = sum(HHPOP, na.rm = TRUE),
    HH = sum(HH, na.rm = TRUE),
    HH_1 = sum(HH_1, na.rm = TRUE),
    HH_2 = sum(HH_2, na.rm = TRUE),
    HH_3 = sum(HH_3, na.rm = TRUE),
    HH_4 = sum(HH_4, na.rm = TRUE),
    DU = sum(DU, na.rm = TRUE),
    # Household Income
    INC_14999 = sum(INC_14999, na.rm = TRUE),
    INC_49999 = sum(INC_49999, na.rm = TRUE),
    INC_50000 = sum(INC_50000, na.rm = TRUE),
    # Employment
    TOTAL_EMP = sum(TOTAL_EMP, na.rm = TRUE),
    AGR_FOR_FI = sum(AGR_FOR_FI, na.rm = TRUE),
    MINING = sum(MINING, na.rm = TRUE),
    CONSTRUCTI = sum(CONSTRUCTI, na.rm = TRUE),
    MANUFACTUR = sum(MANUFACTUR, na.rm = TRUE),
    TRANSP_COM = sum(TRANSP_COM, na.rm = TRUE),
    WHOLESALE = sum(WHOLESALE, na.rm = TRUE),
    RETAIL = sum(RETAIL, na.rm = TRUE),
    FIRE = sum(FIRE, na.rm = TRUE),
    SERVICES = sum(SERVICES, na.rm = TRUE),
    PUBLIC_ADM = sum(PUBLIC_ADM, na.rm = TRUE)
  )

lscog_taz_pop
```

```
Simple feature collection with 585 features and 29 fields
Geometry type: MULTIPOLYGON
Dimension:     XY
Bounding box:  xmin: 1691490 ymin: 331894 xmax: 2237471 ymax: 744679.9
Projected CRS: NAD83(HARN) / South Carolina (ft)
# A tibble: 585 × 30
   ID       Area TAZ_ID COUNTY AREA_TYPE COUNTYID TOTPOP GQPOP HHPOP    HH  HH_1
   <chr>   <dbl> <chr>  <chr>  <chr>     <chr>     <dbl> <dbl> <dbl> <dbl> <dbl>
 1 11050…  37.7  11050… Barnw… RURAL     45011       802     0   802   329    95
 2 11050…  21.5  11050… Barnw… RURAL     45011       715     0   715   320   118
```

```
 3 11050…  24.4  11050… Barnw… RURAL     45011      1406    79  1327   555   194
 4 11050…  17.4  11050… Barnw… RURAL     45011       712     0   712   309   109
 5 11050…  12.6  11050… Barnw… RURAL     45011       941     0   941   395    99
 6 11050… 191.   11050… Barnw… RURAL     45011         7     0     7     8     2
 7 11050…   9.69 11050… Barnw… SUBURBAN  45011       185     0   185    69    15
 8 11050…  16.5  11050… Barnw… RURAL     45011       680     0   680   274    87
 9 11050…  11.4  11050… Barnw… SUBURBAN  45011       490     0   490   221    69
10 11050…   9.02 11050… Barnw… SUBURBAN  45011       711     0   711   276    76
# ℹ 575 more rows
# ℹ 19 more variables: HH_2 <dbl>, HH_3 <dbl>, HH_4 <dbl>, DU <dbl>,
#   INC_14999 <dbl>, INC_49999 <dbl>, INC_50000 <dbl>, TOTAL_EMP <dbl>,
#   AGR_FOR_FI <dbl>, MINING <dbl>, CONSTRUCTI <dbl>, MANUFACTUR <dbl>,
#   TRANSP_COM <dbl>, WHOLESALE <dbl>, RETAIL <dbl>, FIRE <dbl>,
#   SERVICES <dbl>, PUBLIC_ADM <dbl>, geom <MULTIPOLYGON [foot]>
```

Python

```python
# Aggregate population, households, and employment to TAZ
lscog_taz_pop = (lscog_taz
    .sjoin(
     lscog_pop_hh_emp.assign(geometry=lscog_pop_hh_emp.geometry.centroid).to_crs(lscog_taz.crs),
        how='left'
    )
    .groupby(['ID', 'Area', 'TAZ_ID', 'COUNTY', 'AREA_TYPE', 'COUNTYID'],
             as_index=False, dropna=False)
    .agg({
        # Population and Household Size
        'TOTPOP': lambda x: x.sum(skipna=True),
        'GQPOP': lambda x: x.sum(skipna=True),
        'HHPOP': lambda x: x.sum(skipna=True),
        'HH': lambda x: x.sum(skipna=True),
        'HH_1': lambda x: x.sum(skipna=True),
        'HH_2': lambda x: x.sum(skipna=True),
        'HH_3': lambda x: x.sum(skipna=True),
        'HH_4': lambda x: x.sum(skipna=True),
        'DU': lambda x: x.sum(skipna=True),
        # Household Income
        'INC_14999': lambda x: x.sum(skipna=True),
        'INC_49999': lambda x: x.sum(skipna=True),
        'INC_50000': lambda x: x.sum(skipna=True),
        # Employment
        'TOTAL_EMP': lambda x: x.sum(skipna=True),
        'AGR_FOR_FI': lambda x: x.sum(skipna=True),
```

```
        'MINING': lambda x: x.sum(skipna=True),
        'CONSTRUCTI': lambda x: x.sum(skipna=True),
        'MANUFACTUR': lambda x: x.sum(skipna=True),
        'TRANSP_COM': lambda x: x.sum(skipna=True),
        'WHOLESALE': lambda x: x.sum(skipna=True),
        'RETAIL': lambda x: x.sum(skipna=True),
        'FIRE': lambda x: x.sum(skipna=True),
        'SERVICES': lambda x: x.sum(skipna=True),
        'PUBLIC_ADM': lambda x: x.sum(skipna=True),
        'geometry': 'first'
    })
)

lscog_taz_pop = gpd.GeoDataFrame(lscog_taz_pop, crs=lscog_taz.crs)
lscog_taz_pop
```

```
           ID  ...                                           geometry
0    11050058  ...  MULTIPOLYGON (((1940883.78 467711.359, 1940683...
1    11050059  ...  MULTIPOLYGON (((1909744.245 514791.296, 190990...
2    11050060  ...  MULTIPOLYGON (((1933978.652 551400.913, 193349...
3    11050061  ...  MULTIPOLYGON (((1901544.254 537296.043, 190161...
4    11050062  ...  MULTIPOLYGON (((1932677.078 512746.246, 193263...
..        ...  ...                                               ...
580   9050125  ...  MULTIPOLYGON (((1968427.616 539621.663, 196834...
581   9050126  ...  MULTIPOLYGON (((1961524.044 543029.131, 196150...
582   9050128  ...  MULTIPOLYGON (((1994408.254 547077.578, 199440...
583   9050130  ...  MULTIPOLYGON (((2046194.08 478862.054, 2046134...
584   9050132  ...  MULTIPOLYGON (((2012593.472 500179.47, 2013190...

[585 rows x 30 columns]
```

School and college enrollment

The school enrollment combination merges public and private educational institution data into a unified dataset for comprehensive coverage of student populations.

R

```
# Combine school enrollment data
lscog_sch_enroll <- dplyr::bind_rows(
  lscog_pub_sch_enroll,
  lscog_pvt_sch_enroll
) |>
  dplyr::mutate(
```

```
    STUDENT_COUNT = dplyr::coalesce(STUDENT_COUNT_PUB, 0) +
      dplyr::coalesce(STUDENT_COUNT_PVT, 0),
    TEACHER_COUNT = dplyr::coalesce(TEACHER_COUNT_PUB, 0) +
      dplyr::coalesce(TEACHER_COUNT_PVT, 0)
  )

lscog_sch_enroll
```

```
Simple feature collection with 122 features and 9 fields
Active geometry column: geom (with 24 geometries empty)
Geometry type: POINT
Dimension:     XY
Bounding box:  xmin: 1700952 ymin: 406810.6 xmax: 2203406 ymax: 724699.4
Projected CRS: NAD83(HARN) / South Carolina (ft)
# A tibble: 122 × 11
   INSTITUTION_ID NAME                STATE STUDENT_COUNT_PUB TEACHER_COUNT_PUB
 * <chr>          <chr>               <chr>             <dbl>             <dbl>
 1 450108001163   Barnwell Elementary  SC                 462              32
 2 450075000064   Allendale Fairfax H… SC                 283              28.9
 3 450075001184   Allendale Elementary SC                 245              18
 4 450075001415   Allendale-Fairfax M… SC                 268              18
 5 450093000119   Bamberg-Ehrhardt Hi… SC                 381              28.5
 6 450093000120   Bamberg-Ehrhardt Mi… SC                 188              15
 7 450096000122   Denmark Olar High    SC                 162              20
 8 450096000123   Denmark-Olar Middle  SC                 149              10
 9 450096001426   Denmark-Olar Elemen… SC                 353              25
10 450098000127   Barnwell County Car… SC                   0              12
# ℹ 112 more rows
# ℹ 6 more variables: STUDENT_COUNT_PVT <dbl>, TEACHER_COUNT_PVT <dbl>,
#   geom <POINT [foot]>, geometry <POINT [foot]>, STUDENT_COUNT <dbl>,
#   TEACHER_COUNT <dbl>
```

Python

```
# Combine school enrollment data
lscog_sch_enroll = pd.concat([
    lscog_pub_sch_enroll.assign(
        STUDENT_COUNT=lscog_pub_sch_enroll['STUDENT_COUNT_PUB'],
        TEACHER_COUNT=lscog_pub_sch_enroll['TEACHER_COUNT_PUB']
    ),
    lscog_pvt_sch_enroll.assign(
        STUDENT_COUNT=lscog_pvt_sch_enroll['STUDENT_COUNT_PVT'],
        TEACHER_COUNT=lscog_pvt_sch_enroll['TEACHER_COUNT_PVT']
```

```
    )
])

lscog_sch_enroll
```

```
      INSTITUTION_ID  ... TEACHER_COUNT_PVT
0       450108001163  ...               NaN
1       450075000064  ...               NaN
2       450075001184  ...               NaN
3       450075001415  ...               NaN
4       450093000119  ...               NaN
...              ...  ...               ...
17663       K9305640  ...               3.0
17672       A9703170  ...               4.8
17676       01262826  ...              23.0
17722       01932407  ...               6.0
17733       A9903957  ...               1.0

[122 rows x 10 columns]
```

The subsequent TAZ aggregation counts total student enrollment within each zone, providing essential data for modeling education-related trip patterns and supporting specialized trip generation rates for school-based travel.

R

```
# count the number of school enrollment within each TAZ
lscog_taz_enroll <- lscog_taz |>
  sf::st_join(lscog_sch_enroll) |>
  dplyr::group_by(
    ID,
    Area,
    TAZ_ID,
    COUNTY,
    AREA_TYPE,
    COUNTYID,
    .drop = FALSE
  ) |>
  dplyr::summarize(
    .groups = "drop",
    STUDENT_COUNT = sum(STUDENT_COUNT, na.rm = TRUE)
  )
```

```
lscog_taz_enroll
```

```
Simple feature collection with 585 features and 7 fields
Geometry type: MULTIPOLYGON
Dimension:     XY
Bounding box:  xmin: 1691490 ymin: 331894 xmax: 2237471 ymax: 744679.9
Projected CRS: NAD83(HARN) / South Carolina (ft)
# A tibble: 585 × 8
   ID         Area TAZ_ID   COUNTY      AREA_TYPE COUNTYID STUDENT_COUNT
   <chr>     <dbl> <chr>    <chr>       <chr>     <chr>            <dbl>
 1 11050058  37.7  11050058 Barnwell SC RURAL     45011                0
 2 11050059  21.5  11050059 Barnwell SC RURAL     45011                0
 3 11050060  24.4  11050060 Barnwell SC RURAL     45011              598
 4 11050061  17.4  11050061 Barnwell SC RURAL     45011                0
 5 11050062  12.6  11050062 Barnwell SC RURAL     45011                0
 6 11050072 191.   11050072 Barnwell SC RURAL     45011                0
 7 11050073   9.69 11050073 Barnwell SC SUBURBAN  45011                0
 8 11050074  16.5  11050074 Barnwell SC RURAL     45011                0
 9 11050075  11.4  11050075 Barnwell SC SUBURBAN  45011                0
10 11050076   9.02 11050076 Barnwell SC SUBURBAN  45011                0
# ℹ 575 more rows
# ℹ 1 more variable: geom <MULTIPOLYGON [foot]>
```

Python

```
# count the number of school enrollment within each TAZ
lscog_taz_enroll = lscog_taz.sjoin(lscog_sch_enroll, how='left') \
      .groupby(['ID', 'Area', 'TAZ_ID', 'COUNTY', 'AREA_TYPE', 'COUNTYID'],
as_index=False) \
    .agg({'STUDENT_COUNT': 'sum'})

lscog_taz_enroll
```

```
          ID       Area    TAZ_ID  ... AREA_TYPE COUNTYID STUDENT_COUNT
0    11050058  37.707611  11050058  ...     RURAL    45011           0.0
1    11050059  21.450575  11050059  ...     RURAL    45011           0.0
2    11050060  24.411972  11050060  ...     RURAL    45011         598.0
3    11050061  17.351381  11050061  ...     RURAL    45011           3.0
4    11050062  12.587147  11050062  ...     RURAL    45011           2.0
..        ...        ...       ...  ...       ...      ...           ...
580   9050125  12.789308   9050125  ...     RURAL    45009         162.0
```

```
581   9050126   0.633810   9050126  ...  SUBURBAN    45009          0.0
582   9050128  12.890918   9050128  ...     RURAL    45009        693.0
583   9050130  13.308991   9050130  ...     RURAL    45009          0.0
584   9050132  39.194309   9050132  ...     RURAL    45009          0.0

[585 rows x 7 columns]
```

Combine into a single data

This step integrates all TAZ-level socioeconomic datasets into a comprehensive base year file for travel demand modeling. This consolidated dataset contains all essential variables organized in a standardized format with geographic identifiers, demographic characteristics, employment data, and educational enrollment totals for each traffic analysis zone in the study region.

R

```r
# Combine population, household, employments, and school enrollment
lscog_se_base <- lscog_taz_pop |>
  dplyr::left_join(
    lscog_taz_enroll |> sf::st_drop_geometry(),
    by = dplyr::join_by(ID, Area, TAZ_ID, COUNTY, AREA_TYPE, COUNTYID)
  ) |>
  dplyr::select(
    ID,
    Area,
    TAZ_ID,
    COUNTY,
    AREA_TYPE,
    COUNTYID,
    INC_14999,
    INC_49999,
    INC_50000,
    TOTPOP,
    GQPOP,
    HHPOP,
    HH,
    HH_1,
    HH_2,
    HH_3,
    HH_4,
    DU,
    dplyr::everything()
  )
```

```
lscog_se_base
```

```
Simple feature collection with 585 features and 30 fields
Geometry type: MULTIPOLYGON
Dimension:     XY
Bounding box:  xmin: 1691490 ymin: 331894 xmax: 2237471 ymax: 744679.9
Projected CRS: NAD83(HARN) / South Carolina (ft)
# A tibble: 585 × 31
   ID       Area TAZ_ID COUNTY AREA_TYPE COUNTYID INC_14999 INC_49999 INC_50000
   <chr>    <dbl> <chr>  <chr>  <chr>     <chr>        <dbl>     <dbl>     <dbl>
 1 110500…  37.7  11050… Barnw… RURAL     45011           71       198        60
 2 110500…  21.5  11050… Barnw… RURAL     45011           32       137       151
 3 110500…  24.4  11050… Barnw… RURAL     45011          149       179       227
 4 110500…  17.4  11050… Barnw… RURAL     45011           81       111       117
 5 110500…  12.6  11050… Barnw… RURAL     45011           44       132       219
 6 110500… 191.   11050… Barnw… RURAL     45011            8         0         0
 7 110500…   9.69 11050… Barnw… SUBURBAN  45011           23        25        21
 8 110500…  16.5  11050… Barnw… RURAL     45011           25        92       157
 9 110500…  11.4  11050… Barnw… SUBURBAN  45011           76        80        65
10 110500…   9.02 11050… Barnw… SUBURBAN  45011           12        77       187
# ℹ 575 more rows
# ℹ 22 more variables: TOTPOP <dbl>, GQPOP <dbl>, HHPOP <dbl>, HH <dbl>,
#   HH_1 <dbl>, HH_2 <dbl>, HH_3 <dbl>, HH_4 <dbl>, DU <dbl>, TOTAL_EMP <dbl>,
#   AGR_FOR_FI <dbl>, MINING <dbl>, CONSTRUCTI <dbl>, MANUFACTUR <dbl>,
#   TRANSP_COM <dbl>, WHOLESALE <dbl>, RETAIL <dbl>, FIRE <dbl>,
#   SERVICES <dbl>, PUBLIC_ADM <dbl>, geom <MULTIPOLYGON [foot]>,
#   STUDENT_COUNT <dbl>
```

Python

```python
# Define the column order
field_order = [
    'ID', 'Area', 'TAZ_ID', 'COUNTY', 'AREA_TYPE', 'COUNTYID',
    'INC_14999', 'INC_49999', 'INC_50000',
    'TOTPOP', 'GQPOP', 'HHPOP',
    'HH', 'HH_1', 'HH_2', 'HH_3', 'HH_4', 'DU'
]

# Combine population, household, employments, and school enrollment
lscog_se_base = lscog_taz_pop.merge(
    lscog_taz_enroll,
    on=['ID', 'Area', 'TAZ_ID', 'COUNTY', 'AREA_TYPE', 'COUNTYID'],
```

```
    how='left'
)

lscog_se_base = lscog_se_base[field_order +
                          list(lscog_se_base.columns.difference(field_order))]

lscog_se_base
```

```
           ID  ...                                           geometry
0    11050058  ...  MULTIPOLYGON (((1940883.78 467711.359, 1940683...
1    11050059  ...  MULTIPOLYGON (((1909744.245 514791.296, 190990...
2    11050060  ...  MULTIPOLYGON (((1933978.652 551400.913, 193349...
3    11050061  ...  MULTIPOLYGON (((1901544.254 537296.043, 190161...
4    11050062  ...  MULTIPOLYGON (((1932677.078 512746.246, 193263...
..        ...  ...                                               ...
580   9050125  ...  MULTIPOLYGON (((1968427.616 539621.663, 196834...
581   9050126  ...  MULTIPOLYGON (((1961524.044 543029.131, 196150...
582   9050128  ...  MULTIPOLYGON (((1994408.254 547077.578, 199440...
583   9050130  ...  MULTIPOLYGON (((2046194.08 478862.054, 2046134...
584   9050132  ...  MULTIPOLYGON (((2012593.472 500179.47, 2013190...

[585 rows x 31 columns]
```

Data checks and validation

The validation process ensures data integrity and consistency across all socioeconomic variables through systematic checks of categorical totals. These validation steps identify any discrepancies between aggregate totals and component categories that may have occurred during the interpolation or aggregation processes.

Household size total

This validation confirms that the total household count matches the sum of all household size categories for each TAZ. Any discrepancies indicate potential issues in the household size distribution that require investigation and correction before model implementation.

R

```
# check the sum of household by household size
lscog_se_base |>
  dplyr::filter(HH != (HH_1 + HH_2 + HH_3 + HH_4)) |>
  nrow()
```

```
[1] 0
```

Python

```
# check the sum of household by household size
lscog_se_base[
    lscog_se_base['HH'] != (lscog_se_base['HH_1'] + lscog_se_base['HH_2'] +
                            lscog_se_base['HH_3'] + lscog_se_base['HH_4'])
].shape[0]
```

```
0
```

Household income total

The income category validation verifies that household totals equal the sum of all three income brackets across all zones. This check ensures the integrity of the income distribution data following the proportional allocation methodology applied during the ACS interpolation process.

R

```
# check the sum of household by income level
lscog_se_base |>
  dplyr::filter(HH != (INC_14999 + INC_49999 + INC_50000)) |>
  nrow()
```

```
[1] 0
```

Python

```
# check the sum of household by income level
lscog_se_base[
                lscog_se_base['HH']    !=    (lscog_se_base['INC_14999']    +
lscog_se_base['INC_49999'] +
                            lscog_se_base['INC_50000'])
].shape[0]
```

```
0
```

Employment categories

The employment validation confirms that total employment equals the sum of all industry sector categories for each TAZ. This comprehensive check validates the LEHD data integration and ensures that no employment is lost or double-counted during the sectoral disaggregation process.

R

```
# check the sum of employment by categories
lscog_se_base |>
  dplyr::filter(
    TOTAL_EMP !=
      (AGR_FOR_FI +
        MINING +
        CONSTRUCTI +
        MANUFACTUR +
        TRANSP_COM +
        WHOLESALE +
        RETAIL +
        FIRE +
        SERVICES +
        PUBLIC_ADM)
  ) |>
  nrow()
```

```
[1] 0
```

Python

```
# check the sum of employment by categories
lscog_se_base[
    lscog_se_base['TOTAL_EMP'] != (
        lscog_se_base['AGR_FOR_FI'] +
        lscog_se_base['MINING'] +
        lscog_se_base['CONSTRUCTI'] +
        lscog_se_base['MANUFACTUR'] +
        lscog_se_base['TRANSP_COM'] +
        lscog_se_base['WHOLESALE'] +
        lscog_se_base['RETAIL'] +
        lscog_se_base['FIRE'] +
        lscog_se_base['SERVICES'] +
        lscog_se_base['PUBLIC_ADM']
    )
].shape[0]
```

```
0
```

Export the final data

The final export creates the complete TAZ-level socioeconomic dataset in both tabular and spatial formats for direct integration into the travel demand model. This comprehensive dataset serves as the primary input for trip generation, providing all necessary demographic, economic, and educational variables organized by traffic analysis zone for the LSCOG regional modeling system.

Export as CSV flat file

R

```
# Export as CSV
lscog_se_base |>
  sf::st_drop_geometry() |>
  readr::write_csv(
    file.path(output_tabular, "lscog_se_taz.csv"),
    append = FALSE
  )
```

Python

```
# Export as CSV
lscog_se_base.to_csv(
    output_tabular / "lscog_se_taz.csv",
    index=False
)
```

Export as Geodatabase layer

R

```
# Export as GDB
lscog_se_base |>
  sf::write_sf(
    file.path(output_spatial, "LSCOG_2020Base_SE.gdb"),
    layer = "lscog_se_base",
    append = FALSE
  )
```

Python

```
# Export as GDB
lscog_se_base.to_file(
    output_spatial / "LSCOG_2020Base_SE.gdb",
    layer='lscog_se_base',
```

```
    driver='FileGDB'
)
```