Designing Disaggregated Evaluations of AI Systems: Choices, Considerations, and Tradeoffs

Solon Barocas, Anhong Guo, Ece Kamar, Jacquelyn Krones, Meredith Ringel Morris, Jennifer Wortman Vaughan, Duncan Wadsworth, Hanna Wallach

¹Microsoft ²University of Michigan

solon@microsoft.com, anhong@umich.edu, eckamar@microsoft.com, jakrones@microsoft.com, merrie@microsoft.com, jenn@microsoft.com, duwads@microsoft.com, wallach@microsoft.com

Abstract

Several pieces of work have uncovered performance disparities by conducting "disaggregated evaluations" of AI systems. We build on these efforts by focusing on the choices that must be made when designing a disaggregated evaluation, as well as some of the key considerations that underlie these design choices and the tradeoffs between these considerations. We argue that a deeper understanding of the choices, considerations, and tradeoffs involved in designing disaggregated evaluations will better enable researchers, practitioners, and the public to understand the ways in which AI systems may be underperforming for particular groups of people.

Introduction

AI systems are a central part of modern life—even in highstakes domains like education, employment, and healthcare. However, several pieces of work have demonstrated that AI systems can perform differently for different groups of people, often exhibiting especially poor performance for already-disadvantaged groups (e.g., Nicol, Casey, and Mac-Farlane 2002; Rodger and Pendharkar 2004; Tatman 2017; Buolamwini and Gebru 2018; Bolukbasi et al. 2016; De-Vries et al. 2019; Angwin et al. 2016; Raji and Buolamwini 2019; Koenecke et al. 2020; Obermeyer et al. 2019). Many of these studies have relied on "disaggregated evaluations," in which system performance is assessed and reported separately for different groups of people, such as those based on race, gender, or socioeconomic status (Mitchell et al. 2019). There are several reasons to conduct disaggregated evaluations, most notably to demonstrate the existence or absence of suspected performance disparities, or to uncover potential causes of performance disparities. In either case, the performance disparities might be the specific performance disparities that already affected the people who previously interacted with a system, or potential performance disparities that may affect people who will interact with a system in the future. From a normative perspective, disaggregated evaluations therefore provide a way to hold development teams and system owners accountable for past system performance, to decide whether to use or keep using a system, or to identify potential system modifications that would make it acceptable to use or keep using a system.

¹We use the phrase "face-based AI systems" to refer to face-detection systems, face-characterization systems (e.g., gender or age classifiers), face-verification systems, and face-identification systems; the latter two are types of face-recognition systems.

In this paper, we draw attention to the choices that must be made when designing a disaggregated evaluation: At a high level, these choices can be thought of as roughly spanning "why," "who" (both who will design and conduct the evaluation and for whom system performance will be assessed and reported), "when," "what," "where," and "how." For example, a disaggregated evaluation can be either retrospective or forward looking. In either case, the evaluation might be designed and conducted by the development team(s) responsible for the system in question, by outside parties, or by both as a collaborative effort. As another example, a disaggregated evaluation can involve confirmatory or exploratory analyses, or a mix of the two. Some of these design choices influence the results that will be obtained, and thus the conclusions that can be drawn, while others influence its impacts on people and society—both beneficial and harmful.

Using face-based AI systems¹ as a running example, we argue that a deeper understanding of these choices will enable researchers and practitioners to design careful, conclusive disaggregated evaluations, thereby better enabling them—as well as the public—to understand the ways in which AI systems may be underperforming for particular groups of people. To that end, we highlight some of the key considerations that underlie these design choices. We emphasize that these considerations are not independent. Designing a disaggregated evaluation therefore means making tradeoffs between considerations. These tradeoffs must be clearly articulated by the evaluation's designers, so that they, and others, know how to interpret its results and conclusions.

Although we use face-based AI systems as a running example, the choices, considerations, and tradeoffs that we discuss are common to disaggregated evaluations of many other types of AI systems as well. However, face-based AI systems have, in many ways, become a bellwether for AI systems in general. Face-based AI systems are used throughout society in comparatively low-stakes domains like advertising (Gillespie 2019) and digital media management (Google 2019), as well as high-stakes domains like education (Proctorio 2021), employment (HireVue 2019), healthcare (Watch

2021), security (Apple Inc. 2019; Microsoft 2019b; Australian Border Force 2019), and criminal justice (Federal Bureau of Investigation 2019). Despite their growing prevalence, their use remains controversial (Stark 2019) and the industry around them is evolving rapidly. Much of this debate has been spurred by a number of high-profile disaggregated evaluations, most notably the Gender Shades study (Buolamwini and Gebru 2018; Raji and Buolamwini 2019). And, in turn, the debate has helped to highlight some key limitations of disaggregated evaluations and the dangers of a narrow focus on performance disparities (Hassein 2017). For these reasons, we believe that face-based AI systems make a particularly compelling running example. That said, we emphasize that our focus on face-based AI systems should not be viewed as an endorsement of their use.

Throughout this paper, we intentionally avoid using the word "audit" to refer to the process of assessing an AI system for performance disparities. In other industries, the word "audit" refers to an official examination, often conducted by third parties, with mutually agreed-upon actors, responsibilities, and expectations. Audits typically consider procedures and documentation, in addition to considering outcomes. Although a disaggregated evaluation could form part of an audit of an AI system, it would likely not be the only component. Developing a clear definition of what it means to audit an AI system is an extremely important and much-needed research direction. We are particularly encouraged by a recent paper by Raji et al. (2020a), which proposes the "Scoping, Mapping, Artifact Collection, Testing, and Reflection" (SMACTR) framework for conducting comprehensive internal audits of AI systems via a rigorous, multistage process. Disaggregated evaluations would most likely fit within the "Testing" stage of the SMACTR framework.

Lastly, we note that performance disparities are just one type of fairness-related harm. Researchers have highlighted many other types of fairness-related harms (e.g., systematic differences in outcomes (not just model performance), but also stereotyping, denigration, and underrepresentation, among others (Barocas et al. 2017)) that can negatively affect already-disadvantaged, at-risk, or otherwise-marginalized groups of people in a variety of ways. Evaluations—disaggregated or otherwise—that focus on these types of harms are outside the scope of this paper.

In the next section, we provide an overview of disaggregated evaluations and their role to date in the context of AI systems. In the following section, we then describe the choices that must be made when designing a disaggregated evaluation. We highlight the key considerations that underlie these design choices, as well as the tradeoffs between these considerations. Finally, we conclude with a short discussion.

Disaggregated Evaluations

AI systems are typically evaluated by assessing and reporting one or more aggregate performance metrics—such as accuracy, precision, recall, word error rate, and root-mean-square error—calculated using an evaluation dataset. For example, the National Institute of Standards and Technology (NIST) has conducted vendor tests of commercially available face-recognition systems for decades, assessing

and reporting aggregate performance metrics like false positive and false negative rates using evaluation datasets that are comprised of front-facing mugshots, side-view images, webcam images, and photographs taken by photo journalists and amateur photographers (Grother, Ngan, and Hanaoka 2019a,b). However, aggregate performance metrics can obscure poor performance for groups of people that are not well represented in an evaluation dataset. For example, consider an evaluation dataset that contains 100 data points, where 90 data points correspond to people belonging to group A and 10 data points correspond to people belonging to group B. If a system makes correct predictions for the data points associated with group A and incorrect predictions for the data points associated with group B, then the aggregate accuracy of the system, when evaluated using the dataset, will be 90%. But this aggregate accuracy obscures the fact that there is an absolute performance disparity of 100% because the accuracy for group B is zero.

For this reason, researchers and practitioners seeking to understand performance disparities exhibited by AI systems often assess and report system performance separately for different groups of people (Mitchell et al. 2019). This practice draws on and parallels similar practices in other industries. For example, the U.S. Food and Drug Administration mandates that clinical trial results be assessed and reported separately for groups based on race, gender, and age. As another example, also in the U.S., the Biden-Harris administration recently signed an executive order stating that "Many Federal datasets are not disaggregated by race, ethnicity, gender, disability, income, veteran status, or other key demographic variables. This lack of data has cascading effects and impedes efforts to measure and advance equity. A first step to promoting equity in Government action is to gather the data necessary to inform that effort" (White House 2021).

Disaggregated evaluations have proven to be effective at uncovering some of the ways in which AI systems are underperforming for particular groups of people in many different domains. For example, Obermeyer et al. (2019) demonstrated that a system used to enroll patients in a highrisk care management program assigned different risk scores to Black and white patients with comparable health statuses, leading to a large disparity in the proportions of Black and white patients identified for enrollment; DeVries et al. (2019) compared the accuracies of six object-classification systems using images of household objects from fifty countries, finding that all six systems had substantially lower accuracies for images from lower-income countries and households; and Koenecke et al. (2020) showed that five commercially available speech-recognition systems had much higher word error rates for Black people than for white people.

In the context of face-based AI systems, disaggregated evaluations have been used by researchers and practitioners to assess the performance of face-recognition systems since the early 2000s, focusing primarily on performance for groups based on environmental factors like pose and lighting conditions (e.g., Lee, Ho, and Kriegman 2005; Beveridge et al. 2009; Klare et al. 2012) and for groups based on gender, age, and race (e.g., Best-Rowden and Jain 2018; Krishnapriya et al. 2019a,b; Cook et al. 2019). In 2019, however,

NIST finally conducted its own disaggregated evaluation of commercially available face-recognition systems, focusing on false positive and false negative rates for groups based on sex, age, race, and country of birth (Grother, Ngan, and Hanaoka 2019c). The resulting report provides an overview of the literature on performance disparities exhibited by face-based AI systems. The most notable such piece of work is the Gender Shades study, which used a disaggregated evaluation to show that three commercially available gender classifiers, a type of face-characterization system, had higher error rates for women with darker skin tones than for women or people with darker skin tones overall (Buolamwini and Gebru 2018). By focusing on groups based on skin tone, gender, and their intersections, the study demonstrated the need to specifically assess and report system performance for people belonging to groups based on multiple factors, drawing on and highlighting the importance of Crenshaw's work on intersectionality (Crenshaw 1989), which showed that the experiences of Black women differ from the experiences of women or of Black people overall.

As well as being widely cited in the research community, Gender Shades contributed to ongoing changes to the industry around face-based AI systems. Follow-up work revealed that the study was effective at getting the companies responsible for the three gender classifiers to address the performance disparities (Raji and Buolamwini 2019); media coverage of the study led to greater public awareness of the societal impacts of face-based AI systems (Lohr 2018; Buolamwini 2018), spurring calls to action (e.g., Algorithmic Justice League and the Center on Privacy and Technology at Georgetown Law 2018) and legislation (Foundation 2019); and a company responsible for one of the three gender classifiers assessed in the study announced that it would no longer develop any face-based AI systems (IBM 2020), while another announced that it would not sell face-recognition systems to police departments in the U.S. (Greene 2020).

Choices, Considerations, and Tradeoffs

Although disaggregated evaluations are conceptually simple, their results and conclusions, not to mention their impacts on people and society, depend on a variety of design choices. In this section, we describe the most salient of these design choices—which can be thought of as roughly spanning "why," "who," "when," "what," "where," and "how"—and highlight some of the key considerations that underlie them. We emphasize that these considerations are not independent, and discuss some of the tradeoffs that must therefore be made when designing a disaggregated evaluation.

What is the goal of the evaluation?

As we described in the introduction, there are several reasons for conducting a disaggregated evaluation. When designing a disaggregated evaluation, the first choice is therefore its goal: Is the evaluation intended to demonstrate the existence or absence of suspected performance disparities? Or is it intended to uncover potential causes of performance disparities? For example, the ACLU focused on demonstrating the existence of performance disparities exhibited by Amazon's Rekognition (Snow 2018), while

Koennecke et al. attempted to understand *why* five speech-recognition systems had higher word error rates for Black people than for white people (Koenecke et al. 2020). Is the evaluation retrospective—i.e., focused on the specific performance disparities that affected the people who previously interacted with the system? Or is it forward looking—i.e., focused on potential performance disparities that may affect people who will interact with the system in the future? Obermeyer et al. (Obermeyer et al. 2019) investigated the actual risk scores assigned to real patients by a high-risk care management enrollment system, while NIST's disaggregated evaluation of commercially available face-recognition systems focused on potential performance disparities (Grother, Ngan, and Hanaoka 2019c). The answers to these questions will influence many of the subsequent design choices.

Who will design and conduct the evaluation?

Disaggregated evaluations can be designed and conducted by a variety of different actors—most notably, the development teams responsible for the AI systems in question or outside parties, including consultants, researchers, and journalists. When a disaggregated evaluation is designed and conducted by outside parties, this can be done in cooperation with the development team(s) responsible for the system or it can be done without their help or knowledge. In some cases, outside parties can even conduct an evaluation when the development team(s) would prefer that they not—an approach that is sometimes described as adversarial. Disaggregated evaluations that are designed and conducted by outside parties can involve either a small set of experts or a large set of volunteers, each perhaps contributing their data to the evaluation dataset or shaping the design of the evaluation.

Many well-known disaggregated evaluations have been designed and conducted by outside parties. For example, ProPublica, an independent newsroom, evaluated Northpointe's COMPAS recidivism-prediction system (Angwin et al. 2016); researchers from Stanford evaluated speechrecognition systems from Amazon, Apple, Google, IBM, and Microsoft (Koenecke et al. 2020); and the Gender Shades study was conducted by a researcher from MIT and a researcher from a company responsible for one of the three gender classifiers (Buolamwini and Gebru 2018). Comparatively few well-known disaggregated evaluations have been performed by development teams, most likely because evaluations of this sort are never publicly disclosed.

Given that a disaggregated evaluation's results and conclusions can be quite troubling, not to mention damning for the the development team(s) responsible for the system in question, the independence (perceived or real) of the party that designed and conducted the evaluation might affect whether its results and conclusions are seen as trustworthy. As a result, disaggregated evaluations that are designed and conducted by outside parties may carry more credibility. At the same time, outside parties, especially those that have not been hired by development teams, might possess fewer resources and thus struggle to complete as careful or comprehensive evaluations. There are also practical limits to what can be achieved in a completely independent evaluation. In most cases, outside parties will

only be able to engage with the system as a black box—that is, observe the system's outputs, given particular inputs. Moreover, some systems do not produce publicly accessible outputs, thereby making it impossible for outside parties to evaluate these systems. In contrast, development teams will benefit from the fact that they have a deep understanding of their own systems, including the components that make up these systems and how these components fit together, the performance metrics that are already used to evaluate their systems, as well as intended use cases and deployment contexts. Development teams are also likely to be better positioned to design disaggregated evaluations that are focused on identifying immediate opportunities for improvement. Of course, outside parties can possess expertise or perspectives that development teams lack, allowing them to uncover performance disparities that might otherwise be overlooked.

When will the evaluation be conducted?

Many well-known disaggregated evaluations have focused on AI systems that are already commercially available and, in some cases, widely used—in large part because these evaluations were designed and conducted by outside parties, without engagement from the development teams responsible for the systems in question. However, disaggregated evaluations can also take place before system deployment. Indeed, development teams—potentially even in collaboration with outside parties who have been provided with predeployment access—can use pre-deployment disaggregated evaluations to determine whether their AI systems are ready for deployment, thereby reducing the likelihood of harms.

What system or component(s) will be evaluated?

AI systems often consist of multiple components, such as machine-learning models, whose inputs and outputs are interrelated. For example, a speech-recognition system consists of an acoustic model that models the acoustics of speech and a language model that models relationships between words. A disaggregated evaluation can therefore focus either on the performance of a system as a whole or on the performance of one or more of its constituent components.

Focusing on the performance of an AI system as a whole can make it easier to uncover performance disparities that will lead directly to harms when the system is deployed. In contrast, focusing on the performance of one or more constituent components can make it easier to understand the potential causes of any system-level performance disparities. If an evaluation is designed and conducted by an outside party without engagement from the development team responsible for the system, then it may not be possible to assess the performance of its constituent components unless they are also accessible by outside parties. That said, some design choices may allow possible component-level performance disparities to be inferred from system-level performance disparities. For example, by asking Black and white people to speak the same sequence of words, the researchers from Stanford who evaluated five commercially available speech recognition systems could be relatively sure that the higher word error rates for Black people were due to performance disparities in the acoustic models (Koenecke et al. 2020).

Some AI systems depend on the outputs of other AI systems. A disaggregated evaluation can yield distorted results if it does not account for such dependencies. For example, a face cannot be identified by a face-identification system unless it is first detected by a face-detection system. Evaluating the performance of a face-identification system using only images that are known to contain faces will therefore fail to uncover any performance disparities that are due to face-detection errors. As a result, NIST recommends assessing and reporting performance disparities for every component of a face-recognition system, as well as any other systems on which it depends (Grother, Ngan, and Hanaoka 2019b).

In what context will the evaluation occur?

A disaggregated evaluation can take place "in the laboratory" or "in situ." For example, it is possible to evaluate a face-verification system that is used to grant workplace access to employees by presenting the system with photos or by asking employees and non-employees to attempt to gain access to the workplace using the system. In the former scenario, the photos may not accurately reflect environmental factors like lighting conditions or image resolution, or even behavioral factors like pose. Moreover, if the system requires an operator to make decisions (e.g., grant or deny access) based on the system's outputs (e.g., match scores), then the behavior of the operator will not be reflected either (Poursabzi-Sangdeh et al. 2020). In contrast, conducting a disaggregated evaluation in situ allows for the performance of the entire sociotechnical system, of which the AI system may be just one part, to be evaluated (Raji et al. 2020b). Indeed, the performance of an AI system in isolation may not reveal much about the ultimate performance of a sociotechnical system that involves, for example, human discretion and judgment (Selbst et al. 2019). However, conducting a disaggregated evaluation in situ can be expensive and may not even be possible if the evaluation is conducted by an outside party. In addition, some system components may be difficult to evaluate in situ because they cannot be isolated from the system as a whole in a meaningful way. However, as we described above, it may be possible to design an evaluation so that possible component-level performance disparities can be inferred from system-level performance disparities.

For which groups of people will performance be assessed and reported?

There are many different groups of people for which AI systems may exhibit poor performance, including groups based on demographic factors, sociocultural factors, behavioral factors, morphological factors, and their intersections. For example, race, gender, age, facial hair, hairstyle, glasses, facial expression, pose, and skin tone have all been shown to affect the performance of face-based AI systems (Grother, Ngan, and Hanaoka 2019a,b). However, several well-known disaggregated evaluations have assessed and reported system performance for a small number of particularly salient groups—often groups that are already disadvantaged, at risk, or otherwise marginalized. This is because performance disparities involving these groups may compound existing injustices (Hellman 2018). For example, ProPublica focused

on Black and white defendants when evaluating Northpointe's COMPAS recidivism-prediction system (Angwin et al. 2016), while the researchers who conducted the Gender Shades study focused on groups based on skin tone, gender, and their intersections (Buolamwini and Gebru 2018).

The latter example raises an important consideration—namely whether disaggregated evaluations should focus on groups based on factors that capture social constructs, such as race or gender, or groups based on factors that capture observable properties, perhaps even observable properties thought to be meaningfully correlated with social constructs, such as skin tone and hairstyle, which are are thought to be meaningfully correlated with race and gender, respectively.

Taking the former approach is advantageous because social constructs are directly important to society. Indeed, many of the groups that are most disadvantaged, at risk, or marginalized are based on factors that capture social constructs. However, this approach also raises challenging questions about social constructs and the ways in which they are shaped by-and, in turn, shape-society, sometimes in problematic ways (e.g., Benthhall and Haynes 2019; Hanna et al. 2020). In addition, it can be challenging to obtain accurate information about membership of groups based on factors that capture social constructs. In some contexts, this information may be available via self-reports or official documentation (e.g., government-issued identification). In other contexts, though, this may not be possible, meaning that group membership must instead be inferred from observable properties thought to be meaningfully correlated with those social constructs. Making decisions about which observable properties are meaningfully correlated with social constructs is an activity that can be viewed as essentializing, stigmatizing, or alienating, especially if this is done in a way that suggests that these properties are common to all members—or only members—of those groups. It also runs the risk of inaccuracies, especially when group membership is difficult to infer from observable properties or when group membership manifests itself differently for different groups. Moreover, inferring group membership also raises questions about the ethics of imposing labels on people (Bogen, Rieke, and Ahmed 2020; Andrus et al. 2020). We discuss this issue further below in the context of creating evaluation datasets.

In contrast, the latter approach is less directly concerned with social constructs, focusing instead on groups based on factors that capture observable properties. For example, a disaggregated evaluation might focus narrowly on whether a system performs less well for people with long hair than it does for people with short hair, with no particular regard for the relationship between hairstyle and gender. This approach sidesteps the difficult task of defining gender, as well as the task of obtaining accurate information about group membership. However, it also makes it difficult to directly conclude anything about the existence or absence of suspected performance disparities involving groups based on gender.

Just as focusing on aggregate performance metrics can obscure poor performance for people belonging to particular groups, focusing on groups based on single factors can obscure poor performance for people belonging to groups based on multiple factors. For example, the Gender Shades

study demonstrated that three commercially available gender classifiers had higher error rates for women with darker skin tones than for women or people with darker skin tones overall (Buolamwini and Gebru 2018). It is therefore important to specifically assess and report system performance for people belonging to groups based on multiple factors.

Lastly, we emphasize that some people belonging to the groups on which a disaggregated evaluation will focus may not want the evaluation to be designed and conducted, no matter the potential benefits to uncovering performance disparities that affect them. This raises the challenging question of who gets to decide whether an evaluation will take place.

Which other factors will be considered and how?

There are many factors that can affect system performance beyond the factors on which the groups of interest are based. Because some of these factors may be correlated—even spuriously—with the factors on which the groups of interest are based, they can make it difficult to interpret the results of a disaggregated evaluation. Are performance disparities due to the factors on which the groups of interest are based or are they due to other factors that are correlated with them? A failure to account for these additional factors² makes it very difficult to make reliable claims about performance disparities. For example, although NIST's disaggregated evaluation of face-recognition systems revealed a higher false negative rate for Asian faces than for Black or white faces, the resulting report notes that this performance disparity may have actually been due to differences in the time elapsed between each pair of images (Grother, Ngan, and Hanaoka 2019c).

For any system, some of these additional factors will capture observable properties thought to be meaningfully correlated with the factors on which the groups of interest are based, while others will not. For example, when assessing and reporting the performance of a facerecognition system for groups based on gender, there are many additional factors, like hairstyle and glasses, that will affect system performance. Although hairstyle might be understood as something that is meaningfully correlated with gender, glasses might not. If a face-recognition system performs worse for women than for people of other genders, then, from a normative perspective, it does not matter if this performance disparity is actually caused by poor performance for people with particular hairstyles if those hairstyles are commonly worn by women. In contrast, if this performance disparity is caused by poor performance for people wearing glasses and there are proportionally more women wearing glasses in the evaluation dataset than people of other genders, then attributing this disparity to gender may be misleading. In either case, though, a failure to account for these additional factors makes it difficult to draw reliable conclusions about performance disparities or to uncover potential causes of performance disparities.

There are three ways to account for additional factors. The first is to make sure that the evaluation dataset is

²We use the term "additional factor" to refer to any factor that affects system performance and is correlated—even spuriously—with the factors on which the groups of interest are based.

representative of the population of interest—that is, either the people who previously interacted with the system or people who will interact with the system in the future. If this is the case, then barring spurious correlations, there is no need to explicitly account for factors beyond those on which the groups of interest are based: any performance disparities will be reflective of those that either affected or will affect the population of interest. However, this approach makes it difficult to uncover potential causes of these performance disparities—or to be certain that any performance disparities are not, in fact, due to factors that are spuriously correlated with the factors on which the groups of interest are based. Despite these limitations, many well-known disaggregated evaluations have relied on this approach as it is easy to implement (e.g., Angwin et al. 2016; Obermeyer et al. 2019).

The second way to account for additional factors is to control for them by holding their values constant. For example, when evaluating a face-recognition system, one way to account for glasses is to only assess and report performance for people without glasses, regardless of the groups to which they belong. Although this approach means that any performance disparities are likely genuinely due to the factors on which the groups of interest are based, it obscures performance disparities that occur in the context of factor values other than the ones considered. For example, glasses might have a greater negative impact on system performance when they are worn by men than when they are worn by women. A failure to assess and report performance for people wearing glasses will obscure this performance disparity. This is not a purely hypothetical scenario. Poor lighting conditions are known to have a greater negative impact on the performance of face-detection systems for people with darker skin tones than for people with lighter skin tones. Conducting a disaggregated evaluation in only good lighting conditions will obscure this performance disparity.

The third way to account for additional factors is to consider a range of values for each such factor, effectively treating it as if it were an additional focus of a disaggregated evaluation, along with the groups of interest. By assessing and reporting performance separately for each combination of factor values—that is, by focusing on intersections of the groups of interest and the "groups" obtained by considering different combinations of factor values—this approach yields a granular and high-dimensional view of system performance. Moreover, if the distributions over factor values are the same for each group of interest, then any disparities in (aggregate) performance between the groups will likely be due to the factors on which those groups are based. In practice, it may be difficult to ensure that the distributions over factor values are the same for each group of interest. For example, some hairstyles are more common among some genders than among others. However, even if the distributions over factor values are not the same, it is still possible to account for the factors using statistical techniques like generalized linear mixed-effect regression models (e.g., Givens et al. 2013; Beveridge et al. 2010), as we describe below. We note that it can be difficult to identify all relevant additional factors or to choose an appropriate range of values for each such factor. That said, this approach will most conclusively determine the existence or absence of suspected performance disparities, as well as making it much easier to uncover potential causes of performance disparities.

Lastly, we emphasize that no group is a monolith and, regardless of the groups of interest, there are always factors that exhibit within-group variation. For example, people belonging to any group based on race will likely exhibit a wide range of skin tones and ages. If there is any chance that these factors might affect system performance, then they must be accounted for by taking the third approach—i.e., treating them as if they were an additional focus of the evaluation.

How will the evaluation dataset be created?

Because a disaggregated evaluation depends so heavily on the evaluation dataset used to conduct it, this is one of the most important choices that must be made when designing a disaggregated evaluation, with many underlying considerations and tradeoffs. There are four main approaches when creating an evaluation dataset. The first is to reuse an existing dataset that was previously created for some other purpose; the second is to create a new dataset using data scraped from the web or from other data sources; the third is to create a new dataset by reusing deployment data from the system itself or by using data obtained from the context in which the system will be deployed; and the fourth is to create a new dataset by collecting data directly from data subjects who may or may not have not already interacted with the system.

For each approach, we discuss the following considerations and the tradeoffs between them: time, financial cost, suitability for the evaluation's goal, representation of the groups of interest, labeling of group membership, representation of additional factors, labeling of additional factor values, licensing, consent, and compensation. Some of these considerations (e.g., time, financial cost, licensing) are standard when reusing or creating a dataset, while others (e.g., representation of additional factors) influence an evaluation's results and conclusions. Others still (e.g., labeling of group membership, consent, compensation) influence an evaluation's impacts on people and society.

Approach 1: Reuse an existing dataset

Reusing an existing dataset, such as the IARPA Janus Benchmark A (IJB-A) dataset for evaluating face-detection and face-recognition AI systems (Whitelam et al. 2017) or the Adience dataset for evaluating age and gender classifiers (Eidinger, Enbar, and Hassner 2014), is less time consuming and less expensive than creating a new dataset. However, existing datasets may not have sufficient representation of the groups of interest, especially if those groups are based on factors that are rare or on multiple factors. For example, the researchers who conducted the Gender Shades study (Buolamwini and Gebru 2018) analyzed both the IJB-A dataset and the Adience dataset, finding that both are predominantly composed of images of people with lighter skin tones and both contain very few images of women with darker skin tones (7.4% of the IJB-A dataset and 4.4% of the Adience dataset). As a result, they were unable to use either dataset to conduct their disaggregated evaluation, spurring them to create their own dataset-the Pilot Parliaments Benchmark (PPB) dataset, which we describe below. The Gender Shades study motivated the creation of other general-purpose datasets that have better representation of groups based on race, skin tone, gender, and age (e.g., Kärkkäinen and Joo 2019). However, other groups, especially those that are rare, likely remain underrepresented.

Even if existing datasets do have sufficient representation of the groups of interest, the data points may not be labeled so as to indicate group membership. Combined with the fact that existing datasets rarely provide mechanisms for contacting data subjects, this means that reusing an existing data set may require group membership to be inferred, perhaps by asking crowdworkers or by using the outputs of other AI systems. However, as we discussed above, inferring group membership can be problematic due to both the possibility of inaccuracies and the ethics of imposing labels on people (Bogen, Rieke, and Ahmed 2020; Andrus et al. 2020).

Existing datasets may also lack appropriate representation of additional factors. There are several ways in which this might be the case, depending on the approach used to account for additional factors. First, the dataset may not be representative of the population of interest or the system's intended use cases and deployment contexts, meaning that it is not possible to implicitly account for additional factors via the argument that any performance disparities will be reflective of those that will affect the population of interest in situ. For example, when used by a retailer to count in-store customers, a face-detection system may rely on images taken by a wall-mounted camera. Evaluating such a system using a dataset that is composed of well-lit, front-facing images will likely yield results that do not reflect the system's performance in practice. Second, different data points may have different values for additional factors, making it impossible to control for them by holding their values constant. Even if the data points do have the same value for each additional factor, this value may not be representative of the values typically found in situ. Third, if additional factors are to be accounted for by treating each such factor as if it were an additional focus of the evaluation, along with the groups of interest, the data points may not span an appropriate range of values for each factor or there may not be sufficient representation of some combinations of factor values. In all three cases, the data points may not be labeled so as to indicate the values of the additional factors. This is especially likely for additional factors that may not typically be considered "interesting" in and of themselves.

In some cases, licensing restrictions may prevent the reuse of existing datasets, especially for development teams in companies who wish to better understand the performance of their own AI systems. We also note that because existing datasets do not generally provide mechanisms for contacting data subjects, reusing an existing dataset makes it difficult to request data subjects' consent or to compensate them fairly for contributing their data (Arrieta-Ibarra et al. 2018).

Aside from these considerations, reusing an existing dataset can also lead to problems if the dataset is not well documented—for example, with a datasheet (Gebru et al. 2018). This is because the dataset may have been collected or preprocessed in ways that might affect the evaluation but

are not apparent from examining the data points themselves.

Approach 2: Create a new dataset using scraped data

When an appropriate existing dataset does not exist, an alternative is to create a new dataset using data scraped from the web or from other sources. This approach is more time consuming than reusing an existing dataset, and can be more or less expensive. As with existing datasets, new datasets created using scraped data can only be used to conduct forward-looking evaluations. However, provided the data sources are selected carefully, scraping data can make it easier to ensure sufficient representation of the groups of interest. For example, when creating the PPB dataset, the researchers who conducted the Gender Shades study opted to scrape images from the parliamentary websites of six different countries, which were chosen because their parliaments were roughly balanced in terms of gender. To ensure sufficient representation of both darker and lighter skin tones, three of the countries (Rwanda, Senegal, and South Africa) are in Africa, while the other three (Iceland, Finland, and Sweden) are in Europe. This process resulted in a dataset that is roughly balanced by skin tone, gender, and their intersections. Although some data sources may identify the groups of interest, many will not. As a result, creating a new dataset using data scraped from the web or from other data sources often requires labeling the data points so as to indicate group membership, again raising the possibility of inaccuracies, as well as ethical questions.

Scraping data can sometimes make it easier to ensure sufficient representation of additional factors. For example, by scraping images from parliamentary websites, the researchers who conducted the Gender Shades study also ensured the values of some additional factors (i.e., lighting conditions and pose) were held reasonably constant; the values of these factors were not, however, labeled as such. Other additional factors, such as age, facial expression, facial hair, hairstyle, glasses, and image resolution, were not accounted for in any way, likely because the images were not labeled so as to indicate the values of these factors.

We also emphasize that using data scraped from the web or from other data sources raises a number of considerations involving licensing, consent, and compensation. First, it can be difficult to determine whether a data source is licensed in a such a way that data can be legally scraped from it and used to conduct a disaggregated evaluation. Second, even if a data source is appropriately licensed, this does not mean that the data subjects have consented to their data being used in this way. For example, in the context of face-based AI systems, image licenses are typically chosen by the photographer, not the people depicted in them. A failure to obtain consent from data subjects may even result in legal action in some jurisdictions. For instance, the Illinois Biometrics Information Privacy Act has generated significant litigation over whether and how companies may collect or use Illinois residents' biometric information (Law 360 2021). Lastly, even if a data source is appropriately licensed and all data subjects have consented to their data being used to conduct a disaggregated evaluation, most data sources do not provide mechanisms for contacting

data subjects, making it very difficult to compensate them fairly for contributing their data (Arrieta-Ibarra et al. 2018).

Approach 3: Create a new dataset using data from the system's context of use

The third approach is to create a new dataset using data from the system's context of use. If the system has already been deployed, this can mean reusing deployment data from the system itself. For example, when evaluating a high-risk care management enrollment system, Obermeyer et al. (2019) used data about patients that had already interacted with the system. If, however, the evaluation will take place before system deployment, then the data must be obtained via other methods. For example, when evaluating child welfare risk models prior to their potential deployment in Allegheny County, Chouldechova et al. (2018) used records that were previously collected by Allegheny County to assess different models' area under the curve for groups based on race.

Creating a new dataset using data from the system's context of use can be more time consuming than reusing an existing dataset, and more or less time consuming than creating a new dataset using scraped data; the financial cost can vary.

Data from the system's context of use will be representative of the population of interest, provided there are no substantial changes over time. However, there may not be sufficient representation of some groups of interest if these groups are relatively rare in the system's context of use. Moreover, the data points may not be labeled so as to indicate group membership. That said, depending on the system's context of use, it may be possible to contact data subjects, so it may not be necessary to infer group membership.

Because data from the system's context of use will likely be representative of population of interest, it is possible to implicitly account for additional factors via the argument that any performance disparities will be reflective of those that either affected or will affect the population of interest. However, accounting for additional factors by holding their values constant or by considering a range of values for each such factor is likely not possible. As with existing datasets and new datasets created using scraped data, the data points may not be labeled so as to indicate the values of the additional factors, although sometimes they may be.

Data from the system's context of use is unlikely to be subject to licensing restrictions that prevent it from being used by the system's development team(s). However, there may be licensing restrictions that prevent it from being used by outside parties. Using data from the system's context of use also raises questions about consent and compensation. Although it may be possible (though not necessarily easy) to contact data subjects to request their consent or to compensate them fairly for contributing their data, the perceived need to do this may be weaker than when creating a new dataset by collecting data directly from data subjects.

Approach 4: Create a new dataset by collecting data

By far the most flexible approach is to create a new dataset by collecting data directly from data subjects, specifically for the purpose of conducting the disaggregated evaluation. However, this approach is much more time consuming and much more expensive than the other approaches. Indeed, the financial costs may be so great that this approach may only feasible for development teams with extensive resources.

As with existing datasets or new datasets created using scraped data, new datasets created by collecting data directly from data subjects can only be used for forward-looking evaluations. However, they can support evaluations that will take place in the laboratory and evaluations that will take place in situ. One way to achieve the latter is to conduct an in-situ pilot, in which data subjects interact with a complete or partially functioning system in tightly controlled conditions. This provides a way to ensure that the resulting dataset reflects the system's intended use cases and deployment contexts, as well as capturing some of the sociotechnical dynamics and their effects on system performance (Introna and Nissenbaum 2009). That said, in-situ pilots can be extremely time consuming and expensive, thereby limiting the number of use cases and deployment contexts that can be considered.

The flexibility afforded by collecting new data directly from data subjects means that it is possible to ensure sufficient representation of the groups of interest—even if those groups are based on factors that are rare or on multiple factors—and to ask data subjects to self-report group membership. That said, we note that it is important to make sure that the data collection mechanisms are sufficiently inclusive of the groups of interest. For example, Park et al. (2021) found that many people with disabilities were unable to capture and upload video or speech samples. It is also possible to account for additional factors by holding their values constant or by treating them as if they were an additional focus of the evaluation. And, in either case, data points can be labeled so as to indicate the values of the additional factors. Finally, this approach also provides complete control over licensing, and makes it easy to request data subjects' consent and to compensate them fairly for contributing their data. However, despite these numerous advantages, this approach also places a greater burden on members of the groups of interest by requiring their active participation in the evaluation as data subjects—itself a form of injustice.

Which performance metric(s) will be used?

The performance of many AI systems cannot be usefully summarized via a single metric. For example, the performance of a face-recognition system might refer to its false positive rate or its false negative rate. A disaggregated evaluation that uses only false positive rates will fail to uncover disparities involving false negative rates, and vice versa. Moreover, false positives and false negatives can cause different harms to different stakeholders, depending on the use case. If a face-identification system is used to grant workplace access to employees, then false positives may cause harms to the employer (e.g., loss of property) by granting access to non-employees, while false negatives will cause harms to individual employees (e.g., being unable to do their jobs, feeling singled out or discriminated against) by denying them access to their workplace. NIST's disaggregated evaluation of face-recognition systems therefore assessed and reported false positive and false negative rates.

The performance metric(s) that will be used are primarily

determined by what will be evaluated (i.e., the system as a whole or one or more of its constituent components) and by the context in which the evaluation will take place. For example, when evaluating commercially available speech-recognition systems, Koenecke et al. (2020) used word error rate because they were only able to access the systems as a whole. Had they been able to access the systems' language models, they might instead have used perplexity. As another example, if a face-verification system is evaluated in situ, then it is possible to use performance metrics that depend on an operator's decisions, as well as the system's outputs.

We also note that considerations relating to the way in which system performance is reported may also influence the performance metric(s) that will be used. For example, a face-recognition system's false positive rate is one minus its true negative rate. Therefore assessing its false positive rate is equivalent to assessing its true negative rate. However, as noted by NIST in a report on its vendor tests of commercially available face-recognition systems (Grother, Ngan, and Hanaoka 2019a), "readers don't perceive differences in numbers near 100% well, becoming inured to the 'high-nineties' effect where numbers close to 100 are perceived indifferently." Moreover, the harms experienced by people whose faces are being recognized (or not) are directly related to false positive and false negative rates. In contrast, they are inversely related to true negative and true positive rates. The report cites an example that is similar to the workplace access use case described above and explains how doubling the false negative rate doubles the number of employees that will be harmed. Reporting the system's false negative rate, rather than its true positive rate, therefore emphasizes the direct connection between poor performance and harms. Similarly, performance disparities can be reported in absolute or relative terms (Keppel et al. 2005). Reporting each group's performance relative to that of the bestperforming group can make it easier to immediately grasp the extent to which the system is underperforming for these groups. For example, if a system has a false negative rate of 0.01 for women and a false negative rate of 0.1 for people who are non-binary, then the absolute performance disparity is 0.09, while the relative performance disparity is 900%.

Lastly, we emphasize that any set of performance metrics may fail to capture those aspects of system performance that are more subjective, context-dependent, or otherwise harder to quantify. For this reason, different people may experience an AI system differently, even when a disaggregated evaluation appears to demonstrate the absence of any performance disparities involving the groups to which they belong.

How will performance be analyzed?

The way in which performance will be analyzed depends on many of the design choices that we described above, including the goal of the evaluation, the performance metric(s) that will be used, the way in which additional factors are accounted for, and the composition of the evaluation dataset.

At a high level, there are two types of performance analysis: confirmatory and exploratory. A confirmatory analysis is appropriate when a disaggregated evaluation is intended to conclusively demonstrate the existence or

absence of suspected performance disparities. However, for it be possible to conduct a confirmatory analysis, additional factors must be accounted for by holding their values constant or by considering a range of values for each such factor. Moreover, the distributions over factor values must be roughly balanced. And, distributions over the groups of interest must themselves be roughly balanced so as to improve the sensitivity of the analysis. Because it is difficult to meet these requirements, confirmatory analyses are usually only feasible when assessing and reporting system performance for a small number of particularly salient groups in scenarios where there are only a few additional factors. Confirmatory analyses often use datasets that were created by collecting data directly from data subjects.

In contrast, an exploratory analysis is appropriate when a disaggregated evaluation is intended to less conclusively demonstrate the existence or absence of suspected performance disparities or to uncover potential causes of performance disparities-potentially for the purpose of designing and conducting subsequent evaluations that will support confirmatory analyses. An exploratory analysis can be conducted regardless of the approach used to account for additional factors and regardless of the distributions over factor values or the distributions over the groups of interest. Exploratory analyses are therefore feasible even when assessing and reporting system performance for a large number of groups or when there are many additional factors. There are also no restrictions on the types of evaluation datasets that can be used when conducting exploratory analyses. Many well-known disaggregated evaluations are therefore best understood as relying on exploratory analyses.

The simplest way to conduct either a confirmatory analysis or an exploratory analysis is to assess each performance metric for each group of interest and then directly compare the resulting values (i.e., point estimates) for each metric. Although this approach is easy to implement, it does not account for any randomness in the evaluation dataset and therefore introduces the possibility of misleading results. In contrast, using statistical techniques that incorporate uncertainty (e.g., *p*-values, confidence intervals, posterior probabilities, permutation tests) can better guard against misleading results. Furthermore, these techniques can also make it easier to detect subtle differences, thereby reducing the likelihood that performance disparities will fail to be detected.

In the context of face-based AI systems, generalized linear mixed-effect regression models have been used to conduct both confirmatory and exploratory analyses (e.g., Givens et al. 2013; Beveridge et al. 2010). As well as incorporating uncertainty, these models provide a way to account for additional factors when the distributions over factor values are not the same for each group of interest. They are also particularly appropriate when the data points in the evaluation dataset are "grouped"—for example, multiple utterances from the same speaker or multiple images of the same person (Gelman 2006)—and they are well suited to analyzing performance for groups based on multiple factors. However, they often rely on strong distributional assumptions about the evaluation dataset that may not hold.

When conducting an exploratory analysis, decision trees

and other partitioning methods can be used to construct a granular and high-dimensional view of system performance. This approach is particularly effective at uncovering potential causes of performance disparities. For example, researchers have used these high-dimensional "error terrains" to understand the effects of demographic factors, sociocultural factors, and environmental factors on face-based AI systems (Lakkaraju et al. 2017; Nushi, Kamar, and Horvitz 2018). High-dimensional performance analyses can "automatically" find groups based on multiple factors for which a system is underperforming using variable importance ranking or other variable selection methods. However, such methods will struggle to distinguish between the effects of factors that are highly correlated. For example, when assessing and reporting the performance of a face-recognition system, if all images of people wearing glasses are poorly lit and all poorly lit images are of people wearing glasses, but only one of these groups actually causes the system to perform poorly, then it will be difficult to determine which one. This highlights the value of accounting for factors by considering a range of values, as we described above. We also note that high-dimensional error terrains can yield misleading results without efforts to mitigate overfitting or p-hacking. For this reason, high-dimensional performance analyses are best used to inform the design of subsequent disaggregated evaluations that will support confirmatory analyses.

Lastly, we note that there are other—non-statistical—ways to uncover potential causes of performance disparities. For example, Muthukumar et al. (2019) used computer vision post-processing techniques and post-hoc explanation methods to investigate potential causes of the performance disparities that were revealed by the Gender Shades study.

How transparent will the evaluation be?

Disaggregated evaluations can vary considerably in their level of transparency. For example, ProPublica made all aspects of their evaluation of Northpointe's COMPAS recidivism-prediction system publicly available, including their results and conclusions (Angwin et al. 2016), a full description of their design choices (Larson et al. 2016), their evaluation dataset, and the source code that they used to analyze system performance (ProPublica 2016). In contrast, development teams who design and conduct disaggregated evaluations to better understand the performance of their own AI systems often choose not to disclose any details, though some have disclosed results and other information as a way to inform others about their systems' characteristics and limitations (e.g., Google 2020; Microsoft 2019a).

There are many considerations and tradeoffs that underlie choices about transparency. If all aspects of a disaggregated evaluation are made publicly available, then others can easily repeat the evaluation to verify its results and conclusions or use the evaluation dataset to conduct disaggregated evaluations of other AI systems. For example, many researchers have drawn on ProPublica's design choices, evaluation dataset, and source code to further interrogate its results and conclusions (e.g., Kleinberg, Mullainathan, and Raghavan 2017a; Corbett-Davies et al. 2016; Chouldechova 2017). We note that the public may be more likely to trust

disaggregated evaluations if all aspects are made publicly available. However, development teams may be reluctant to do this for reasons relating to their competitive advantage.

Making evaluation datasets publicly available raises the possibility of dataset misuse, such as using evaluation datasets to develop AI systems that cause new harms to already-disadvantaged, at-risk, or otherwise-marginalized groups. The researchers who conducted the Gender Shades study attempted to reduce this possibility by restricting access to the PPB dataset to researchers wishing to use it for non-commercial purposes. The downside to this choice is that development teams in companies who wish to understand the performance of their own gender classifiers must recreate the evaluation dataset themselves, and it is not be possible do this in a way that yields an identical dataset.

Discussion and Conclusion

In this paper, we have drawn attention to the choices that must be made when designing a disaggregated evaluation, as well as some of the key considerations that underlie these choices and the tradeoffs between these considerations. Making these choices is rarely an easy task and the ramifications can be hard to predict. Although we have approached this topic from the perspective of evaluation designers, our paper can also serve as a road map when interpreting an evaluation's results and conclusions. However, for this to be possible, evaluation designers must document their choices, along with the underlying considerations and tradeoffs that that have made. Existing documentation approaches, like datasheets for datasets (Gebru et al. 2018) and model cards (Mitchell et al. 2019), may be of value here.

Our paper highlights the importance of taking a rigorous approach to designing and conducting disaggregated evaluations. The time and effort spent on careful dataset construction, including labeling the values of additional factors that may affect system performance, will lead to more conclusive—and more actionable—results. Similarly, ensuring that an evaluation dataset is representative of a system's intended use cases and deployment contexts will yield results that better reflect the system's performance in practice. Of course, there are tradeoffs too. For example, tailoring a disaggregated evaluation too closely to one use case or deployment context may lead to results that do not generalize.

There are several questions we have left unaddressed. For example, we have assumed that an evaluation's designers have access to ground truth labels for the task that the system is intended to perform. However, in many scenarios, the labels may be inaccurate, either due to measurement issues (Jacobs and Wallach 2021) or due to discrimination (Friedler, Scheidegger, and Venkatasubramanian 2016). When this is the case and when there is no way to identify the extent or nature of the mislabeling, an evaluation's results will be meaningless. We also emphasize that although uncovering performance disparities is essential to the responsible deployment of AI systems, reducing performance disparities can be a fraught task. For example, well-known impossibility results imply that performance disparities according to one metric may originate from a decision to reduce performance disparities according to another metric (Chouldechova 2017; Kleinberg, Mullainathan, and Raghavan 2017b). In addition, improving performance may not be a desirable outcome for the groups of people for which a system is underperforming. This is especially true for face-recognition systems, which may be perceived as a threat whether they perform well or poorly (Hassein 2017). Although disaggregated evaluations can add urgency to normative debates about AI systems, there are many other considerations beyond performance that can determine a system's desirability, trustworthiness, or acceptance.

References

Algorithmic Justice League and the Center on Privacy and Technology at Georgetown Law. 2018. Safe Face Pledge. https://www.safefacepledge.org/.

Andrus, M.; Spitzer, E.; Brown, J.; and Xiang, A. 2020. "What We Can't Measure, We Can't Understand": Challenges to Demographic Data Procurement in the Pursuit of Fairness. *arXiv preprint arXiv:2011.02282*.

Angwin, J.; Larson, J.; Mattu, S.; and Kirchner, L. 2016. Machine Bias: There's software used across the country to predict future criminals. And it's biased against blacks. *ProPublica*.

Apple Inc. 2019. About Face ID advanced technology. https://support.apple.com/en-us/HT208108.

Arrieta-Ibarra, I.; Goff, L.; Jiménez-Hernández, D.; Lanier, J.; and Weyl, E. G. 2018. Should We Treat Data as Labor? Moving Beyond "Free". *American Economic Association Papers and Proceedings* 108: 38–42.

Australian Border Force. 2019. SmartGates. https://www.abf.gov.au/entering-and-leaving-australia/smartgates.

Barocas, S.; Crawford, K.; Shapiro, A.; and Wallach, H. 2017. The problem with bias: from allocative to representational harms in machine learning. Special Interest Group for Computing. *Information and Society (SIGCIS)* 2.

Benthhall, S.; and Haynes, B. D. 2019. Racial categories in machine learning. In *FAT*'19: Proceedings of the Conference on Fairness, Accountability, and Transparency*, 289–298.

Best-Rowden, L.; and Jain, A. K. 2018. Longitudinal study of automatic face recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence* 40(1): 148–162.

Beveridge, J. R.; Givens, G. H.; Phillips, P. J.; and Draper, B. A. 2009. Factors that influence algorithm performance in the Face Recognition Grand Challenge. *Computer Vision and Image Understanding* 113(6): 750–762. ISSN 10773142. doi:10.1016/j.cviu.2008.12.007.

Beveridge, J. R.; Givens, G. H.; Phillips, P. J.; Draper, B. A.; Bolme, D. S.; and Lui, Y. M. 2010. FRVT 2006: Quo Vadis face quality. *Image and Vision Computing* 28(5): 732–743. ISSN 02628856. doi:10.1016/j.imavis.2009.09.005.

Bogen, M.; Rieke, A.; and Ahmed, S. 2020. Awareness in Practice: Tensions in Access to Sensitive Attribute Data for Antidiscrimination. *Proceedings of FAT**.

Bolukbasi, T.; Chang, K.-W.; Zou, J. Y.; Saligrama, V.; and Kalai, A. T. 2016. Man is to computer programmer as woman is to homemaker? Debiasing word embeddings. In *Advances in Neural Information Processing Systems*, 4349–4357

Buolamwini, J. 2018. When the Robot Doesn't See Dark Skin. *The New York Times*.

Buolamwini, J.; and Gebru, T. 2018. Gender shades: Intersectional accuracy disparities in commercial gender classification. In *Conference on Fairness, Accountability and Transparency*, 77–91.

Chouldechova, A. 2017. Fair prediction with disparate impact: A study of bias in recidivism prediction instruments. *Big Data* 5(2): 153–163.

Chouldechova, A.; Putnam-Hornstein, E.; Prado, D. B.; Fialko, O.; and Vaithianathan, R. 2018. A case study of algorithm-assisted decision making in child maltreatment hotline screening decisions. In *Proceedings of the Conference on Fairness, Accountability, and Transparency (FAT*)*.

Cook, C.; Howard, J.; Sirotin, Y.; Tipton, J.; and Vemury, A. 2019. Demographic effects in facial recognition and their dependence on image acquisition: An evaluation of eleven commercial systems. *IEEE Transactions on Biometrics, Behavior, and Identity Science*.

Corbett-Davies, S.; Pierson, E.; Feller, A.; and Goel, S. 2016. A computer program used for bail and sentencing decisions was labeled biased against blacks. It's actually not that clear. *Washington Post*.

Crenshaw, K. 1989. Demarginalizing the Intersection of Race and Sex: A Black Feminist Critique of Antidiscrimination Doctrine, Feminist Theory and Antiracist Politics. *University of Chicago Legal Forum*.

DeVries, T.; Misra, I.; Wang, C.; and van der Maaten, L. 2019. Does object recognition work for everyone? https://research.fb.com/wp-content/uploads/2019/06/Does-Object-Recognition-Work-for-Everyone.pdf.

Eidinger, E.; Enbar, R.; and Hassner, T. 2014. Age and gender estimation of unfiltered faces. *IEEE Transactions on Information Forensics and Security* 9(12): 2170–2179. ISSN 15566013. doi:10.1109/TIFS.2014.2359646.

Federal Bureau of Investigation. 2019. Next Generation Identification (NGI). https://www.fbi.gov/services/cjis/fingerprints-and-other-biometrics/ngi.

Foundation, E. F. 2019. Bans, Bills and Moratoria. https://www.eff.org/aboutface/bans-bills-and-moratoria.

Friedler, S. A.; Scheidegger, C.; and Venkatasubramanian, S. 2016. On the (im)possibility of fairness. CoRR arXiv:1609.07236.

Gebru, T.; Morgenstern, J.; Vecchione, B.; Vaughan, J. W.; Wallach, H.; Daumeé III, H.; and Crawford, K. 2018. Datasheets for datasets. CoRR arXiv:1803.09010.

Gelman, A. 2006. Multilevel (hierarchical) modeling: What It can and cannot do. *Technometrics* 48(3): 432–435. ISSN 00401706. doi:10.1198/004017005000000661.

- Gillespie, E. 2019. Are you being scanned? How facial recognition technology follows you, even as you shop. https://www.theguardian.com/technology/2019/feb/24/are-you-being-scanned-how-facial-recognition-technology-follows-you-even-as-you-shop.
- Givens, G. H.; Beveridge, J. R.; Phillips, P. J.; Draper, B.; Lui, Y. M.; and Bolme, D. 2013. Introduction to face recognition and evaluation of algorithm performance. *Computational Statistics and Data Analysis* 67: 236–247. ISSN 01679473. doi:10.1016/j.csda.2013.05.025. URL http://dx.doi.org/10.1016/j.csda.2013.05.025.
- Google. 2019. Google Photos Help Search by people, things, & places in your photos. https://support.google.com/photos/answer/6128838.
- Google. 2020. Google Cloud Model Cards: Face Detection Model Card v0. https://modelcards.withgoogle.com/face-detection.
- Greene, J. 2020. Microsoft won't sell police its facial-recognition technology, following similar moves by Amazon and IBM. *The Washington Post* URL https://www.washingtonpost.com/technology/2020/06/11/microsoft-facial-recognition/.
- Grother, P.; Ngan, M.; and Hanaoka, K. 2019a. Face Recognition Vendor Test (FRVT) Part 1: Verification. Interagency report draft, National Institute of Standards and Technology (NIST). URL https://nist.gov/programs-projects/frvt-11-verification.
- Grother, P.; Ngan, M.; and Hanaoka, K. 2019b. Face Recognition Vendor Test (FRVT) Part 2: Identification. Interagency report 8271, National Institute of Standards and Technology (NIST). URL https://doi.org/10.6028/NIST.IR.8271.
- Grother, P.; Ngan, M.; and Hanaoka, K. 2019c. Face Recognition Vendor Test (FRVT) Part 3: Demographic Effects. Retrieved on at https://doi.org/10.6028/NIST.IR.8280.
- Hanna, A.; Denton, E.; Smart, A.; and Smith-Loud, J. 2020. Towards a critical race methodology in algorithmic fairness. In FAT*'20: Proceedings of the Conference on Fairness, Accountability, and Transparency, 501–512.
- Hassein, N. 2017. Against Black Inclusion in Facial Recognition. https://digitaltalkingdrum.com/2017/08/15/against-black-inclusion-in-facial-recognition/.
- Hellman, D. 2018. Indirect Discrimination and the Duty to Avoid Compounding Injustice. In Collins, H.; and Khaitan, T., eds., *Foundations of Indirect Discrimination Law*. Hart.
- HireVue. 2019. HireVue Hiring Intelligence Assessment & Video Interview Software. https://www.hirevue.com.
- IBM. 2020. IBM CEO's Letter to Congress on Racial Justice Reform. https://www.ibm.com/blogs/policy/facial-recognition-sunset-racial-justice-reforms/.
- Introna, L. D.; and Nissenbaum, H. 2009. Facial Recognition Technology: A Survey of Policy and Implementation Issues. *Center for Catastrophe Preparedness and Response, New York University*.

- Jacobs, A. Z.; and Wallach, H. 2021. Measurement and Fairness. In *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*.
- Kärkkäinen, K.; and Joo, J. 2019. FairFace: Face Attribute Dataset for Balanced Race, Gender, and Age. *arXiv preprint arXiv:1908.04913*.
- Keppel, K.; Pamuk, E.; Lynch, J.; Carter-Pokras, O.; Kim, I.; Mays, V.; Pearcy, J.; Schoenbach, V.; and Weissman, J. S. 2005. Methodological issues in measuring health disparities. *Vital and Health Statistics, Series 2: Data Evaluation and Methods Research* "(141): 1–16. ISSN 00832057.
- Klare, B. F.; Burge, M. J.; Klontz, J. C.; Vorder Bruegge, R. W.; and Jain, A. K. 2012. Face recognition performance: Role of demographic information. *IEEE Transactions on Information Forensics and Security* 7(6): 1789–1801. ISSN 15566013. doi:10.1109/TIFS.2012.2214212.
- Kleinberg, J.; Mullainathan, S.; and Raghavan, M. 2017a. Inherent trade-offs in the fair determination of risk scores. *ITCS*.
- Kleinberg, J.; Mullainathan, S.; and Raghavan, M. 2017b. Inherent Trade-Offs in the Fair Determination of Risk Scores. In 8th Innovations in Theoretical Computer Science Conference (ITCS 2017). Schloss Dagstuhl-Leibniz-Zentrum fuer Informatik.
- Koenecke, A.; Nam, A.; Lake, E.; Nudell, J.; Quartey, M.; Mengesha, Z.; Toups, C.; Rickford, J. R.; Jurafsky, D.; and Goel, S. 2020. Racial disparities in automated speech recognition. *Proceedings of the National Academy Sciences* 117(14): 7684–7689.
- Krishnapriya, K. S.; Vangara, K.; King, M. C.; Albiero, V.; and Bowyer, K. 2019a. Characterizing the variability in face recognition accuracy relative to race. *IEEE Computer Society Conference on Computer Vision and Pattern Recognition Workshops* 2019-June: 2278–2285. ISSN 21607516. doi: 10.1109/CVPRW.2019.00281.
- Krishnapriya, K. S.; Vangara, K.; King, M. C.; Albiero, V.; and Bowyer, K. 2019b. Characterizing the variability in face recognition accuracy relative to race. CoRR arXiv:1904.07325.
- Lakkaraju, H.; Kamar, E.; Caruana, R.; and Horvitz, E. 2017. Identifying unknown unknowns in the open world: Representations and policies for guided exploration. *31st AAAI Conference on Artificial Intelligence, AAAI 2017* 2124–2132.
- Larson, J.; Mattu, S.; Kirchner, L.; and Angwin, J. 2016. How We Analyzed the COMPAS Recidivism Algorithm. *ProPublica* URL https://www.propublica.org/article/howwe-analyzed-the-compas-recidivism-algorithm?token= SV45W9VHgigYbUE-m7o9xnvExqobnjcg.
- Law 360. 2021. Illinois Cases To Watch In 2021. https://www.law360.com/articles/1336065/illinois-cases-to-watch-in-2021.
- Lee, K. C.; Ho, J.; and Kriegman, D. J. 2005. Acquiring linear subspaces for face recognition under variable

- lighting. *IEEE Transactions on Pattern Analysis and Machine Intelligence* 27(5): 684–698. ISSN 01628828. doi: 10.1109/TPAMI.2005.92.
- Lohr, S. 2018. Facial Recognition Is Accurate, if You're a White Guy. *The New York Times*.
- Microsoft. 2019a. Transparency Note: Azure Cognitive Services Face API. https://azure.microsoft.com/enus/resources/transparency-note-azure-cognitive-services-face-api/.
- Microsoft. 2019b. Windows Hello: Discover facial recognition on Windows 10. https://www.microsoft.com/en-us/windows/windows-hello.
- Mitchell, M.; Wu, S.; Zaldivar, A.; Barnes, P.; Vasserman, L.; Hutchinson, B.; Spitzer, E.; Raji, I. D.; and Gebru, T. 2019. Model cards for model reporting. In *Proceedings of the Conference on Fairness, Accountability, and Transparency*, 220–229. ACM.
- Muthukumar, V.; Pedapati, T.; Ratha, N.; Sattigeri, P.; Wu, C.-W.; Kingsbury, B.; Kumar, A.; Thomas, S.; Mojsilovic, A.; and Varshney, K. R. 2019. Understanding Unequal Gender Classification Accuracy from Face Images. CoRR arXiv:1812.00099.
- Nicol, A.; Casey, C.; and MacFarlane, S. 2002. Children are ready for speech technology-but is the technology ready for them. *Interaction Design and Children, Eindhoven, The Netherlands*.
- Nushi, B.; Kamar, E.; and Horvitz, E. 2018. Towards accountable ai: Hybrid human-machine analyses for characterizing system failure. In *Proceedings of the AAAI Conference on Human Computation and Crowdsourcing*.
- Obermeyer, Z.; Powers, B.; Vogeli, C.; and Mullainathan, S. 2019. Dissecting racial bias in an algorithm used to manage the health of populations. *Science* 366: 447–453.
- Park, J. S.; Bragg, D.; Kamar, E.; and Morris, M. R. 2021. Designing an Online Infrastructure for Collecting AI Data From People With Disabilities. In *Proceedings of the 2021 Conference on Fairness, Accountability, and Transparency*.
- Poursabzi-Sangdeh, F.; Samadi, S.; Vaughan, J. W.; and Wallach, H. 2020. A Human in the Loop is Not Enough: The Need for Human-Subject Experiments in Facial Recognition. In *CHI workshop on Human-Centered Approaches to Fair and Responsible AI*.
- Proctorio. 2021. A Comprehensive Learning Integrity Platform Proctorio. https://proctorio.com/.
- ProPublica. 2016. Data and analysis for 'Machine Bias'. https://github.com/propublica/compas-analysis.
- Raji, I. D.; and Buolamwini, J. 2019. Actionable auditing: Investigating the impact of publicly naming biased performance results of commercial ai products. In *AAAI/ACM Conf. on AI Ethics and Society*, volume 1.
- Raji, I. D.; Smart, A.; White, R. N.; Mitchell, M.; Gebru, T.; Hutchinson, B.; Smith-Loud, J.; Theron, D.; and Barnes, P. 2020a. Closing the AI Accountability Gap: Defining an End-to-End Framework for Internal Algorithmic Auditing.

- Raji, I. D.; Smart, A.; White, R. N.; Mitchell, M.; Gebru, T.; Hutchinson, B.; Smith-Loud, J.; Theron, D.; and Barnes, P. 2020b. Closing the AI accountability gap: defining an end-to-end framework for internal algorithmic auditing. In *Proceedings of the 2020 Conference on Fairness, Accountability, and Transparency*, 33–44.
- Rodger, J. A.; and Pendharkar, P. C. 2004. A field study of the impact of gender and user's technical experience on the performance of voice-activated medical tracking application. *International Journal of Human-Computer Studies* 60(5-6): 529–544.
- Selbst, A. D.; Boyd, D.; Friedler, S. A.; Venkatasubramanian, S.; and Vertesi, J. 2019. Fairness and abstraction in sociotechnical systems. In *Proceedings of the Conference on Fairness, Accountability, and Transparency*, 59–68.
- Snow, J. 2018. Amazon's Face Recognition Falsely Matched 28 Members of Congress With Mugshots. https://www.aclu.org/blog/privacy-technology/surveillance-technologies/amazons-face-recognition-falsely-matched-28.
- Stark, L. 2019. Facial Recognition is the Plutonium of AI. *ACM XRDS* 25(3): 50–55.
- Tatman, R. 2017. Gender and dialect bias in YouTube's automatic captions. In *Proceedings of the First ACL Workshop on Ethics in Natural Language Processing*, 53–59.
- Watch, S. 2021. Sepsis Watch: the implementation of a Duke-specific early warning system for sepsis Duke Institute for Health Innovation. https://dihi.org/project/sepsiswatch/.
- White House, T. 2021. Executive Order On Advancing Racial Equity and Support for Underserved Communities Through the Federal Government. https://www.whitehouse.gov/briefing-room/presidential-actions/2021/01/20/executive-order-advancing-racial-equity-and-support-for-underserved-communities-through-the-federal-government/.
- Whitelam, C.; Taborsky, E.; Blanton, A.; Maze, B.; Adams, J.; Miller, T.; Kalka, N.; Jain, A. K.; Duncan, J. A.; Allen, K.; Cheney, J.; and Grother, P. 2017. IARPA Janus Benchmark-B Face Dataset. *IEEE Computer Society Conference on Computer Vision and Pattern Recognition Workshops* 2017-July: 592–600. ISSN 21607516. doi:10.1109/CVPRW. 2017.87.