

Generating Datasets with Pretrained Language Models

Timo Schick and Hinrich Schütze

Center for Information and Language Processing

LMU Munich, Germany

`schickt@cis.lmu.de`

Abstract

To obtain high-quality sentence embeddings from pretrained language models, they must either be augmented with additional pretraining objectives or finetuned on large amounts of labeled text pairs. While the latter approach typically outperforms the former, it requires great human effort to generate suitable datasets of sufficient size. In this paper, we show how large pretrained language models can be leveraged to obtain high-quality embeddings without requiring any labeled data, finetuning or modifications to their pretraining objective: We utilize their generative abilities to generate entire datasets of labeled text pairs from scratch, which can then be used for regular finetuning of much smaller models. Our fully unsupervised approach outperforms strong baselines on several English semantic textual similarity datasets.¹

1 Introduction

While pretrained language models (PLMs) achieve strong results for a variety of NLP tasks (Peters et al., 2018; Radford et al., 2018; Devlin et al., 2019), they do not produce good sentence embeddings out of the box (Reimers and Gurevych, 2019). Various recent approaches try to fix this by augmenting or replacing the language modeling objective with likewise unsupervised sentence-level objectives (e.g., Zhang et al., 2020; Li et al., 2020), but they typically lag behind their supervised counterparts trained on human-annotated sentence pairs. Unfortunately, obtaining large amounts of high-quality training data can be both difficult and prohibitively expensive (Bowman et al., 2015; Agirre et al., 2016). Furthermore, as model sizes continually increase (Radford et al., 2019; Raffel et al., 2020; Brown et al., 2020; Fedus et al., 2021) it becomes increasingly more expensive and challenging to finetune PLMs.

¹Our implementation is publicly available at <https://github.com/timoschick/dino>

Task: Write two sentences that mean the same thing.

Sentence 1: “A man is playing a flute.”

Sentence 2: “He’s playing a flute.”

Task: Write two sentences that are somewhat similar.

Sentence 1: “A man is playing a flute.”

Sentence 2: “A woman has been playing the violin.”

Task: Write two sentences that are on completely different topics.



Sentence 1: “A man is playing a flute.”

Sentence 2: “A woman is walking down the street.”

Figure 1: **Continuations** generated by GPT2-XL with DINO for three different **task descriptions**. If not given, **input sentences** are also generated automatically.

To alleviate both problems, we explore a very different approach for obtaining high-quality sentence embeddings: Inspired by how existing NLI datasets have been created by human crowdworkers (Bowman et al., 2015; Williams et al., 2018), we loosely replicate this setup but replace human annotators with large PLMs. This enables us to automatically create entire datasets from scratch that can be used for supervised training of much smaller models. Not only does this solve the problem of limited training data, it also provides a viable path to leverage big models like GPT-3 (Brown et al., 2020) without requiring any updates to their parameters. As illustrated in Figure 1, our approach is based on recent methods for providing instructions to PLMs (e.g., Radford et al., 2019; Brown et al., 2020; Schick and Schütze, 2020a, 2021). We use the *self-debiasing* approach of Schick et al. (2021) to ensure that each generated text pair is not only a good fit for a given similarity label, but also *not* a good fit for other labels. We refer to our method as **Datasets from Instructions (DINO)**.

In summary, our contributions are as follows:

- We introduce DINO, a method for automatically generating labeled datasets of arbitrary size by providing PLMs with instructions.
- We release STS-, the first textual similarity dataset exclusively generated by a PLM without any human annotation effort.
- We show that Sentence-RoBERTa (Reimers and Gurevych, 2019) trained on STS- outperforms strong baselines on several semantic textual similarity datasets.

2 Related Work

There are many unsupervised approaches for obtaining sentence embeddings, for example by averaging word embeddings (Mikolov et al., 2013; Pennington et al., 2014; Bojanowski et al., 2017) or with carefully designed sentence-level objectives (Le and Mikolov, 2014; Kiros et al., 2015). Several recent approaches obtain sentence representations by supplementing BERT (Devlin et al., 2019) or other PLMs with additional unsupervised objectives (Zhang et al., 2020; Li et al., 2020; Wu et al., 2020; Giorgi et al., 2020). Often, labeled datasets such as paraphrase databases (Wieting and Gimpel, 2018) or natural language inference datasets (Conneau et al., 2017; Cer et al., 2018; Reimers and Gurevych, 2019) are used.

Various approaches *augment* existing datasets with automatically generated examples (Anaby-Tavor et al., 2020; Papanikolaou and Pierleoni, 2020; Yang et al., 2020; Kumar et al., 2021), but in contrast to our work, all of these approaches require that there already exists a labeled dataset on which the generator is finetuned. Providing PLMs with task descriptions for zero- or few-shot learning has been studied extensively (e.g., Radford et al., 2019; Puri and Catanzaro, 2019; Opitz, 2019; Brown et al., 2020; Schick and Schütze, 2020a,b, 2021; Weller et al., 2020; Gao et al., 2020; Tam et al., 2021). However, none of these approaches is suitable for generating sentence embeddings.

Closely related to our work, Efrat and Levy (2020) examine the ability of PLMs to follow natural language instructions for generating examples in place of human crowdworkers, but they use a different approach and find that PLMs perform poorly across all tasks considered.

Task: Write two sentences that i_y .

Sentence 1: “ \mathbf{x}_1 ”

Sentence 2: “

Figure 2: Instruction template $I_y(\mathbf{x}_1)$ for similarity label y and input sentence \mathbf{x}_1 ; i_y is described in Section 3

3 Datasets from Instructions

Let M be a PLM with vocabulary V , $X = V^*$ be the set of all token sequences and Y be a finite set of semantic similarity labels. Our aim is to generate a dataset $Z \subset X \times X \times Y$ of text *pairs* $(\mathbf{x}_1, \mathbf{x}_2)$ with corresponding similarity scores y . For $x \in V$ and $\mathbf{x} \in X$, we denote with $p_M(x | \mathbf{x})$ the probability that M assigns to x as a continuation for \mathbf{x} .

We first assume that we already have access to a set $X_1 \subset X$ of texts; this is a realistic setting for many real-world applications, where large amounts of unlabeled text are abundant, but it is difficult to obtain *interesting* text pairs and corresponding labels. DINO requires a set of *instructions* $\mathcal{I} = \{I_y | y \in Y\}$ where each $I_y \in \mathcal{I}$ is a function that, given an input $\mathbf{x}_1 \in X_1$, prompts its recipient to generate an appropriate second text \mathbf{x}_2 . We use the instructions shown in Figure 2 and consider three levels of similarity ($Y = \{0, 1, 2\}$), where

$$i_y = \begin{cases} \text{mean the same thing} & \text{if } y = 2 \\ \text{are somewhat similar} & \text{if } y = 1 \\ \text{are on completely different topics} & \text{if } y = 0 \end{cases}$$

is loosely based on the five-level similarity scheme of Cer et al. (2017). Note that for all y , I_y ends with an (opening) quotation mark. This is because we need to know when the PLM has completed the requested text; the opening quotation mark allows us to treat the next quotation mark generated by the model as a sign that it is done.

For a given $\mathbf{x}_1 \in X_1$ and $y \in Y$, we could directly use the set of instructions to obtain \mathbf{x}_2 by continuously sampling tokens

$$x_k \sim p_M(x_k | I_y(\mathbf{x}_1), x_1, \dots, x_{k-1})$$

starting from $k = 1$ until x_k is a quotation mark and setting $\mathbf{x}_2 = x_1, \dots, x_{k-1}$. However, we may want the PLM to generate a text \mathbf{x}_2 that is not only a good fit for instruction $I_y(\mathbf{x}_1)$, but also explicitly *not* a good fit for some other instruction $I_{y'}(\mathbf{x}_1)$. We refer to the corresponding label y' as a *counter label* for y and denote the set of all counter

labels for y as $\text{CL}(y)$. For example, $2 \in \text{CL}(1)$ means that for $y = 1$, we want M to generate a sentence \mathbf{x}_2 that is somewhat similar to, but at the same time does *not* mean the same thing as \mathbf{x}_1 . We achieve this goal using the self-debiasing algorithm of Schick et al. (2021): When sampling x_k , we consider not just $p_y = p_M(x_k | I_y(\mathbf{x}_1), x_1, \dots, x_{k-1})$, its probability given $I_y(\mathbf{x}_1)$, but also $p_{y'}$, its probability given $I_{y'}(\mathbf{x}_1)$ for each $y' \in \text{CL}(y)$. We penalize each token x_k for which p_y is lower than any $p_{y'}$ by multiplying its probability with a factor $\alpha = \exp(\lambda \cdot \delta_y)$ where

$$\delta_y = p_y - \max_{y' \in \text{CL}(y)} p_{y'}$$



is the difference between x_k 's probability given $I_y(\mathbf{x}_1)$ and its maximum probability given $I_{y'}(\mathbf{x}_1)$ for any $y' \in \text{CL}(y)$, and the *decay constant* λ is a hyperparameter.


For settings where no set of unlabeled texts X_1 is available, a straightforward approach would be to use the phrase shown in Figure 2 up to and including the first quotation mark as an instruction to let the PLM generate both \mathbf{x}_1 and \mathbf{x}_2 . However, this approach has various issues: First, generated texts may not match the schema shown in Figure 1 (e.g., the model may never produce the string ‘‘Sentence 2:’’). Secondly, the set of texts \mathbf{x}_1 should ideally be highly diverse, whereas we want to give the model less leeway when generating \mathbf{x}_2 , so each sentence may require a different sampling strategy.

We solve both problems as follows: We first use I_y (Figure 2) up to and including the first quotation mark to generate \mathbf{x}_1 ; we stop as soon as the model produces a quotation mark. We then collect all so-obtained sentences in a set X_1 and proceed exactly as in the case where X_1 is already given.

4 Experiments

We evaluate DINO on various English semantic textual similarity datasets: the STS tasks 2012 - 2016 (Agirre et al., 2012, 2013, 2014, 2015, 2016), the STS benchmark (STSb) (Cer et al., 2017), and the SICK-Relatedness dataset (SICK) (Marelli et al., 2014). For all tasks, we consider an unsupervised setting without task-specific training examples.


We use DINO to generate two datasets: STSb-, a dataset for which we make use of STSb to obtain a set of texts X_1 , and STS-, where X_1 is generated from scratch. For both datasets, we use GPT2-XL as PLM with the set of counter labels defined as $\text{CL}(y) = \{y' \in Y \mid y' > y\}$ and a decay constant

of $\lambda = 100$, following Schick et al. (2021). We apply top- p (Holtzman et al., 2020) and top- k (Fan et al., 2018; Holtzman et al., 2018) sampling with $p = 0.9$, $k = 5$ and generate up to 40 output tokens. For each $\mathbf{x}_1 \in X_1$ and $y \in Y$, we generate up to two corresponding \mathbf{x}_2 's.² For STS-, we obtain X_1 by generating 15,000 sentences using only top- p sampling (again with $p = 0.9$) and no top- k sampling to ensure more diversity in the generated outputs. For both datasets, we remove all examples where $\mathbf{x}_1 = \mathbf{x}_2$ as those provide no training signal to a siamese model architecture. We split both datasets into training and validation sets using a 90/10 split.

To assess the quality of the generated datasets, we use them to train Sentence-RoBERTa (Reimers and Gurevych, 2019), a siamese network architecture based on RoBERTa (base) (Liu et al., 2019). As our datasets contain many noisy examples, we use a technique similar to label smoothing (Szegedy et al., 2016) with $\epsilon = 0.2$ and replace each y with

$$\tilde{y} = (1 - \epsilon) \cdot y + \sum_{y' \in Y} \epsilon \cdot y' / |Y|$$

which simplifies to $\tilde{y} = (1 - \epsilon) \cdot y + \epsilon$. Additionally, for each \mathbf{x}_1 , we sample two \mathbf{x}_2 's from *other* dataset entries and augment the dataset with $(\mathbf{x}_1, \mathbf{x}_2, 0)$. We use the default parameters of Reimers and Gurevych (2019) with a batch size of 32 and train for at most one epoch; the number of training steps is determined on the validation set.

Results We compare S-RoBERTa (base) trained on datasets generated with DINO to S-BERT and S-RoBERTa finetuned on NLI data as well as Universal Sentence Encoder (USE) (Cer et al., 2018) and InferSent (Conneau et al., 2017), all of which are trained on hundreds of thousands of labeled text pairs from SNLI (Bowman et al., 2015) and MNLI (Williams et al., 2018). We additionally compare to various fully unsupervised approaches: averaging word-level GloVe (Pennington et al., 2014) or BERT (Devlin et al., 2019) embeddings, using BERT's CLS token, and recent methods by Zhang et al. (2020) and Li et al. (2020) based on pretrained BERT models. As shown in Table 1, training on datasets generated with DINO clearly outperforms the fully unsupervised baselines; on average, training on STSb- even outperforms all approaches

²As the PLM does not always generate a closing quotation mark within the first 40 tokens, we use a maximum of five tries to generate the two \mathbf{x}_2 's for each \mathbf{x}_1 and y .



	Model	UD	STS12	STS13	STS14	STS15	STS16	STSb	SICK	Avg.
sup.	InferSent, GloVe	–	52.86	66.75	62.15	72.77	66.87	68.03	65.65	65.01
	USE	–	64.49	67.80	64.61	76.83	73.18	74.92	76.69	71.22
	S-BERT (base)	–	70.97	76.53	<u>73.19</u>	79.09	74.30	77.03	72.91	74.89
	S-RoBERTa (base)	–	<u>71.54</u>	72.49	70.80	78.74	73.69	77.77	<u>74.46</u>	74.21
unsup.	Avg. GloVe	–	55.14	70.66	59.73	68.25	63.66	58.02	53.76	61.32
	Avg. BERT	–	38.78	57.98	57.98	63.15	61.06	46.35	58.40	54.81
	BERT CLS	–	20.16	30.01	20.09	36.88	38.08	16.50	42.63	29.19
	Zhang et al. (2020)	NLI	56.77	69.24	61.21	75.23	70.16	69.21	64.25	66.58
	Li et al. (2020)	NLI	59.54	64.69	64.66	72.92	71.84	58.56	65.44	65.38
	Li et al. (2020)	STS	63.48	72.14	68.42	73.77	75.37	70.72	63.11	69.57
	DINO (STS- )	–	64.87	78.30	66.38	79.60	76.47	76.51	74.26	73.77
	DINO (STSb- )	STS	70.27	81.26	71.25	80.49	77.18	77.82	68.09	75.20

Table 1: Spearman’s rank correlation on STS12–16, STSb and SICK without task-specific finetuning for models with NLI supervision (“sup.”) and fully unsupervised (“unsup.”) models using the same evaluation setup as Reimers and Gurevych (2019). The second column shows which unlabeled data (“UD”) is used by unsupervised approaches in addition to original pretraining data; the final column shows average performance. Results for all baselines except Zhang et al. (2020) and Li et al. (2020) are from Reimers and Gurevych (2019). The best unsupervised result is shown in bold, the best overall results is underlined.





Model	STS12-16	STSb	SICK
DINO (STSb- )	76.09	77.82	68.09
^L decay constant $\lambda = 0$	65.50	70.71	67.60
^L decay constant $\lambda = 200$	75.40	77.49	66.83
^L no label smoothing	74.50	76.26	66.23
^L no augmentation	70.90	73.81	63.98


Table 2: Effect of removing self-debiasing ($\lambda = 0$) or increasing the decay constant ($\lambda = 200$), using no label smoothing and performing no data augmentation (sampling random \mathbf{x}_2 ’s for each \mathbf{x}_1) on the performance of DINO on STS12-16 (avg), STSb and SICK

with NLI supervision. STSb- gives better results than STS- on all STS datasets as its examples are – by design – very similar to examples found in these datasets, while training on STS- gives better results on SICK.

We investigate the importance of self-debiasing (Schick et al., 2021) in Table 2 (top); as can be seen, removing self-debiasing ($\lambda = 0$) dramatically hurts performance. Table 2 (bottom) shows that training on DINO datasets requires some measures to limit the effect of noisy labels: removing label smoothing and performing no data augmentation (i.e., not generating additional pairs $(\mathbf{x}_1, \mathbf{x}_2, 0)$ by sampling random \mathbf{x}_2 ’s for each \mathbf{x}_1) clearly hurts performance.

We finally take a qualitative look at some of the errors contained in the datasets created with DINO. As shown in Table 3, for $y = 2$ the PLM often generates sentences that omit or mix up important information, and sometimes produces sentences with an entirely different meaning. For $y = 0$,

y	\mathbf{x}_1	\mathbf{x}_2
2	US closes embassy in Syria	US Embassy in Syria
2	A man is playing the cello.	The cello is playing the man.
2	A plane is taking off.	I want to be a pilot.
0	Closed roads in Armenia	Open roads in Azerbaijan
0	The man is playing the guitar.	I’m not a guitar player.
0	A man is playing a large flute.	A man is listening to a small flute.

Table 3: Selection of low-quality examples in STSb-. Many examples for $y = 2$ do not actually mean the exact same thing, some examples for $y = 0$ are not on completely different topics.

we found the model to often simply flip words (“closed” \mapsto “open”, “large” \mapsto “small”) instead of producing sentences on completely different topics.

5 Conclusion

We have introduced DINO, a method for using large PLMs to generate entire datasets of sentence pairs with similarity labels from scratch, requiring no parameter updates. This is achieved by providing instructions in natural language, combined with the self-debiasing method of Schick et al. (2021). With appropriate measures for limiting the influence of noisy data, models trained on datasets generated with DINO achieve strong results on several semantic textual similarity datasets.

For future work, it would be interesting to see whether the noise in datasets generated with DINO can further be reduced, e.g. by using different sets of instructions (Jiang et al., 2020; Schick and Schütze, 2021).

References

- Eneko Agirre, Carmen Banea, Claire Cardie, Daniel Cer, Mona Diab, Aitor Gonzalez-Agirre, Weiwei Guo, Iñigo Lopez-Gazpio, Montse Maritxalar, Rada Mihalcea, German Rigau, Larraitz Uria, and Janyce Wiebe. 2015. [SemEval-2015 task 2: Semantic textual similarity, English, Spanish and pilot on interpretability](#). In *Proceedings of the 9th International Workshop on Semantic Evaluation (SemEval 2015)*, pages 252–263, Denver, Colorado. Association for Computational Linguistics.
- Eneko Agirre, Carmen Banea, Claire Cardie, Daniel Cer, Mona Diab, Aitor Gonzalez-Agirre, Weiwei Guo, Rada Mihalcea, German Rigau, and Janyce Wiebe. 2014. [SemEval-2014 task 10: Multilingual semantic textual similarity](#). In *Proceedings of the 8th International Workshop on Semantic Evaluation (SemEval 2014)*, pages 81–91, Dublin, Ireland. Association for Computational Linguistics.
- Eneko Agirre, Carmen Banea, Daniel Cer, Mona Diab, Aitor Gonzalez-Agirre, Rada Mihalcea, German Rigau, and Janyce Wiebe. 2016. [SemEval-2016 task 1: Semantic textual similarity, monolingual and cross-lingual evaluation](#). In *Proceedings of the 10th International Workshop on Semantic Evaluation (SemEval-2016)*, pages 497–511, San Diego, California. Association for Computational Linguistics.
- Eneko Agirre, Daniel Cer, Mona Diab, Aitor Gonzalez-Agirre, and Weiwei Guo. 2013. [*SEM 2013 shared task: Semantic textual similarity](#). In *Second Joint Conference on Lexical and Computational Semantics (*SEM), Volume 1: Proceedings of the Main Conference and the Shared Task: Semantic Textual Similarity*, pages 32–43, Atlanta, Georgia, USA. Association for Computational Linguistics.
- Eneko Agirre, Mona Diab, Daniel Cer, and Aitor Gonzalez-Agirre. 2012. Semeval-2012 task 6: A pilot on semantic textual similarity. In *Proceedings of the First Joint Conference on Lexical and Computational Semantics - Volume 1: Proceedings of the Main Conference and the Shared Task, and Volume 2: Proceedings of the Sixth International Workshop on Semantic Evaluation, SemEval '12*, page 385–393, USA. Association for Computational Linguistics.
- Ateret Anaby-Tavor, Boaz Carmeli, Esther Goldbraich, Amir Kantor, George Kour, Segev Shlomov, Naama Tepper, and Naama Zwerdling. 2020. [Do not have enough data? deep learning to the rescue!](#) *Proceedings of the AAAI Conference on Artificial Intelligence*, 34(05):7383–7390.
- Piotr Bojanowski, Edouard Grave, Armand Joulin, and Tomas Mikolov. 2017. Enriching word vectors with subword information. *Transactions of the Association for Computational Linguistics*, 5:135–146.
- Samuel R. Bowman, Gabor Angeli, Christopher Potts, and Christopher D. Manning. 2015. [A large annotated corpus for learning natural language inference](#). In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pages 632–642, Lisbon, Portugal. Association for Computational Linguistics.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. [Language models are few-shot learners](#). In *Advances in Neural Information Processing Systems*, volume 33, pages 1877–1901. Curran Associates, Inc.
- Daniel Cer, Mona Diab, Eneko Agirre, Iñigo Lopez-Gazpio, and Lucia Specia. 2017. [SemEval-2017 task 1: Semantic textual similarity multilingual and crosslingual focused evaluation](#). In *Proceedings of the 11th International Workshop on Semantic Evaluation (SemEval-2017)*, pages 1–14, Vancouver, Canada. Association for Computational Linguistics.
- Daniel Cer, Yinfei Yang, Sheng-yi Kong, Nan Hua, Nicole Limtiaco, Rhomni St. John, Noah Constant, Mario Guajardo-Cespedes, Steve Yuan, Chris Tar, Brian Strope, and Ray Kurzweil. 2018. [Universal sentence encoder for English](#). In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 169–174, Brussels, Belgium. Association for Computational Linguistics.
- Alexis Conneau, Douwe Kiela, Holger Schwenk, Loïc Barrault, and Antoine Bordes. 2017. [Supervised learning of universal sentence representations from natural language inference data](#). In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pages 670–680, Copenhagen, Denmark. Association for Computational Linguistics.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. [BERT: Pre-training of deep bidirectional transformers for language understanding](#). In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.
- Avia Efrat and Omer Levy. 2020. [The turking test: Can language models understand instructions?](#) *Computing Research Repository*, arXiv:2010.11982.

- Angela Fan, Mike Lewis, and Yann Dauphin. 2018. [Hierarchical neural story generation](#). In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 889–898, Melbourne, Australia. Association for Computational Linguistics.
- William Fedus, Barret Zoph, and Noam Shazeer. 2021. [Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity](#). *Computing Research Repository*, arXiv:2101.03961.
- Tianyu Gao, Adam Fisch, and Danqi Chen. 2020. [Making pre-trained language models better few-shot learners](#).
- John M. Giorgi, Osvald Nitski, Gary D. Bader, and Bo Wang. 2020. [Declutr: Deep contrastive learning for unsupervised textual representations](#).
- Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. 2020. [The curious case of neural text de-generation](#). In *International Conference on Learning Representations*.
- Ari Holtzman, Jan Buys, Maxwell Forbes, Antoine Bosselut, David Golub, and Yejin Choi. 2018. [Learning to write with cooperative discriminators](#). In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1638–1649, Melbourne, Australia. Association for Computational Linguistics.
- Zhengbao Jiang, Frank F. Xu, Jun Araki, and Graham Neubig. 2020. [How can we know what language models know?](#) *Transactions of the Association for Computational Linguistics*, 8:423–438.
- Ryan Kiros, Yukun Zhu, Russ R Salakhutdinov, Richard Zemel, Raquel Urtasun, Antonio Torralba, and Sanja Fidler. 2015. [Skip-thought vectors](#). In *Advances in Neural Information Processing Systems*, volume 28. Curran Associates, Inc.
- Varun Kumar, Ashutosh Choudhary, and Eunah Cho. 2021. [Data augmentation using pre-trained transformer models](#).
- Quoc Le and Tomas Mikolov. 2014. [Distributed representations of sentences and documents](#). In *Proceedings of the 31st International Conference on Machine Learning*, volume 32 of *Proceedings of Machine Learning Research*, pages 1188–1196, Beijing, China. PMLR.
- Bohan Li, Hao Zhou, Junxian He, Mingxuan Wang, Yiming Yang, and Lei Li. 2020. [On the sentence embeddings from pre-trained language models](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 9119–9130, Online. Association for Computational Linguistics.
- Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. [RoBERTa: A robustly optimized BERT pre-training approach](#). *Computing Research Repository*, arXiv:1907.11692.
- Marco Marelli, Stefano Menini, Marco Baroni, Luisa Bentivogli, Raffaella Bernardi, and Roberto Zamparelli. 2014. [A SICK cure for the evaluation of compositional distributional semantic models](#). In *Proceedings of the Ninth International Conference on Language Resources and Evaluation (LREC’14)*, pages 216–223, Reykjavik, Iceland. European Language Resources Association (ELRA).
- Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. 2013. [Efficient estimation of word representations in vector space](#). *arXiv*.
- Juri Opitz. 2019. [Argumentative relation classification as plausibility ranking](#). In *Preliminary proceedings of the 15th Conference on Natural Language Processing (KONVENS 2019): Long Papers*, pages 193–202, Erlangen, Germany. German Society for Computational Linguistics & Language Technology.
- Yannis Papanikolaou and Andrea Pierleoni. 2020. [Dare: Data augmented relation extraction with gpt-2](#).
- Jeffery Pennington, Richard Socher, and Christopher D. Manning. 2014. [Glove: global vectors for word representation](#). In *EMNLP*, pages 1532–1543.
- Matthew Peters, Mark Neumann, Mohit Iyyer, Matt Gardner, Christopher Clark, Kenton Lee, and Luke Zettlemoyer. 2018. [Deep contextualized word representations](#). In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 2227–2237, New Orleans, Louisiana. Association for Computational Linguistics.
- Raul Puri and Bryan Catanzaro. 2019. [Zero-shot text classification with generative language models](#). *Computing Research Repository*, arXiv:1912.10165.
- Alec Radford, Karthik Narasimhan, Tim Salimans, and Ilya Sutskever. 2018. [Improving language understanding by generative pre-training](#).
- Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. 2019. [Language models are unsupervised multitask learners](#). Technical report.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020. [Exploring the limits of transfer learning with a unified text-to-text transformer](#). *Journal of Machine Learning Research*, 21(140):1–67.
- Nils Reimers and Iryna Gurevych. 2019. [Sentence-BERT: Sentence embeddings using Siamese BERT-networks](#). In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*

- and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), pages 3982–3992, Hong Kong, China. Association for Computational Linguistics.
- Timo Schick and Hinrich Schütze. 2020a. [Few-shot text generation with pattern-exploiting training](#). *Computing Research Repository*, arXiv:2012.11926.
- Timo Schick and Hinrich Schütze. 2020b. [It’s not just size that matters: Small language models are also few-shot learners](#). *Computing Research Repository*, arXiv:2009.07118.
- Timo Schick and Hinrich Schütze. 2021. [Exploiting cloze questions for few shot text classification and natural language inference](#). In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics*, Kyiv, Ukraine (Online). International Committee on Computational Linguistics.
- Timo Schick, Sahana Udupa, and Hinrich Schütze. 2021. [Self-diagnosis and self-debiasing: A proposal for reducing corpus-based bias in NLP](#). *Computing Research Repository*, arXiv:2103.00453.
- C. Szegedy, V. Vanhoucke, S. Ioffe, J. Shlens, and Z. Wojna. 2016. [Rethinking the inception architecture for computer vision](#). In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 2818–2826.
- Derek Tam, Rakesh R Menon, Mohit Bansal, Shashank Srivastava, and Colin Raffel. 2021. [Improving and simplifying pattern exploiting training](#).
- Orion Weller, Nicholas Lourie, Matt Gardner, and Matthew Peters. 2020. [Learning from task descriptions](#). *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.
- John Wieting and Kevin Gimpel. 2018. [ParaNMT-50M: Pushing the limits of paraphrastic sentence embeddings with millions of machine translations](#). In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 451–462, Melbourne, Australia. Association for Computational Linguistics.
- Adina Williams, Nikita Nangia, and Samuel Bowman. 2018. [A broad-coverage challenge corpus for sentence understanding through inference](#). In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 1112–1122. Association for Computational Linguistics.
- Zhuofeng Wu, Sinong Wang, Jiatao Gu, Madian Khabsa, Fei Sun, and Hao Ma. 2020. [Clear: Contrastive learning for sentence representation](#).
- Yiben Yang, Chaitanya Malaviya, Jared Fernandez, Swabha Swayamdipta, Ronan Le Bras, Ji-Ping Wang, Chandra Bhagavatula, Yejin Choi, and Doug Downey. 2020. [Generative data augmentation for commonsense reasoning](#). In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 1008–1025, Online. Association for Computational Linguistics.
- Yan Zhang, Ruidan He, Zuozhu Liu, Kwan Hui Lim, and Lidong Bing. 2020. [An unsupervised sentence embedding method by mutual information maximization](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 1601–1610, Online. Association for Computational Linguistics.