Effect of Radiology Report Labeler Quality on Deep Learning Models for Chest X-Ray Interpretation

Saahil Jain*
Akshay Smit*
Andrew Y. Ng
Pranav Rajpurkar
Stanford University

SAAHIL.JAIN@CS.STANFORD.EDU AKSHAYSM@CS.STANFORD.EDU ANG@CS.STANFORD.EDU PRANAVSR@CS.STANFORD.EDU

Abstract

Although deep learning models for chest X-ray interpretation are commonly trained on labels generated by automatic radiology report labelers, the impact of improvements in report labeling on the performance of chest X-ray classification models has not been systematically investigated. We first compare the CheXpert, CheXbert, and VisualCheXbert labelers on the task of extracting accurate chest X-ray image labels from radiology reports, reporting that the VisualCheXbert labeler outperforms the CheXpert and CheXbert labelers. Next, after training image classification models using labels generated from the different radiology report labelers on one of the largest datasets of chest X-rays, we show that an image classification model trained on labels from the VisualCheXbert labeler outperforms image classification models trained on labels from the CheXpert and CheXbert labelers. Our work suggests that recent improvements in radiology report labeling can translate to the development of higher performing chest X-ray classification models.

Keywords: Chest X-Ray Diagnosis, Computer Vision, Radiology, Deep Learning

1. Introduction

Given the high cost of obtaining expert labels for radiology images, deep learning models for radiology image interpretation are often trained on labels automatically extracted from reports accompanying images. Although automatic radiology report labelers are routinely used to label large chest X-ray datasets (Irvin et al., 2019; Johnson et al., 2019), the impact of recent improvements in report labeling on the training of automated chest X-ray classification models is unexplored. To determine the utility of such improvements for the development of radiology image interpretation models, we explore how radiology report labeler quality affects the performance of chest X-ray classification models. Here, we compare the quality of three radiology report labelers. We then show that improvements in radiology report labeling translate to improvements in chest X-ray interpretation models.

2. Data

We use the CheXpert dataset (Irvin et al., 2019), which contains a training set of 224,316 chest radiographs, a validation set of 200 chest X-ray studies, and a test set of 500 chest X-ray studies. Validation and test set labels are obtained by radiologists annotating X-rays. For our experiments, we evaluate on conditions with at least 10% prevalence in the test set.

^{*} Contributed equally

Table 1: F1 scores with 95% confidence intervals obtained by different radiology report labelers on the CheXpert test set.

Condition (n = $\#$ positive)	CheXpert U-Zeros	CheXpert U-Ones	CheXbert U-Zeros	CheXbert U-Ones	VisualCheXbert
Atelectasis (n=153)	$0.30\ (0.22,\ 0.38)$	$0.51\ (0.44,\ 0.58)$	0.30 (0.22, 0.38)	0.51 (0.44, 0.57)	$0.63 \ (0.58, \ 0.69)$
Cardiomegaly (n=151)	$0.44 \ (0.36, \ 0.52)$	$0.46 \ (0.38, \ 0.54)$	$0.43 \ (0.35, \ 0.51)$	$0.46 \ (0.38, \ 0.54)$	$0.62 \ (0.55, \ 0.67)$
Edema (n=78)	$0.46 \ (0.36, \ 0.55)$	$0.53 \ (0.45, \ 0.61)$	$0.49 \ (0.39, \ 0.58)$	$0.53 \ (0.44, \ 0.62)$	$0.54 \ (0.46, \ 0.62)$
Pleural Effusion (n=104)	$0.65 \ (0.58, \ 0.71)$	$0.65 \ (0.59, \ 0.72)$	$0.66 \ (0.59, \ 0.72)$	$0.66 \ (0.59, \ 0.72)$	$0.65 \ (0.58, \ 0.71)$
Enlarged Cardiom. (n=253)	$0.10 \ (0.05, \ 0.15)$	$0.20 \ (0.14, \ 0.26)$	$0.12\ (0.07,\ 0.17)$	$0.23 \ (0.17, \ 0.28)$	$0.73 \ (0.68, \ 0.77)$
Lung Opacity (n=264)	$0.69 \ (0.63, \ 0.74)$	$0.68 \ (0.63, \ 0.73)$	$0.67 \ (0.62, \ 0.72)$	$0.67 \ (0.62, \ 0.72)$	$0.83 \ (0.79, \ 0.86)$
Support Devices (n=261)	$0.85 \ (0.81, \ 0.88)$	$0.84 \ (0.81, \ 0.87)$	$0.84 \ (0.80, \ 0.88)$	$0.84 \ (0.79, \ 0.87)$	$0.87 \ (0.84, \ 0.90)$
No Finding (n=62)	$0.39 \ (0.28, \ 0.49)$	$0.38 \ (0.28, \ 0.48)$	$0.36 \ (0.26, \ 0.46)$	$0.36\ (0.27,\ 0.45)$	$0.54 \ (0.45, \ 0.62)$
Average	0.48 (0.46, 0.51)	$0.53 \ (0.51, \ 0.56)$	0.48 (0.46, 0.51)	$0.53 \ (0.51, \ 0.56)$	$0.68 \ (0.65, \ 0.70)$
Weighted Average	$0.50 \ (0.48, \ 0.53)$	$0.55 \ (0.53, \ 0.58)$	$0.50 \ (0.48, \ 0.53)$	$0.55 \ (0.53, \ 0.58)$	$0.73 \ (0.71, \ 0.75)$

3. Experiments

3.1. Comparison of Radiology Report Labelers

We compare the CheXpert (Irvin et al., 2019), CheXbert (Smit et al., 2020), and VisualCheXbert (Jain et al., 2021) labelers on the task of extracting chest X-ray image labels from radiology reports, described in Jain et al. (2021). To handle the uncertain classes outputted by the CheXpert and CheXbert labelers, we use two common uncertainty handling strategies in Irvin et al. (2019); we either map all the uncertain classes to the negative class (U-Zeros) or to the positive class (U-Ones). We evaluate the performance of each labeler on the CheXpert test set on the different conditions. We also report the weighted average across conditions, where scores are weighted by their prevalence in the test set. We report F1 scores with 95% confidence intervals generated using the non-parametric percentile bootstrap method with 1000 bootstrap replicates.

The VisualCheXbert labeler achieves a statistically significant improvement in average and weighted average F1 scores across conditions compared to the CheXbert and CheXpert labeler approaches, which perform similarly. As shown in Table 1, the VisualCheXbert labeler obtains a weighted average F1 of 0.73 (95% CI 0.71, 0.75), higher than the weighted average F1 of 0.55 (95% CI 0.53, 0.58) for the next best approach.

3.2. Comparison of Chest X-Ray Classification Models

We train image classification models using labels generated by different radiology report labelers on the CheXpert training set. For each model, we follow the training procedure specified in Irvin et al. (2019). We use the best checkpoint, as measured on the validation set, for evaluation. We evaluate the performance of each model on the CheXpert test set, reporting AUROC scores with 95% confidence intervals generated as specified previously.

The image classification model trained on labels from the VisualCheXbert labeler achieves a statistically significant improvement in average and weighted average AUROC scores across conditions compared to models trained on labels from the CheXbert and CheXpert labelers, which perform similarly. As shown in Table 2, the model trained on Visu-

Table 2: AUROC scores with 95% confidence intervals obtained by vision models on the CheXpert test set. Column names correspond to respective labelers used.

Condition (n = $\#$ positive)	CheXpert U-Zeros	CheXpert U-Ones	CheXbert U-Zeros	CheXbert U-Ones	VisualCheXbert
Atelectasis (n=153)	$0.70 \ (0.65, \ 0.75)$	0.75 (0.71, 0.79)	0.76 (0.71, 0.80)	0.77 (0.72, 0.81)	0.84 (0.81, 0.88)
Cardiomegaly (n=151)	$0.82 \ (0.78, \ 0.85)$	$0.79 \ (0.74, \ 0.84)$	$0.79 \ (0.75, \ 0.83)$	$0.74 \ (0.69, \ 0.79)$	$0.83 \ (0.79, \ 0.86)$
Edema (n=78)	$0.88 \ (0.85, \ 0.92)$	$0.91\ (0.88,\ 0.94)$	0.88 (0.84, 0.91)	$0.89 \ (0.85, \ 0.92)$	$0.89 \ (0.86, \ 0.92)$
Pleural Effusion (n=104)	$0.92 \ (0.89, \ 0.95)$	$0.90\ (0.87,\ 0.92)$	0.91 (0.88, 0.94)	$0.90\ (0.87,\ 0.93)$	$0.90 \ (0.86, \ 0.92)$
Enlarged Cardiom. (n=253)	$0.69 \ (0.65, \ 0.74)$	$0.30\ (0.26,\ 0.35)$	$0.73 \ (0.68, \ 0.77)$	$0.55 \ (0.51, \ 0.60)$	$0.85 \ (0.81, \ 0.88)$
Lung Opacity (n=264)	0.90 (0.88, 0.93)	0.92 (0.89, 0.94)	0.89 (0.87, 0.92)	0.89 (0.87, 0.92)	0.91 (0.89, 0.94)
Support Devices (n=261)	$0.89 \ (0.86, \ 0.92)$	$0.89 \ (0.86, \ 0.92)$	$0.85 \ (0.82, \ 0.88)$	$0.86 \ (0.82, \ 0.89)$	$0.87 \ (0.84, \ 0.90)$
No Finding (n=62)	$0.89 \ (0.86, \ 0.93)$	$0.88 \ (0.84, \ 0.91)$	$0.89 \ (0.86, \ 0.92)$	$0.89 \ (0.86, \ 0.92)$	$0.92 \ (0.89, \ 0.95)$
Average	0.84 (0.82, 0.85)	0.79 (0.78, 0.80)	0.84 (0.82, 0.85)	0.81 (0.80, 0.83)	0.88 (0.86, 0.89)
Weighted Average	0.83 (0.81, 0.84)	$0.76 \ (0.74, \ 0.77)$	0.83 (0.81, 0.84)	0.79 (0.77, 0.81)	$0.87 \ (0.86, \ 0.89)$

alCheXbert labels obtains a weighted average AUROC of 0.87 (95% CI 0.86, 0.89), higher than the weighted average AUROC of 0.83 (95% CI 0.81, 0.84) for the next best approach.

4. Conclusion

Given the statistically significant overall improvement achieved by a chest X-ray classification model using a higher quality radiology report labeler, we show that improvements in radiology report labeling can translate to improvements in chest X-ray classification models.

References

Jeremy Irvin, Pranav Rajpurkar, Michael Ko, Yifan Yu, Silviana Ciurea-Ilcus, Chris Chute, Henrik Marklund, Behzad Haghgoo, Robyn Ball, Katie Shpanskaya, Jayne Seekins, David A. Mong, Safwan S. Halabi, Jesse K. Sandberg, Ricky Jones, David B. Larson, Curtis P. Langlotz, Bhavik N. Patel, Matthew P. Lungren, and Andrew Y. Ng. Chexpert: A large chest radiograph dataset with uncertainty labels and expert comparison, 2019.

Saahil Jain, Akshay Smit, Steven QH Truong, Chanh DT Nguyen, Minh-Thanh Huynh, Mudit Jain, Victoria A. Young, Andrew Y. Ng, Matthew P. Lungren, and Pranav Rajpurkar. Visualchexbert. *Proceedings of the Conference on Health, Inference, and Learning*, Apr 2021. doi: 10.1145/3450439.3451862. URL http://dx.doi.org/10.1145/3450439.3451862.

Alistair E. W. Johnson, Tom J. Pollard, Nathaniel R. Greenbaum, Matthew P. Lungren, Chih ying Deng, Yifan Peng, Zhiyong Lu, Roger G. Mark, Seth J. Berkowitz, and Steven Horng. Mimic-cxr-jpg, a large publicly available database of labeled chest radiographs, 2019.

Akshay Smit, Saahil Jain, Pranav Rajpurkar, Anuj Pareek, Andrew Y. Ng, and Matthew P. Lungren. Chexbert: Combining automatic labelers and expert annotations for accurate radiology report labeling using bert, 2020.