

Miscellaneous topics

Abhijit Dasgupta

BIOF 339

BIOF 339: Practical R

Search strategies

Google/Bing/DuckDuckGo

- A problem we have here is that "R" is just a letter of the alphabet, so we get too many results
- The same term (say, `filter` or `print`) is used in various contexts and in various computer languages

Google/Bing/DuckDuckGo

- **Strategy 1:** Use "CRAN" instead of "R" to mean R. If there is a package that meets your needs, this will pick it up
- **Strategy 2:** You can use "-" to qualify what you don't want to search for. So you could do "signal R -python" to look for sites which are not talking about Python
- **Strategy 3:** Restrict yourself to [StackOverflow](#) or [Cross-Validated](#), which are dedicated to computer issues
 - On StackOverflow and CrossValidated, R issues have the tag "r"
 - Have thick skin, since things can get heated sometimes if you are thought to have asked a "stupid" question

rseek.org, a better choice

Twitter

The R community is organized on Twitter with the hashtag "#rstats"

- This is a very active community
- Welcoming, diverse, patient, quick, fun
- Lots of top developers contribute daily (Wickham, Averick, lots of RStudio folk, package developers)
- Can virtually follow all the major and minor R conferences, since someone is certainly live-tweeting. Just need to find the hashtag or conference Twitter handle
- Almost never bashed for asking a "stupid" question

Israel-based blog aggregator dedicated to R.

- Find blogs on almost any R topic under the sun (since 2005)
- Announcements of new packages
- Hundreds of contributing blogs
- Some curated tutorials

Other websites of interest

- [Awesome-R](#): A curated list of R packages and tools
- [Flowing Data](#): One of the top visualization blogs out there, based in R, by Nathan Yau

BIOF 339: Practical R

Stealing code



GitHub is a website where developers come to play. It hosts *repositories* of code where people can submit issues, contribute code and co-develop software products.

Most R developers put their developing code on GitHub. There are over 108,000 repositories on GitHub using R.

To see what's there, [click here](#)

Developers to follow:

- [RStudio](#)
- [ROpenSci](#)
- [tidyverse](#)

BIOF 339: Practical R

Changing some default behaviors

.Rprofile

You can create a [.Rprofile](#) file either in each project or globally (place the file in your HOME folder)

Every time R starts, it will look at this file and load things if you so specify

Some examples you could put in there to be available every time

```
## ht == headtail
ht = function(d, n=6) rbind(head(d, n), tail(d, n))

local({
  r = getOption("repos")
  r["CRAN"] = "https://cran.rstudio.com/"
  options(repos = r)
})
```

Don't put anything in there that might make your R non-portable, for example [options\(stringsAsFactors=F\)](#).

See this [chapter](#) of "Efficient R Programming" by Gillespie and Lovelace.

Changing default operations for a R class

R uses what is called the *S3* system for object oriented programming. It is a simplistic system where you create a default function and then specify functions for different classes. For example:

```
format_output <- function(x,...){  
  # Make a S3 class  
  UseMethod('format_output',x)  
}  
  
format_output.lm <- function(x, refs=NULL, labs=NULL, pretty=T){  
  tmp <- summary(x)$coef  
  if(is.null(refs)){  
    term <- attr(x$terms, 'term.labels')  
  } else {  
    term <- names(refs)  
  }  
  out <- data.frame(tmp[,c(1,2,4)])  
  names(out) <- c('LOR', 'SE', 'pvalue')  
  
  ## Truncated for space, see https://github.com/webbedfeet/abhiR.git
```

So class-specific functions just need the name of the class after the dot.

Changing default operations for a R class

Sometimes, there already is a default that you want to change. Then you don't need to create the generic first since it already exists

```
print.lm <- function(x){  
  suppressPackageStartupMessages(require(tidyverse))  
  require(broom)  
  out <- tidy(x) %>%  
    select(term, estimate, p.value)  
  print(out)  
}
```

So now:

```
m <- lm(mpg ~ wt, data = mtcars)  
print(m)
```

```
# A tibble: 2 × 3  
  term      estimate p.value  
  <chr>      <dbl>    <dbl>  
1 (Intercept)  37.3  8.24e-19  
2 wt          -5.34  1.29e-10
```

Creating your own function repository

You should create functions that you use all the time and make your own repository

Create each function in a separate file, and then load them using the `source` function.

Creating packages

Creating packages sounds intimidating, but really isn't

The [devtools](#) package makes it very easy. So does RStudio.

R packages