Transport Delay Analytics API (0.1.0)

Download OpenAPI specification: Download

Incidents

Get All

Responses

> **200** Successful Response

GET /incidents/

Response samples

200

Content type
application/json

Copy

```
null
```

Create Incident

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json
required

location required	string (Location)
route required	string (Route)
delay_minutes required	integer (Delay Minutes)
description required	string (Description)

Responses

> **200** Successful Response

> **422** Validation Error

POST /incidents/

Request samples

Payload

Content type
application/json

Copy

```
{
    "location": "string",
    "route": "string",
    "delay_minutes": 0,
    "description": "string"
}
```

Response samples

200 422

Content type
application/json

Copy

```
null
```

Update Incident

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

`id` required	integer (Id)

REQUEST BODY SCHEMA: application/json
required

`location` required	string (Location)
`route` required	string (Route)
`delay_minutes` required	integer (Delay Minutes)
`description` required	string (Description)

Responses

> **200** Successful Response

> **422** Validation Error

PUT `/incidents/{id}`

Request samples

Payload

Content type
application/json

Copy

```
{
    "location": "string",
    "route": "string",
    "delay_minutes": 0,
    "description": "string"
}
```

Response samples

200 **422**

Content type
application/json

Copy

```
null
```

Delete Incident

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

`id` required	integer (Id)

Responses

> **200** Successful Response

> **422** Validation Error

DELETE /incidents/{id}

Response samples

200 422

Content type
application/json

Copy

```
null
```

Analytics

Get Traffic Hotspots

Identifies locations with the highest total delay minutes.

Responses

> **200** Successful Response

GET /analytics/hotspots

Response samples

200

Content type
application/json

Copy

```
null
```

Get Route Performance

Provides deep analytics for a specific route.

PATH PARAMETERS

route_name required	string (Route Name)

Responses

> 200 Successful Response

> 422 Validation Error

GET /analytics/route/{route_name}

Response samples

200 422

Content type
application/json

Copy

```
null
```

Get Recent Trends

Analyzes delays over the last X days to find temporal patterns.

QUERY PARAMETERS

`days`	integer (Days) Default: `7` Number of days to look back

Responses

> **200** Successful Response

> **422** Validation Error

GET `/analytics/trends/recent`

Response samples

200 422

Content type
application/json

Copy

```
null
```

Auth

Register

REQUEST BODY SCHEMA: application/json
required

`username` required	string (Username)
`password` required	string (Password)

Responses

> **200** Successful Response

> **422** Validation Error

POST /register

Request samples

Payload

Content type
application/json

Copy

```
{
    "username": "string",
    "password": "string"
}
```

Response samples

200 **422**

Content type
application/json

Copy

```
null
```

Login

REQUEST BODY SCHEMA: application/x-www-form-urlencoded
required

grant_type >	Grant Type (string) or Grant Type (null) (Grant Type)
username required	string (Username)
password required	string <password> (Password)
scope	string (Scope) Default: `""`
client_id >	Client Id (string) or Client Id (null) (Client Id)
client_secret >	Client Secret (string) or Client Secret (null) <password> (Client Secret)

Responses

> **200** Successful Response

> **422** Validation Error

POST /login

Response samples

200 422

Content type
application/json

Copy

```
null
```

Get Me

AUTHORIZATIONS: > *OAuth2PasswordBearer*

Responses

> **200** Successful Response

GET /me

Response samples

200

Content type
application/json

Copy

```
null
```

Root

Responses

> **200** Successful Response

GET /

Response samples

200

Content type
application/json

Copy

```
null
```