Table of Contents

PYTORCH CHEAT SHEET

Imports

General

```
import torch
from torch.utils.data import Dataset, Dataloader # dataset representation and loading
```

Neural Network API

```
import torch.autograd as autograd  # computation graph
from torch.autograd import Variable  # variable node in computation graph
import torch.nn as nn  # neural networks
import torch.nn.functional as F  # layers, activations and more
import torch.optim as optim  # optimizers e.g. gradient descent, ADAM, etc.
from torch.jit import script, trace  # hybrid frontend decorator and tracing jit
```

See autograd, nn, functional and optim

Hybrid frontend

See hybrid frontend

ONNX

```
torch.onnx.export(model, dummy data, xxxx.proto)  # exports an ONNX formatted
# model using a trained model, dummy
# data and the desired file name

model = onnx.load("alexnet.proto")  # load an ONNX model
onnx.checker.check_model(model)  # check that the model
# IR is well formed

onnx.helper.printable_graph(model.graph)  # print a human readable
# representation of the graph
```

See onnx

Vision

```
from torchvision import datasets, models, transforms # vision datasets,
# architectures &
# transforms

import torchvision.transforms as transforms # composable transforms
```

See torchvision

Distributed Training

```
import torch.distributed as dist  # distributed communication
from multiprocessing import Process  # memory sharing processes
```

Tensors Creation

```
torch.randn(*size)  # tensor with independent N(0,1) entries
torch.[ones|zeros](*size)  # tensor with all 1's [or 0's]
torch.Tensor(L)  # create tensor from [nested] list or ndarray L
x.clone()  # clone of x
with torch.no_grad():  # code wrap that stops autograd from tracking tensor history
requires_grad=True  # arg, when set to True, tracks computation
  # history for future derivative calculations
```

See tensor

Dimensionality

```
# return tuple-like object of dimensions
x.size()
torch.cat(tensor_seq, dim=0)
                                      # concatenates tensors along dim
                                      # reshapes x into size (a,b,...)
x.view(a,b,...)
x.view(-1,a)
                                      # reshapes x into size (b,a) for some b
x.transpose(a,b)
                                      # swaps dimensions a and b
x.permute(*dims)
                                      # permutes dimensions
x.unsqueeze(dim)
                                      # tensor with added axis
x.unsqueeze(dim=2)
                                      # (a,b,c) tensor -> (a,b,1,c) tensor
```

See tensor

Algebra

```
A.mm(B) # matrix multiplication
A.mv(x) # matrix-vector multiplication
x.t() # matrix transpose
```

See math operations

GPU Usage

```
torch.cuda.is_available
x.cuda()
                                                        # move x's data from
                                                        # CPU to GPU and return new object
x.cpu()
                                                        # move x's data from GPU to CPU
                                                        # and return new object
if not args.disable_cuda and torch.cuda.is_available(): # device agnostic code
    args.device = torch.device('cuda')
                                                        # and modularity
    args.device = torch.device('cpu')
                                                        # recursively convert their
net.to(device)
                                                        # parameters and buffers to
                                                        # device specific tensors
mvtensor.to(device)
                                                        # copy your tensors to a device
                                                        # (gpu, cpu)
```

See cuda

Deep Learning

```
nn.Linear(m,n)
                                               # fully connected layer from
                                               # m to n units
nn.ConvXd(m,n,s)
                                               # X dimensional conv layer from
                                               # m to n channels where X \in \{1, 2, 3\}
                                               # and the kernel size is s
nn.MaxPoolXd(s)
                                               # X dimension pooling layer
                                               # (notation as above)
nn.BatchNorm
                                               # batch norm layer
nn.RNN/LSTM/GRU
                                               # recurrent layers
nn.Dropout(p=0.5, inplace=False)
                                               # dropout layer for any dimensional input
nn.Dropout2d(p=0.5, inplace=False)
                                               # 2-dimensional channel-wise dropout
nn.Embedding(num_embeddings, embedding_dim)
                                               # (tensor-wise) mapping from
                                               # indices to embedding vectors
```

See nr

```
nn.X where for example X is ... # BCELoss, CrossEntropyLoss,
```

Liloss, MSELoss, NLLLoss, SoftMarginLoss, # MultiLabelSoftMarginLoss, CosineEmbeddingLoss, # KLDivLoss, MarginRankingLoss, HingeEmbeddingLoss # or CosineEmbeddingLoss

See loss functions

LOSS FUNCTIONS

Activation Functions

```
nn.X where for example X is ... # ReLU, ReLU6, ELU, SELU, PReLU, LeakyReLU,
# Threshold, HardTanh, Sigmoid, Tanh,
# LogSigmoid, Softplus, SoftShrink,
# Softsign, TanhShrink, Softmin, Softmax,
# Softmax2d or LogSoftmax
```

See activation functions

Optimizers

```
opt = optim.x(model.parameters(), ...)  # create optimizer
opt.step()  # update weights
optim.X where for example X is ...  # SGD, Adadelta, Adagrad, Adam,
# SparseAdam, Adamax, ASGD,
# LBFGS, RMSProp or Rpxop
```

See optimizers

Learning rate scheduling

See learning rate scheduler

Data Utilities

Datasets

```
Dataset # abstract class representing dataset

TensorDataset # labelled dataset in the form of tensors

Concat Dataset # concatenation of Datasets
```

See datasets

Dataloaders and DataSamplers

```
DataLoader(dataset, batch_size=1, ...)  # loads data batches agnostic
  # of structure of individual data points

sampler.Sampler(dataset,...)  # abstract class dealing with
  # ways to sample from dataset

sampler.XSampler where ...  # Sequential, Random, Subset,
  # WeightedRandom or Distributed
```

See dataloader

Also see

- Deep Learning with PyTorch: A 60 Minute Blitz (pytorch.org)
- PyTorch Forums (discuss.pytorch.org)
- $\bullet \quad \text{PyTorch for Numpy users } \textit{(github.com/wkentaro/pytorch-for-numpy-users)}$

[©] Copyright 2017, PyTorch.

Docs

Access comprehensive developer documentation for $\label{eq:pyTorch} \mbox{\sc View Docs}$

Tutorials

Get in-depth tutorials for beginners and advanced developers

View Tutorials

Email Address

Resources

Find development resources and get your questions answered

View Resources

PyTorch

Support

Follow Us

Get Started Features Tutorials Docs

Docs Discuss

Ecosystem Blog

Github Issues

Resources

CI I

Slack Contributing