

A. Surround sound systems

(United States Patents On, September 16, 2014)

This paper proposes an idea of developing a system that comprises of receiver for receiving a multichannel spatial signal that comprises at least one surround channel.

This system comprises of a directional ultrasonic transducer for emitting ultrasound towards surface to reach a listening position via a reflection of the surface and a driver ckt to drive ultrasonic transducer.

The proposed system is capable of producing virtual surround sound without requiring a speaker a speaker to be located .

B. Shadow Sound System Embodied with Directional Ultrasonic Speaker

(ICISA.2013 on 2013)

The paper talks about usage of ultrasonic speaker and computer vision system installed on a motorized mount that can freely change the speaker's directions and altitude for a specific registered user.

The resulting system is proven to be able to track the registered user for providing user selected sound contents without being interfered by other people.

This method seems promising but it requires individual hardware for each speaker and the solution does not cover the implementation on multi channel audio system efficiently.

C. An Efficient Implementation of Acoustic Crosstalk Cancellation for 3D Audio Rendering

(IEEE China SIP on July 2014)

In this paper given method the use of ultrasonic speaker and computer vision system installed on a motorized mount that can freely change the speaker's directions and altitude for a specific registered user.

The resulting system is proven to be able to track the registered user for providing user selected sound contents without being interfered by other people.

This method seems promising but it requires individual hardware for each speaker and the solution does not cover the implementation on multi channel audio system efficiently.

D. Multirate adaptive filtering for immersive audio

(IEEE Xplore on February 2001)

This paper describes a method for implementing immersive audio rendering filters for single or multiple listeners and loudspeakers.

In particular, the paper is focused on the case of single or two listeners with different loudspeaker arrays to determine the weighting vectors for the necessary FIR and IIR filters using the LMS (least-mean-squares) adaptive inverse algorithm.

It describes transform-domain LMS adaptive inverse algorithm that is designed for crosstalk cancellation necessary in loudspeaker-based immersive audio rendering.

The algorithm used in this paper is only for single listener and only two loudspeakers are used.