
Compiler Design

No	Problem Name
01	Write a C program for developing a lexical analyzer (LA) that will eliminate white spaces from a source program in C and collect numbers.
02	Write a C program for developing a lexical analyzer (LA) that will eliminate white spaces from a source program in C and collect numbers as token and then also display the token value as attribute.
03	Write a C program for developing a lexical analyzer (LA) that will recognize the variables in a source program. ✓
04	Write a C program for developing a lexical analyzer (LA) that will recognize the keywords in a source program.
05	Design a compiler front-end based on syntax-directed translation technique that will function as an infix translator for a language consists of sequence of expressions terminated by semicolon. ✓
06	Write a program to remove left factoring.
07	Write a program to check whether a string belongs to the grammar or not.
08	Write a C program to implement Shift-Reduce Parser.
09	Write a C program to implement a recursive descent parser.

1. Write a C program for developing a lexical analyzer (LA) that will eliminate white spaces from a source program in C and collect numbers.

```
#include<iostream>

#include<stdio.h>

using namespace std;

int sign_check(char pre_value){

    if(pre_value=='+'||pre_value=='-'||pre_value=='*'||pre_value=='/'||pre_value=='%'||pre_value=='=')

        return 1;

    else

        return 0;

}

int main()

{

    int n,len,s,i;

    char pre_value=' ';

    string str;

    FILE *f2;

    freopen("1 Input.txt","r",stdin);

    f2=fopen("1 Output.txt","w");

    printf("Collect no. given below\n");

    while(getline(cin,str)){

        len =str.size();

        for(i=0;i<len;i++){

            if(str[i]!=' ')

                putc(str[i],f2);

        }

        putc('\n',f2);

        for(i=0;i<len;i++){

            if(str[i]>='0'&&str[i]<='9'){

                s=str[i]-'0';
```

```

        for(i=i+1;i<len;i++){
            if(str[i]>='0'&&str[i]<='9')
                s=s*10+(str[i]-'0');
            else
                break;
        }
        i--;
        if(pre_value=='['&&str[i+1]==']')
            cout<<s<<endl;
        else if((sign_check(pre_value)||pre_value==' ')&&(sign_check(str[i+1])||str[i+1]==';'||i==len1))
            cout<<s<<endl;
        }
    else
        pre_value=str[i];
    }
}

return 0;
}

```

Input:

```

#include<stdio.h>
#include<iostream>
using namespace std;
int main()
{
    char t,f;
    int n;
    FILE *f1,*f2;
    f1=fopen("basir.txt","r");
    f2=fopen("rajib.txt","w");
    while(t=getc(f1)!=EOF){

```

```

        if(t!="&&isdigit(t))
            putc(t,f2);
        else{
            n=0;
            while(isdigit(t)){
                putc(t,f2);
                n=n*10+(t-'0');
                t=getc(f1);
            }
            if(n){
                putc(t,f2);
                cout<<n<<endl;
            }
        }
    }
}

return 0;
}

```

Output:

```


#include<stdio.h>
#include<iostream>
usingnamespacestd;
intmain()
{
    chart,f;
    intn;
    FILE*f1,*f2;
    f1=fopen("basir.txt","r");
    f2=fopen("rajib.txt","w");
    while(t=getc(f1)!=EOF){

```

```

        if(t!="&&isdigit(t))
            putc(t,f2);
        else{
            n=0;
            while(isdigit(t)){
                putc(t,f2);
                n=n*10+(t-'0');
                t=getc(f1);
            }
            if(n){
                putc(t,f2);
                cout<<n<<endl;
            }
        }
    }
    return 0;
}

```



```

G:\Porasuna\4th Year\ACMy coding\Final\Compiler\1.exe
Collect no. given below
0
10
0
Process returned 0 (0x0)   execution time : 0.208 s
Press any key to continue.

```

2. Write a C program for developing a lexical analyzer (LA) that will eliminate white spaces from a source program in C and collect numbers as token and then also display the token value as attribute.

```
#include<iostream>

#include<stdio.h>

using namespace std;

int punctuation_check(char pre_value){

    if(pre_value=='+'||pre_value=='-'||pre_value=='*'||pre_value=='/'||pre_value=='%')

        return 1;

    else if(pre_value=='['||pre_value==']'||pre_value=='{'||pre_value=='}'||pre_value=='('||pre_value==')')

        return 1;

    else if(pre_value=='"'||pre_value==';'||pre_value==':'||pre_value==','||pre_value=='.'||pre_value=='\\')

        return 1;

    else

        return 0;

}

int keyword(string str){

    if(str=="int"||str=="char"||str=="float"||str=="double"||str=="string"||str=="typedef"||str=="long"||str=="string")

        return 1;

    else if(str=="while"||str=="do"||str=="for"||str=="if"||str=="else"||str=="switch"

||str=="case"||str=="break"||str=="continue")

        return 1;

    else if(str=="const"||str=="goto"||str=="static"||str=="union"||str=="return"||str=="default"

||str=="short"||str=="signed"||str=="unsigned"||str=="void")

        return 1;

    else

        return 0;

}

int sign_check(char pre_value){

    if(pre_value=='+'||pre_value=='-'||pre_value=='*'||pre_value=='/'||pre_value=='=')
```

```

        return 1;
    else
        return 0;
}

int main()
{
    char t,f;
    int n,checks,s,len;
    string str,stt;
    FILE *f2;
    freopen("2 Input.txt","r",stdin);
    char pre_value='1';
    cout<<"token   token value as attributes\n";
    cout<<"=====\\n";
    while(getline(cin,str)){
        pre_value='1';
        stt="";
        len=str.size();
        for(int i=0;i<len;i++){
            if(punchuation_check(str[i])){
                cout<<"Punchuation "<<str[i]<<"\\n";
                pre_value=str[i];
            }
            else if(str[i]=='<' or str[i]=='>' or str[i]=='='){
                if(i+1<len){
                    if(str[i+1]=='='){
                        cout<<"CO      "<<str[i]<<str[i+1]<<endl;
                        i++;
                    }
                }
                else

```



```

        cout<<"RO        "<<str[i]<<endl;
    }
    pre_value=str[i];
}
else if(str[i]==' ')
    pre_value=str[i];
else if((str[i]>='0' and str[i]<='9') and sign_check(pre_value)){
    s=0;
    s=s*10+str[i]-'0';
    for(i=i+1;i<len;i++){
        if((str[i]>='0' and str[i]<='9'))
            s=s*10+str[i]-'0';
        else
            break;
    }
    i--;
    if(pre_value=='[' and str[i+1]==']')
        cout<<"num        "<<s<<"\n";
    else if( sign_check(pre_value) and i==len-1 )
        cout<<"num        "<<s<<"\n";
    else if( sign_check(pre_value) and (sign_check(str[i+1]) or str[i+1]==';' ))
        cout<<"num        "<<s<<"\n";
}
else{
    stt+=str[i];
    if(punctuation_check(str[i+1]) or str[i+1]==' ' or str[i+1]=='=' or str[i+1]=='<'){
        if(keyword (stt))
            cout<<"Keyword    "<<stt<<"\n";
        else
            cout<<"ID        "<<stt<<"\n";
    }
}

```

```
        stt="";  
    }  
    pre_value=str[i];  
    }  
    }  
    }  
    return 0;  
}
```

Input:

```
char t;  
int n;  
FILE *f1;  
f1=fopen("Input.txt","r");  
while(t=getc(f1)){  
    if(n  
        putc(t,f2);  
}
```

Output:

```
"G:\Porasuna\4th Year\ACMy coding\Final\Compiler\2.exe"
token    token value as attributes
=====
char      char
ID        t
Punctuation ;
int       int
ID        n
Punctuation ;
ID        FILE
Punctuation *
ID        f1
Punctuation ;
ID        f1
RE        =
ID        fopen
Punctuation (
Punctuation "
ID        Input
Punctuation .
ID        txt
Punctuation "
Punctuation ,
Punctuation "
ID        r
Punctuation "
Punctuation )
Punctuation ;
while     while
Punctuation (
ID        t
RE        =
ID       getc
Punctuation (
ID        f1
Punctuation )
Punctuation )
Punctuation {
if        if
Punctuation (
ID        n
Punctuation )
ID        putchar
Punctuation (
ID        t
Punctuation ,
ID        f2
Punctuation )
Punctuation ;
Punctuation }
```

Process returned 0 (0x0) execution time : 0.242 s
Press any key to continue.

3. Write a C program for developing a lexical analyzer (LA) that will recognize the variables in a source program.

```
#include<stdio.h>

#include<iostream>

using namespace std;

int check(string str){

    if(str=="int"||str=="char"||str=="float"||str=="double"||str=="long"||str=="long
long"||str=="signed"||str=="unsigned")

        return 1;

    else

        return 0;

}

int main()

{

    freopen("3 Input.txt","r",stdin);

    string str;

    while(cin>>str){

        if(check(str)){

            cout<<str<<" variable= ";

            int k=0;

            while(1){

                char ch=getchar();

                if(ch==';')

                    break;

                if(k==0&&ch!=' ')

                    cout<<ch;

                if(ch=='=')

                    k=1;

                if(ch==',')
```

```
        k=0;

    }

    cout<<"."<<endl;

}

}


return 0;

}
```

Input:

```
void main()
{
    int i,j,k;
    char ch,d;
    float g,h,pi;
    for(i=0;i<5;i++)
        printf("%d ",i);
    return 0;
}
```

Output:



```
"G:\Porasuna\4th Year\ACMy coding\Final\Compiler\3.exe"
int variable= i,j,k.
char variable= ch,d.
float variable= g,h,pi.
Process returned 0 (0x0)   execution time : 0.188 s
Press any key to continue.
```

4. Write a C program for developing a lexical analyzer (LA) that will recognize the keywords in a source program.

```
#include<bits/stdc++.h>

using namespace std;

int check(string s){

if(s=="auto"||s=="int"||s=="char"||s=="long"||s=="float"||s=="double"||s=="struct"||s=="if"||s=="else"||s=="break"||s=="continue"||

s=="while"||s=="do"||s=="for"||s=="return"||s=="signed"||s=="unsigned"||s=="default"||s=="goto"||s=="case"||s=="sizeof"||s=="short"||

s=="switch"||s=="void"||s=="static"||s=="typedef")

return 1;

else

return 0;

}

int main()

{

char t,f,ch;

int n,k;

int anu;

string st;

freopen("9 Input.txt","r",stdin);

char pre_value='1';

printf("Keywords are given bellow\n\n");

while(cin>>st){

if(check(st)){

cout<<st<<" is a keyword\n";

}

}
```

```
    return 0;
}


Input:

#include<iostream>

using namespace std;

void main()
{
    int i,a,b,c;
    char ch;
    string str;
    for(i=1;i<=15;i++)
        cout<<"The number is: "<<i<<endl;
    return 0;
}
```

Output:



```
"G:\Porasuna\4th Year\ACMy coding\Final\Compiler\9.exe"
Keywords are given bellow
void is a keyword
int is a keyword
char is a keyword
return is a keyword
Process returned 0 (0x0) execution time : 0.381 s
Press any key to continue.
```

5. Design a compiler front-end based on syntax-directed translation technique that will function as an infix translator for a language consists of sequence of expressions terminated by semicolon.

```
#include<bits/stdc++.h>

using namespace std;

int len,i;

char ch;

void infix(string str){

    stack<char> stack_string;

    str='('+str+');'

    len=str.size();

    for(i=0;i<len;i++){

        if(str[i]>='a'&& str[i]<='z')

            cout<<str[i];

        else if(str[i]=='(')

            stack_string.push('(');

        else if(str[i]==')'){

            while(stack_string.top()!='('){

                cout<<stack_string.top();

                stack_string.pop();

            }

            stack_string.pop();

        }

        else if(str[i]=='+'||str[i]=='-'){

            while(1){

                ch=stack_string.top();

                if(ch=='+'||ch=='-')

                    break;
```



```

        else if(ch=='(')
            break;

        cout<<ch;

        stack_string.pop();
    }

    stack_string.push(str[i]);
}

else if(str[i]=='*'||str[i]=='/'){
    while(1){
        ch=stack_string.top();

        if(ch=='+'||ch=='-'||ch=='*'||ch=='/'){
            break;

            else if(ch=='(')
                break;

            cout<<ch;

            stack_string.pop();
        }

        stack_string.push(str[i]);
    }

    else if(str[i]=='^')
        stack_string.push(str[i]);
}

}

int main()
{
    string str;

    cout<<"Enter the expression: ";

    cin>>str;

    cout<<"\n=====The expression in infix notation=====\\n\\n";

```

```

infix(str);

cout<<endl;

return 0;

}

```

Input & Output:

```

G:\Porasuna\4th Year\ACMy coding\Final\Compiler\4.exe
Enter the expression: a+(b+c)*b*d
====The expression in infix notation====
abc+bd**+
Process returned 0 (0x0)   execution time : 12.113 s
Press any key to continue.

```

6. Write a program to remove left factoring.

```

#include<bits/stdc++.h>

using namespace std;

int main()
{
    int len,i,j,k,kk,check=0;
    string str;
    while(1){
        cout<<"Enter the string: ";
        cin>>str;
        len=str.size();

        for(i=0;i<len;i++){
            if(str[i]=='\n')
                break;
        }
    }
}

```

```
j=i;
kk=j+1;

for(k=0;k<len;k++,kk++){
    if(str[k]!=str[kk]){
        check=1;
        break;
    }
}
```

```
if(check && k!=0){
    cout<<"A-> ";
    for(i=0;i<k;i++){
        cout<<str[i];
    }
    cout<<"A'"<<endl;
    cout<<"A'-> ";
}
```

```
if(k==j)
    cout<<"#";
```

```
for(i=k;i<j;i++){
    cout<<str[i];
}
cout<<"|";
```

```
for(i=j+k+1;i<len;i++){
    cout<<str[i];
}
cout<<endl;
}else{
    cout<<"A-> ";
    for(i=0;i<j+1;i++){
```

```
        cout<<str[i];  
    cout<<"A"<<endl;  
    cout<<"A'-> ";  
  
    for(i=j+1;i<len;i++)  
        cout<<str[i];  
    cout<<endl;  
}  
cout<<endl;  
}  
return 0;  
}
```

Input & Output:



The screenshot shows a terminal window with a black background and white text. It displays two separate runs of the program. In the first run, the user enters 'a+b!a+c', and the program outputs 'A-> a+A'' and 'A'-> b!c'. In the second run, the user enters 'iEtS!iEtSeS', and the program outputs 'A-> iEtSA'' and 'A'-> #!eS'. A vertical scrollbar is visible on the right side of the terminal window.

```
Enter the string: a+b!a+c  
A-> a+A'  
A'-> b!c  
  
Enter the string: iEtS!iEtSeS  
A-> iEtSA'  
A'-> #!eS
```

7. Write a program to check whether a string belongs to the grammar or not.

```
#include<bits/stdc++.h>

using namespace std;

int main()
{
    string str;


    cout<<"the grammar is: \nS->aS \nS->Sb \nS->ab\n";

    cout<<"enter the string to check: ";

    cin>>str;

    int len=str.size();
    int flag=0,i,a,b;
    for(i=0;i<len;i++){
        if(str[i]!='a'){
            a=i-1;
            break;
        }
    }
    for(i=len-1;i>=0;i--){
        if(str[i]!='b'){
            b=i+1;
            break;
        }
    }
    if(a>=0 && b<len && a+1==b)
        flag=1;
    if(flag==1)
        cout<<endl<<str<<" is accepted."<<endl;
    else
        cout<<endl<<str<<" is not accepted."<<endl;
    return 0;}
```

Input & Output:



```
"G:\Porasuna\4th Year\ACMy coding\Final\Compiler\6.exe"
the grammar is:
S->aS
S->Sb
S->ab
enter the string to check: aaab
aaab is accepted.
Process returned 0 (0x0) execution time : 2.614 s
Press any key to continue.
```

8. Write a C program to implement Shift-Reduce Parser.

```
//(id+id)*id
#include<bits/stdc++.h>
#include<string.h>
using namespace std;

string str,shift_action="Shift ",reduce_action="Reduce to E ";
char stuck[100];
int i,j,len,k;

void checking(){
    for(k=0;k<len;k++){
        if(stuck[k]=='i'&&stuck[k+1]=='d'){
            stuck[k]='E';
            stuck[k+1]='\0';
            cout<<"$"<<stuck<<"\t"<<str<<"$\t"<<reduce_action<<endl;
            j++;
        }
    }
    for(k=0;k<len;k++){
        if(stuck[k]=='E' && stuck[k+1]=='+' && stuck[k+2]=='E'){
            stuck[k]='E';
```

```

        stuck[k+1]='\0';
        stuck[k+2]='\0';
        cout<<"$"<<stuck<<"\t"<<str<<"$\t"<<reduce_action<<endl;
        i=i-2;
    }
}

for(k=0;k<len;k++){
    if(stuck[k]=='E'&&stuck[k+1]=='*'&&stuck[k+2]=='E'){
        stuck[k]='E';
        stuck[k+1]='\0';
        stuck[k+1]='\0';
        cout<<"$"<<stuck<<"\t"<<str<<"$\t"<<reduce_action<<endl;
        i=i-2;
    }
}

for(k=0;k<len;k++){
    if(stuck[k]=='('&&stuck[k+1]=='E'&&stuck[k+2]=='')){
        stuck[k]='E';
        stuck[k+1]='\0';
        stuck[k+1]='\0';
        cout<<"$"<<stuck<<"\t"<<str<<"$\t"<<reduce_action<<endl;
        i=i-2;
    }
}

}

int main()
{
    puts("Grammar is:\n\nE->E+E\nE->E*E\nE->(E)\nE->id\n\n");
    cout<<"Enter the input string: ";
    cin>>str;

```

```

len=str.size();

puts("\nStack\tInput\t\tAction");

//cout<<"$t"<<str<<"$"<<"\t\t"<<shift_action;

for(i=0,j=0;j<len;i++,j++){
    if(str[j]=='i'&&str[j+1]=='d'){
        stuck[i]=str[j];
        stuck[i+1]=str[j+1];
        stuck[i+2]='\0';
        str[j]=' ';
        str[j+1]=' ';
        cout<<"$"<<stuck<<"\t"<<str<<"$"<<"\t"<<shift_action<<"id"<<endl;
        checking();
    }
    else{
        stuck[i]=str[j];
        stuck[i+1]='\0';
        str[j]=' ';
        cout<<"$"<<stuck<<"\t"<<str<<"$"<<"\t"<<shift_action<<"symbol"<<endl;
        checking();
    }
}

if(str[len-1]==' ')
    cout<<"$"<<stuck<<"\t"<<str<<"$t"<<"Accept"<<endl;

return 0;
}

```


Input & Output:

```
"G:\Porasuna\4th Year\ACMy coding\Final\Compiler\7.exe"
Grammar is:
E->E+E
E->E*E
E->(E)
E->id

Enter the input string: <id+id>*id

Stack   Input           Action
$(<      id+id)*id$    Shift symbol
$id      +id)*id$      Shift id
$(E      +id)*id$      Reduce to E
$(E+     id)*id$      Shift symbol
$(E+id   )*id$      Shift id
$(E+E    )*id$      Reduce to E
$(E      )*id$      Reduce to E
$(E)     *id$      Shift symbol
$E       *id$      Reduce to E
$E*      id$      Shift symbol
$E*id    $        Shift id
$E*E     $        Reduce to E
$E       $        Reduce to E
$E       $        Accept

Process returned 0 (0x0)   execution time : 8.011 s
Press any key to continue.
```

9. Write a C program to implement a recursive descent parser.

```
//E->TE'
//E'->+TE'|NULL
//T->FT'
//T'->*F'|NULL
//F->(E)|a|b|c

#include<bits/stdc++.h>
using namespace std;
int i,error;
string str;

void E();
void Eds();
void T();
```

```
void Tds();
```

```
void F();
```

```
int main()
```

```
{
```

```
    cout<<"Enter the input string: ";
```

```
    cin>>str;
```

```
    E();
```

```
    if(i==str.size()&&error==0)
```

```
        cout<<endl<<"String is accepted"<<endl;
```

```
    else
```

```
        cout<<endl<<"String is rejected"<<endl;
```

```
    return 0;
```

```
}
```

```
void E(){
```

```
    T();
```

```
    Eds();
```

```
}
```

```
void Eds(){
```

```
    if(str[i]=='+'){
```

```
        i++;
```

```
        T();
```

```
        Eds();
```

```
    }
```

```
}
```

```
void T(){
```

```
    F();
```

```


    Tds();
}

void Tds(){
    if(str[i]=='*'){
        i++;
        F();
        Tds();
    }
}

void F(){
    if(str[i]=='a' || str[i]=='b' || str[i]=='c')
        i++;
    else if(str[i]=='('){
        E();
        if(str[i]==')')
            i++;
        else
            error=1;
    }
    else
        error=1;
}

```

Input & Output:



```

"G:\Porasuna\4th Year\ACMy coding\Final\Compiler\8.exe"
Enter the input string: a*b+c
String is accepted
Process returned 0 (0x0)   execution time : 7.600 s
Press any key to continue.

```

System Simulation

No	Problem Name
01	Develop a computer program for determining the value of π and run the simulation for 1000 observations.
02	Write a C Program to simulate pure pursuit problem.
03	Write a C program to generate the area of an irregular figure using monte-carlo method.
04	Write a C program to determine the value of numerical integration using monte-carlo method.
05	Write a C program to determine the value of π by monte-carlo method.
06	Write a C program for Mid-square Method of Generating 4-digit Random Numbers.
07	Write a C program to generate variables from NEGATIVE BINOMIAL distribution having Parameters k (number of successes) and p (probability of success in trial).
08	Write a C program to generate random variable from a Normal distribution having mean mue and standard deviation sigma.
09	

1. Develop a computer program for determining the value of π and run the simulation for 1000 observations.


```
#include<bits/stdc++.h>

#include<math.h>

using namespace std;

int main()
{
    float r1,r2,m=0;
    int i,n=1000;
    for(i=1;i<=n;i++){
        r1=rand()/32768.0;
        r2=rand()/32768.0;
        if(r2<=sqrt(1-r1*r1))
            m++;
    }
    cout<<"The value of pi= "<<(m*4)/n<<endl;
    return 0;
}
```

Input & Output:



```
"G:\Study\4th Year\ACMy coding\Final\Simulation\1.exe"
The value of pi= 3.112
Process returned 0 (0x0) execution time : 0.021 s
Press any key to continue.
```

2. Write a C Program to simulate pure pursuit problem.

```
#include<bits/stdc++.h>

using namespace std;

int main()
{
    float xb[]={100,110,120,129,140,149,158,168,179,188,198,209,219,226,234,240};
```

```

float yb[]={0,3,6,10,15,20,26,32,37,34,30,27,23,19,16,14};
float dist,time_limit=12,xf[20],yf[20],s=20;
int i;
xf[0]=0;
yf[0]=0;
cout<<"Time\tDistance\n";
for(i=0;i<=12;i++){
    dist=sqrt(pow(yf[i]-yb[i],2)+pow(xf[i]-xb[i],2));
    cout<<i<<"\t"<<dist<<endl;
    if(i>time_limit)
        printf("\nTarget escapes");
    if(dist<=10)
        break;
    else{
        xf[i+1]=xf[i]+s*(xb[i]-xf[i])/dist;
        yf[i+1]=yf[i]+s*(yb[i]-yf[i])/dist;
    }
}
cout<<"\nPersuitends shot at "<<i<<" minutes and at "<<dist<<" kms\n";
return 0;
}

```

Input & Output:

```

G:\Study\4th Year\ACMy coding\Final\Simulation\2.exe
Time    Distance
0       100
1       90.05
2       81.3442
3       74.1885
4       72.1815
5       71.8918
6       73.6105
7       77.3324
8       82.7332
9       94.0721
10      106.905
11      118.691
12      130.612

Persuitends shot at 13 minutes and at 130.612 kms

Process returned 0 (0x0)   execution time : 0.025 s
Press any key to continue.

```

3. Write a C program to generate the area of an irregular figure using monte-carlo method.

```
#include<bits/stdc++.h>

using namespace std;

int main()
{
    int i,xmin,xmax,ymin,ymax,n;
    float area,mf,r1,r2,m,a,x,y;
    cout<<"Enter the value of xmin: ";
    cin>>xmin;
    cout<<"Enter the value of xmax: ";
    cin>>xmax;
    cout<<"Enter the value of ymin: ";
    cin>>ymin;
    cout<<"Enter the value of ymax: ";
    cin>>ymax;
    cout<<"\nEnter the number of random number you want to generate: ";
    cin>>n;
    if(xmin<=0)
        xmax=xmax-xmin;
    if(ymin<=0)
        ymax=ymax-ymin;
    if(ymax>xmin)
        mf=ymax+10;
    else
        mf=xmax+10;
    for(i=1;i<=n;i++){
        x=rand()/32768.0;
        y=rand()/32768.0;
        x*=mf;
        y*=mf;
```




```

        if(x>=xmin&& x<=xmax&& y>=ymin&& y<=ymax)
            m++;
    }
    mf*=mf;
    area=m/float(n);
    area*=mf;
    cout<<"\nArea= "<<area<<endl;
    return 0;
}

```

Input & Output:



```

"G:\Study\4th Year\ACMy coding\Final\Simulation\3.exe"
Enter the value of xmin: 20
Enter the value of xmax: 40
Enter the value of ymin: 20
Enter the value of ymax: 50

Enter the number of random number you want to generate: 60

Area= 540

Process returned 0 (0x0)   execution time : 6.541 s
Press any key to continue.

```

4. Write a C program to determine the value of numerical integration using monte-carlo method.

```

#include<stdio.h>
#include<stdlib.h>
#include<math.h>
int n,i=1;
float r,x,y,x3,h,w,area,I,m,u;
int main()
{
    printf("Enter the number of observation: ");
    scanf("%d",&n);
    printf("Enter the height: ");


```

```

scanf("%f",&h);
printf("Enter the weight: ");
scanf("%f",&w);
area=h*w;
printf("\nArea= %.3f\n",area);
do{
    r=rand()/32768.0;
    r*=50;
    if(r>20&&r<50){
        x=0.1*r;
        y=rand()*140/32768.0;
        x3=x*x*x;
        if(y<=x3)
            m++;
        i++;
    }
}while(i!=n);
u=n;
I=(m/u)*area;
printf("\nThe Integration is= %.2f\n\n",I);
return 0;
}

```

Input & Output:



```

G:\Study\4th Year\ACMy coding\Final\Simulation\4.exe
Enter the number of observation: 20
Enter the height: 140
Enter the weight: 3

Area= 420.000

The Integration is= 63.00

```

N.B: For this program can have different result on your console because different compiler can generate different random numbers.

5. Write a C program to determine the value of π by monte-carlo method.

```
#include<bits/stdc++.h>

using namespace std;

int main()
{
    int n,i;

    float r1,r2,m=0,p,ra;

    cout<<"How many numbers you want to generate: ";

    cin>>n;

    for(i=1;i<=n;i++){

        r1=rand()/32768.0;

        r2=rand()/32768.0;

        ra=sqrt(1- pow(r1,2));

        if(r2<=ra)

            m++;

    }


    p=(m/float(n)*4);

    cout<<"\nPi= "<<p<<endl;

    return 0;

}
```

Input & Output:



```
"G:\Study\4th Year\ACMy coding\Final\Simulation\5.exe"
How many numbers you want to generate: 1000
Pi= 3.112
Process returned 0 (0x0)   execution time : 2.427 s
Press any key to continue.
```

6. Write a C program for Mid-square Method of Generating 4-digit Random Numbers.

```
#include<stdio.h>

#include<stdlib.h>

#include<math.h>

int main()

{

    long seed=6785,a,b,c,i,j,k,x,y,z;

    for(i=1;i<=30;i++){

        y=seed*seed/100.0;

        z=y/10000.0;

        x=((y/10000.0)-z)*10000);

        seed=x;

        printf("%4ld ",x);

    }

    return 0;

}
```

Input & Output:

7. Write a C program to generate variables from NEGATIVE BINOMIAL distribution having Parameters k (number of successes) and p (probability of success in trial).

```
#include<bits/stdc++.h>

using namespace std;

int main()

{

    int i,k,s,x,n;


    float p,r;
```

```

printf("Enter the value of p(<1.0): ");
scanf("%f",&p);
printf("Enter the value of k(>=1.0): ");
scanf("%d",&k);
printf("Enter the number of variates to be generated: ");
scanf("%d",&n);
printf("\n\nValues of variates: ");
for(i=1;i<=n;i++){
    x=0;
    s=0;
    while(s<k){
        r=rand()/32768.0;
        if(r<=p)
            s++;
        x++;
    }
    printf("%d ",x);
}
printf("\n");
return 0;
}

```

Input & Output:



```

"G:\Study\4th Year\ACMy coding\Final\Simulation\7.exe"
Enter the value of p(<1.0): 0.45
Enter the value of k(>=1.0): 3
Enter the number of variates to be generated: 15

Values of variates: 7 9 3 4 3 9 13 9 4 4 9 12 3 9 8
Process returned 0 (0x0)   execution time : 6.259 s
Press any key to continue.


```

8. Write a C program to generate random variable from a Normal distribution having mean μ and standard deviation σ .

```
#include<stdio.h>
#include<stdlib.h>

int main()
{
    int i,j,s,n;
    float meu,sigma,sum,x,t;
    printf("Enter the value of Meu: ");
    scanf("%f",&meu);
    printf("Enter the value of sigma: ");
    scanf("%f",&sigma);
    printf("Enter the number of variates to be generated: ");
    scanf("%d",&n);
    printf("\n\nValues of variates: ");
    for(i=1;i<=n;i++){
        sum=0;
        for(j=0;j<=12;j++){
            x=rand()/32768.0;
            sum+=x;
        }
        t=meu+sigma*(sum-6);
        printf("%.2f ",t);
    }
    printf("\n");
    return 0;
}
```

Input & Output:



A screenshot of a Windows command prompt window. The title bar is light blue and contains the text "G:\Study\4th Year\ACMy coding\Final\Simulation\8.exe" along with standard window controls (minimize, maximize, close). The command prompt area has a black background with white text. It shows three lines of input: "Enter the value of Meu: 10", "Enter the value of sigma: 1.5", and "Enter the number of variates to be generated: 10". Below these, it displays the output: "Values of variates: 11.79 6.32 11.07 12.79 9.46 12.43 10.35 11.23 11.14 10.37". At the bottom, it shows "Process returned 0 (0x0) execution time : 10.223 s" and "Press any key to continue.".

```
"G:\Study\4th Year\ACMy coding\Final\Simulation\8.exe"  
Enter the value of Meu: 10  
Enter the value of sigma: 1.5  
Enter the number of variates to be generated: 10  
  
Values of variates: 11.79 6.32 11.07 12.79 9.46 12.43 10.35 11.23 11.14 10.37  
  
Process returned 0 (0x0) execution time : 10.223 s  
Press any key to continue.
```