L4Sys User Manual

Martin Unzner (munzner@os.inf.tu-dresden.de)

November 28, 2012

Abstract

This document describes how to use the L4Sys experiment suite. However, this is not a complete documentation. When in doubt, please read the source code or contact me. Still, I would like you to read this whole document before investigating further.

This is the user manual on the L4Sys generic system test framework. It provides four experiment types: GPRFlip to simulate a bit flip in a general purpose register, RATFlip to simulate a wrong association in the register allocation table, IDCFLip to corrupt a specific instruction and ALUInstrFlip to modify the behaviour of the arithmetic logic unit, so that it performs a different calculation using the same parameters.

1 Emulator Setup

These experiments work with Bochs only. This is partly due to some issues with timing — as soon as a valid model of time in the target emulator as well as an assembler/disassembler functionality in the Fail* framework are established, I would recommend a backend change, as Bochs' reliability is very limited.

To setup your system, first, you need a dedicated bochsrc file. It has proven handy to have a Bochs resource file or an independent Bochs instance with GUI enabled for the initial testing, however the experiments are intended to be conducted without graphical output.

2 Client Setup

All parameters of the L4Sys experiment client can be found in the file experimentInfo.hpp. Normally, it should not be necessary to change the program flow directly, however, if something bothers you, you are always free to take a look at experiment.cc, too.

2.1 Constants

Some values are constant throughout all steps of the preparation and also when the workload program is run. The most important constant is L4SYS_BOCHS_IPS, which has to be consistent with your bochsrc setting and is used for several timely calculations in the client.

2.2 Step 0: Determine the address space

First, you need to find what are the addresses of the start and end instructions of your workload program. Therefore, you should use a disassembler like *objdump* or *IDA Pro* and set L4SYS_FUNC_ENTRY and L4SYS_FUNC_EXIT accordingly. L4SYS_NUMINSTR is determined automatically in a later preparation step and can be ignored for now.

To test instructions that are run only in a specific address space, L4Sys uses the address space filtering mechanism of Fail*. If your fault injection campaign is not limited to a specific address space, you may set L4SYS_ADDRESS_SPACE to ANY_ADDR. Keep in mind that in that case, your instruction addresses must be unique among all those executed in the system, which in general is not the case.

Basically, there are two ways to find out the identifier of a certain address space in Fail*: You can look up the value in the emulator using a debugger. In the case of Bochs, you may want to study this page, and, according to its instructions, dump the content of the CR3 control register at the beginning of your program.

You can also utilise the Fail* framework, which is easier and more reliable, but as there is no real reason to include this "feature" in the framework, in order to do so, you need to patch it. Namely, src/core/sal/Listener.cc and src/experiments/14-sys/experiment.cc need to be modified using the two patch files supplied alongside with this manual in the current directory. You should check the patch files for their release date and content: In case the framework's event handling structure has changed, the line numbers in Listener.cc are incorrect, and you need to apply the patch manually.

As soon as you have applied the patch, set PREPARATION_STEP to 1 in experimentInfo.hpp and recompile the framework. Now start the experiment client (fail-client) in your emulator directory, and it will show you which address space is active whenever a breakpoint triggers. Ideally, you still have a graphical interface enabled to monitor your system's progress and check if the breakpoints are triggered at the right points in time.

When your program has reached the function entry point, note the address space and exit the program simply by pressing Ctrl+C.

2.3 Step 1: Save the initial state of the machine

If you have modified the Fail* framework in Step 0, you should now restore the original framework data using svn revert.

Make sure PREPARATION_STEP is still set to 1, and you have set L4SYS_ADDRESS_SPACE accordingly. Now recompile and execute the framework code again, this time with the graphical user interface disabled. The experiment client runs until L4SYS_FUNC_ENTRY is reached and then saves the complete configuration.

2.4 Step 2: Determine the instructions to execute

For this part, it depends on how you want to conduct the injection experiments. Setting L4SYS_FILTER_INSTRUCTIONS stores all instructions by default, and enables the filter functionality to store only those instructions that match

the filter. Each instruction in the trace requires an address plus an unsigned breakpoint counter, which means 8 bytes per instruction on a 32-bit system and 12 bytes per instruction on a 64-bit system.

If L4SYS_FILTER_INSTRUCTIONS is not set, the instruction to perform the fault injection at is determined by single-stepping through the program from the beginning, which is quite slow. I only recommend it for long programs, where a complete instruction trace would require several hundred megabytes of data.

No matter which method you choose, the default implementation of the campaign server reads the total instruction count from L4SYS_NUMINSTR. Thus, it is mandatory to set this value to the number of instructions available.

To obtain this number and optionally the instruction trace, set PREPARATION_STEP to 2 and recompile, then execute the experiment client. You do not have to pass parameters to Bochs any more, because the configuration is overwritten with the state saved in step 1.

After the program has finished, you will get a summary on the total of instructions executed.

If you have L4SYS_FILTER_INSTRUCTIONS enabled, this is not the value you look for; it merely claims how many instructions have been processed at all. To set L4SYS_NUMINSTR correctly, you need to look for the number before the word accepted, which points out how many instructions have been accepted by the applied filter. Of course, if no filtering is selected, these two figures should be equal. Please contact me if that is not the case.

If L4SYS_FILTER_INSTRUCTIONS is disabled, you should get a statistical output on how many of the instructions were executed in userland and kernel space, respectively, but the interesting figure in this case is of course the overall sum of executed instructions.

2.5 Step 3: Determine the correct output

This is the easiest step: Set PREPARATION_STEP to 3, recompile the client and execute it in the target directory. It runs the complete program and logs the output. You can check the resulting file (by default golden.out), and if it does not comply with your expectations of a valid run, you should correct the entry and exit point, the address space or, in the worst case, your Bochs settings.

3 Campaign Setup

To setup the actual campaign, you need to edit campaign.cc. The full language capabilities of AspectC++ are at your hand to define the course of your experiments; a sample covering all experiment types at random is already provided. In the experiment client, set PREPARATION_STEP to 0, which means there is nothing more to prepare.

After you have successfully compiled both programs, you need to start both the campaign server (14-sys-server) and the experiment client. By default, they should run on the same machine, but you can adapt the L4SysExperiment constructor in experiment.cc to connect the JobClient to a remote server instead of localhost. Each experiment client processes exactly one experiment and exits. To complete your campaign, you should use the client.sh script in the scripts subdirectory of Fail*.

4 To Be Continued

This is everything I consider important so far. If you still encounter problems you may contact me and I will try to set the record straight. Happy experimenting! :)