

HYDRANT MASTER - 4.0"STORZ X 4.0"STORZ

www.tft.com 3701 Innovation Way Valparaiso IN 46383-9327 800-348-2686

4.0 Inch (100mm)

4.0 Inch (100mm)

Powdercoated Stardust Silver

Hydraulic/Battery Power

Slide Valve (Aluminum)

Storz Swivel

Storz Rigid

Aluminum

Remote Control

RC Hydrant Valve

4.5 Inch (115mm)

AU2P1P Task Force Tips © 2013

Part No: AU2P1P



Related Videos
 Hydrant Master Video

Online Technical Support Material

Coupling Size Side A

Coupling Size Side B

Operation Energy Source

Valve Actuation Method

Finish

Material

Valve Design

Water Flow Style

Waterway Size

Coupling Swiveling/Rigid Side A

Coupling Swiveling/Rigid Side B

- Really Campaign Hydrant master RC
- Oasis Hydrant Assist and Hydrant Master Valve Stor A2114-KIT: Hydrant Master/5-Way Manifold Valve Se
- **Hydrant Master**

Details

HYDRANT MASTER - 4.0"STORZ X 4.0"STORZ 900 MHZ PSI

Weight: 31.000 lbs (kg)

PRODUCT SERIES OVERVIEW

VALVE SPECIFICATIONS

Main LDH Waterway size (at valve seat): 4.5" (114 mm)

Minimum Operating Pressure: 5 psi (0.7 Bar) NOT FOR SUCTION USE.

Maximum Operating Pressure: 300 psi (20 bar) Hydrostatic Proof Test Pressure: 900 psi (62 bar) Temperature Rating*: -25°F to 135°F (-32°C to 57°C) Batteries: 4 AA batteries, Lithium recommended

Expected valve battery life: 140 hours lithium, 100 hours alkaline

*For temperatures below 32°F (0°C), valves must be drained after use to avoid damage.