

Test of Goodness for Population Receptive Field Estimates simulation study

A. Ashrafnejad¹ H. Mehrzadfar² H. Boyaci^{2 3}

¹Department of Electrical and Electronics Engineering

²Neuroscience Graduate Program

³Department of Psychology
Bilkent University

November 5, 2018

- drifting bar stimulation in Dumoulin and Wandell, 2008:



BOLD response model

$$B(t) = \mathcal{H}(r(t, \Theta = \theta)) + e(t)$$

BOLD response model

$$B(t) = \mathcal{H}(r(t, \Theta = \theta)) + e(t)$$

Linear or Non-linear HRF function

fMRI Signal Modelling

assumed pRF response (neuronal response)

BOLD response model

$$B(t) = \mathcal{H}(r(t, \Theta = \theta)) + e(t)$$

Linear or Non-linear HRF function

fMRI Signal Modelling

assumed pRF response (neuronal response)

BOLD response model

$$B(t) = \mathcal{H}(r(t, \Theta = \theta)) + e(t)$$

Linear or Non-linear HRF function

assumed pRF parameters; x_0, y_0, σ

fMRI Signal Modelling

assumed pRF response (neuronal response)

Gaussian noise due to large population of neurons

BOLD response model

$$B(t) = \mathcal{H}(r(t, \Theta = \theta)) + e(t)$$

Linear or Non-linear HRF function

assumed pRF parameters; x_0, y_0, σ

Neuronal Response Modelling

- Neurons within a small region of visual cortex respond to stimuli within a restricted region of the visual field.
- The population response of such neurons can **not** be modeled using a model that sums contrast linearly across the visual field. hence, Compressive spatial summation (CSS) model is used Kay et al., 2013,

pRF response model

$$r(t, \Theta = \theta) = \left(\sum_{x,y} s(x, y, t) g(x, y, \theta) \right)^n$$

Neuronal Response Modelling

- Neurons within a small region of visual cortex respond to stimuli within a restricted region of the visual field.
- The population response of such neurons can **not** be modeled using a model that sums contrast linearly across the visual field. hence, Compressive spatial summation (CSS) model is used Kay et al., 2013,

pRF response model

$$r(t, \Theta = \theta) = \left(\sum_{x,y} s(x, y, t) g(x, y, \theta) \right)^n$$

stimulus function
to be presented

Neuronal Response Modelling

- Neurons within a small region of visual cortex respond to stimuli within a restricted region of the visual field.
- The population response of such neurons can **not** be modeled using a model that sums contrast linearly across the visual field. hence, Compressive spatial summation (CSS) model is used Kay et al., 2013,

pRF response model

$$r(t, \Theta = \theta) = \left(\sum_{x,y} s(x, y, t) g(x, y, \theta) \right)^n$$

stimulus function
to be presented

assumed pRF
model

Neuronal Response Modelling

- Neurons within a small region of visual cortex respond to stimuli within a restricted region of the visual field.
- The population response of such neurons can **not** be modeled using a model that sums contrast linearly across the visual field. hence, Compressive spatial summation (CSS) model is used Kay et al., 2013,


pRF response model

$$r(t, \Theta = \theta) = \left(\sum_{x,y} s(x, y, t) g(x, y, \theta) \right)^n$$

stimulus function
to be presented

assumed pRF
model


spatial linearity
factor from 0 to 1



$$\sigma = \frac{1}{2} \ln(e + \sqrt{x_0^2 + 2y_0^2})$$

pRF response model

$$g(x, y, \Theta = \theta) = e^{-\frac{(x-x_0)^2 + (y-y_0)^2}{2\sigma^2}}$$




$$\sigma = \frac{1}{2} \ln(e + \sqrt{x_0^2 + 2y_0^2})$$

pRF response model

$$g(x, y, \Theta = \theta) = e^{-\frac{(x-x_0)^2 + (y-y_0)^2}{2\sigma^2}}$$

assumed pRF center for the voxel




$$\sigma = \frac{1}{2} \ln(e + \sqrt{x_0^2 + 2y_0^2})$$

pRF response model

$$g(x, y, \Theta = \theta) = e^{-\frac{(x-x_0)^2 + (y-y_0)^2}{2\sigma^2}}$$

assumed pRF center for the voxel

pRF Modelling



$$\sigma = \frac{1}{2} \ln(e + \sqrt{x_0^2 + 2y_0^2})$$

pRF size assumed to be a log-polar function of pRF center Harvey and Dumoulin, 2011

pRF response model

$$g(x, y, \Theta = \theta) = e^{-\frac{(x-x_0)^2 + (y-y_0)^2}{2\sigma^2}}$$

assumed pRF center for the voxel

Haemodynamic Response Function Modelling

Canonical Linear HRF model

$$\mathcal{H}(r(t)) = r(t) * h(t)$$

$$h(t) = \frac{1}{C} \frac{\lambda_1^{n_1} (t - t_1)^{n_1-1} e^{-\lambda_1(t-t_1)}}{(n_1 - 1)!} - a \frac{\lambda_2^{n_2} (t - t_2)^{n_2-1} e^{-\lambda_2(t-t_2)}}{(n_2 - 1)!}$$

Friston Non-Linear HRF

$$\mathcal{H}(r(t)) = \sum_{i=1}^3 \beta_i x_i(t) + \sum_{i=1}^3 \sum_{j=1}^3 \beta_{ij} x_i(t) x_j(t)$$

$$x_i(t) = (r * b_i)(t), \quad b_i(t) = \frac{1}{k!} t^k e^{-t} \quad k = 5, 7, 15$$

MSE model

$$r(t, \Theta) = \left(\sum_{x,y} s(x, y, t) g(x, y, \Theta) \right)^n$$

$$p(t, \Theta) = \mathcal{H}(r(t, \Theta))$$


$$\hat{\Theta} = \arg \min_{\Theta} \sum_t (B(t) - p(t, \Theta))^2$$

Accuracy Map Evaluation

$$\tilde{x} = \frac{|\hat{x}_0 - x_0|}{x_0}, \quad \tilde{y} = \frac{|\hat{y}_0 - y_0|}{y_0}, \quad \tilde{\sigma} = \frac{|\hat{\sigma} - \sigma|}{\sigma}$$


Preliminary Results

- Estimating with non-linear HRF.




Preliminary Results



- Estimating with non-linear HRF.



- Estimating with linear HRF.




- Optimization of parameters.



Optimization

- Optimization of parameters.




- Optimized Stimulus.




Optimized Results

- Estimating with linear HRF via Non-optimized stimulus




Optimized Results

- Estimating with linear HRF via Non-optimized stimulus



- Estimating with linear HRF via Optimized stimulus



Discussion

- We found that non-linearity in simulation HRFs may lead to erroneous pRF estimations. However, we showed that it is possible to optimize the stimulation parameters to ameliorate the effect this non-linearity.
- Therefore, we highly recommend that the stimulation protocol (i.e., stimulation and experiment parameters) should be fine-tuned using computer simulations before an actual fMRI experiment is conducted.

Future work

- Optimization of more parameters using different stimulus.
- fMRI experiments to validate the improvement of pRF estimates.

References I

- Dumoulin, Serge O. and Brian A. Wandell (2008). "Population receptive field estimates in human visual cortex". In: *NeuroImage* 39.2, pp. 647–660. ISSN: 10538119. DOI: 10.1016/j.neuroimage.2007.09.034.
- Harvey, B. M. and S. O. Dumoulin (2011). "The Relationship between Cortical Magnification Factor and Population Receptive Field Size in Human Visual Cortex: Constancies in Cortical Architecture". In: *Journal of Neuroscience* 31.38, pp. 13604–13612. ISSN: 0270-6474. DOI: 10.1523/JNEUROSCI.2572-11.2011. URL: <http://www.jneurosci.org/cgi/doi/10.1523/JNEUROSCI.2572-11.2011>.
- Kay, Kendrick N. et al. (2013). "Compressive spatial summation in human visual cortex." In: *Journal of neurophysiology*. ISSN: 1522-1598. DOI: 10.1152/jn.00105.2013.