

# Test of Goodness for Population Receptive Field Estimates simulation study

A. Ashrafnejad<sup>1</sup>   H. Mehrzadfar<sup>2</sup>   H. Boyaci<sup>2 3</sup>

<sup>1</sup>Department of Electrical and Electronics Engineering

<sup>2</sup>Neuroscience Graduate Program

<sup>3</sup>Department of Psychology  
Bilkent University

November 5, 2018

We first used the exact drifting bar stimulation in Dumoulin and Wandell, 2008:

## BOLD response model

$$B(t) = \mathcal{H}(r(t, \Theta = \theta)) + e(t)$$

## BOLD response model

$$B(t) = \mathcal{H}(r(t, \Theta = \theta)) + e(t)$$

Linear or Non-linear HRF function

# fMRI Signal Modelling

assumed pRF response (neuronal response)

BOLD response model

$$B(t) = \mathcal{H}(r(t, \Theta = \theta)) + e(t)$$

Linear or Non-linear HRF function

# fMRI Signal Modelling

assumed pRF response (neuronal response)

BOLD response model

$$B(t) = \mathcal{H}(r(t, \Theta = \theta)) + e(t)$$

Linear or Non-linear HRF function

assumed pRF parameters;  $x_0, y_0, \sigma$

# fMRI Signal Modelling

assumed pRF response (neuronal response)

Gaussian noise due to large population of neurons

BOLD response model

$$B(t) = \mathcal{H}(r(t, \Theta = \theta)) + e(t)$$

Linear or Non-linear HRF function

assumed pRF parameters;  $x_0, y_0, \sigma$

# Neuronal Response Modelling

- Neurons within a small region of visual cortex respond to stimuli within a restricted region of the visual field.
- The population response of such neurons can **not** be modeled using a model that sums contrast linearly across the visual field. hence, Compressive spatial summation (CSS) model is used Kay et al., 2013,

## pRF response model

$$r(t, \Theta = \theta) = \left( \sum_{x,y} s(x, y, t) g(x, y, \theta) \right)^n$$



# Neuronal Response Modelling

- Neurons within a small region of visual cortex respond to stimuli within a restricted region of the visual field.
- The population response of such neurons can **not** be modeled using a model that sums contrast linearly across the visual field. hence, Compressive spatial summation (CSS) model is used Kay et al., 2013,

## pRF response model

$$r(t, \Theta = \theta) = \left( \sum_{x,y} s(x, y, t) g(x, y, \theta) \right)^n$$

stimulus function  
to be presented

# Neuronal Response Modelling

- Neurons within a small region of visual cortex respond to stimuli within a restricted region of the visual field.
- The population response of such neurons can **not** be modeled using a model that sums contrast linearly across the visual field. hence, Compressive spatial summation (CSS) model is used Kay et al., 2013,

## pRF response model

$$r(t, \Theta = \theta) = \left( \sum_{x,y} s(x, y, t) g(x, y, \theta) \right)^n$$

stimulus function  
to be presented

assumed pRF  
model

# Neuronal Response Modelling

- Neurons within a small region of visual cortex respond to stimuli within a restricted region of the visual field.
- The population response of such neurons can **not** be modeled using a model that sums contrast linearly across the visual field. hence, Compressive spatial summation (CSS) model is used Kay et al., 2013,


## pRF response model

$$r(t, \Theta = \theta) = \left( \sum_{x,y} s(x, y, t) g(x, y, \theta) \right)^n$$

stimulus function  
to be presented

assumed pRF  
model


spatial linearity  
factor from 0 to 1



$$\sigma = \frac{1}{2} \ln(e + \sqrt{x_0^2 + 2y_0^2})$$

pRF response model

$$g(x, y, \Theta = \theta) = e^{-\frac{(x-x_0)^2 + (y-y_0)^2}{2\sigma^2}}$$




$$\sigma = \frac{1}{2} \ln(e + \sqrt{x_0^2 + 2y_0^2})$$

## pRF response model

$$g(x, y, \Theta = \theta) = e^{-\frac{(x-x_0)^2 + (y-y_0)^2}{2\sigma^2}}$$

assumed pRF center for the voxel




$$\sigma = \frac{1}{2} \ln(e + \sqrt{x_0^2 + 2y_0^2})$$

## pRF response model

$$g(x, y, \Theta = \theta) = e^{-\frac{(x-x_0)^2 + (y-y_0)^2}{2\sigma^2}}$$

assumed pRF center for the voxel

# pRF Modelling



$$\sigma = \frac{1}{2} \ln(e + \sqrt{x_0^2 + 2y_0^2})$$

pRF response model

$$g(x, y, \Theta = \theta) = e^{-\frac{(x-x_0)^2 + (y-y_0)^2}{2\sigma^2}}$$

pRF size assumed to be a log-polar function of pRF center

assumed pRF center for the voxel

# References I

- Dumoulin, Serge O. and Brian A. Wandell (2008). "Population receptive field estimates in human visual cortex". In: *NeuroImage* 39.2, pp. 647–660. ISSN: 10538119. DOI: 10.1016/j.neuroimage.2007.09.034.
- Kay, Kendrick N. et al. (2013). "Compressive spatial summation in human visual cortex." In: *Journal of neurophysiology*. ISSN: 1522-1598. DOI: 10.1152/jn.00105.2013.