


Movie Recommendation Using Graph Neural Networks

Kuan Tung, Chun-Hung Yeh, Hiroki Hayakawa and Jinhui Guo




Introduction




- Dataset: Movielens 100k
 - 100,000 ratings (1-5) from 943 users on 1682 movies
 - Each user has rated at least 20 movies.
 - Simple demographic info for the users (age, gender, occupation, zip)
- Network structures of movies and users
 - Movies: top rated, highest rating score, genres
 - Users: genders, occupation
- Similar Movies according to Genres
- Graph Convolutional Matrix Completion





Top rated movies



Top rating movies



Gender and occupation



Movies and Genres

Network structure

Dimension reduction and clustering

Overview of Genres






TABLE I
MOVIE GRAPH STATISTICS

Statistics	Value
Nodes	1682
Edges	642422
Average Degree	763.879
Diameter	6
Density	0.454
Modularity	0.168
Clustering Coefficient	0.797
Connected Component	1

- Nodes: movies
- Edges: the distance between two movies as computed based on one-hot vectors of their genres





Movie graph

- Degree distribution
- Visualization
 - Link: <https://dinotuku.com/ntds-2019-project-team-7/exploration/figure/genres-graph/>

TABLE II
USER GRAPH STATISTICS

Statistics	Value
Nodes	943
Edges	41326
Average Degree	87.648
Diameter	1
Density	0.093
Modularity	0.744
Clustering Coefficient	1.0
Connected Component	21


- Nodes: User
- Edges: the distance between two users as computed based on one-hot vectors of their jobs




User graph

- Degree distribution
- Visualization
 - Link: <https://dinotuku.com/ntds-2019-project-team-7/exploration/figure/genres-graph/>


Positive weights only



Negative weights only




Genres Graph Using Co-occurrence and Correlation Matrix




The most apparent pair that two genres co-occur is **Documentary and Drama** (edge weight: 0.6)

Similar Movies According to Genres

- ❑ Dimension reduction: t-Distributed Stochastic Neighbor Embedding (t-SNE)
- ❑ Clustering: K-means



21.01.2020




Prediction of Movie Ratings

Graph convolutional matrix completion (GC-MC)

Matrix factorization

Model comparison

Graph Convolutional Matrix Completion Method



Graph Convolutional Matrix Completion (Cont.)

□ Graph Convolutional Encoder

$$\mu_{j \rightarrow i, r} = \frac{1}{c_{ij}} W_r x_j, \quad c_{ij} = |\mathcal{N}_i| \quad (\text{Info. Transfer: movie } j \text{ to user } i)$$

$$h_i = \sigma \left[\text{accum} \left(\sum_{j \in \mathcal{N}_{i,1}} \mu_{j \rightarrow i,1}, \dots, \sum_{j \in \mathcal{N}_{i,R}} \mu_{j \rightarrow i,R} \right) \right] \quad (\text{Accumulation})$$

$$u_i = \sigma(W h_i) \quad \text{or} \quad u_i = \sigma(W h_i + W_2^f f_i) \quad \text{with} \quad f_i = \sigma(W_1^f x_i^f + b),$$

(Activation to obtain user embedding vector)

□ Bilinear Decoder

$$\check{M}_{ij} = \mathbb{E}_{p(\check{M}_{ij}=r)}[R] = \sum_{r \in R} r p(\check{M}_{ij} = r), \quad p(\check{M}_{ij} = r) = \frac{e^{u_i^T Q_r v_j}}{\sum_{r \in R} e^{u_i^T Q_r v_j}}$$

(Calculate expectation of rate from user i to movie j)

Models



- Two based on graph convolutional matrix completion (GC-MC) methods
 - The hidden sizes of the stack graph convolution layer and dense layer were set as 500 and 75
 - Dropout (dropout rate = 0.7) was applied
- Three based on matrix factorization:
 - Sum of the dot value of the two latent factors and the two bias terms
 - Concatenate the two latent factors and feed into DNN
 - Add user and movie features
- For both:
 - The train/validation/test split was 72/8/20
 - Adam was chosen as the optimizer

Results

- ❑ GC-MC with features is the best model with the lowest RMSE (0.901)
- ❑ The validation losses of both graph-based models are surprisingly lower than the training losses, and they keep decreasing

TABLE III
RECOMMENDATION SYSTEM RESULTS

Model	RMSE
MF	0.954
MF + DNN	0.942
MF + DNN with features	0.923
GC-MC	0.908
GC-MC with features	0.901




Conclusions and future prospective



Network structures:

Movie ratings by users with different gender and occupation
Movie graph and user graph (hubs and giant component)
Co-occurrence and correlation between movie genres



Dimension reduction and clustering:

t-SNE and K-means
9 meaningful clusters
Similar new movie recommendation



Rating prediction

Five models: MF, MF- DNN, MF- DNN with features, GC-MC, and GC-MC with features
GC-MC with features scored the lowest RMSE value of 0.901
Tuning model configurations such as size of hidden layers, accumulation method, the number of training epochs, and optimization methods (e.g. SGD)

dinotuku / ntds-2019-project-team-7

Unwatch

1

Star

1

Fork

0

<> Code

Issues 0

Pull requests 0

Actions

Projects 0

Wiki

Security

Insights

Settings

A personalized movie recommendation system and exploration of MovieLens 100k.

Edit

Manage topics

28 commits

1 branch

0 packages

0 releases

1 environment

2 contributors

MIT

Branch: master

New pull request

Create new file

Upload files

Find file

Clone or download

yehchunhung Update README.md

Latest commit 05cd0b3 7 days ago

exploitation	Upload exploitation folder	7 days ago
exploration	Delete classification.ipynb	7 days ago
recommenders	Add history plotting codes	8 days ago
.gitignore	Remove .DS_Store	7 days ago
LICENSE.md	Add LICENSE.md	9 days ago
README.md	Update README.md	7 days ago

README.md

NTDS 2019 Project Team 7 - Movie Recommendation

Presentation Slides

Check out our GitHub [repository](#) for more information



Thank you for
listening !

Any question?

Reference

- Toy Story Poster, <https://www.imdb.com/title/tt00114709/>
- Harper, F. Maxwell, and Joseph A. Konstan. "The movielens datasets: History and context." *Acm transactions on interactive intelligent systems (tiis)* 5.4 (2015): 1-19.
- MovieLens 100K Dataset, <https://grouplens.org/datasets/movielens/100k/>
- Berg, Rianne van den, Thomas N. Kipf, and Max Welling. "Graph convolutional matrix completion." *arXiv preprint arXiv:1706.02263* (2017).
- Graph Convolutional Matrix Completion (GitHub repository), <https://github.com/riannevdberg/gc-mc>
- Matrix Factorization (lecture given by Hung-yi Lee), http://speech.ee.ntu.edu.tw/~tlkagk/courses/ML_2017/Lecture/MF.pdf