

```
mysql> create table Dept(dept_id int not null primary key,dept_name
varchar(20));
Query OK, 0 rows affected (1.61 sec)
```

```
mysql> desc Dept;
```

Field	Type	Null	Key	Default	Extra
dept_id	int(11)	NO	PRI	NULL	
dept_name	varchar(20)	YES		NULL	

2 rows in set (0.11 sec)

```
mysql> insert into Dept values(1,'Finance');
Query OK, 1 row affected (0.25 sec)
```

```
mysql> insert into Dept values(1,'Training');
ERROR 1062 (23000): Duplicate entry '1' for key 'PRIMARY'
mysql> insert into Dept values(2,'Training');
Query OK, 1 row affected (0.14 sec)
```

```
mysql> insert into Dept values(3,'Marketing');
Query OK, 1 row affected (0.15 sec)
```

```
mysql> select * from Dept;
```

dept_id	dept_name
1	Finance
2	Training
3	Marketing

3 rows in set (0.00 sec)

```
mysql> create table employee(emp_id int,emp_name varchar(50) not
null,dept_id int,salary int(20),manager int,primary key(emp_id),foreign
key(dept_id) references department(dept_id));
Query OK, 0 rows affected (1.11 sec)
```

```
mysql> insert into employee values(1,'Arun',1,8000,4);
Query OK, 1 row affected (0.40 sec)
```

```
mysql> insert into employee values(2,'kiran',1,7000,1);
Query OK, 1 row affected (0.12 sec)
```

```
mysql> insert into employee values(3,'scott',1,3000,1);
Query OK, 1 row affected (0.17 sec)
```

```
mysql> insert into employee values(4,'max',2,9000,null);
Query OK, 1 row affected (0.15 sec)
```

```
mysql> insert into employee values(5,'jack',2,8000,4);
Query OK, 1 row affected (0.19 sec)
```

```
mysql> insert into employee values(6,'king',null,6000,1);
Query OK, 1 row affected (0.11 sec)
```

```
mysql> select * from employee;
```

emp_id	emp_name	dept_id	salary	manager
1	Arun	1	8000	4
2	kiran	1	7000	1
3	scott	1	3000	1
4	max	2	9000	null
5	jack	2	8000	4
6	king	null	6000	1

1	Arun	1	8000	4
2	kiran	1	7000	1
3	scott	1	3000	1
4	max	2	9000	NULL
5	jack	2	8000	4
6	king	NULL	6000	1

6 rows in set (0.00 sec)

```
mysql> select count(emp_id),emp_name from employee group by emp_name;
```

count(emp_id)	emp_name
1	Arun
1	kiran
1	scott
1	max
1	jack
1	king

6 rows in set (0.08 sec)

```
mysql> select * from Dept order by dept_name;
```

dept_id	dept_name
1	Finance
3	Marketing
2	Training

3 rows in set (0.00 sec)

```
mysql> select dept_id, sum(salary) from employee group by dept_id;
```

dept_id	sum(salary)
NULL	6000
1	18000
2	17000

3 rows in set (0.07 sec)

```
mysql> select dept_id from employee where salary>17000 group by dept_id;
Empty set (0.00 sec)
```

```
mysql> select dept_id,sum(salary) from employee group by dept_id having
sum(salary)>18000;
Empty set (0.05 sec)
```

```
mysql> select dept_id,sum(salary) from employee group by dept_id having
sum(salary)>17000;
```

dept_id	sum(salary)
1	18000

1 row in set (0.00 sec)

```
mysql> select dept_id,sum(salary) from employee group by dept_id having  
sum(salary)<20000;
```

```
+-----+-----+  
| dept_id | sum(salary) |  
+-----+-----+  
|      NULL |          6000 |  
|         1 |         18000 |  
|         2 |         17000 |  
+-----+-----+  
3 rows in set (0.04 sec)
```