

# Emacs Initialization

John Jacobsen

November 13, 2014

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
<b>2</b>	<b>Utilities</b>	<b>2</b>
<b>3</b>	<b>Package management</b>	<b>2</b>
<b>4</b>	<b>Startup</b>	<b>3</b>
<b>5</b>	<b>Initial keybindings</b>	<b>3</b>
<b>6</b>	<b>Remembering Where We Were Last Time Around</b>	<b>3</b>
<b>7</b>	<b>General Lisp stuff</b>	<b>3</b>
<b>8</b>	<b>Stuff for Editing Emacs Lisp</b>	<b>3</b>
<b>9</b>	<b>Ruby stuff</b>	<b>4</b>
<b>10</b>	<b>Backups</b>	<b>4</b>
<b>11</b>	<b>File Completion</b>	<b>4</b>
<b>12</b>	<b>Autocomplete Mode</b>	<b>4</b>
<b>13</b>	<b><math>\lambda</math></b>	<b>4</b>
<b>14</b>	<b>Highlighting of long lines</b>	<b>5</b>
<b>15</b>	<b>Lots of keybindings</b>	<b>5</b>
<b>16</b>	<b>Clojure setup</b>	<b>7</b>
16.1	Key bindings special to Midje facts . . . . .	7
16.2	Correcting single-whitespaced toplevel forms . . . . .	8
16.3	Mode line hack . . . . .	9
<b>17</b>	<b>Stuff for running shells within Emacs</b>	<b>10</b>
17.1	Path Magic . . . . .	10
17.2	Moar Shells . . . . .	10
17.3	Kill shell buffers quickly . . . . .	10
<b>18</b>	<b>Stuff related to configuring Emacs-in-a-window</b>	<b>11</b>

19 Common Lisp	11
20 Org Mode	11
21 Blogging	13
22 Tidying up	15

## 1 Introduction

Here's my Emacs init code. Some of it was adapted from Matthew Wampler-Doty. Other things have been borrowed from Sacha Chua and other places around the Internetz.

You'll find this code highly focused on Clojure and Org Mode. I have a lot of unconventional keybindings since I didn't bother to learn all the classic ones when I started with Emacs (probably sometime in the 1990s).

## 2 Utilities

Matt wrote a Clojure-like `filter` function. Probably I'll write more like it as I need them, since I am more used to Clojure than Emacs Lisp. (Why else would one bother with a "programmable programming language"<sup>1</sup>, if not to tailor one's language to one's liking?)

```
(defun filter (pred lst)
  "Use PRED to filter a list LST of elements."
  (delq nil (mapcar (lambda (x) (and (funcall pred x) x)) lst)))
```

## 3 Package management

MELPA is a bit too bleeding edge; since CIDER has broken for me before after upgrading, I use the more stable releases from `melpa-stable` only. To get back MELPA(-bleeding-edge), swap in the following:

```
;; (add-to-list 'package-archives
;;            '("MELPA" . "http://melpa.milkbox.net/packages/") t)
```

Define which remote archives to pull from, and which packages to use:

```
(require 'package)
(add-to-list
 'package-archives
 '("melpa-stable" . "http://melpa-stable.milkbox.net/packages/") t)
(add-to-list 'package-archives
 '("marmalade" . "http://marmalade-repo.org/packages/") t)
(package-initialize)
(defvar my-packages)
(setq my-packages
 '(company auto-complete autopair ac-cider cider color-theme
  zenburn-theme diminish goto-last-change main-line maxframe
  clojure-mode epl popup rainbow-delimiters smex undo-tree
  flycheck flycheck-hdevtools org git-timemachine paredit
  auto-indent-mode slamhound lorem-ipsuim midje-mode
  hungry-delete metar helm htmlize magit expand-region))
```

---

<sup>1</sup>John Foderaro, CACM, Sept. 1991.

Install any missing packages:

```
(let ((uninstalled-packages (filter (lambda (x) (not (package-installed-p x)))
  my-packages)))
  (when (and (not (equal uninstalled-packages '()))
    (y-or-n-p (format "Install packages %s?" uninstalled-packages)))
    (package-refresh-contents)
    (mapc 'package-install uninstalled-packages)))
```

## 4 Startup

Some configuration to make things quieter on start up:

```
(setq inhibit-splash-screen t
  initial-scratch-message nil)
```

## 5 Initial keybindings

At some point I took it into my head to map most of my personal key bindings to combinations starting with `\C-o`. We have to set it free from its usual use (`open-line`) before we can use it as a prefix.

```
(global-unset-key "\C-o")
```

## 6 Remembering Where We Were Last Time Around

```
(require 'saveplace)
(setq-default save-place t)
(setq save-place-file "~/emacs.d/saved-places")
```

## 7 General Lisp stuff

Rainbow delimiters for all programming major modes:

```
(require 'rainbow-delimiters)
(add-hook 'prog-mode-hook 'rainbow-delimiters-mode)
```

Show paren balancing nicely:

```
(require 'paren)
(set-face-background 'show-paren-match "white")
(add-hook 'prog-mode-hook 'show-paren-mode)
```

## 8 Stuff for Editing Emacs Lisp

I add a hook for evaluating the expression just before point; I've played with `auto-indent-mode` and `flycheck-mode` but tired of them. I do want `paredit` though (and therefore don't want `autopair-mode`).

```
(define-key emacs-lisp-mode-map (kbd "<s-return>") 'eval-last-sexp)

;;(add-hook 'emacs-lisp-mode-hook 'flycheck-mode)
;;(add-hook 'emacs-lisp-mode-hook 'auto-indent-mode)
```

```
(add-hook 'emacs-lisp-mode-hook
  (lambda ()
    (paredit-mode 1)
    (autopair-mode 0)))
```

## 9 Ruby stuff

Sometimes I have to write Rails or Ruby code. You might, too. Do two space indents for Ruby code:

```
(setq ruby-indent-level 2)
```

## 10 Backups

Tell Emacs to write backup files to their own directory, and make backups even for files in revision control:

```
(setq backup-directory-alist
  '(("." . ,(expand-file-name
    (concat user-emacs-directory "backups")))))

(setq vc-make-backup-files t)
```

## 11 File Completion

Trying out Helm<sup>2</sup>:

```
(require 'helm-config)
(helm-mode)
```

## 12 Autocomplete Mode

This is one of several available auto-complete modes for Emacs. It's basic but I've found it more reliable than `company-mode`.

```
(require 'auto-complete)
(add-hook 'prog-mode-hook 'auto-complete-mode)
```

## 13 $\lambda$

Make lambda show as  $\lambda$ :

```
(font-lock-add-keywords
  'emacs-lisp-mode
  '(("(\\"(lambda\\")\\>"
    (0 (prog1 ()
      (compose-region (match-beginning 1)
        (match-end 1)
        ?))))))
```

---

<sup>2</sup><http://emacs-helm.github.io/helm/>

## 14 Highlighting of long lines

```
(defun highlight-long-lines ()
  "Turn on highlighting of long lines."
  (interactive)
  (highlight-lines-matching-regexp ".\\{81\\}" 'hi-pink))

(defun unhighlight-long-lines ()
  "Turn off highlighting of long lines."
  (interactive)
  (unhighlight-regexp "^.*\\(?:\\.\\{81\\}\\|\\).*")

(global-set-key "\C-oH" 'highlight-long-lines)
(global-set-key "\C-oh" 'unhighlight-long-lines)
```

## 15 Lots of keybindings

Many of these are extremely old, having followed me from machine to machine over the years. Some could probably be deleted.

```
(global-set-key [S-deletechar] 'kill-ring-save)
;; Set up the keyboard so the delete key on both the regular keyboard
;; and the keypad delete the character under the cursor and to the right
;; under X, instead of the default, backspace behavior.
(global-set-key [delete] 'delete-char)
(global-set-key [kp-delete] 'delete-char)

(define-key function-key-map "\e[1~" [find])
(define-key function-key-map "\e[2~" [insertchar])
(define-key function-key-map "\e[3~" [deletechar])
(define-key function-key-map "\e[4~" [select])
(define-key function-key-map "\e[5~" [prior])
(define-key function-key-map "\e[6~" [next])
(define-key global-map [select] 'set-mark-command)
(define-key global-map [insertchar] 'yank)
(define-key global-map [deletechar] 'kill-region)

(global-unset-key "\C- ")
(global-set-key [?\C- ] 'other-window)
(global-set-key "\C-oW" (lambda ()
  (interactive)
  (org-babel-load-file (concat user-emacs-directory "org/init.org"))))
(global-set-key "\C-A" 'split-window-horizontally)
(global-set-key "\C-oa" 'split-window-vertically)
(global-set-key "\C-K" 'kill-line)
(global-set-key "\C-os" 'isearch-forward-regexp)
(global-set-key "\C-oD" 'find-name-dired)
(global-set-key "\C-xS" 'sort-lines)
(global-set-key "\C-w" 'backward-kill-word)
(global-set-key "\C-x\C-k" 'kill-region)
```

```

(global-set-key "\C-c\C-k" 'kill-region)
(global-set-key "\C-ok" 'comment-region)
(global-set-key "\C-ou" 'uncomment-region)
(global-set-key "\C-on" 'er/expand-region)
(global-set-key "\C-oe" 'eval-current-buffer)
(global-set-key "\C-od" 'delete-horizontal-space)
(global-set-key "\C-ob" 'backward-word)
(global-set-key "\C-oq" 'query-replace-regexp)
(global-set-key "\C-oL" 'lorem-ipsuim-insert-paragraphs)
(global-set-key "\C-]" 'fill-region)
(global-set-key "\C-ot" 'beginning-of-buffer)
(global-set-key "\C-oT" 'toggle-window-split)
(global-set-key "\C-N" 'enlarge-window)
(global-set-key "\C-o\C-n" 'enlarge-window-horizontally)
(global-set-key "\C-oc" 'paredit-duplicate-closest-sexp)
(global-set-key "\C-ol" 'goto-line)
(global-set-key "\C-ob" 'end-of-buffer)
(global-set-key "\C-op" 'fill-region)
(global-set-key "\C-og" 'save-buffers-kill-emacs)
(global-set-key "\C-od" 'downcase-region)
(global-set-key "\C-oR" 'indent-region)
(global-set-key "\C-or" 'rgrep)
(global-set-key "\C-L" 'delete-other-windows)
(global-set-key "\C-B" 'scroll-down)
(global-set-key "\C-F" 'scroll-up)
(global-set-key "\C-V" 'save-buffer)
(global-set-key "\C-R" 'isearch-forward)
(global-set-key "\C-^" 'wnt-alog-add-entry)
(global-set-key "\C-T" 'set-mark-command)
(global-set-key "\C-Y" 'yank)
(global-set-key "\C-D" 'backward-delete-char-untabify)
(global-set-key "\C-\\\" 'shell)
(global-set-key "\C-oi" 'quoted-insert)
(global-set-key "\e[1~" 'isearch-forward)
(global-set-key [select] 'set-mark-command)
(global-set-key [insertchar] 'yank)
(global-set-key [deletechar] 'kill-region)
(global-set-key "\C-\\\" 'shell)
(global-set-key "\C-oi" 'quoted-insert)
(global-set-key "\e[1~" 'isearch-forward)
(global-set-key [select] 'set-mark-command)
(global-set-key [insertchar] 'yank)
(global-set-key [deletechar] 'kill-region)
(global-set-key (kbd "s-0") 'org-todo-list)

```

Shortcuts for jumping directly into most commonly-used buffers:

```

(global-set-key "\C-o0" (lambda ()
  (interactive)
  (find-file "~/Dropbox/org/toplevel.org")))
(global-set-key "\C-oE" (lambda ()

```

```
(interactive)
(find-file "~/emacs.d/org/init.org"))))
```

Keyboard shortcuts for joining lines before and after point (thanks to <http://whattheemacs.com/> for the (join-line -1) trick):

```
(global-set-key (kbd "M-j")
  (lambda () (interactive) (join-line -1)))
(global-set-key "\C-oo" 'join-line)
```

Show trailing whitespace, ‘cause *we hates it...*

```
(setq-default show-trailing-whitespace t)
```

## 16 Clojure setup

Don’t go to REPL buffer when starting Cider:

```
(setq cider-repl-pop-to-buffer-on-connect nil)
```

### 16.1 Key bindings special to Midje facts

Set up Midje fact with mark inserted at beginning of comment text (refill as needed in appropriate columns, using C-oF).

```
(global-set-key "\C-of" (lambda ()
  (interactive)
  (insert "(fact"                                     "\"\"\\n\\n  )")
  (backward-char 6)
  (set-mark (point)))))
```

Perform the refill operation for the text string in a Midje fact:

```
(global-set-key "\C-oF" (lambda ()
  (interactive)
  (set-left-margin (mark) (point) 37)
  (fill-region (mark) (point)))))
```

Append result of evaluating previous expression (Clojure):

```
(defun cider-eval-last-sexp-and-append ()
  "Evaluate the expression preceding point and append result."
  (interactive)
  (let ((last-sexp (cider-last-sexp)))
    ;; we have to be sure the evaluation won't result in an error
    (cider-eval-and-get-value last-sexp)
    (with-current-buffer (current-buffer)
      (insert ";;=>\\n"))
    (cider-interactive-eval-print last-sexp)))
```

```
(defun cider-format-with-out-str-pprint-eval (form)
  "Return a string of Clojure code that will return pretty-printed FORM."
  (format "(clojure.core/let [x %s] (with-out-str (clojure.pprint/pprint x)))" form))
```

```
(defun cider-eval-last-sexp-and-pprint-append ()
  "Evaluate the expression preceding point and append pretty-printed result."
  (interactive)
  (let ((last-sexp (cider-last-sexp)))
    ;; we have to be sure the evaluation won't result in an error
    (with-current-buffer (current-buffer)
      (insert ";;=>\n")
      (insert (cider-eval-and-get-value (cider-format-with-out-str-pprint-eval last-sexp))))))

;; A few paredit things, also from whattheemacs.com:
(defun paredit--is-at-start-of-sexp ()
  (and (looking-at "(\\|\\|[\"")
        (not (nth 3 (syntax-ppss))) ;; inside string
        (not (nth 4 (syntax-ppss)))) ;; inside comment

(defun paredit-duplicate-closest-sexp ()
  (interactive)
  ;; skips to start of current sexp
  (while (not (paredit--is-at-start-of-sexp))
    (paredit-backward))
  (set-mark-command nil)
  ;; while we find sexps we move forward on the line
  (while (and (bounds-of-thing-at-point 'sexp)
              (<= (point) (car (bounds-of-thing-at-point 'sexp)))
              (not (= (point) (line-end-position))))
    (forward-sexp)
    (while (looking-at " ")
      (forward-char)))
  (kill-ring-save (mark) (point))
  ;; go to the next line and copy the sexprs we encountered
  (paredit-newline)
  (yank)
  (exchange-point-and-mark))
```



```

(define-key clojure-mode-map (kbd "C-c e") 'shell-eval-last-expression)
(define-key clojure-mode-map (kbd "C-o x") 'cider-eval-defun-at-point)
(define-key clojure-mode-map (kbd "C-o j") 'cider-jack-in)
(define-key clojure-mode-map (kbd "C-o J") 'cider-restart)
(define-key clojure-mode-map (kbd "C-<up>") 'paredit-backward)
(define-key clojure-mode-map (kbd "C-<down>") 'paredit-forward)
(define-key clojure-mode-map (kbd "C-o y")
  'cider-eval-last-sexp-and-append)
(define-key clojure-mode-map (kbd "C-o Y")
  'cider-eval-last-sexp-and-pprint-append)
(define-key clojure-mode-map (kbd "s-i") 'cider-eval-last-sexp)
(define-key clojure-mode-map (kbd "C-c x") 'shell-eval-defun)))

;; Minibuffer size
(add-hook 'minibuffer-setup-hook 'my-minibuffer-setup)
(defun my-minibuffer-setup ()
  (set (make-local-variable 'face-remapping-alist)
    '((default :height 1.5))))

;;; Swap window split orientation
;;; (http://emacs.stackexchange.com/questions/318/switch-window-split-orientation-fastest-way):
(defun toggle-window-split ()
  (interactive)
  (if (= (count-windows) 2)
    (let* ((this-win-buffer (window-buffer))
           (next-win-buffer (window-buffer (next-window)))
           (this-win-edges (window-edges (selected-window)))
           (next-win-edges (window-edges (next-window)))
           (this-win-2nd (not (and (<= (car this-win-edges)
                                         (car next-win-edges))
                                     (<= (cadr this-win-edges)
                                         (cadr next-win-edges))))))
      (splitter
       (if (= (car this-win-edges)
              (car (window-edges (next-window))))
         'split-window-horizontally
         'split-window-vertically)))
    (delete-other-windows)
    (let ((first-win (selected-window)))
      (funcall splitter)
      (if this-win-2nd (other-window 1))
      (set-window-buffer (selected-window) this-win-buffer)
      (set-window-buffer (next-window) next-win-buffer)
      (select-window first-win)
      (if this-win-2nd (other-window 1))))))

```

### 16.3 Mode line hack

Shorten clojure-mode in mode line<sup>3</sup>.

---

<sup>3</sup>From <http://whattheemacs.com/>

```
(defmacro rename-modeline (package-name mode new-name)
  '(eval-after-load ,package-name
    '(defadvice ,mode (after rename-modeline activate)
      (setq mode-name ,new-name))))
```

```
(rename-modeline "clojure-mode" clojure-mode "Clj")
```

## 17 Stuff for running shells within Emacs

### 17.1 Path Magic

Smooth the waters for starting processes from the shell. “Set up Emacs’ ‘exec-path’ and PATH environment variable to match the user’s shell. This is particularly useful under Mac OSX, where GUI apps are not started from a shell<sup>4</sup>.”

```
(defun set-exec-path-from-shell-PATH ()
  (interactive)
  (let ((path-from-shell
        (replace-regexp-in-string
         "[ \\t\\n]*$" ""
         (shell-command-to-string "$SHELL --login -i -c 'echo $PATH'"))))
    (setenv "PATH" path-from-shell)
    (setq exec-path (split-string path-from-shell path-separator))))
```

### 17.2 Moar Shells

Create shell in new buffer when needed, rather than just loading up the existing shell buffer.

```
(defun create-shell-in-new-buffer ()
  (interactive)
  (let ((currentbuf (get-buffer-window (current-buffer)))
        (newbuf (generate-new-buffer-name "*shell*")))
    (generate-new-buffer newbuf)
    (set-window-dedicated-p currentbuf nil)
    (set-window-buffer currentbuf newbuf)
    (shell newbuf)))
```

```
(global-set-key "\C-oS" 'create-shell-in-new-buffer)
```

### 17.3 Kill shell buffers quickly

“With this snippet, [a second] press of C-d will kill the buffer. It’s pretty nice, since you then just tap C-d twice to get rid of the shell and go on about your merry way<sup>5</sup>”

```
(defun comint-delchar-or-eof-or-kill-buffer (arg)
  (interactive "p")
  (if (null (get-buffer-process (current-buffer)))
      (kill-buffer)
      (comint-delchar-or-maybe-eof arg)))
```

---

<sup>4</sup>See <http://stackoverflow.com/questions/8606954/path-and-exec-path-set-but-emacs-does-not-find-executable>

<sup>5</sup>From <http://whattheemacs.com>.

```
(add-hook 'shell-mode-hook
  (lambda ()
    (define-key shell-mode-map
      (kbd "C-d") 'comint-delchar-or-eof-or-kill-buffer))))
```

## 18 Stuff related to configuring Emacs-in-a-window

When running GUI Emacs (i.e. on OS-X, which is the only way I run Emacs these days anyways), set the theme to Zenburn, turn off visual noise, fix up the PATH for shells, and allow resizing of window.

```
(when window-system
  (load-theme 'zenburn t)
  (tool-bar-mode -1)
  (scroll-bar-mode -1)
  (set-exec-path-from-shell-PATH)
  (global-set-key (kbd "s-=") 'text-scale-increase)
  (global-set-key (kbd "s--") 'text-scale-decrease))
```

Don't pop up newly-opened files in a new frame – use existing one:

```
(setq ns-pop-up-frames nil)
```

## 19 Common Lisp

I haven't done too much Common Lisp programming yet, but have just played around. So far I find Emacs integration to be at least as good as with Clojure. Here I mimic two of the keybindings I use most from Clojure.

```
(require 'slime-autoloads)
(setq inferior-lisp-program "/usr/local/bin/sbcl")
(setq slime-contribs '(slime-fancy))
(add-hook 'lisp-mode-hook
  '(lambda ()
    (paredit-mode 1)
    (highlight-long-lines)
    (define-key lisp-mode-map (kbd "C-o j") 'slime)
    (define-key lisp-mode-map (kbd "s-i")
      'slime-eval-last-expression))))
```

## 20 Org Mode

General setup:

```
(require 'org)
(require 'ob-clojure)
```

Show source code highlighting in code blocks:

```
(setq org-src-fontify-natively t)
```

Allow alphabetical plain lists (a., A., a), A)).

```
(setq org-list-allow-alphabetical t)
```

Put clock in/out timestamps into drawer, so they stay hidden when expanding items.

```
(setq org-clock-into-drawer t)
```

Set Clojure backend for literate programming.

```
(setq org-babel-clojure-backend 'cider)
```

Don't ask for confirmation before evaluating code in these languages (**use at your own risk**):

```
(defun my-org-confirm-babel-evaluate (lang body)
  (and
    (not (string= lang "lisp"))
    (not (string= lang "emacs-lisp"))
    (not (string= lang "clojure"))))
(setq org-confirm-babel-evaluate 'my-org-confirm-babel-evaluate)
```

Clock in/out based on TODO state changes<sup>6</sup>.

```
(eval-after-load 'org
  '(progn
    (defun wicked/org-clock-in-if-starting ()
      "Clock in when the task is marked STARTED."
      (when (and (string= org-state "STARTED")
        (not (string= org-last-state org-state)))
        (org-clock-in)))
    (add-hook 'org-after-todo-state-change-hook
      'wicked/org-clock-in-if-starting)
    (defadvice org-clock-in (after wicked activate)
      "Set this task's status to 'STARTED'."
      (org-todo "STARTED"))
    (defun wicked/org-clock-out-if-waiting ()
      "Clock out when the task is marked WAITING."
      (when (and (string= org-state "WAITING")
        (equal (marker-buffer org-clock-marker) (current-buffer))
        (< (point) org-clock-marker)
        (> (save-excursion (outline-next-heading) (point))
          org-clock-marker)
        (not (string= org-last-state org-state)))
        (org-clock-out)))
    (add-hook 'org-after-todo-state-change-hook
      'wicked/org-clock-out-if-waiting)))
```

Log when an item goes to DONE state:

```
(setq org-log-done t)
```

Refile things sensibly based on where they occur in original outline:

```
(setq org-refile-targets (quote ((nil :maxlevel . 10)
  (org-agenda-files :maxlevel . 10))))
(setq org-refile-use-outline-path t)
(setq org-outline-path-complete-in-steps nil)
(setq org-refile-allow-creating-parent-nodes (quote confirm))
```

---

<sup>6</sup>From <http://sachachua.com/blog/2007/12/clocking-time-with-emacs-org/>

GTD-style TODO states:

```
(setq org-todo-keywords
  '((sequence "TODO" "STARTED" "WAITING" "SOMEDAY" "DONE")))
```

Where to find agenda files:

```
(setq org-agenda-files '("~/Dropbox/org"))
```

Quickly launch agenda:

```
(define-key global-map "\C-ca" 'org-agenda)
```

Use Org's capture system:

```
(setq org-default-notes-file "~/Dropbox/org/toplevel.org")
(define-key global-map "\C-cc" 'org-capture)
```

Export " as “ and “:

```
(setq org-export-with-smart-quotes t)
```

## 21 Blogging

```
(setq org-sitemap-link-format
"@@html:<span class='sm-d'>%d</span> &nbsp; &nbsp; &nbsp; <span class='sm-t'>%t</span>@@")
org-sitemap-html-preamble
"<link rel=\"stylesheet\" href=\"../css/style.css\" type=\"text/css\" />
<link rel=\"stylesheet\" href=\"http://code.jquery.com/ui/1.10.3/themes/smoothness/jquery-ui.css\"
<link rel=\"stylesheet\" href=\"https://cdn.jsdelivr.net/bootstrap/3.3.0/css/bootstrap.min.css\">
<link rel=\"stylesheet\" href=\"https://cdn.jsdelivr.net/bootstrap/3.3.0/css/bootstrap-theme.min.c
<script src=\"http://code.jquery.com/jquery-1.9.1.js\"></script>
<script src=\"http://code.jquery.com/ui/1.10.3/jquery-ui.js\"></script>
<script src=\"https://cdn.jsdelivr.net/bootstrap/3.3.0/js/bootstrap.min.js\"></script>
<link rel=\"shortcut icon\" href=\"../images/favicon.gif\">
<div id=\"my-org-div-home-and-up\">
  <a href=\"index.html\">home </a>
  <span class=\"muted\">...</span>
  <a href=\"sitemap.html\"> archive </a>
</div>"
org-sitemap-html-postamble
"<div id=\"disqus_thread\"></div>
<script type=\"text/javascript\">
  var disqus_shortcode = 'eigenhombrecom'; // required: replace example with your forum shortcode
  /* * * DON'T EDIT BELOW THIS LINE * * */
  (function() {
var dsq = document.createElement('script'); dsq.type = 'text/javascript'; dsq.async = true;
dsq.src = 'http://' + disqus_shortcode + '.disqus.com/embed.js';
(document.getElementsByTagName('head')[0] || document.getElementsByTagName('body')[0]).appendChild(
  })();
</script>
<noscript>Please enable JavaScript to view the <a href=\"http://disqus.com/?ref_noscript\">comments
<a href=\"http://disqus.com\" class=\"dsq-brlink\">blog comments powered by <span class=\"logo-disq
```

```

<script type="text/javascript">
var _gaq = _gaq || [];
_gaq.push(['_setAccount', 'UA-40279882-1']);
_gaq.push(['_trackPageview']);

(function() {
  var ga = document.createElement('script');
  ga.type = 'text/javascript';
  ga.async = true;
  ga.src = ('https:' == document.location.protocol ? 'https://ssl' : 'http://www') + '.google-anal
  var s = document.getElementsByTagName('script')[0]; s.parentNode.insertBefore(ga, s);
})();
</script>"

```

```

(setq org-publish-project-alist
'(("blog"
  :base-directory "~/Dropbox/org/blog/src"
  :html-extension "html"
  :htmlized-source t
  :exclude "^\\(style\\|theindex\\)"
  :base-extension "org"
  :publishing-directory "~/Dropbox/org/blog/html"
  :publishing-function (org-html-publish-to-html)
  :section-numbers nil
  :auto-sitemap t
  :sitemap-sort-files "chronologically"
  :sitemap-file-entry-format ,org-sitemap-link-format
  :html-link-up ""
  :html-link-home ""
  :sitemap-title "Things you can find here"
  :html-head-extra nil
  :html-preamble ,org-sitemap-html-preamble
  :html-postamble ,org-sitemap-html-postamble)))

```

Keyboard mappings to publish and to open local copy of new blog. Using `\C-oX` forces Org to (re-)publish even unmodified files.

```

(global-set-key "\C-ox" (lambda () (interactive) (org-publish-project "blog")))
(global-set-key "\C-oX" (lambda () (interactive) (org-publish-project "blog" t)))

(defun open-blog-index ()
  (interactive)
  (shell-command (concat "open file://" (expand-file-name "~/Dropbox/org/blog/html/index.html"))))

(global-set-key "\C-oZ" 'open-blog-index)

(defun open-blog-sitemap ()
  (interactive)
  (shell-command (concat "open file://" (expand-file-name "~/Dropbox/org/blog/html/vita.html"))))

(global-set-key "\C-oz" 'open-blog-sitemap)

```

I use this little bit of magic to reformat blog posts extracted from Blogger [/delete when not needed/].

```
(global-set-key "\C-oV" (lambda ()
  (interactive)
  (search-forward "# layout")
  (beginning-of-line)
  (set-mark-command nil)
  (search-forward "---")
  (comment-or-uncomment-region (region-beginning) (region-end))))
```

## 22 Tidying up

Be a nicely-behaved module or “feature”:

```
(provide 'init)
```