Georgia Seismic Design Data: Where It Came From and How to Redo It

A plain-English guide for anyone who needs to understand, check, or reproduce this dataset — no programming background required.

---

1. What this dataset is

This project fills in a table of earthquake design numbers for about 213,000 points spread evenly across the state of Georgia, roughly one point every 800 meters. The table follows the AASHTO (American Association of State Highway and Transportation Officials) 9th Edition bridge design standard. For each point, the table needs two kinds of numbers:

- **Design values** — the official shaking numbers an engineer plugs into a bridge design (As, Sd1, PGA, Ss, S1, Sds, and a design category letter).
- **The "characteristic earthquake"** — in plain terms, the single most representative earthquake (how big, and how far away) behind the shaking risk at that point. The table calls these "Modal Mw" (size) and "Modal R" (distance).

2. Where the numbers come from

Both kinds of numbers come from free, public tools run by the **US Geological Survey (USGS)**, the US government's earth-science agency. No number here was guessed or estimated by AI. Every number traces back to one of these two official USGS tools, running USGS's current national earthquake hazard model (the "2018 update", the standard one at the time this was built).

Tool	What it gives you	Website people can use by hand
AASHTO Design Maps	Design values (As, Sd1, PGA, Ss, S1, Sds, design category)	earthquake.usgs.gov/ws/building-codes
Hazard Disaggregation	The characteristic earthquake (Modal Mw and Modal R)	earthquake.usgs.gov/nshmp/hazard/disagg

3. The settings that were used

Every request to USGS used the same settings, so the whole table is consistent:

- **Hazard level:** a 1,033-year return period — the standard AASHTO bridge level, sometimes described as "about a 7% chance in 75 years."
- **What is measured:** PGA, "peak ground acceleration" — roughly, how hard the ground shakes.
- **Soil stiffness ("Vs30"):** each AASHTO Site Class stands for a different soil stiffness. The table below is what USGS uses for each letter; this project ran the stiffer-soil values (530, 260 and 150) plus 760, which doubles as the stiff end of Class B.

Site Class	A	B	C	D	E
Soil stiffness (Vs30, m/s)	1500	1080	530	260	150
Run in this project?	no (see Sec. 7)	partly (via 760)	yes	yes	yes

4. How the numbers were actually collected

The ordinary USGS website only answers one location at a time. This project needed answers for roughly 213,000 locations, times several soil classes. That is far too slow to do by hand. Luckily, both USGS tools also work as an “API”: a plain web address that hands back the numbers directly, instead of showing a page. A short program can send that same web address thousands of times in a row, automatically.

A program in this folder sent one such request per location and saved each answer. Here is what one request looks like. Paste it into a browser to see the real answer for that one spot (Atlanta, Site Class D):

```
https://earthquake.usgs.gov/ws/building-codes/aashto-2009/calculate?latitude=33.75&longitude=-84.39&siteClass=D
```

And the matching request for the characteristic earthquake (same spot, soil stiffness 260, 1,033-year level):

```
https://earthquake.usgs.gov/ws/nshmp/conus-2018.R1/dynamic/disagg/-84.39/33.75/260/1033?imt=PGA
```

5. A necessary shortcut, and its small tradeoff

The characteristic-earthquake tool is slow, several seconds per request, and must be asked once per soil class. Asking it directly at all 213,000 points, for every soil class, would have taken many days per class just waiting on that one tool. So the program took a shortcut: it asked the tool directly at a well-spread sample of points, then estimated the points in between from their nearest already-answered neighbors. Think of reading a value between two marked points on a graph. It only estimated where nearby points already agreed closely. Anywhere they did not agree, it asked more points nearby until they did.

To check this shortcut, the program re-asked USGS directly for 300 random estimated points per soil class, then compared the two answers. Across all four soil classes, 96% to 97% of those checks matched USGS's real answer closely (earthquake size within 0.1, distance within 5 km). Almost all the rest still named the right earthquake, just with the distance figure one step off. A small handful showed a real difference, right at a boundary where the governing earthquake switches from a nearby small one to a distant large one. The design-value numbers (As, Sd1, PGA, Ss, S1, Sds) never use this shortcut. The program asked for every one of the 213,000-plus points directly.

6. What is in this folder

File / folder	What it is
output/	The finished tables. See Section 8 for which file to use.
aashto_batch.py	Asks the AASHTO Design Maps tool for a list of points, one soil class at a time or several at once.
disagg_adaptive.py	Asks the Disaggregation tool for the characteristic earthquake, using the sampling shortcut from Se
fill_table.py	Combines the two tools' answers into one spreadsheet, in the original table's layout.
usgs_client.py	Shared plumbing: makes sure requests don't go to USGS faster than it allows, and automatically w
run_*.sh, watchdog*.sh	Convenience scripts that run the above in the right order for hours or days at a time without someo
test_disagg_adaptive.py	Automated checks confirming the shortcut in Section 5 behaves correctly.

7. Step by step: how to redo this in the future

Anyone with this folder and the two Python programs below, plus the Georgia coordinate list (a spreadsheet of longitude, latitude, county, and existing soil data — the same list this project started from), can redo any part of this or extend it to a soil class not yet run (Class A, soil stiffness 1500, or a full statewide Class B at 1080).

1. **Install Python 3** on the computer doing the work. No other setup is required; the scripts use only Python's built-in tools.
2. **Ask for the characteristic earthquake** for a soil class, for example Class A:

```
python3 disagg_adaptive.py your_coordinate_list.csv --out disagg_out_A --vs30 1500 --spot-check 300
```

3. **Ask for the design values** for the same soil class, for every point:

```
python3 aashto_batch.py your_coordinate_list.csv --out aashto_out_A --site-classes A
```

4. **Combine the two** into one finished spreadsheet:

```
python3 fill_table.py your_coordinate_list.csv --force-class A --trim-to-force-class --aashto aashto_out_A/aashto_values.csv --disagg disagg_out_A/disagg_grid.csv
```

Expect each soil class to take somewhere between several hours and about a day, because USGS limits how fast any one computer may ask it questions. The scripts already wait and retry on their own when that happens — it is normal to start a step and leave it running unattended, and it will pick back up on its own if it is ever interrupted, re-using what it already collected instead of starting over.

8. Which finished file to use

Inside `output/`, use the files named `..._forced_class_X_trimmed.csv` (X = C, D, or E). These are the clean, self-consistent tables. Every point in one of these files used that one soil class for both the design values and the characteristic earthquake, with no mixing. Hand one of these to an engineer. The earlier files named `..._filled.csv` and `..._own_class.csv` use each point's own real soil class for the design values, but one fixed soil stiffness (760) for the characteristic earthquake everywhere. Treat those as a quick first look, not a final answer, except where a point's real class is already close to 760.

Every number in this dataset can be independently re-checked at any time by typing the website addresses above (with different coordinates) directly into a web browser — no special access or account is needed; these are free public USGS tools.