USGS API Calls Used for the Georgia Seismic Design Table

All numbers in this dataset come from two free USGS web services. One call per point gets the design values; one call per point gets the characteristic earthquake (Modal Mw, Modal R). Substitute `LAT` / `LON` for the point's coordinates, `CLASS` for the site class letter (A–E), and `VS30` for that class's Vs30 (table below). Both use the 2018 national hazard model, PGA, and the 1,033-year (7%-in-75-year) return period, fixed in the calls themselves.

Design values (As, Sd1, PGA, Ss, S1, Sds, design category):

```
https://earthquake.usgs.gov/ws/building-codes/aashto-2009/calculate?latitude=LAT&longitu
↪ de=LON&siteClass=CLASS
```

Characteristic earthquake (Modal Mw, Modal R):

```
https://earthquake.usgs.gov/ws/nshmp/conus-2018.R1/dynamic/disagg/LON/LAT/VS30/1033?imt=
↪ PGA
```

Site Class	`VS30` (m/s)
A	1500
B	1080
C	530
D	260
E	150

Example, Atlanta (33.75, -84.39), Site Class D:

```
https://earthquake.usgs.gov/ws/building-codes/aashto-2009/calculate?latitude=33.75&longi
↪ tude=-84.39&siteClass=D
```

```
https://earthquake.usgs.gov/ws/nshmp/conus-2018.R1/dynamic/disagg/-84.39/33.75/260/1033?
↪ imt=PGA
```