CENTURION UNIVERSITY // CSE DEPARTMENT // DSA CAPSTONE SPECIFICATION

📘 The Trie & Inverted Index Search Engine // Comprehensive Presentation Explainer & Study Guide

This document is the **official, in-depth explanation manual** for the 6-slide PowerPoint presentation `Trie_Search_Engine_DSA_6Slides.pptx`.

It is designed to give you a complete, intuitive, and mathematically rigorous understanding of every slide, diagram, algorithm, and design choice in this Data Structures & Algorithms (DSA) project. Use this guide to study the core concepts, prepare for viva/interviews, and deliver an articulate presentation with confidence.

📑 Table of Contents

1. Executive Summary (The Big Picture in Plain English)
2. Slide-by-Slide Breakdown & Visual Guide
3. Slide 1: Title & Project Identity
4. Slide 2: The Problem: Why Traditional Search Fails
5. Slide 3: Component 1 — Prefix Trie (Instant Autocomplete)
6. Slide 4: Component 2 — Inverted Index (Fast Multi-Tag Filtering)
7. Slide 5: How It All Works Together (The Full Pipeline)
8. Slide 6: Results, Metrics & Key Takeaways
9. Deep-Dive: How the Two Data Structures Work Together
10. Algorithmic Complexity & Big-O Proofs
11. Codebase Architecture & File Mapping
12. Top 10 Viva & Interview Defense Questions with Bulletproof Answers

---

1. Executive Summary (The Big Picture in Plain English)

What is this project?

When you use modern operating systems (like macOS Spotlight or Windows PowerToys Run), you press a shortcut like `Cmd` + `K`, start typing, and instantaneous search suggestions appear on the screen **before your finger even lifts off the key**.

In standard web applications, developers usually take the easy route: - They either write a crude loop like `items.filter(item ⇒ item.name.includes(query))`, which lags and freezes the screen as datasets grow. - Or they pay for third-party cloud services like Algolia or Elasticsearch, which send your keystrokes over the internet, causing a noticeable 200ms–400ms delay, costing money, and completely failing if you are offline.

Our Project Solves This:
We engineered an **in-memory algorithmic search engine** written in vanilla JavaScript without any external

libraries. It combines two fundamental computer science data structures: 1. A **Prefix Trie** for instant $O(k)$ prefix autocomplete suggestions. 2. An **Inverted Index** for lightning-fast multi-tag and multi-term boolean filtering (AND / OR).

It is integrated live into **AceDevs** (the collective developer portfolio and 3D digital twin for **Arbaz Arshad** and **Devesh Das**), executing queries in **under 1.5 milliseconds** directly inside the browser's RAM while maintaining a silky-smooth 60 FPS WebGL 3D animation loop.

---

2. Slide-by-Slide Breakdown & Visual Guide

Slide 1: Title & Project Identity


🖼️ **What is on the slide?**

- **Top Badge**: `CENTURION UNIVERSITY // CSE DEPARTMENT // DSA CAPSTONE`
- **Main Heading**: **The Trie & Inverted Index Search Engine**
- **Subtitle**: Zero-latency in-memory prefix autocomplete and multi-tag discovery built for the AceDevs platform.
- **Presenter Card 1**: **Arbaz Arshad** `[DEV-01]` (Lead Architect, Game Systems & AI Engineer, `arbazarshad.com`, `github.com/arbazarshad7`).
- **Presenter Card 2**: **Devesh Das** `[DEV-02]` (CS & Physics Engineer, Game Mechanics & Engines, `mrdeveshdas.vercel.app`, `github.com/ninja27dev`).
- **Key Highlights Pill**: `< 1.5ms` Latency · `100%` Client-Side In-Memory · `0` NPM Search Dependencies · `100%` Offline Resilient.

💡 **How to explain this slide:**

> *"Good morning/afternoon, evaluators and peers. Today, we present our Data Structures and Algorithms Capstone Project: **The Trie & Inverted Index Search Engine**.*
> *My name is **Arbaz Arshad**, and with my co-developer **Devesh Das** from the Department of Computer Science and Engineering at Centurion University, we designed, implemented, and benchmarked an in-memory search engine that delivers zero-latency prefix autocompletion and multi-tag filtering without any third-party search libraries or remote cloud dependencies. This engine is not a toy simulation; it is deployed live inside our production platform, **AceDevs**."*

Slide 2: The Problem: Why Traditional Search Fails



🖼️ What is on the slide?

A high-contrast 3-column comparative diagram contrasting: 1. **Red Column (Naive Array Loops)**: Scanning with `filter()` and `includes()`. 2. **Amber Column (Cloud Search APIs)**: Remote services like Algolia, Elastic, or Firebase. 3. **Green Column (Our Solution)**: Client-side Trie + Inverted Index.

💡 Deep Technical Explanation:

- **The Failure of Linear Array Scans ($O(N \cdot L)$)**:
- If you have N records, each with text of length L, checking if `item.title.includes(query)` checks every character sequentially.
- To match multiple tags (e.g., `#unity` AND `#csharp` AND `#multiplayer`), you have nested loops: $O(N \cdot T)$.
- In JavaScript, the UI and JavaScript run on a **single thread**. When this loop executes, the browser cannot render. In our AceDevs app, we have an interactive Three.js 3D WebGL scene running at 60 FPS (which requires rendering a frame every 16.6 milliseconds). A linear scan that takes 30ms causes visible stutter ("jank").
- **The Failure of Remote Cloud APIs**:
- Even if a cloud search engine returns in 10ms, physical network roundtrips over cellular/Wi-Fi take **200ms to 400ms**.
- Typing feels sluggish; autocomplete cannot keep up with human typing speed (which is ~50ms per keypress).
- If the user is on an airplane, underground, or has spotty internet, search fails completely.

💡 How to explain this slide:

> *"To understand why we built this, let's look at how modern web search typically fails.*
> *If you use standard JavaScript `Array.filter()`, you are doing an $O(N \cdot L)$ brute-force linear scan. In an application with interactive 3D WebGL graphics like AceDevs, running linear loops on the main JavaScript thread causes dropped frames and UI stutter.*
> *The standard industry workaround is to offload search to cloud APIs like Algolia or Elasticsearch. But that introduces a physical network roundtrip of 200 to 400 milliseconds per keystroke, incurs monthly billing costs, and completely breaks if the user goes offline.*
> *Our approach solves both extremes: by pairing a **Prefix Trie** with an **Inverted Index** directly inside the browser's heap memory, we achieve **sub-1.5 millisecond** search speeds with zero network latency, 100% offline uptime, and zero external npm dependencies."*

Slide 3: Component 1 — Prefix Trie (Instant Autocomplete)

🖼️ What is on the slide?

- **Left Side**: A clean, visual **Trie Tree Diagram** showing the path of characters: `(Root) / \ [g] [u] | | [a] [n] | | [m] ◄── User types "gam" | | [e] [i] / \ | [s] [y] [t] | | | "games" "game" [y] ──► "unity"`
- **Right Side**: 3 Simple Explainer Pillars:
- **Character-by-Character Branching**: Words are stored as letter transitions down a tree.
- $O(k)$ **Bounded Traversal Speed**: Search time depends strictly on the length of the typed word k (e.g. 3 letters), NOT on the number of items in the database N!

- **Instant Bounded Autocomplete**: Reaching node `m` immediately unrolls downstream words (`game` , `games`) via a bounded Depth-First Search (DFS) in < 0.8 ms.

💡 **Deep Technical Explanation:**

- **What is a Trie?**
- A Trie (from re**TRIE**val) is an n-ary tree where each node represents a single character.
- The path from the root down to a node spells out a word prefix.
- Nodes have a boolean flag `isWord = true` if that node represents the completion of a valid indexed token.
- Nodes store an associative Set of document IDs (`entityIds: Set`) that match that word, plus a `frequency` weight.
- **Why is it $O(k)$ instead of $O(N)$?**
- Suppose your portfolio has 1,000,000 repositories and articles.
- If a user types `"gam"` , a linear search scans all 1,000,000 records.
- In a Trie, the algorithm starts at the root:
  - Step 1: Follow pointer to `'g'`
  - Step 2: Follow pointer to `'a'`
  - Step 3: Follow pointer to `'m'`
- It takes exactly **3 operations** ($k = 3$), regardless of whether there are 10 items or 10 million items in the database! It never even looks at words starting with other letters.
- **Memory Optimization (Map Branching vs Fixed Arrays)**:
- Standard textbook Tries use a fixed array `new TrieNode[26]` for lowercase English. But this wastes 90% of heap memory on null pointers and cannot handle digits or punctuation.
- We engineered our nodes using ES6 `Map<char, TrieNode>()` . Nodes only instantiate memory for characters that actually exist, saving **72% of heap space**.

💡 **How to explain this slide:**

> *"Now let's examine our first core data structure: the **Prefix Trie** (`PrefixTrie.js`).*
> *As you can see in the diagram, words are stored character-by-character along directed branches. When a user types the letters `g-a-m` , the algorithm takes exactly three steps down the tree: Root to `g` , to `a` , to `m` .*
> *This gives us an asymptotic time complexity of $O(k)$, where k is the length of the query token. Notice what is missing from that formula: N, the size of the database! Whether we have 50 projects or 50,000 projects, looking up a 3-letter prefix takes the exact same tiny fraction of a millisecond.*
> *Once at node `m` , a bounded Depth-First Search (DFS) collects the top 8 completion suggestions—such as 'game' and 'games'—in less than 0.8 milliseconds."*

Slide 4: Component 2 — Inverted Index (Fast Multi-Tag Filtering)

🖼️ **What is on the slide?**

- **Left Side**: A clean visual **Set Intersection Diagram**:
- Box A: `TAG: "game"` ➔ `{ Arbaz Arshad [DEV-01], Devesh Das [DEV-02], Blackjacker }`
- Intersection Operator: `∩ (AND)`

- Box B: `TAG: "physics"` ➔ `{ Devesh Das [DEV-02], White-Ninja, Mini-Car-Sim }`
- Result Box: `✓ MATCH FOUND: DEVESH DAS [DEV-02]` (computed in 0.4 ms).
- **Right Side**: 3 Simple Insights:
- **Reverse Mapping Dictionary**: Maps words/tags directly to document IDs rather than scanning documents for words.
- $O(\min(|P_1|, |P_2|))$ **Set Intersect**: Finding overlapping tags only requires iterating through the smallest set, instantly pruning 95% of non-matching records.
- **Zero Scanning Overhead**: Constant dictionary lookup time $O(1)$ without nested loops.

💡 **Deep Technical Explanation:**

- **What is an Inverted Index?**
- In a standard index, you look at a Document to see what words it contains.
- In an **Inverted** Index, you look at a Word or Tag to see what Documents contain it:


$$\text{Index} : \text{Term} \longrightarrow \text{DocID}_1, \text{DocID}_2, \ldots, \text{DocID}_n$$

- The array or set of Document IDs associated with a term is called a **Posting List**.
- **The Mathematics of Set Conjunction (AND Intersection)**:
- Suppose a user filters by two tags: `"game"` and `"physics"`.
- Let P_{game} have size 100, and P_{physics} have size 3.
- A naive algorithm compares all elements: $100 \times 3 = 300$ checks.
- Our engine sorts posting lists by cardinality, selects the smallest set (P_{physics} with 3 items), and checks if each of those 3 IDs exists in the larger Hash Set ($O(1)$ lookup per check).
- Total time complexity: $O(\min(|P_1|, |P_2|))$. The remaining 97 non-matching documents are pruned instantly without ever being evaluated!

💡 **How to explain this slide:**

> *"While the Trie excels at autocompleting single words, modern users search using combinations of tags—for example, looking for developers or projects that match both **'game'** and **'physics'**.*
> *This is handled by our second data structure: the **Inverted Index** (`InvertedIndex.js`).*
> *As illustrated on the left, an Inverted Index inverts the relationship between documents and terms. It maintains a dictionary where every tag points directly to a pre-computed Set of matching entity IDs—called a Posting List.*
> *When a user queries multiple tags, the algorithm performs a set intersection: $P_1 \cap P_2$. By iterating through the smallest posting list as the pivot, it verifies membership in $O(\min(|P_1|, |P_2|))$ time. In this example, it finds that **Devesh Das [DEV-02]** is the exact intersection, returning the result in just 0.4 milliseconds."*

Slide 5: How It All Works Together (The Full Pipeline)



🖼️ What is on the slide?

- **Top Flowchart**: 4 connected step boxes with right-pointing transition arrows:
- **Step 1: User Keystroke** — User presses `Cmd+K` and types `"uni phy"`.
- **Step 2: Prefix Trie** — Autocompletes `"uni"` ➔ `"unity"` in < 0.4 ms.
- **Step 3: Inverted Index** — Intersects posting lists `#unity` ∩ `#physics`.
- **Step 4: Instant Display** — Ranks match (Devesh Das `[DEV-02]`), updates UI, and triggers 1200Hz sound chirp.
- **Bottom Banner**: **Real-Time Production Integration in AceDevs**:
- Global `Cmd+K` / `Ctrl+K` command palette overlay.
- Live Incremental Re-Indexing in < 3 ms when articles are posted in the admin cockpit.
- Web Audio API procedural synthesis on every keystroke.

💡 Deep Technical Explanation:

- `searchEngine.js` **Unified Orchestrator**:
- The orchestrator maintains instances of both `PrefixTrie` and `InvertedIndex`.
- When the user types a query string, the orchestrator:
  1. Normalizes the string (trims whitespace, converts to lowercase, splits into tokens).
  2. Passes the last token to `PrefixTrie.startsWith()` to generate live autocomplete chips.
  3. Passes all tokens to `InvertedIndex.search()` to execute multi-tag boolean intersections.
  4. Merges suggestions and document hits, removing duplicates by document ID.
  5. Computes a multi-factor relevance score:
  6. Exact Title Match: $+50$ pts
  7. Title Prefix Match: $+30$ pts
  8. Matching Topic/Tag: $+25$ pts
  9. Body/Description Match: $+10$ pts
  10. Historic Trie Frequency: $+1$ to $+5$ pts
- **Live Incremental Re-Indexing**:
- Many search engines require rebuilding the entire index when new data arrives.
- When Arbaz or Devesh writes a new article in the AceDevs Admin Dashboard, `blogService` notifies the search engine.
- Because `TrieNode.entityIds` and Inverted Index posting lists are implemented as `Set` objects, adding or removing an entity is an $O(k)$ operation taking less than 3 milliseconds without freezing the screen.

💡 **How to explain this slide:**

> *"Slide 5 shows how both data structures collaborate inside `searchEngine.js` during a real user interaction in AceDevs.*
> *Let's trace a user typing **'uni phy'** in our Command Palette: - In **Step 1**, the keystroke enters the engine without debouncing delay. - In **Step 2**, the Prefix Trie expands the prefix 'uni' into 'unity' in less than 0.4 milliseconds. - In **Step 3**, the Inverted Index takes those terms and performs a boolean set intersection: `#unity` ∩ `#physics`. - In **Step 4**, the orchestrator scores the results, identifies **Devesh Das [DEV-02]** as the top ranked match, renders the card, and fires a subtle 1200Hz synthetic micro-chirp via the Web Audio API.*
> *Furthermore, the engine supports **live incremental re-indexing**. When a new technical article is published from our Admin panel, the index updates in under 3 milliseconds without requiring a full rebuild or page refresh."*

Slide 6: Results, Metrics & Key Takeaways

🖼️ **What is on the slide?**

- **4 Big Metric Badges**:
- ⚡ `< 1.5 ms` — Total Search Latency (instantaneous response)
- 🔒 `0 ms` — Network Delay (100% in-memory)
- 🌐 `100%` — Offline Uptime (never fails without Wi-Fi)
- 💾 `72%` — RAM Saved (via dynamic hash map branching)
- **Bottom Left Card**: **Project Summary**:
- Algorithmic synergy between Trie and Inverted Index.
- Fluid 60 FPS experience with zero UI thread blocking.
- Battle-tested in the production AceDevs portfolio.
- **Bottom Right Card**: **Project Access & Q&A**:
- Co-founders: Arbaz Arshad (`arbazarshad.com`) & Devesh Das (`mrdeveshdas.vercel.app`).
- Code repository: `github.com/arbazarshad7/AceDevs` .
- Open for questions and discussion.

💡 **How to explain this slide:**

> *"To conclude, here are the empirical results from our Chrome V8 benchmarks:*
> 1. ***Total Search Latency is under 1.5 milliseconds**—well below the 16.6ms threshold required to keep our 3D WebGL scene running at a flawless 60 FPS.*
> 2. ***Network Delay is exactly 0 milliseconds**, because search executes entirely inside client RAM.*
> 3. ***Offline Uptime is 100%**—meaning the portfolio can be demonstrated anywhere, even in airplane mode.*
> 4. ***Memory overhead is reduced by 72%** thanks to dynamic Map branching instead of static 26-pointer arrays.*
>
> *This project proves that thoughtful application of classical computer science data structures can completely eliminate the need for expensive, high-latency cloud search services in modern single-page applications.*
> *Thank you for your time. Devesh and I are now ready to answer any questions."*

---

3. Deep-Dive: How the Two Data Structures Work Together

To understand the core innovation of this project, consider why neither data structure is sufficient on its own:

Capability	Prefix Trie Alone	Inverted Index Alone	Our Combined Engine
Instant Prefix Autocomplete (e.g. `"gam"` ➔ `"games"`)	**Excellent ($O(k)$)**	Poor ($O(N)$ scanning terms)	**Excellent ($O(k)$)**
Multi-Tag Conjunction (e.g. `#game` AND `#physics`)	Poor (Cannot intersect paths)	**Excellent ($O(\min \lvert P_i \rvert)$)**	**Excellent ($O(\min \lvert P_i \rvert)$)**
Typo / Substring Search	Limited	Moderate	**Combined Ranking**
Memory Efficiency	High (Prefix compression)	High (Set posting lists)	**Optimal (Dynamic Maps)**

The Division of Labor:

1. **The Trie is the Frontend of Search**: It answers the question, *"What words or tags could the user be typing right now?"*
2. **The Inverted Index is the Backend of Search**: It answers the question, *"Now that we know the words/tags, which exact projects or developers possess all of them?"*

---

4. Algorithmic Complexity & Big-O Proofs

1. Prefix Trie Complexity

Let: - k = length of the search token (number of characters, typically $3 \leq k \leq 12$) - m = number of suggestions collected (bounded at $m \leq 8$) - N = total number of indexed words - Σ = alphabet size

Exact Match / Insert: $\mathcal{O}(k)$

- **Proof**: Inserting or looking up a word of length k requires traversing exactly k character pointers from the root. Each character step uses an ES6 `Map.get()` or `Map.set()`, which operates in $\mathcal{O}(1)$ amortized time.

$$\text{Time} = \sum_{i=1}^{k} \mathcal{O}(1) = \mathcal{O}(k)$$

Prefix Autocomplete: $\mathcal{O}(k + m)$

- **Proof**: Traversal to the prefix node takes $\mathcal{O}(k)$ steps. From that node, a depth-first search explores children until m terminal words are collected. Since m is capped at 8:

$$\text{Time} = \mathcal{O}(k) + \mathcal{O}(m) = \mathcal{O}(k + 8) \equiv \mathcal{O}(k)$$

---

2. Inverted Index Complexity

Let: - $P_1, P_2, \ldots, P_n$ = Posting lists for each query term - $|P_{\min}|$ = cardinality of the smallest posting list

Term Lookup: $\mathcal{O}(1)$

- **Proof**: Terms are stored as keys in an ES6 `Map<string, Set<DocID>>`. Retrieving the posting list is a hash table lookup in $\mathcal{O}(1)$ average time.

Set Conjunction (AND): $\mathcal{O}(\min(|P_1|, |P_2|))$

- **Proof**: To compute $P_1 \cap P_2$:
- Identify the smaller set, say P_1 where $|P_1| \leq |P_2|$.
- For each element $x \in P_1$, check whether $x \in P_2$ using `Set.has()`, which is $\mathcal{O}(1)$.
- Total operations: $|P_1| \times \mathcal{O}(1) = \mathcal{O}(|P_1|) = \mathcal{O}(\min(|P_1|, |P_2|))$.

---

5. Codebase Architecture & File Mapping

You can reference the exact source code files directly in the AceDevs repository:

File Path	Primary Class / Function	Responsibility
`src/services/search/PrefixTrie.js`	`TrieNode`, `PrefixTrie`	Character tree node branching, `insert()`, `startsWith()`, `collectWords()` DFS.
`src/services/search/InvertedIndex.js`	`InvertedIndex`	Tokenization, posting lists `Map<term, Set<id>>`, boolean `intersect()` and `union()`.
`src/services/search/searchEngine.js`	`SearchEngine`	Ingestion of developers, repos, articles; unified query dispatch, relevance scoring.
`src/components/search/SearchModal.jsx`	`SearchModal`	The HUD UI overlay triggered by `Cmd+K`, keyboard navigation, category pills.

6. Top 10 Viva & Interview Defense Questions with Bulletproof Answers

Here are the exact questions professors, evaluators, or senior engineers will ask, along with the precise, high-scoring answers you should give:

Q1: "Why did you use both a Trie AND an Inverted Index? Wouldn't an Inverted Index alone be enough?"

> ***Answer**:*
> *"An Inverted Index is fantastic at exact keyword lookup and boolean set intersections (AND / OR). However, an Inverted Index cannot perform prefix autocomplete efficiently. If a user types just 'gam', an Inverted Index would have to scan every term in its dictionary to see which terms start with 'gam'—which devolves into a linear $O(N)$ scan.*
> *The Trie solves this by finding all words starting with 'gam' in $O(k)$ time. Once the Trie gives us the completed terms, the Inverted Index immediately resolves their document posting lists. They solve two different halves of the search problem."*

Q2: "In textbook Tries, children are stored in an array of size 26. Why did you use an ES6 `Map` instead?"

> ***Answer**:*
> *"A fixed 26-pointer array has three major flaws: 1. **Memory Waste**: Most characters in real vocabularies never branch. 90% of the pointers remain null, creating enormous memory overhead. 2. **Character Set Limitations**: An array of 26 only supports English letters (a–z). It cannot handle numbers (like `3D` or `DEV-01`), hyphens, or punctuation. 3. **Dynamic Memory in V8**: By using an ES6 `Map<char, TrieNode>`, child nodes are allocated lazily only when a character actually appears. This reduced our heap memory allocation by **72%** while retaining $\mathcal{O}(1)$ amortized lookup time."*

Q3: "What happens if a user makes a typo, like typing 'unty' instead of 'unity'?"

> ***Answer**:*
> *"In the current implementation, if the Trie cannot traverse a branch, it terminates and the Inverted Index falls back to an OR union across any matching tokens. As outlined in our future scope, the next algorithmic enhancement is integrating a **Levenshtein Automaton** onto the Trie, which allows the traversal to explore branches within an edit distance of 1 or 2 characters to provide 'Did you mean?' suggestions."*

Q4: "How does your engine handle upper-case vs lower-case letters and punctuation?"

> ***Answer**:*
> *"We implement a strict **normalization pipeline** before any string enters the Trie or Inverted Index. The string is trimmed, converted to lowercase using `.toLowerCase()`, and stripped of non-alphanumeric punctuation. This guarantees that whether a user types 'Unity', 'UNITY', or 'unity', they all map to the exact same tree branch."*

Q5: "How does your engine update when a user adds or edits an article in real time?"

> ***Answer**:*
> *"We implemented **live incremental re-indexing** rather than a full index rebuild. When `blogService` saves an article, it passes the updated article list to `searchEngine.indexBlogPosts()`. Because our Trie nodes and posting lists store document references as `Set` objects, inserting or deleting an entity operates in $O(k)$ time. The entire update completes in **under 3 milliseconds**, without freezing the 60 FPS animation loop or requiring a page reload."*

Q6: "How does this engine prevent blocking the browser's single-threaded event loop?"

> ***Answer**:*
> *"Because our total query execution time is strictly under 1.5 milliseconds, it easily fits within the 16.6ms frame budget of modern 60 Hz displays. Furthermore, for future expansion into 100,000+ documents, we have architected the Inverted Index intersection routines so they can be offloaded directly into a **Web Worker** running on a separate background CPU thread."*

Q7: "How is relevance scoring determined? How do you decide which result appears first?"

> ***Answer**:*
> *"We use a multi-factor scoring function: - Exact Title Match: $+50$ points - Title Prefix Match: $+30$ points - Exact Topic/Tag Match: $+25$ points per tag - Description Body Match: $+10$ points - Historic Trie Frequency: $+1$ to $+5$ points based on how often that token is queried. The results are then sorted in descending order by total score."*

Q8: "How would this scale if the dataset grew to 1 million documents?"

> ***Answer**:*
> *"At 1 million documents, storing full metadata objects in memory would consume too much RAM (~500MB). To scale to 1 million records: 1. The Trie and Inverted Index would store only 32-bit integer document IDs (consuming ~8MB of RAM). 2. Document metadata would be stored in browser `IndexedDB` or a local SQLite WASM database. 3. Search intersections would run in a Web Worker, fetching only the top 10 matching document bodies on demand."*

Q9: "Why didn't you use standard binary search on a sorted array of words?"

> ***Answer***:
> *"Binary search on a sorted array can find a word in $\mathcal{O}(\log N)$ time, but it has severe limitations: 1.* ***Dynamic Mutations****: Inserting a new word into a sorted array requires shifting elements, which is an expensive $\mathcal{O}(N)$ operation. 2.* ***Multi-Tag Intersections****: A sorted array cannot perform set intersections across multiple tags without sorting and merging multiple lists. In contrast, our Trie inserts dynamically in $\mathcal{O}(k)$, and the Inverted Index intersects tags in $\mathcal{O}(\min(|P_1|, |P_2|))$."*

Q10: "What is the biggest engineering lesson you learned from building this project?"

> ***Answer***:
> *"The biggest takeaway is that modern web development often defaults to SaaS cloud APIs or heavy npm libraries when classical computer science data structures are far more efficient, resilient, and elegant. By pairing a Prefix Trie with an Inverted Index, we eliminated 300ms of network latency, made the app work 100% offline, and maintained a flawless 60 FPS user experience with zero third-party dependencies."*