

# Altair Exercises

This notebook will explore multiple different visualizations in Altair.

---

## Part 7

The following exercise is based on the show [The Simpsons](https://en.wikipedia.org/wiki/The_Simpsons) ([https://en.wikipedia.org/wiki/The\\_Simpsons](https://en.wikipedia.org/wiki/The_Simpsons)), and will be analyzing key quotes from the history of the Simpsons as a network problem.

We will be leveraging an extracted dataset, [quote data from the wikiquotes project](https://en.wikiquote.org/wiki/The_Simpsons) ([https://en.wikiquote.org/wiki/The\\_Simpsons](https://en.wikiquote.org/wiki/The_Simpsons)). For each season, we look at each episode. For each episode, we identify the quotes recorded in wikiquotes.

While some quotes are "one-liners" by a single character:

- **Homer:** Aww, it makes no sense; I haven't changed since high school and all of a sudden I'm uncool.

We are interested in interactions between characters. For example:

- **Homer:** Doughnut?
- **Lisa:** No, thanks. Do you have any fruit?
- **Homer:** This has purple stuff inside. Purple is a fruit.

These multi-character quotes will become the "edges" in our network, where appropriate. We're going to start with a simpler analysis of the hierarchical data in this database.

```
In [1]: # !pip install nx_altair
        # !pip install squarify
```

```
In [2]: import pandas as pd
import json
import networkx as nx
import nx_altair as nxa
import json
import squarify
import altair as alt
import numpy as np
import matplotlib
from sklearn.cluster import AgglomerativeClustering
from networkx.algorithms.community import *
from scipy.cluster.hierarchy import dendrogram, leaves_list
from scipy.cluster.hierarchy import ClusterWarning
from warnings import simplefilter
simplefilter("ignore", ClusterWarning)
```

```
In [3]: # enable correct rendering (unnecessary in later versions of Altair)
```

```
alt.renderers.enable('default')

# uses intermediate json files to speed things up
alt.data_transformers.enable('json')
```

Out[3]: DataTransformerRegistry.enable('json')

### Hierarchical representation of Quote Database

We have data for multiple seasons, and for each season, we have multiple episodes. For each episode, we have multiple characters who have participated in funny/memorable scenes. Our goal is to have a visualization that allows us to compare which seasons/episodes/characters had the most quoted conversations. The questions we wish to be able to answer with the visualization are:

- Does a certain character have many conversations in one episode, and fewer in others?
- Were there any outlier episodes with lots of conversations?
- Was there a season with many conversations?

There are 5076 conversations in our dataset.

```
In [4]: with open('./assets/simpsonshier.jsonl') as json_file:
        allseasons = json.load(json_file)
```

```
In [5]: # this variable is a massive JSON object with a hierarchy of seasons
# hierarchy is a dictionary which has an id, a type (one of 'season',
# label (episodes had names as well as numerical ids), the value (the
# list of nodes that sit underneath)

allseasons

# for example, we can find season 2's quote quote:
season2 = allseasons[1]
print("season ", season2['id'], "had", season2['value'], "quotes")

# for the first episode of season 1 we see the following
season2e1 = season2['children'][0]
print(season2e1)

# you'll see that this episode was called "Bart Gets and F" and it had
# Bart was responsible for 2 of these

season s02 had 124 quotes
{'id': 's02e14', 'type': 'episode', 'label': 'Bart Gets an F', 'value': 7, 'children': [{'id': 'Bart', 'type': 'character', 'value': 2}, {'id': 'Mrs. Krabappel', 'type': 'character', 'value': 1}, {'id': 'Martin', 'type': 'character', 'value': 1}, {'id': 'Otto', 'type': 'character', 'value': 1}, {'id': 'Sherri', 'type': 'character', 'value': 1}, {'id': 'Terri', 'type': 'character', 'value': 1}]}
```

There are two main ways to display hierarchies. Node link diagrams, and space-filling versions such as TreeMaps. For this exercise we will use TreeMaps.

Unfortunately, Altair doesn't have a treemap layout built in. We'll be using the [squarify](https://github.com/laserson/squarify) (<https://github.com/laserson/squarify>) library to generate the coordinates. Squarify works by generating one level of the hierarchy at a time. So we need a function that lays out the seasons, and then for each episode re-runs squarify but restricts it to the space allocated to the season. After that we re-run squarify to plot the position of each character in that

episode.

```
In [6]: def rectangleIter(data,width,height,xof=0,yof=0,frame=None,level=-1,parentid=None):
# data: hierarchical structured data
# width: width we can work in
# height: height we can work in
# xof: x offset
# yof: y offset
# frame: the dataframe to add the data to, if None, we create one
# the level of the treemap (will default to 0 on first run)
# parentid: a string representing the parent of this node
# returns dataframe of all the rectangles

if (frame is None):
    frame = pd.DataFrame()
level = level + 1
values = []
children = []
for parent in data:
    values.append(parent['value'])
    if ('children' in parent):
        children.append(parent['children'])
    else:
        children.append([])

# normalize
values = squarify.normalize_sizes(values, width, height)

# generate the
padded_rects = squarify.padded_squarify(values, xof, yof, width, height)

i = 0
for rect in padded_rects:
    # adjust the padding and copy the useful pieces of data over
    parent = data[i]
    rect['width'] = rect['dx']
    rect['height'] = rect['dy']
    del rect['dx']
    del rect['dy']
    rect['x2'] = rect['x'] + rect['width'] - 2
    rect['y2'] = rect['y'] + rect['height'] - 2
    rect['x'] = rect['x'] + 2
    rect['y'] = rect['y'] + 2
    rect['width'] = rect['x2'] - rect['x']
    rect['height'] = rect['y2'] - rect['y']
    rect['id'] = parent['id']
    rect['type'] = parent['type']
    rect['value'] = parent['value']
    rect['level'] = level
    if 'label' in parent:
        rect['label'] = parent['label']
    else:
        rect['label'] = parent['id']
    rect['parentid'] = parentid
    frame = frame.append(rect,ignore_index=True)

    # iterate
    frame = rectangleIter(children[i],rect['width'],rect['height'],frame=frame,level=level,parentid=parentid)

    i = i + 1
return(frame)
```

To keep the chart manageable and readable, we will work with a sample of the first 6 seasons.

```
In [7]: shortseason = allseasons[0:6] # let's grab the first 6 seasons
rect_table = rectangleIter(shortseason,800,800) # and run them through
```

```
In [8]: # let's look at what's inside
rect_table.sample(5)
```

Out[8]:

	height	id	label	level	parentid	type	value	width	
140	12.873734	Apu	Apu	2.0	→ s02 → Homer vs. Lisa and the 8th Commandment	character	1.0	15.049490	114.3239
355	14.949838	Milhouse	Milhouse	2.0	→ s04 → Kamp Krusty	character	1.0	15.148526	293.9674
851	19.414401	Sam	Sam	2.0	→ s06 → Fear of Flying (The Simpsons)	character	1.0	12.663221	434.3848
194	21.882184	Homer	Homer	2.0	→ s02 → Blood Feud (The Simpsons)	character	2.0	24.045185	195.5262
117	18.337761	Audience	Audience	2.0	→ s02 → Itchy & Scratchy & Marge	character	1.0	11.475000	9.0000

Now let's make a TreeMap.

```
In [9]: def staticTreemap(inputFrame):
# input inputFrame the rectangles frame as described above
# return a static Altair treemap visualization

lvl_0 = inputFrame[inputFrame['level'] == 0.0]
level_0 = alt.Chart(lvl_0).mark_rect(color="#000000").encode(x=alt.X('x:Q', axis=0), y=alt.Y('y:Q', axis=0))

lvl_1 = inputFrame[inputFrame['level'] == 1.0]
level_1 = alt.Chart(lvl_1).mark_rect(color="808080").encode(x=alt.X('x:Q', axis=0), y=alt.Y('y:Q', axis=0))


lvl_2 = inputFrame[inputFrame['level'] == 2.0]
level_2 = alt.Chart(lvl_2).mark_rect().encode(x=alt.X('x:Q', axis=0), y=alt.Y('y:Q', axis=0))


final = (level_0 + level_1 + level_2).properties(
    width=800,
    height=800
)

return(final)
```

```
In [10]: staticTreemap(rect_table)
```

Out[10]:





That doesn't do much for us aside from show some relative values. Let's make this interactive so that we can better understand what we are looking at.

```
In [11]: def interactiveTreemap(inputFrame):
# input inputFrame the rectangles frame as described above
# return a static Altair treemap visualization

label_select = alt.selection_single(empty='all', fields=['id'])
colorCondition2 = alt.condition(label_select, "id:N", alt.value('lig

lvl_0 = inputFrame[inputFrame['level'] == 0.0]
level_0 = alt.Chart(lvl_0).mark_rect(color="#000000").encode(x=alt.
x2='>
y=alt
y2='y

lvl_1 = inputFrame[inputFrame['level'] == 1.0]
level_1 = alt.Chart(lvl_1).mark_rect(color="808080").encode(x=alt.
x2='x2
y=alt.
y2='y2

lvl_2 = inputFrame[inputFrame['level'] == 2.0]
level_2 = alt.Chart(lvl_2).mark_rect().encode(x=alt.X('x:Q',axis=M
x2='x2:Q',
y=alt.Y('y:Q',axis=M
y2='y2:Q',
color=alt.Color("id:
tooltip=['parentid:M

base = (level_0 + level_1).properties(
width=800,
height=800
)
```

```

interactive_lvl2 = level_2.add_selection(
    label_select
).encode(
    color=colorCondition2
)

i_treemap = (base + interactive_lvl2)

return i_treemap

```

In [12]: interactiveTreemap(rect\_table)

Out[12]:



Now, you should be able to scroll over to see id's, and if you click to select, you can compare character-by-character, episode-over-episode.

### Network Analysis for Conversational Quotes

For the next graphic, we will look more closely at conversation networks. Each quotable conversation can be modeled as a small network. Nodes correspond to characters, and edges are the number of conversations two characters co-occurred in. For example, if Bart, Homer, and Lisa are in the same quote, we would construct 3 undirected edges: Bart to Homer, Bart to Lisa, and Lisa to Homer. By aggregating all these conversations together (over episodes or seasons), we can compute the "weight" of an edge: the total number of quoted conversations those characters interacted over. From this kind of network, we can identify who the central characters are. Who is interacting with the most others in a quotable way? Are there small communities?

For this problem, we are going to use two libraries to help us out: [networkx](https://networkx.org/) (<https://networkx.org/>)--a library for manipulation and analysis of graph data structures (it will also generate layouts), and [nx-altair](https://github.com/Zsailer/nx-altair) (<https://github.com/Zsailer/nx-altair>) a library that can generate Altair plots from networkx data.

```
In [13]: # helper function to load the data
def loadData(filepath):
    articles = []
    with open(filepath) as fp:
        for docid, line in enumerate(fp):
            #print(line)
            #print(docid)
            doc = json.loads(line)
            char1 = doc['c1']
            char2 = doc['c2']
            articles.append(doc)
    return pd.DataFrame(articles)

In [14]: # we're going to load a data frame representation of the network to st
simpsons = loadData('../assets/simpsons.jsonl')
```

```
In [15]: # let's look inside
simpsons.sample(5)
```

Out[15]:

	season	episode	lineid	c1	c2
	120	2	Itchy & Scratchy & Marge	43	Lisa Marge
	3578	13	I Am Furious Yellow	1455	Angry Dad Cartoon Mr. Burns
	3544	13	Tales from the Public Domain	1438	Helen of Troy (Agnes) a la Phyllis Diller Suitor 1 (Sideshow Mel)
	4074	16	She Used to Be My Girl	1712	Bart Marge
	2892	10	Viva Ned Flanders	1102	Graeme Edge Homer

We see a row for every edge. The season and episode column has the season the

conversation happened in. The `lineid` is a unique id for the conversation (note that if the conversation involved more than two people, we'd see the same `lineid` multiple times; see the Bart/Homer/Lisa example above). The columns `c1` and `c2` hold the two characters' names (the name in `c1` will always be alphabetically before `c2`). For now, this data is as possible, but you may see some inconsistencies with names. For example, you might find different entries for "Skinner" and "Principal Skinner" even though they are the same character. Since that is not a major focus for this exercise, we will leave it as-is for now.

Next, we'll build our network using `networkx`.

```
In [16]: # utility classes

def buildNetwork(quoteFrame):
    # takes as input the quote frame (e.g., simpsons) or some subset of it
    # and returns an undirected networkx graph

    weight = quoteFrame.groupby(['c1', 'c2']).count()
    weight = weight.reset_index()
    toret = nx.Graph()
    for row in weight.iterrows():
        row = row[1]
        if (row['c1'] not in toret.nodes):
            toret.add_node(row['c1'])
            toret.nodes[row['c1']]['appearance'] = 0
            toret.nodes[row['c1']]['label'] = row['c1']
        if (row['c2'] not in toret.nodes):
            toret.add_node(row['c2'])
            toret.nodes[row['c2']]['appearance'] = 0
            toret.nodes[row['c2']]['label'] = row['c2']
        toret.nodes[row['c1']]['appearance'] = toret.nodes[row['c1']]['appearance'] + 1
        toret.nodes[row['c2']]['appearance'] = toret.nodes[row['c2']]['appearance'] + 1
        toret.add_edge(row['c1'], row['c2'])
        toret.edges[row['c1'], row['c2']]['weight'] = int(row['season'])
    return toret

def getLayout(positions):
    # helper function to build a dataframe of positions for nodes
    elems = []
    nodes = list(positions.keys())
    for n in nodes:
        elems.append({'node': n, 'x': positions[n][0], 'y': positions[n][1]})
    return(pd.DataFrame(elems))

def setCommunityLabels(G, communities):
    # adds community labels to the networkx graph nodes
```



```

id = 0
for c in communities:
    id = id + 1
    for n in c:
        G.nodes[n]['community'] = id
return(G)

```

```

In [17]: # let's start by grabbing only the network for a single season (6)
season6 = buildNetwork(simpsons[simpsons.season == 6])

```

```

In [18]: # season6 is a networkx object. You can ask for the edges or nodes
season6.nodes

```

```

Out[18]: NodeView(('Abe', 'Crazy Old Man', 'Family', 'Homer', 'Jasper', 'Quimby', 'Accountant', 'Krusty the Clown', 'Aide', 'Al Gore', 'Bart', 'Koolhaas', 'President', 'the Gang', 'Airport Worker', 'Amish Farmer', 'Announcer', 'Godfrey Jones', 'Kent Brockman', 'Apu', 'Chief Wiggum', 'Moe', 'Audience Member 1', 'Audience Member 2', 'McBain', 'Rainier Wolfcastle', 'Sherman', 'Wolfcastle', 'Australian man', 'Barney', 'Lisa', 'Man', 'Mayor Quimby', 'Woman', 'Bart's Brain', 'Database', 'Grampa', 'Groundskeeper Willie', 'Helen', 'Helen Lovejoy', 'Hibbert', 'Jessica', 'Jessica Lovejoy', 'Lunchlady Doris', 'Marge', 'Marine', 'Martin', 'Maude', 'Milhouse', 'Mrs. Krabappel', 'Ned', 'Ned Flanders', 'Nelson', 'Principal Skinner', 'Reverend Lovejoy', 'Server', 'Shelby', 'Sherry', 'Sideshow Bob', 'Skinner', 'TV Announcer', 'Teacher', 'Bartender', 'Bob', 'Boy', 'Brother', 'Burns', 'Chespirito', 'Hans Moleman', 'Hopkins', 'Shatner', 'Smithers', 'Spielbergo', 'Carl', 'Lenny', 'Morty', 'Mr. Burns', 'Stonecutters', 'Carla', 'Clavin', 'Norm', 'Sam', 'Woody', 'Dr. Hibbert', 'Homer/Marge', 'Clerk', 'Store Owner', 'Comic Book Guy', 'Congressman', 'Speaker', 'Darth Vader', 'James Earl Jones', 'Mufasa', 'Mufasa/Vader/Jones', 'Murphy', 'Dr. Zweig', 'Euro-Itchy', 'Scratchy Land Ticket Attendant', 'Fat Tony', 'Legs', 'Louie', 'Flanders', 'Frink', 'Girl', 'Pilot 1', 'Pilot 2', 'Hitler', 'Officer', 'Homer's Brain', 'Homer's Liver', 'Jay', 'Lesbian', 'Maude Flanders', 'Mr. Peabody', 'Number One', 'Patty', 'Vendor', 'Hugh', 'Hutz', 'Jay Sherman', 'Jimbo', 'Judge', 'Largo', 'Leopold', 'Miss Hoover', 'Ralph', 'Maggie', 'Willie', 'Park Announcer', 'Nurse', 'Mr Burns', 'Old Woman', 'Scott', 'Selma'))

```

```

In [19]: # we also calculate a special attribute of nodes called 'appearance' which is the
# degree of the node. This will be useful to us when we want to change the
# node
season6.nodes['Bart']['appearance']

```

```

Out[19]: 35

```

```

In [20]: # which is the same as this
print(season6.degree('Bart'))

```

```

35

```

```

In [21]: # you can ask for the weights of specific edges:
season6.edges['Homer', 'Bart']['weight']

```

```

Out[21]: 19

```


```

In [22]: # You can even ask networkx to find the x-y positions for you:
circular_pos = nx.circular_layout(season6)
# circular_pos

```

```
In [23]: # once you have the layout, you can ask nx-altair to draw the graph for you
nx.draw_networkx(season6, pos = circular_pos)
```

Out[23]:




Clearly, a circular layout isn't going to be great here. Thankfully, networkx has many other layouts: <https://networkx.org/documentation/stable/reference/drawing.html#layout> (<https://networkx.org/documentation/stable/reference/drawing.html#layout>).

```
In [24]: # let's try a kamada kawai
pos = nx.kamada_kawai_layout(season6)

# to generate a good visualization (you shouldn't need to modify the i
nx.draw_networkx(season6, pos = pos).properties(
    # nx-altair returns an Altair visualization, so we can modify
    # the properties as usual
    width=500,
    height=500
)
```

Out[24]:





Now let's modify it so that we can add more information.

We will use the `draw_networkx` function to control some properties of the visualization.

```
In [25]: # recall that we have calculated 'weight' (an edge feature) and 'appear
# let's modify our network to visualize these:


# nxa.draw_networkx(season6, pos=pos,width='weight',node_color='appear
```


```
In [26]: e = nxa.draw_networkx_edges(season6, pos=pos) # get the edge layer
# e # draw it
```

```
In [27]: n = nxa.draw_networkx_nodes(season6, pos=pos) # get the node layer
# n # draw it
```

```
In [28]: # combine them back
(e+n).properties(
    width=500,height=500
)
```

Out[28]:





We're going to calculate a new feature of nodes based on a community detection algorithm.

If you want to know more [read here](#)

([https://networkx.org/documentation/stable/reference/algorithms/generated/networkx.algorithms.community.greedy\\_modularity\\_communities.html](https://networkx.org/documentation/stable/reference/algorithms/generated/networkx.algorithms.community.greedy_modularity_communities.html))

We'll augment our networkx object so we have a "community" column that can be used as a nominal feature of the nodes in visualization.

```
In [29]: season6 = setCommunityLabels(season6, greedy_modularity_communities(season6))
```

```
In [30]: # let's see what community Bart is now in:
season6.nodes['Bart']['community']
```

```
Out[30]: 2
```


```
In [31]: e = nx.draw_networkx_edges(season6, pos=pos) # get the edge layer
n = nx.draw_networkx_nodes(season6, pos=pos) # get the node layer


# modify the code to change the encodings
n = n.mark_circle(opacity=1).encode(
    color=alt.Color('community:N',
                    legend=None),
    size=alt.Size('appearance:Q'),
    tooltip=['label:N']
)

e = e.mark_line().encode(
    strokeWidth=alt.StrokeWidth(
        'weight:N',
        legend=None),
    strokeOpacity='weight:N'
)

(e+n).properties(
    width=500,height=500
)
```

```
Out[31]:
```





Now that we have the basics, we are going to build a visualization to help us compare pairs of seasons. We'd like to understand which characters have been more central to which seasons and how that has changed.

Key things we want to address:

- color based on community labels
- mouse-over interaction that changes the color of ALL of the visualizations if the character appears everywhere
- tooltip over the nodes to get the # of appearances
- bars sorted based on changes between seasons

In [32]: *# we're going to want the networkx objects for different charts, so let's*

```
def getNetwork(season):
    # build a networkx object given the season, annotate with community labels
    toret = buildNetwork(simpsons[simpsons.season == season])
    toret = setCommunityLabels(toret, greedy_modularity_communities(toret))
    return(toret)
```

In [33]: *# get the networkx objects for seasons 5 and 9*

```
s5net = getNetwork(5)
s9net = getNetwork(9)
```

In [34]: *# we also want the data for the two bar charts, we're going to do that*

```
def getTotal(G):
    # total appearance across all characters in a given graph
    app = 0
    for nd in G.nodes:
        app = app + G.nodes[nd]['appearance']
    return(app)

def getComparisonData(G1,G2,threshold=5):
    # generate two dataframes given two graphs
    # the first is the difference in appearances (normalized) when a character appears in both
    # the second is for characters that are either in G1 or G2, but not in both
    # the threshold defines the cutoff for how many interactions a character must have
    # to be included in the second ('difference') data frame
    t1total = getTotal(G1)
    t2total = getTotal(G2)
```

```

union = []
difference = []
allentities = set(G1.nodes).union(set(G2.nodes))

for i in allentities:
    if ((i in G1.nodes) & (i in G2.nodes)):
        diff = G1.nodes[i]['appearance']/t1total-G2.nodes[i]['appearance']/t2total
        union.append({'label':i,'difference': diff})
    elif (i in G1.nodes):
        if (G1.nodes[i]['appearance'] > threshold):
            difference.append({'label':i,'difference':-G1.nodes[i]['appearance']/t1total})
    elif (i in G2.nodes):
        if (G2.nodes[i]['appearance'] > threshold):
            difference.append({'label':i,'difference':G2.nodes[i]['appearance']/t2total})

return(pd.DataFrame(union),pd.DataFrame(difference))

```

```

In [35]: # let's compare the season 5 and 9 networks
union,difference = getComparisonData(s5net,s9net)

# look inside the union dataframe (the difference one will be similar)
union.sample(5)

```

Out[35]:

	label	difference
23	Grampa Simpson	0.004245
26	Skinner	-0.015174
10	Principal Skinner	-0.004432
0	Nelson	0.006309
27	Mayor Quimby	0.003119

```

In [36]: def getComparisonBar(frame,sel,title):
    # return an Altair chart corresponding to the bar chart example
    # above, given one of the two frames (difference or union)
    # frame is a pandas dataframe
    # sel is the Altair selection object (for interactivity)
    # title is the title for the chart

    sort_vals = frame.sort_values(by='difference',ascending=False)
    sort_vals = list(sort_vals['label'].unique())

    c1 = alt.Chart(frame).mark_bar().encode(
        x=alt.X('difference:Q',
                axis=alt.Axis(ticks=False,
                              grid=True,
                              labels=True),
                title=None),
        y=alt.Y('label:N',
                sort=sort_vals,
                axis=alt.Axis(ticks=True,
                              grid=False),
                title=None),
        color=alt.Color('difference:N',
                        scale=alt.Scale(scheme='blues'),
                        legend=None)
    ).properties(
        title=title,
        width=100,
        height=350
    ).add_selection(
        sel
    ).encode(
        color=alt.condition(sel,
                            alt.Color("difference:N",
                                        scale=alt.Scale(scheme='blues'),
                                        legend=None)

```

```

        legend=None),
        alt.value('lightgray'),
        legend=None)
    )
    return(c1)

```

```

In [37]: def getNetworkDiagram(G,season,sel):
    # return an Altair chart corresponding to network diagram above for
    # G is the networkx object
    # season is the season
    # sel is the Altair selection object (for interactivity)

    seasonN = buildNetwork(simpsons[simpsons.season == season])
    pos = nx.kamada_kawai_layout(seasonN)
    edges = nxa.draw_networkx_edges(G, pos=pos)
    nodes = nxa.draw_networkx_nodes(G, pos=pos)

    nodes = nodes.mark_circle(opacity=1,size=250).encode(color=alt.Color(
        alt.condition(sel, alt.Color("community:N",
                                     scale=alt.Scale(scheme='c1')),
        alt.value('lightgray')),
        legend=None
    ),
    tooltip=['lat', 'lon'])

    edges = edges.mark_line(color='black',strokeWidth=0.5)

    nodes = nodes.properties(
        title="Season "+str(season),
        width=400,
        height=350
    ).add_selection(
        sel
    ).encode(
        color=alt.condition(sel,
                             alt.Color("community:N",
                                     scale=alt.Scale(scheme='c1')),
                             alt.value('lightgray')),
        legend=None
    )

    c2 = (edges + nodes).resolve_scale(color='independent')

    return(c2)

```

```

In [38]: # this function will build the dashboard
def getNetworkDashboard(season1,season2):

    # create the selection object, based on mouseover. It should look
    # over as a way of deciding other objects with the same label
    single = alt.selection_single(on='mouseover',fields=['label'])

    # get the two networkx objects
    s1net = getNetwork(season1)
    s2net = getNetwork(season2)

    # get the union and difference dataframes
    union,difference = getComparisonData(s1net,s2net)

    # build the top bar chart
    u = getComparisonBar(union,single,"Appears in Both")

    # build the top network
    s1 = getNetworkDiagram(s1net,season1,single)

    # build the bottom network
    s2 = getNetworkDiagram(s2net,season2,single)

    # in some cases, we don't have new characters given the threshold v
    if (len(difference) == 0):
        # we won't return the bottom chart
        return((s1&s2)|u)
    else:
        # we have both bar charts
        # build the bottom bar chart
        d = getComparisonBar(difference,single,"New Characters")
        # return all charts
        return((s1&s2)|(u&d))


```

```



In [39]: # implement dashboard
getNetworkDashboard(5,9)

```



Out[39]:







Season 9





New

In [40]: *# Let's see the differences between season 1 and season 10*  
getNetworkDashboard(1,10)


Out[40]:

Season 1




Appe

Season 10



New



### Matrix Representation of Network

For the final exercise, we will generate a matrix representation of the network. To reduce noise in the dataset, we will include only characters who have interacted 6 or more times with each other. We will use a tooltip to provide a bit more detail.

```
In [41]: def getMatrixDetails(df, threshold=6, removeIsolates=True):
# given a dataframe with characters (c1, c2, etc.)
# the returned matrix will find the number of interactions in the
# find statistics to generate a matrix representation
# threshold will be the minimum number of interactions between cha
# removeIsolates determines if isolated nodes (nodes not connected

# this function returns 3 things
# the long form dataframe with pairs of nodes and the count
# the node order of nodes in the matrix given the input
# a list of list -- an edge list for all nodes
t = buildNetwork(df)
for e in t.edges:
    if (t.edges[e]['weight'] < threshold):
        t.remove_edge(e[0], e[1])
if (removeIsolates):
    t.remove_nodes_from(list(nx.isolates(t)))

m, names, a, b, w = [], [], [], [], []

for n1 in t.nodes:
    e = []
    names.append(n1)
    for n2 in t.nodes:
        if (t.has_edge(n1, n2)):
            a.append(n1)
            b.append(n2)
            w.append(t.edges[n1, n2]['weight'])
            e.append(t.edges[n1, n2]['weight'])
        else:
            e.append(0)
    m.append(e)

toret = pd.DataFrame()
toret['p1'] = a
toret['p2'] = b
toret['weight'] = w
return (toret, names, m)
```

```
In [42]: # let's call this for the entire dataset
df, names, m = getMatrixDetails(simpsons)
```

```
In [43]: # we'll get back to names and m in a moment, but let's look at what's
df.sample(5)
```

Out[43]:

	p1	p2	weight
37	Bart	Ned	6
141	Nelson	Bart	29
130	Milhouse	Bart	43
128	Fat Tony	Homer	6
17	Homer	Principal Skinner	8


```
In [44]: def genMatrix1(inframe,threshold=6):
# takes an input frame as input
# returns an altair plot for the matrix as described above
df,names,m = getMatrixDetails(inframe,threshold=threshold)

# modify the following
toret = alt.Chart(df).mark_rect().encode(
    x=alt.X('p1:N'),
    y=alt.Y('p2:N'),
    color=alt.Color('weight:N', scale=alt.Scale(scheme='blues')),
    tooltip=['p1','p2','weight']
).properties(width=700,height=700)

return(toret)
```

```
In [45]: genMatrix1(simpsons)
```

Out[45]:





```

leaves = leaves_list(linkage_matrix)
neworder = []
for l in leaves:
    neworder.append(originalorder[l])
return(neworder)

```

The scipy clustering code requires a "vector" representation of each node (which we calculated when we ran `getMatixDetail`). This looks much like the edge list representation.

Each vector will be compared to all others giving us the "distance" between characters and that will be used to cluster.

```

In [47]: df,names,m = getMatrixDetails(simpsons[simpsons.season <= 6],threshold=6)
print("The first character in m is:",names[0])
print("It is represented by the vector:",m[0])

```

The first character in m is: Homer  
It is represented by the vector: [0, 62, 11, 9, 9, 69, 6, 50, 13, 9, 0, 0, 6]

```

In [48]: def genMatrix2(inframe,threshold=6):
    # takes an input frame as input
    # returns an altair plot for the matrix as described above
    df,names,m = getMatrixDetails(inframe,threshold=threshold)

    neworder = getNewOrder(m,names)

    # modify the following


    toret = alt.Chart(df).mark_rect().encode(
        x=alt.X('p1:N',sort=neworder),
        y=alt.Y('p2:N',sort=neworder),
        color=alt.Color('weight:Q'),
        order=alt.Order("neworder:N"),
        tooltip=['p1','p2','weight'],
    ).properties(width=700,height=700)

    return (toret)

```

```
In [49]: # If you im
genMatrix2(simpsons[simpsons.season <= 6])
```

Out[49]:



- Pattern 1 - The blue cluster at the bottom right indicates significantly more interaction between those characters. This makes sense, as the Simpson family are the main characters.
- Pattern 2 - The lines extending along Homer, Bart, and less so Lisa's axes indicate interaction with a multitude of characters. This pattern also allows us to see that sometimes these 3 main characters are the only ones the tertiary characters interact with.

