Recap

Creating/naming objects

Creating/naming objects

Objects are created with the assignment arrow `<-`; `=` is only used to set the arguments of a function

```
1 x1 <- 3 # name <- object
2 x1
```

```
[1] 3
```

```
1 my_vector <- c(1, 2, 3)              # <- creates an object
2 mean(x = my_vector, na.rm = TRUE)  # = sets the arguments
```

```
[1] 2
```

Object names must start with a letter!! NOT “name” <- … but name <- …

Logical Operators

In R we can combine several relations to evaluate a given statement.


```
1 x <- 30 # Assign the value 30 to x.
```

Function	Name	Example	Result
`&`	Conjunction (AND)	`x>25 & x<60`	`TRUE`
`|`	Inclusive disjunction (OR)	`x>25 | x>60`	`TRUE`
`!`	Negation (NOT)	`!(x<18)`	`TRUE`

Vectors

Vectors

- **a value**: the value of the element, which can be of any type, for example a number or a string of characters
- **a position index**: a positive integer that identifies its position within the vector.



Creating a vector

Vectors can be created with the `c()` command, writing inside the brackets the values of the elements in the desired order, separated by commas.

```r
num_vect <- c(1,2,3,4)
# you can also use the seq() function
num_vect_seq <- seq(from = 1,to = 4, by = 1)

num_vect;num_vect_seq
```

```
[1] 1 2 3 4
```

```
[1] 1 2 3 4
```

```r
char_vect <- c("R","R","R","ok")
# you can also use the rep() function
char_vect_rep <- c(rep("R", 3), "ok")

char_vect;char_vect_rep
```

```
[1] "R"  "R"  "R"  "ok"
[1] "R"  "R"  "R"  "ok"
```

Vector type

A vector must be made of **elements all of the same type**!

```r
wrong <- c(1,2,3,"don't know", 4)
class(wrong)
```

```
[1] "character"
```

```r
wrong
```

```
[1] "1"          "2"          "3"          "don't know" "4"
```

Otherwise you “risk” everything being converted to character.

```r
correct <- c(1,2,3,NA, 4)
class(correct)
```

```
[1] "numeric"
```

```r
correct
```

```
[1]  1  2  3 NA  4
```

is.* & as.*

We can test or convert (when possible) the type of a vector with the **`is.`** & **`as.`** functions

```
1 is.character(char_vect)
```

```
[1] TRUE
```

```
1 as.numeric(char_vect) #!!
```

```
[1] NA NA NA NA
```

```
1 is.numeric(num_vect)
```

```
[1] TRUE
```

```
1 as.character(num_vect) #!!
```

```
[1] "1" "2" "3" "4"
```

```
1 logi_vect <- c(TRUE,FALSE,TRUE)
2 is.logical(logi_vect)
```

```
[1] TRUE
```

```r
as.numeric(logi_vect)
```

```
[1] 1 0 1
```

Indexing

We can select, remove and extract elements simply by using the position index inside square brackets vector[pos]

```
# Create a vector of 20 random numbers drawn between 1 and
my_vect <- round(runif(n = 20,min = 1,max = 100))
my_vect
```

```
 [1]  8 57  8 54 50 42 85 48 22 34 45 48 34 43 39 15 30 61 85
6
```

```
my_vect[1] # extract the first element
```

```
[1] 8
```

```
my_vect[1:5] # extract the first 5 elements
```

```
[1]  8 57  8 54 50
```

```
my_vect[c(1,4,2,9)] # extract elements of our choice
```

```
[1]  8 54 57 22
```

```r
my_vect[length(my_vect)] # last element (why?)
```

```
[1] 6
```

Negative indexing

In the same way, we can extract all the elements of the vector except some

```
my_vect[-c(1)] # all except the first element
```

```
[1] 57  8 54 50 42 85 48 22 34 45 48 34 43 39 15 30 61 85  6
```

```
my_vect[-c(1:10)] # all except the first 10
```

```
[1] 45 48 34 43 39 15 30 61 85  6
```

Logical Indexing

Indexing by position is the simplest and most intuitive approach. We can also select using **TRUE** and **FALSE** values: we can extract elements from the vector based on specific logical conditions

```
1 numbers <- 1:7
2 numbers
```

```
[1] 1 2 3 4 5 6 7
```

```
1 numbers[numbers<2]
```

```
[1] 1
```

Factors

Factors

Factors can be created either by converting a character vector with the `as.factor()` command or by explicitly creating a factor with the `factor()` command

```
char_vect <- rep(c("hello","ciao", "hola"), each = 2)
my_fact <- as.factor(char_vect)

my_fact2 <- factor(rep(c("hello","ciao", "hola"), each = 2

my_fact == my_fact2
```

```
[1] TRUE TRUE TRUE TRUE TRUE TRUE
```

Properties of factors

In practice, they assign a label to an integer value:

```
1 typeof(my_fact)
```

```
[1] "integer"
```

```
1 as.integer(my_fact)
```

```
[1] 2 2 1 1 3 3
```

```
1 my_fact
```

```
[1] hello hello ciao  ciao  hola  hola
Levels: ciao hello hola
```

Factor levels

Factors store **`levels()`** as metadata, regardless of which ones are actually present in the vector

```
1 levels(my_fact)
```

```
[1] "ciao"  "hello" "hola"
```

```
1 my_fact2 <- my_fact[my_fact!="ciao"]
2 my_fact2
```

```
[1] hello hello hola  hola
Levels: ciao hello hola
```

However, we can drop the levels that are no longer needed with the **`droplevels()`** command

```
1 droplevels(my_fact2)
```

```
[1] hello hello hola  hola
Levels: hello hola
```

We can also rename the levels of a factor

```
# the factor I created
my_fact
```

```
[1] hello hello ciao  ciao  hola  hola
Levels: ciao hello hola
```

```
# create another factor "my_fact_lev" identical to "my_fac
my_fact_lev <- my_fact
my_fact_lev == my_fact
```

```
[1] TRUE TRUE TRUE TRUE TRUE TRUE
```

```
# rename the levels of the factor
levels(my_fact_lev) <- c("italian","english","spanish")

my_fact_lev
```

```
[1] english english italian italian spanish spanish
Levels: italian english spanish
```

```
1 my_fact
```

```
[1] hello hello ciao  ciao  hola  hola
Levels: ciao hello hola
```

We can both reorder and rename the levels of a factor with the **`factor()`** function

```
1 my_fact
```

```
[1] hello hello ciao  ciao  hola  hola
Levels: ciao hello hola
```

```
1 # by default levels are assigned in alphabetical order
2 as.integer(my_fact)
```

```
[1] 2 2 1 1 3 3
```

```
1 new_fact <- factor(my_fact, levels = c("hello","ciao","hol
2 new_fact
```

```
[1] hello hello ciao  ciao  hola  hola
Levels: hello ciao hola
```

```
1 as.integer(new_fact)
```

```
[1] 1 1 2 2 3 3
```

```
1 new_fact2 <- factor(my_fact, levels = c("hello","ciao","ho
2                     labels = c("english","italian","spanish
```

```
3 new_fact2
```

```
[1] english english italian italian spanish spanish
Levels: english italian spanish
```

Remember: the ***`levels`*** argument inside the **`factor()`** function is used to **reorder** the levels of the factor, while the **`levels()`** function **renames** them, it does not reorder them!

```
# the factor I created
my_fact
```

```
[1] hello hello ciao  ciao  hola  hola
Levels: ciao hello hola
```

```
as.integer(my_fact)
```

```
[1] 2 2 1 1 3 3
```

```
levels(my_fact) <- c("hello","ciao","hola")

# What do you notice compared to the my_fact vector shown
my_fact
```

```
[1] ciao  ciao  hello hello hola  hola
Levels: hello ciao hola
```

```r
as.integer(my_fact)
```

```
[1] 2 2 1 1 3 3
```

Lists

Lists

Lists are flexible structures that can contain objects of different types and different sizes (each element can itself be a list)

```r
my_list <- list("hello!", 1:3, c(TRUE,FALSE),
                list("hello!", 1:3, c(TRUE,FALSE)))
str(my_list)
```

```
List of 4
 $ : chr "hello!"
 $ : int [1:3] 1 2 3
 $ : logi [1:2] TRUE FALSE
 $ :List of 3
  ..$ : chr "hello!"
  ..$ : int [1:3] 1 2 3
  ..$ : logi [1:2] TRUE FALSE
```

Lists

Although a list is one-dimensional, it develops in depth

```
1 str(my_list)
```

```
List of 4
 $ : chr "hello!"
 $ : int [1:3] 1 2 3
 $ : logi [1:2] TRUE FALSE
 $ :List of 3
  ..$ : chr "hello!"
  ..$ : int [1:3] 1 2 3
  ..$ : logi [1:2] TRUE FALSE
```

Lists

First Level: list

```
1 str(my_list[2])
```

```
List of 1
 $ : int [1:3] 1 2 3
```

Second Level: numeric vector

```
1 str(my_list[[2]])
```

```
int [1:3] 1 2 3
```

Third Level: integer

```
1 str(my_list[[2]][1]) # integer
```

```
int 1
```

Lists

We can assign names to the elements of a list…

```
my_list_nam <- list(word = "hello!",numbers =  1:3,
                    logical = c(TRUE,FALSE),
                  list = list("hello!", 1:3, c(TRUE,FALSE)))
my_list_nam
```

```
$word
[1] "hello!"

$numbers
[1] 1 2 3

$logical
[1]  TRUE FALSE

$list
```

Lists

… and access them by calling them by “name” with the `$` operator

```
1 my_list_nam$word
```

```
[1] "hello!"
```

```
1 my_list_nam$list # list created as an element of the list
```

```
[[1]]
[1] "hello!"

[[2]]
[1] 1 2 3

[[3]]
[1]  TRUE FALSE
```

Lists - Attributes

Like vectors, lists also have a length (**`length()`**) and possibly names (**`names()`**). The **`str()`** (structure) command is very useful for lists because it gives an overview of their structure:

```
1 length(my_list_nam); names(my_list_nam)
```

```
[1] 4
```

```
[1] "word"    "numbers" "logical" "list"
```

```
1 str(my_list_nam)
```

```
List of 4
 $ word   : chr "hello!"
 $ numbers: int [1:3] 1 2 3
 $ logical: logi [1:2] TRUE FALSE
 $ list   :List of 3
  ..$ : chr "hello!"
```

```
..$ : int [1:3] 1 2 3
..$ : logi [1:2] TRUE FALSE
```

Lists - Indexing

The difference between the square brackets is whether we want to subset the list, getting another list, or directly access the inner element:

```
1 my_list_nam[1] # getting another list
```

```
$word
[1] "hello!"
```

```
1 my_list_nam[[1]] # accessing the inner element
```

```
[1] "hello!"
```

Lists - Indexing

If we want to select several elements (i.e. actually subset the list) we must always use single square brackets:

```
1 # list made of the first two elements of my_list_nam
2 my_list_nam[1:2]
```

```
$word
[1] "hello!"

$numbers
[1] 1 2 3
```

Lists - Nested Indexing

Lists have a one-dimensional structure that can develop in depth. To select nested elements we can chain several brackets:

```
1 my_list_nam[[4]]
```

```
[[1]]
[1] "hello!"

[[2]]
[1] 1 2 3

[[3]]
[1]  TRUE FALSE
```

```
1 my_list_nam[[4]][[1]]
```

```
[1] "hello!"
```

```
1 my_list_nam[[4]][[2]]
```

```
[1] 1 2 3
```

Matrices

Matrices

Matrices are a **two-dimensional** data structure (characterized by 2 dimensions, `dim()`), where the number of rows is dimension 1 and the number of columns is dimension 2.

```
1 my_mat <- matrix(data = 1:10, nrow = 2, ncol = 5, byrow =
2 my_mat
```

```
     [,1] [,2] [,3] [,4] [,5]
[1,]    1    3    5    7    9
[2,]    2    4    6    8   10
```

```
1 matrix(data = 1:10, nrow = 2, ncol = 5, byrow = TRUE)
```

```
     [,1] [,2] [,3] [,4] [,5]
[1,]    1    2    3    4    5
[2,]    6    7    8    9   10
```

Matrices - Properties

- They can contain **only one type** of data
- Since they are **two-dimensional**, we need two position indices (rows and columns) to identify an element
- They can be seen as a **set** of single **vectors**

Matrices - Properties

The number of rows and columns does not have to be the same (square matrix), but the size of the matrix must be compatible with the data vector:

```r
matrix(data = 1:10, ncol = 3, nrow = 3)
```

```
Warning in matrix(data = 1:10, ncol = 3, nrow = 3): data
length [10] is not a
sub-multiple or multiple of the number of rows [3]
```

```
     [,1] [,2] [,3]
[1,]    1    4    7
[2,]    2    5    8
[3,]    3    6    9
```

Matrices

What does R do by default?

```r
matrix(data = 1:10, ncol = 3, nrow = 3)
```

```
     [,1] [,2] [,3]
[1,]    1    4    7
[2,]    2    5    8
[3,]    3    6    9
```

```r
matrix(data = 1:2, ncol = 3, nrow = 3)
```

```
     [,1] [,2] [,3]
[1,]    1    2    1
[2,]    2    1    2
[3,]    1    2    1
```

warnings: the function informs us about something potentially problematic, but (more or less!!) everything is fine

Matrices - Indexing

To identify one or more elements of a matrix we need row and/or column indices separated by a comma, again inside square brackets: matrix[row, column]

```
1 my_mat
```

```
     [,1] [,2] [,3] [,4] [,5]
[1,]    1    3    5    7    9
[2,]    2    4    6    8   10
```

```
1 my_mat[1,1]
```

```
[1] 1
```

Matrices - Indexing

We can also select an entire row or column

```
1 my_mat[1,]
```

```
[1] 1 3 5 7 9
```

```
1 my_mat[,1]
```

```
[1] 1 2
```

Matrices - Indexing

As with vectors, here too we can apply logical indexing:

```
1 my_mat>2
```

```
      [,1] [,2] [,3] [,4] [,5]
[1,] FALSE TRUE TRUE TRUE TRUE
[2,] FALSE TRUE TRUE TRUE TRUE
```

```
1 # All the elements greater than two
2 my_mat[my_mat>2]
```

```
[1]  3  4  5  6  7  8  9 10
```

Vectors and Matrices

Vectors are created with the `c()` function and can be concatenated using the same function:

```
my_vect1 <- c(1:4); my_vect2 <- c(5:10)
my_vect12 <- c(my_vect1,my_vect2)
my_vect12
```

```
[1]  1  2  3  4  5  6  7  8  9 10
```

Matrices

Similarly, matrices can be joined together with the **`cbind()`** and **`rbind()`** commands:

```
1 my_mat <- matrix(1:4,2,2)
2
3 cbind(my_mat, my_mat)
```

```
     [,1] [,2] [,3] [,4]
[1,]    1    3    1    3
[2,]    2    4    2    4
```

```
1 rbind(my_mat, my_mat)
```

```
     [,1] [,2]
[1,]    1    3
[2,]    2    4
[3,]    1    3
[4,]    2    4
```

Dataframe

Dataframe

The dataframe is the most “complex”, useful and powerful structure in R. Intuitively it is an excel sheet, while from R’s point of view it is a type of list with some properties/restrictions

- each element of the list is a **vector** with an **associated name** (aka a column)
- each list/column must have the same number of elements
- as a consequence, each row has the same number of elements (**rectangular structure**)

Creating a dataframe

With the data.frame() function we can create a dataframe…

```r
# Create a dataframe with 3 columns
my_df <- data.frame( col1 = 1:4, col2 = letters[1:4],
                     col3 = rnorm(4))
my_df
```

```
  col1 col2       col3
1    1    a  1.0448101
2    2    b  0.1357442
3    3    c  0.1539800
4    4    d -1.1813148
```

Attributes

The `dataframe` has both the attributes of a **list**, i.e. the ***names***, and the attributes of a **matrix**, i.e. the ***dimensions*** (rows and columns)

```
1 typeof(my_df)
```

```
[1] "list"
```

```
1 attributes(my_df)
```

```
$names
[1] "col1" "col2" "col3"

$class
[1] "data.frame"

$row.names
[1] 1 2 3 4
```

```
1 dim(my_df)
```

```
[1] 4 3
```

Indexing

We can use either square brackets `[]` or the dollar sign `$`

```
1 my_df[1] # extract a 4x1 data.frame
```

```
  col1
1    1
2    2
3    3
4    4
```

```
1 my_df[[1]]# extract the first column of the data.frame
```

```
[1] 1 2 3 4
```

```
1 my_df$col1# extract the first column of the data.frame
```

```
[1] 1 2 3 4
```

```
1 my_df[1,1]# extract the first element of the first column
```

```
[1] 1
```

Indexing - Relational operators

One of the most common operations you will deal with is extracting/evaluating a subset of the values in your dataset:

```
1 # keep only the rows where the values of column1 are great
2 my_df[my_df$col1 > 2, ]
```

```
  col1 col2       col3
3    3    c  0.153980
4    4    d -1.181315
```

```
1 my_df[my_df[1] > 2, ]
```

```
  col1 col2       col3
3    3    c  0.153980
4    4    d -1.181315
```

Examples

```
  col1 col2       col3
1    1    a  1.0448101
2    2    b  0.1357442
3    3    c  0.1539800
4    4    d -1.1813148
```

- `my_df[my_df$col1 > 1 & my_df$col1 < 4, ]`
  - 2 b -0.5630882
  - 3 c -0.5672335
- `my_df[my_df$col1== 1,  "col3"]`
  - -1.481937
- `my_df[my_df$col1== 1,  3]`
  - -1.481937

Indexing

There are also alternative, more compact ways of indexing. For example, using the `subset()` function:

```
1 subset(iris, subset = Species == "setosa" & Petal.Length >
```

```
   Sepal.Length Sepal.Width Petal.Length Petal.Width Species
25          4.8         3.4          1.9         0.2  setosa
45          5.1         3.8          1.9         0.4  setosa
```

equivalent to:

```
1 iris[iris$Species == "setosa" & iris$Petal.Length > 1.7,]
```

```
   Sepal.Length Sepal.Width Petal.Length Petal.Width Species
25          4.8         3.4          1.9         0.2  setosa
45          5.1         3.8          1.9         0.4  setosa
```

We can also select columns rather than rows with the ***select*** argument:

```
1 head(subset(iris, select = c(Sepal.Length, Species)), n =
```

```
  Sepal.Length Species
1          5.1  setosa
2          4.9  setosa
3          4.7  setosa
```

We can also combine the two:

```r
head(subset(iris, Species == "setosa" & Sepal.Length > 4,
            c(Sepal.Length, Species)), n = 3)
```

```
  Sepal.Length Species
1          5.1  setosa
2          4.9  setosa
3          4.7  setosa
```

equivalent to:

```r
head(iris[iris$Species == "setosa" & iris$Sepal.Length > 4
          c("Sepal.Length","Species")],n = 3)
```

```
  Sepal.Length Species
1          5.1  setosa
2          4.9  setosa
3          4.7  setosa
```

$$$$$$

Most of the time you will access variables with the `$` operator. This command can also be used to create a new variable...

```
1 iris$sum <- iris$Sepal.Length + iris$Sepal.Width
2 str(iris)
```

```
'data.frame':   150 obs. of  6 variables:
 $ Sepal.Length: num  5.1 4.9 4.7 4.6 5 5.4 4.6 5 4.4 4.9 ...
 $ Sepal.Width : num  3.5 3 3.2 3.1 3.6 3.9 3.4 3.4 2.9 3.1
...
 $ Petal.Length: num  1.4 1.4 1.3 1.5 1.4 1.7 1.4 1.5 1.4 1.5
...
 $ Petal.Width : num  0.2 0.2 0.2 0.2 0.2 0.4 0.3 0.2 0.2 0.1
...
 $ Species     : Factor w/ 3 levels "setosa","versicolor",..:
1 1 1 1 1 1 1 1 1 1 ...
```

EXAM

https://etherpad.wikimedia.org/p/arca-corsoR