

TESTs - Lesson 14 - Integration

What framework combinations does Scaffold-ETH 2 use to help developers build frontend applications quickly?



A Angular with Express.js

B Vue.js with Laravel

C React with Next.js

What two `yarn` commands are initially needed to start a Scaffold-ETH 2 application and its local blockchain?



A `yarn deploy` and `yarn install`

B `yarn start` and `yarn chain`

C `yarn build` and `yarn test`

Why does the Scaffold-ETH 2 application initially show 'no read methods' and errors when attempting to interact with contracts?



A The local blockchain has not been initialized.

B The smart contracts have not yet been deployed to the blockchain.

C The frontend is not correctly linked to the backend.

The `useAccount` hook from Wagmi is used to retrieve what kind of information?



A Only the connected wallet's balance.

B The connected wallet's address, connection status, and chain information.

C Transaction history for the connected wallet.

When using the `useReadContract` hook from Wagmi to interact with a smart contract, what two essential pieces of information are required?



A The contract's address and its Application Binary Interface (ABI).

B The contract's deployment date and gas limit.

C The contract's byte code and compiler version.

What is the primary purpose of Scaffold-ETH 2 as described in the video?

- A To create secure backend APIs for dApps.
- B To accelerate frontend dApp development by providing pre-configured tools for blockchain interaction.**
- C To develop complex smart contracts from scratch.

What is the significance of the `use client` directive in Next.js for dApp development?

- A It ensures components are rendered on the server-side for better SEO.
- B It indicates components should be processed and rendered client-side, enabling dynamic interactions with the wallet.**
- C It optimizes database queries for faster data retrieval.

Explain the concept of 'signing a message' in the context of blockchain and wallets.

- A It's a process of sending cryptocurrency to another address, requiring a gas fee.
- B It's a cryptographic operation using a private key to prove ownership or agreement over a piece of data without incurring transaction fees.**
- C It generates a unique transaction hash for tracking on a block explorer.

What is the main difference between fetching on-chain data and fetching public off-chain data, and what tools are used for each?

- A On-chain data is retrieved from a local database using SQL, while off-chain data uses REST APIs.
- B On-chain data comes directly from the blockchain via hooks like `useReadContract`, while off-chain data is pulled from external APIs using `fetch`.**
- C On-chain data requires authentication, whereas off-chain data is always public and open source.

What are some use cases that would necessitate building a backend (APIs) in addition to a frontend for a blockchain project?

- A When only a simple user interface is needed for basic contract interactions.
- B When automated services, off-chain data processing, or integrations between machines are required.**
- C When developing a fully static website hosted on IPFS.