

Semantics for (Hybrid) Programming

Renato Neves



Universidade do Minho



Table of Contents

Overview

Semantics for Linear Terms

Semantics for Boolean Terms

Semantics for While Programs


Explored a simple language (CCS) and its semantics

Used it to model and analyse communicating systems

Expanded our study to the timed setting, via UPPAAL


Used it to save us from zombies!

Going Beyond the Timed Setting



Described via classical methods of computation

+



Described via differential equations

Computational devices now interact with **arbitrary** physical processes (and not just time)

Which Language?

This time we explore a simple **imperative language**

No concurrency, no communication, and no higher-order func.

(languages with such features are still underdeveloped)

Perhaps some of you would like to improve them :-)

The Hybrid While-Language

Fix a stock of variables $X = \{x_1, \dots, x_n\}$. Then we have,

Linear Terms

$$\text{LTerm}(X) \ni r \mid r \cdot t \mid x \mid t + s$$


real number

Atomic Programs

$$\text{At}(X) \ni x := t \mid x'_1 = t_1, \dots, x'_n = t_n \text{ for } t$$


"run" the system of differential equations for t seconds

Hybrid Programs

$$\text{Prog}(X) \ni a \mid p ; q \mid \text{if } b \text{ then } p \text{ else } q \mid \text{while } b \text{ do } \{ p \}$$

First we tackle a **while-language** without differential equations and its semantics

Then we move to the hybrid case and see how the corresponding semantics helps the engineer to analyse hybrid programs

Throughout this journey, we will:

- write implementations in `HASKELL`
- do analyses in `LINCE`

Table of Contents

Overview

Semantics for Linear Terms

Semantics for Boolean Terms

Semantics for While Programs

A Language of Linear Terms and its Semantics

Linear Terms

$\text{LTerm}(X) \ni r \mid r \cdot t \mid x \mid t + s$

Let $\sigma : X \rightarrow \mathbb{R}$ be an **environment**, i.e. a memory on which the program performs computations

The expression $\langle t, \sigma \rangle \Downarrow r$ tells that the linear expression t outputs r if the current memory is σ

$$\frac{}{\langle x, \sigma \rangle \Downarrow \sigma(x)} \text{ (var)}$$


$$\frac{}{\langle r, \sigma \rangle \Downarrow r} \text{ (con)}$$

$$\frac{\langle t, \sigma \rangle \Downarrow r}{\langle s \cdot t, \sigma \rangle \Downarrow s \cdot r} \text{ (scl)}$$

$$\frac{\langle t_1, \sigma \rangle \Downarrow r_1 \quad \langle t_2, \sigma \rangle \Downarrow r_2}{\langle t_1 + t_2, \sigma \rangle \Downarrow r_1 + r_2} \text{ (add)}$$

The Semantics at Work

The linear term $x + 2 \cdot y$ corresponds to the tree



Consider an environment σ such that $\sigma(x) = 3$ and $\sigma(y) = 4$. We can then build the following derivation tree:

$$\frac{\langle x, \sigma \rangle \Downarrow 3 \quad \frac{\langle y, \sigma \rangle \Downarrow 4}{\langle 2 \cdot y, \sigma \rangle \Downarrow 8}}{\langle x + 2 \cdot y, \sigma \rangle \Downarrow 11}$$

- $\langle 2 \cdot x + 2 \cdot y, \sigma \rangle \Downarrow ?$
- $\langle 3 \cdot (2 \cdot x) + 2 \cdot (y + z), \sigma \rangle \Downarrow ?$

- $\langle 2 \cdot x + 2 \cdot y, \sigma \rangle \Downarrow ?$
- $\langle 3 \cdot (2 \cdot x) + 2 \cdot (y + z), \sigma \rangle \Downarrow ?$

Boring computations? If so why not implement the semantics in
HASKELL?

Equivalence of Linear Terms

The previous semantics yields the following notion of **equivalence**:
 $t \sim s$ if for all environments σ

$$\langle t, \sigma \rangle \Downarrow r \text{ iff } \langle s, \sigma \rangle \Downarrow r$$

Examples of equivalent terms:

- $r \cdot (x + y) \sim r \cdot x + r \cdot y$
- $0 \cdot x \sim 0$
- $(r \cdot s) \cdot x \sim r \cdot (s \cdot x) ?$

Table of Contents

Overview

Semantics for Linear Terms

Semantics for Boolean Terms

Semantics for While Programs

A Language of Boolean Terms and its Semantics

Boolean Terms

$\text{BTerm}(X) \ni t_1 \leq t_2 \mid b \wedge c \mid \neg b$

A Language of Boolean Terms and its Semantics

Boolean Terms

$$\text{BTerm}(X) \ni t_1 \leq t_2 \mid b \wedge c \mid \neg b$$

The expression $\langle b, \sigma \rangle \Downarrow v$ says that the Boolean term b outputs v if the current memory is σ

$$\frac{\langle t_1, \sigma \rangle \Downarrow r_1 \quad \langle t_2, \sigma \rangle \Downarrow r_2 \quad r_1 \leq r_2}{\langle t_1 \leq t_2, \sigma \rangle \Downarrow \text{tt}} \text{ (leq)}$$

$$\frac{\langle t_1, \sigma \rangle \Downarrow r_1 \quad \langle t_2, \sigma \rangle \Downarrow r_2 \quad r_1 \not\leq r_2}{\langle t_1 \leq t_2, \sigma \rangle \Downarrow \text{ff}} \text{ (gtr)}$$

$$\frac{\langle b, \sigma \rangle \Downarrow v}{\langle \neg b, \sigma \rangle \Downarrow \neg v} \text{ (not)}$$

$$\frac{\langle b_1, \sigma \rangle \Downarrow v_1 \quad \langle b_2, \sigma \rangle \Downarrow v_2}{\langle b_1 \wedge b_2, \sigma \rangle \Downarrow v_1 \wedge v_2} \text{ (and)}$$

Table of Contents

Overview

Semantics for Linear Terms

Semantics for Boolean Terms

Semantics for While Programs

A While-language and its Semantics

While-Programs

$\text{Prog}(X) \ni x := t \mid p ; q \mid \text{if } b \text{ then } p \text{ else } q \mid \text{while } b \text{ do } \{ p \}$

$$\frac{\langle t, \sigma \rangle \Downarrow r}{\langle x := t, \sigma \rangle \Downarrow \sigma[r/x]} \text{ (asg)}$$

$$\frac{\langle p, \sigma \rangle \Downarrow \sigma' \quad \langle q, \sigma' \rangle \Downarrow \sigma''}{\langle p ; q, \sigma \rangle \Downarrow \sigma''} \text{ (seq)}$$

$$\frac{\langle b, \sigma \rangle \Downarrow \text{tt} \quad \langle p, \sigma \rangle \Downarrow \sigma'}{\langle \text{if } b \text{ then } p \text{ else } q, \sigma \rangle \Downarrow \sigma'} \text{ (if1)}$$

$$\frac{\langle b, \sigma \rangle \Downarrow \text{ff} \quad \langle q, \sigma \rangle \Downarrow \sigma'}{\langle \text{if } b \text{ then } p \text{ else } q, \sigma \rangle \Downarrow \sigma'} \text{ (if2)}$$

$$\frac{\langle b, \sigma \rangle \Downarrow \text{tt} \quad \langle p, \sigma \rangle \Downarrow \sigma' \quad \langle \text{while } b \text{ do } \{ p \}, \sigma' \rangle \Downarrow \sigma''}{\langle \text{while } b \text{ do } \{ p \}, \sigma \rangle \Downarrow \sigma''} \text{ (wh1)}$$

$$\frac{\langle b, \sigma \rangle \Downarrow \text{ff}}{\langle \text{while } b \text{ do } \{ p \}, \sigma \rangle \Downarrow \sigma} \text{ (wh2)}$$

The Semantics at Work

The program $x := x + 1 ; x := x + 2$ corresponds to the tree



Consider the environment $\sigma = x \mapsto 3$. We build the following derivation tree:

$$\frac{\frac{\langle x + 1, x \mapsto 3 \rangle \Downarrow 4}{\langle x := x + 1, x \mapsto 3 \rangle \Downarrow x \mapsto 4} \quad \frac{\langle x + 2, x \mapsto 4 \rangle \Downarrow 6}{\langle x := x + 2, x \mapsto 4 \rangle \Downarrow x \mapsto 6}}{\langle x := x + 1 ; x := x + 2, x \mapsto 3 \rangle \Downarrow x \mapsto 6}$$

Exercise

- $x := 0 ; y := 1 ; \text{while } x \leq y \text{ do } \{x := x + y ; y := y + 1\} \Downarrow ?$

Equivalence of While-Programs

The previous semantics yields the following notion of **equivalence**:
 $p \sim q$ if for all environments σ

$$\langle p, \sigma \rangle \Downarrow \sigma' \text{ iff } \langle q, \sigma \rangle \Downarrow \sigma'$$

Examples of equivalent terms:

- $x := x + 1 ; x := x + 2 \sim x := x + 3$
- $(p ; q) ; r \sim p ; (q ; r)$

Pause for Meditations

We have just built and implemented our first progr. language

Note that we used its semantics to **run** our programs and also to **prove** properties about them

Which features would you like to add to this language next?

Probabilistic operations or perhaps concurrency?

Next step: add **differential operations**