

Denotational Semantics

Renato Neves



Universidade do Minho



Table of Contents

Outline

Motivation

My first denotational semantics

Denotational semantics for a while-language

Domain theory

Semantics for every season

Operational semantics	How a program operates
<u>Denotational semantics</u>	What a program is
Axiomatic semantics	Which logical properties a program satisfies

Table of Contents

Outline

Motivation

My first denotational semantics

Denotational semantics for a while-language

Domain theory

Compiler correctness and contextual equivalence

We adopted the following notion of equivalence

$$p \equiv_o q \text{ iff } \left(\text{for every } \sigma. \langle p, \sigma \rangle \Downarrow \sigma' \text{ iff } \langle q, \sigma \rangle \Downarrow \sigma' \right)$$

Compiler correctness and contextual equivalence

We adopted the following notion of equivalence

$$p \equiv_o q \text{ iff } \left(\text{for every } \sigma. \langle p, \sigma \rangle \Downarrow \sigma' \text{ iff } \langle q, \sigma \rangle \Downarrow \sigma' \right)$$

Compilers adopt the stronger version

$$p \equiv q \text{ iff } \left(\text{for every context } C. C[p] \equiv_o C[q] \right)$$

Compiler correctness and contextual equivalence

We adopted the following notion of equivalence

$$p \equiv_o q \text{ iff } \left(\text{for every } \sigma. \langle p, \sigma \rangle \Downarrow \sigma' \text{ iff } \langle q, \sigma \rangle \Downarrow \sigma' \right)$$

Compilers adopt the stronger version

$$p \equiv q \text{ iff } \left(\text{for every context } C. C[p] \equiv_o C[q] \right)$$

Why is that ?

Contextual equivalence

Contexts

$C ::= [-] \mid C \wedge b \mid b \wedge C \mid \neg C$

Exercise

Prove the equivalence $b_1 \equiv_o b_2 \iff b_1 \equiv b_2$

Contextual equivalence

Contexts

$$C ::= [-] \mid C \wedge b \mid b \wedge C \mid \neg C$$

Exercise

Prove the equivalence $b_1 \equiv_o b_2 \iff b_1 \equiv b_2$

Homework: repeat the exercise now for arithmetic expressions

Contextual equivalence

Contexts

$C ::= [-] \mid C ; p \mid \text{if } b \text{ then } C \text{ else } p \mid \text{while } b \text{ do } \{ C \} \mid \dots$

Contextual equivalence

Contexts

$C ::= [-] \mid C ; p \mid \text{if } b \text{ then } C \text{ else } p \mid \text{while } b \text{ do } \{ C \} \mid \dots$

Can we still prove $p \equiv_o q \iff p \equiv q$?

Next challenge: programs as part of a mathematical theory

Programming language



Mathematical theory

The latter include e.g.

- functions (recall program calculus)
- linear algebra
- relations
- domain theory (theory of computability and beyond)
- ...

Table of Contents

Outline

Motivation

My first denotational semantics

Denotational semantics for a while-language

Domain theory

Boolean terms and their denotational semantics

$$b ::= x \mid b \wedge b \mid \neg b$$

Terms interpreted as functions $\llbracket b \rrbracket : \text{State} \rightarrow 2$

Term operations interpreted via the boolean algebra 2

$$\llbracket x \rrbracket(\sigma) = \sigma(x)$$

$$\llbracket b_1 \wedge b_2 \rrbracket = (\wedge) \cdot \langle \llbracket b_1 \rrbracket, \llbracket b_2 \rrbracket \rangle$$

$$\llbracket \neg b \rrbracket = (\neg) \cdot \llbracket b \rrbracket$$

The relation between big-step and denotational semantics

Theorem

For every term b and memory σ we have $\langle b, \sigma \rangle \Downarrow v$ iff $\llbracket b \rrbracket(\sigma) = v$

Proof.

Straightforward induction



Corollary

$b_1 \equiv b_2$ iff $b_1 \equiv_o b_2$ iff $\llbracket b_1 \rrbracket = \llbracket b_2 \rrbracket$

We can now reduce checking for equivalence to ...

Program calculus and Boolean algebra

We can now reduce checking for equivalence to ...

Program calculus and Boolean algebra

Example

$$\begin{aligned}\llbracket b_1 \wedge b_2 \rrbracket &= (\wedge) \cdot \langle \llbracket b_1 \rrbracket, \llbracket b_2 \rrbracket \rangle \\ &= (\wedge) \cdot \text{sw} \cdot \langle \llbracket b_1 \rrbracket, \llbracket b_2 \rrbracket \rangle \\ &= (\wedge) \cdot \langle \pi_2, \pi_1 \rangle \cdot \langle \llbracket b_1 \rrbracket, \llbracket b_2 \rrbracket \rangle \\ &= (\wedge) \cdot \langle \pi_2 \cdot \langle \llbracket b_1 \rrbracket, \llbracket b_2 \rrbracket \rangle, \pi_1 \cdot \langle \llbracket b_1 \rrbracket, \llbracket b_2 \rrbracket \rangle \rangle \\ &= (\wedge) \cdot \langle \llbracket b_2 \rrbracket, \llbracket b_1 \rrbracket \rangle \\ &= \llbracket b_2 \wedge b_1 \rrbracket\end{aligned}$$

1. Show that $b \wedge b \equiv b$ via the denotational semantics
2. Define a denotational semantics for arithmetic expressions e
3. Prove that $\llbracket e_1 + e_2 \rrbracket = \llbracket e_2 + e_1 \rrbracket$
4. Prove the equivalence $\langle e, \sigma \rangle \Downarrow v$ iff $\llbracket e \rrbracket(\sigma) = v$

Table of Contents

Outline

Motivation

My first denotational semantics

Denotational semantics for a while-language

Domain theory

Key takeaways

Programs interpreted as functions $\llbracket p \rrbracket : State_{\perp} \rightarrow State_{\perp}$

$State_{\perp} = State \cup \{\perp\}$ where \perp represents non-termination

Sequential composition is function composition

Programs and their denotational semantics

$$p ::= x := e \mid p ; p \mid \text{if } b \text{ then } p \text{ else } p \mid \text{while } b \text{ do } \{ p \}$$

$$\llbracket x := e \rrbracket = \sigma \mapsto \sigma[\llbracket e \rrbracket / x]$$

$$\llbracket p ; q \rrbracket = \llbracket q \rrbracket \cdot \llbracket p \rrbracket$$

$$\llbracket \text{if } b \text{ then } p \text{ else } p \rrbracket = [\llbracket p \rrbracket, \llbracket q \rrbracket] \cdot \text{dist} \cdot \langle \llbracket b \rrbracket, \text{id} \rangle$$

$$\llbracket \text{while } b \text{ do } \{ p \} \rrbracket = \dots\dots$$

The relation between big-step and denotational semantics

Danger, Will Robinson: no while-loops yet ...

Theorem

For every p and σ we have $\langle p, \sigma \rangle \Downarrow \sigma'$ iff $\llbracket p \rrbracket(\sigma) = \sigma'$

Proof.

Straightforward induction



Corollary

$p \equiv q$ iff $p \equiv_o q$ iff $\llbracket p \rrbracket = \llbracket q \rrbracket$

Recall when we had to prove the two equivalences

- $(p ; q) ; r \equiv p ; (q ; r)$
- $(\text{if } b \text{ then } p \text{ else } q) ; r \equiv \text{if } b \text{ then } p ; r \text{ else } q ; r$

with the big-step semantics

Show the same via the denotational semantics

Programs and a (tentative) denotational semantics

$$p ::= x := e \mid p ; p \mid \text{if } b \text{ then } p \text{ else } p \mid \text{while } b \text{ do } \{ p \}$$

$$\llbracket x := e \rrbracket = \sigma \mapsto \sigma[\llbracket e \rrbracket / x]$$

$$\llbracket p ; q \rrbracket = \llbracket q \rrbracket \cdot \llbracket p \rrbracket$$

$$\llbracket \text{if } b \text{ then } p \text{ else } p \rrbracket = [\llbracket p \rrbracket, \llbracket q \rrbracket] \cdot \text{dist} \cdot \langle \llbracket b \rrbracket, \text{id} \rangle$$

$$\llbracket \text{while } b \text{ do } \{ p \} \rrbracket = [\llbracket \text{while } b \text{ do } \{ p \} \rrbracket, \llbracket p \rrbracket] \cdot \text{dist} \cdot \langle \llbracket b \rrbracket, \text{id} \rangle$$

Programs and a (tentative) denotational semantics

$$p ::= x := e \mid p ; p \mid \text{if } b \text{ then } p \text{ else } p \mid \text{while } b \text{ do } \{ p \}$$

$$\llbracket x := e \rrbracket = \sigma \mapsto \sigma[\llbracket e \rrbracket / x]$$

$$\llbracket p ; q \rrbracket = \llbracket q \rrbracket \cdot \llbracket p \rrbracket$$

$$\llbracket \text{if } b \text{ then } p \text{ else } p \rrbracket = [\llbracket p \rrbracket, \llbracket q \rrbracket] \cdot \text{dist} \cdot \langle \llbracket b \rrbracket, \text{id} \rangle$$

$$\llbracket \text{while } b \text{ do } \{ p \} \rrbracket = [\llbracket \text{while } b \text{ do } \{ p \} \rrbracket, \llbracket p \rrbracket] \cdot \text{dist} \cdot \langle \llbracket b \rrbracket, \text{id} \rangle$$

I'm very clear, Brexit does mean brexit

(Theresa May) <https://www.youtube.com/watch?v=oRDfFJAu6Bo>

Table of Contents

Outline

Motivation

My first denotational semantics

Denotational semantics for a while-language

Domain theory

Partially ordered set

Definition (Poset)

A set with a reflexive, anti-symmetric, and transitive relation \leq

Examples

- (\mathbb{N}, \leq) (the usual order \leq on natural numbers)
- (\mathbb{R}, \leq) (the usual order \leq on the real numbers)
- $(X, =)$ (for any set X)

Partially ordered set

Definition (Poset)

A set with a reflexive, anti-symmetric, and transitive relation \leq

Examples

- $(\mathbb{N}, \text{the usual order } \leq \text{ on natural numbers})$
- $(\mathbb{R}, \text{the usual order } \leq \text{ on the real numbers})$
- $(X, =)$ (for any set X)

In our context $x \leq y$ reads as

y more informative than x

New posets from old ones

Addition of a bottom element

If (X, \leq_X) is a poset then (X_\perp, \leq) is a poset when defined as

- $x_1 \leq x_2$ iff $x_1 \leq_X x_2$
- $\perp \leq x$ (for all $x \in X$)

\perp is the least informative element, akin to non-termination

New posets from old ones

Addition of a bottom element

If (X, \leq_X) is a poset then (X_\perp, \leq) is a poset when defined as

- $x_1 \leq x_2$ iff $x_1 \leq_X x_2$
- $\perp \leq x$ (for all $x \in X$)

\perp is the least informative element, akin to non-termination

Example

In what way is $State_\perp$ a poset ?

We will often wish to collect an increasing seq. of information

$$x_1 \leq x_2 \leq x_3 \leq \dots$$

into a single datum, denoted by $\bigvee_{i \in \mathbb{N}} x_i$

We will often wish to collect an increasing seq. of information

$$x_1 \leq x_2 \leq x_3 \leq \dots$$

into a single datum, denoted by $\bigvee_{i \in \mathbb{N}} x_i$

This element should be more informative than any x_j ($j \in \mathbb{N}$), *i.e.*

$$x_j \leq \bigvee_{i \in \mathbb{N}} x_i$$

and contain no more information than the one in the chain, *i.e.*

$$(\forall j \in \mathbb{N}. x_j \leq y) \implies \bigvee_{i \in \mathbb{N}} x_i \leq y$$

Definition (ω -CPO)

A poset with data aggregation as previously described

Examples

- \mathbb{N} is not an ω -CPO but $\mathbb{N} \cup \{\infty\}$ is
- \mathbb{R} is not an ω -CPO but $\mathbb{R} \cup \{\infty\}$ and $[0, 1]$ are

Definition (ω -CPO)

A poset with data aggregation as previously described

Examples

- \mathbb{N} is not an ω -CPO but $\mathbb{N} \cup \{\infty\}$ is
- \mathbb{R} is not an ω -CPO but $\mathbb{R} \cup \{\infty\}$ and $[0, 1]$ are

Exercise

Show that $State_{\perp}$ is an ω -CPO