

COOLANT / SUMP CLEANING

Coolant / Sump Cleaning System

Vacuum-suction sump cleaning for removing chips, swarf and contamination from machine coolant systems, with cleaned coolant returned to the machine.

Catalogue highlights

- No filter element to replace
- Reusable stainless-steel mesh filtration
- Very fine dirt removal from coolant down to 10 micron
- Reduced coolant consumption
- Extended coolant change period
- Reduced machine downtime
- Improved product finish

Applications

- CNC / VMC chips
- Glass grinding
- Chip suction
- Centralized coolant tanks
- Grinding
- Polymer quenching
- Oil suction
- Water filtration

Technical data

Parameter	SC 50	SC 200	SC 300	SC 400	SC 500
Tank capacity (L)	50	200	300	400	500
Basket capacity (L)	10	18	25	25	25
Max. vacuum (mm Hg)	180	200	300	300	300
Vacuum pump motor (HP)	1	3	5	5	5
Dimensions (L x W x H)	34 x 25 x 48 in	60 x 25 x 40 in	70 x 30 x 50 in	82 x 30 x 50 in	98 x 30 x 50 in

Model suitability and current specifications should be confirmed with SHK for the intended application.

Discuss your application with SHK

Share the machine, process, contamination or airflow requirement so SHK can confirm suitability before selection.