

INDUSTRIAL MIST FILTRATION

Air Seiki Industrial Mist Filtration Systems

Mist filtration systems for machine-tool and industrial applications where oil or emulsion mist needs to be captured at source.

Catalogue highlights

- AS AIR5, AIR10, AIR15 and AIR20 MIST models
- 99% filtration efficiency stated by the manufacturer
- Suitable for oil and emulsion mist
- Compact construction
- Mist removal at source
- Three-stage filter cassette arrangement

Applications

- Turning centres
- Surface grinding
- Industrial saws
- Parts washing
- Machining centres
- Cylindrical grinding
- Electro discharge machining
- Food processing

Technical data

Model	Air flow (CMH)	Voltage (V)	Current (A)	Input power (W)	Speed (RPM)	Noise (dB)
AS AIR5 MIST	600	230	0.42	100	2480	70
AS AIR10 MIST	1100	230	0.81	190	2450	71
AS AIR15 MIST	1500	230	1.05	240	2480	79
AS AIR20 MIST	2000	230	1.20	260	1350	64

Required airflow, machine enclosure, mist loading and installation arrangement should be confirmed with SHK before selection.

Discuss your application with SHK

Share the machine, process, contamination or airflow requirement so SHK can confirm suitability before selection.