



Universidad Nacional de San Agustín

Detección de neo antígenos utilizando *deep learning* en el marco del desarrollo de vacunas personalizadas en la inmunoterapia del Cáncer

MSc. Vicente Machaca Arceda

2022-I



Marco teórico

Bioinformática y DNA

Mutaciones

Neo antígenos

Problema y Objetivos

Motivación y Problema

Objetivo

Revisión Sistemática de la Literatura (RSL)

Metodología

Resultados

Propuesta

Resultados

Conclusiones

Trabajos futuros



Marco teórico

Bioinformática y DNA

Mutaciones

Neo antígenos

Problema y Objetivos

Motivación y Problema

Objetivo

Revisión Sistemática de la Literatura (RSL)

Metodología

Resultados

Propuesta

Resultados

Conclusiones

Trabajos futuros




Figure: Where DNA is located [1].

DNA

De DNA a proteínas




Figure: Transcription and translation [2].

Variantes y Mutaciones



Single Nucleotide Variant



Deletion



Insertion



Tandem Duplication



Interspersed Duplication



Inversion



Translocation



Copy Number Variant



Types of Variants

Figure: Example of structural variants. Source: [3]

Variantes y Mutaciones

Frameshift




Figure: Ejemplo de una mutación INDELS causante de un *frameshift*.

Fusión de genes




Figure: Ejemplo de una fusión de genes.

Inmunoterapia del Cáncer



Es un tipo de tratamiento contra el Cáncer que estimula las defensas naturales del cuerpo para combatir el Cáncer [4].




Figure: Ejemplo de como una célula T destruye células del cancer [5].

Inmunoterapia del Cáncer

Neo antígenos



Es una **proteína** que se forma en las células de Cáncer cuando ocurre mutaciones en el DNA, cumplen un rol importante al **estimular una respuesta inmune** [1, 6].

En la actualidad hay varios métodos para detectar a predecir neo antígenos, pero **solo una pequeña cantidad de ellos** logran estimular al sistema inmune [7, 8].

MHC-I




Figure: Presentación de antígenos por MHC-I. Fuente: [9]




Figure: Presentación de antígenos por MHC-II. Fuente: [9]

Inmunoterapia del Cáncer

Generación de vacunas




Figure: Proceso para la generación de vacunas personalizadas [10].



Marco teórico

Bioinformática y DNA

Mutaciones

Neo antígenos

Problema y Objetivos

Motivación y Problema

Objetivo

Revisión Sistemática de la Literatura (RSL)

Metodología

Resultados

Propuesta

Resultados

Conclusiones

Trabajos futuros



El cáncer representa el mayor problema de salud mundial, pero lamentablemente los métodos basados en cirugías, radioterapias, quimioterapias tienen baja efectividad [10].

La inmunoterapia del cáncer es una alternativa para el desarrollo de vacunas personalizadas, pero este proceso depende de una correcta detección de neo antígenos [11, 10].



Menos del **5% de péptidos** detectados en *pMHC binding*, llegan a la membrana de la células. Para *peptide-MHC presentation*, propuestas recientes solo llegan a **0.6 de precisión y 0.4 de recall** [12].

En este contexto, la tesis se enfoca en el problema de *pMHC presentation*, considerándolo como un problema de clasificación binaria, y tomando como entrada la secuencia de aminoácidos del péptido y la secuencia de aminoácidos de la proteína MHC.



Objetivo general

Proponer un método basado en *deep learning* para la detección de neo antígenos, enfocados en el problema de *peptide-MHC presentation*.



Marco teórico

Bioinformática y DNA

Mutaciones

Neo antígenos

Problema y Objetivos

Motivación y Problema

Objetivo

Revisión Sistemática de la Literatura (RSL)

Metodología

Resultados

Propuesta

Resultados

Conclusiones

Trabajos futuros

Table: Cadenas de búsqueda utilizadas en la RSL.

Cadena de búsqueda

neoantigen AND (detection OR pipeline) AND deep learning

(MHC OR HLA) AND binding AND deep learning

(MHC-I OR MHC-II OR MHC OR HLA) AND (peptide OR epitope) AND (binding OR affinity OR prediction OR detection OR presentation)

TCR interaction prediction



Table: Bases de datos utilizadas en la RSL.

Bases de datos

IEEE Xplore

Science Direct

Springer

ACM Digital Library

PubMed

BioRxiv

Table: Criterios de inclusión y exclusión de artículos utilizados en la RSL.

Criterios de inclusión

Artículos con categoría ERA (A, B o C) si son conferencias y Journals Q1, Q2 o Q3.

Sobre *deep learning*

La metodología es detallada.

Tiene repositorio de código fuente y base de datos (de-seable).

Criterios de exclusión

Trabajos de baja calidad, que no esten rankeados.

Table: Cantidad de artículos encontrados y seleccionados según los criterios de inclusión y exclusión en la RSL.

| Año | Artículos encontrados | Artículos seleccionados |
|--------------|------------------------------|--------------------------------|
| 2018 | 57 | 21 |
| 2019 | 72 | 31 |
| 2020 | 86 | 29 |
| 2021 | 61 | 34 |
| 2022 | 58 | 19 |
| Total | 334 | 134 |



Table: List of research since 2018 that uses CNNs for peptide-MHC binding and presentation.

| Year | Ref. | Approach | Name | MHC | Encoding |
|------|------|----------|-------------|-----|--|
| 2022 | [13] | pMHC(b) | DeepMHCII | II | PFR |
| 2021 | [14] | pMHC(b) | DeepImmuno | I | AAindex1 |
| 2021 | [15] | pMHC(p) | APPM | I | One-hot |
| 2021 | [16] | pMHC(p) | MHCfovea | I | One-hot |
| 2021 | [17] | pMHC(b) | CNN-PepPred | II | BLOSUM |
| 2020 | [18] | pMHC(b) | IConMHC | I | PCA and AAindex3 |
| 2020 | [19] | pMHC(b) | OnionMHC | I | BLOSUM and structural features |
| 2020 | [20] | pMHC(p) | MINERVA | I | Physicochemical properties |
| 2019 | [21] | pMHC(b) | CNN-NF | I | Sequence, Hydropathy, Polarity, Length |
| 2019 | [22] | pMHC(b) | DeepSeqPan | I | One-hot |
| 2018 | [23] | pMHC(b) | ConvMHC | I | Contact HLA.peptide side |



Table: List of research since 2018 that uses CNNs s with RNN or attention mechanisms for peptide-MHC binding and presentation. MHCherryPan uses CNN with RNN, the other uses CNN with Attention mechanisms.

| Year | Ref. | Approach | Name | MHC | Encoding |
|------|------|----------|--------------------|-----|----------|
| 2021 | [24] | pMHC(b) | DeepNetBim | I | BLOSUM |
| 2021 | [25] | pMHC(b) | Deep Attention Pan | I | BLOSUM |
| 2019 | [26] | pMHC(b) | ACME | I | BLOSUM |
| 2020 | [27] | pMHC(b) | MHCherryPan | I | BLOSUM |



Table: List of research since 2018 that uses RNNs for peptide-MHC binding and presentation. MATHLA, DeepSeqPanII and DeepHLApan uses RNN with attention mechanisms, meanwhile the other focus on GRU and LSTM.

| Year | Ref. | Approach | Name | MHC | Encoding |
|------|------|----------|---------------|-------|---------------------|
| 2021 | [28] | pMHC(b) | MATHLA | I | BLOSUM |
| 2021 | [29] | pMHC(b) | DeepSeqPanII | II | One-hot and BLO-SUM |
| 2021 | [30] | pMHC(b) | GRU-based RNN | II | Embedding layer |
| 2021 | [31] | pMHC(b) | BVLSTM-MHC | I | One-hot and BLO-SUM |
| 2020 | [32] | pMHC(b) | MHCnuggets | I, II | One-hot |
| 2019 | [33] | pMHC(b) | DeepHLApan | I | One-hot |

Table: List of research since 2018 that uses Transformers (self-attention) for peptide-MHC binding and presentation.

| Year | Ref. | Approach | Name | MHC | Encoding |
|------|------|----------|------------|-----|------------------------------------|
| 2022 | [34] | pMHC(b) | MHCRoBERTa | I | Tokenized from a pre-trained model |
| 2022 | [35] | pMHC(b) | TransPHLA | I | Character embedding model |
| 2021 | [36] | pMHC(b) | BERTMHC | II | Embedding layer |
| 2021 | [37] | pMHC(p) | ImmunoBERT | I | Embedding layer |

Table: Public databases of *pMHC binding*, *pMHC presentation*, *pMHC-TCR interaction*, and 3D structures of proteins.

| Name | Year ref. | Description |
|--------------|-----------|---|
| VDJdb | 2018 [38] | TCR binding to pMHC, contains 5491 samples. |
| IEDB | 2018 [39] | The bigger database, contains information <i>T-cell epitopes</i> |
| TSNAdb | 2018 [40] | It contains 7748 samples of mutations and HLA of 16 types of cancer. |
| NeoPeptide | 2019 [41] | It contains samples of neoantigens resulting from somatic mutations and related items. 1818137 epitopes of more than 36000 neoantigens. |
| pHLA3D | 2019 [42] | Presents 106 3D structures of the alpha, <i>beta2M</i> chains, and peptides of HLA-I molecules |
| dbPepNeo | 2020 [43] | It has validated samples of the <i>peptide-MHC</i> bond, from MS. It contains 407794 low-quality samples, 247 medium-quality, and 295 high-quality samples. |
| dbPepNeo2.0 | 2022 [44] | It gathers a list of neoantigens and HLA molecules. It presents 801 high-quality and 842,289 poor-quality HLAs. Also, 55 class II neoantigens and 630 TCR-bound neo antigens. |
| IntroSpect | 2022 [45] | Tool for building databases on <i>peptide-MHC binding</i> . It uses data from <i>Mass Spectrometry</i> . |
| IPD-IMGT/HLA | 2022 [46] | With 25000 MHC molecules and 45 alleles. |

Table: List of *pipelines* since 2018 for the detection of neoantigens.

| Name | Year ref. | Input | Output |
|--------------|-----------|---|--|
| Neopepsee | 2018 [47] | RNA-seq, somatic mutations (VCF), HLA type (optional) | Neoantigens and gene expression levels |
| PGV Pipeline | 2018 [48] | DNA-seq | Neoantigens |
| ScanNeo | 2019 [49] | RNA-seq | Neoantigens |
| NeoPredPipe | 2019 [50] | Mutations (VCF) y HLA type | Neoantigens and variant annotation |
| pVACtools | 2020 [51] | Mutations (VCF) | Neoantigens |
| ProGeo-neo | 2020 [52] | RNA-seq y somatic mutations (VCF) | Neoantigens |
| Neopepscope | 2020 [53] | Somatic mutations (VCF) and BAM files | Neoantigens and mutations |
| NeoANT-HILL | 2020 [54] | RNA-seq y somatic mutations (VCF) | Neoantigens and gene expression levels |
| NAP-CNB | 2021 [55] | RNA-seq | Neoantigens |
| PEPPRMIT | 2021 [56] | DNA-seq | Neoantigens |
| Valid-NEO | 2022 [57] | Somatic mutations (VCF), HLA type (optional) | Neoantigens |



Marco teórico

Bioinformática y DNA

Mutaciones

Neo antígenos

Problema y Objetivos

Motivación y Problema

Objetivo

Revisión Sistemática de la Literatura (RSL)

Metodología

Resultados

Propuesta

Resultados

Conclusiones

Trabajos futuros

La propuesta se basa en los modelos BERTMHC [36] y APPM [8]. También, se utilizará *transfer learning* de ESM-1b [58], esta red neuronal fue entrenada con 250 millones de proteínas a diferencia de TAPE (utilizada por BERTMHC), que fue entrenada con 30 millones de proteínas.




Figure: Proceso general utilizado para la detección de neo antígenos a partir de secuencias de DNA. Fuente: [59].




Figure: BERTMHC.





Figure: Proceso para obtener una matriz (imagen) a partir de un péptido (APPM).



Marco teórico

Bioinformática y DNA

Mutaciones

Neo antígenos

Problema y Objetivos

Motivación y Problema

Objetivo

Revisión Sistemática de la Literatura (RSL)

Metodología

Resultados

Propuesta

Resultados

Conclusiones

Trabajos futuros




Table: Cantidad de muestras por tipo de *allele*.

| <i>Alleles</i> | Label = 1 | Label = 0 | Train | Test |
|-----------------------|------------------|------------------|--------------|-------------|
| A*01:01 | 3398 | 48700 | 45498 | 6600 |
| A*02:01 | 6779 | 165342 | 160921 | 11200 |
| A*02:03 | 1780 | 116299 | 107879 | 10200 |
| A*31:01 | 1879 | 45918 | 41597 | 6200 |
| B*44:02 | 1525 | 44760 | 40085 | 6200 |
| B*44:03 | 1487 | 39482 | 34769 | 6200 |
| MHC-II alleles | 1917 | 496 | 1533 | 384 |




Table: Resultados obtenidos en cada base de datos.


| <i>Allele</i> | <i>Accuracy</i> | <i>F1 score</i> | <i>Precision</i> | <i>Recall</i> |
|----------------------|------------------------|------------------------|-------------------------|----------------------|
| A*01:01 | 0.978 | 0.917 | 0.982 | 0.887 |
| A*0201 | 0.962 | 0.956 | 0.965 | 0.948 |
| A*02:03 | 0.992 | 0.979 | 0.994 | 0.969 |
| A*31:01 | 0.980 | 0.968 | 0.989 | 0.951 |
| B*44:02 | 0.991 | 0.981 | 0.968 | 0.997 |
| B*44:03 | 0.992 | 0.987 | 0.995 | 0.980 |




(a) A*01:01



(b) A*02:01



(c) A*02:03



(d) A*31:01

Figure: Accuracy durante cada *epoch*, para cada base de datos. Las bases de datos representan las células HLA A*01:01, A*02:01, A*02:03, A*31:01.



Marco teórico

Bioinformática y DNA

Mutaciones

Neo antígenos

Problema y Objetivos

Motivación y Problema

Objetivo

Revisión Sistemática de la Literatura (RSL)

Metodología

Resultados

Propuesta

Resultados

Conclusiones

Trabajos futuros



Se ha desarrollado una RSL, sobre los métodos de detección de neoantígenos utilizando *deep learning*. Esto ha logrado identificar las tendencias, retos y problemas del tema de interes.

Se ha realizado experimentos preliminares, sobre el uso de CNNs para el problema de peptide-MHC presentation. Se ha utilizado muestras de MS con un enfoque *single allele* (se entrena varios modelos para cada tipo de MHC).



Marco teórico

Bioinformática y DNA

Mutaciones

Neo antígenos

Problema y Objetivos

Motivación y Problema

Objetivo

Revisión Sistemática de la Literatura (RSL)

Metodología

Resultados

Propuesta

Resultados


Conclusiones

Trabajos futuros



Recientemente un trabajo [60] también propone el uso de *transfer learning* pero de un modelo pre-entrenado con 250 millones de proteínas. Entonces, se plantea utilizar la misma red, aumentar la cantidad de muestras y evaluar los resultados.

Actualmente se cuenta con una base de datos de proteínas MHC [42], entonces utilizando AlphaFold de Google, se plantea predecir la estructura de varios péptidos y analizar el enlace péptido-MHC desde un punto de vista de la computación gráfica.




- [1] NCI, “National cancer institute dictionary,” 2022. [Online]. Available: <https://www.cancer.gov/publications/dictionaries/genetics-dictionary>
- [2] —, “Nci dictionary of cancer terms,” <https://www.cancer.gov/publications/dictionaries/cancer-terms/def/transcription>, 2020, accessed: 2020-03-20.
- [3] PacBio, “Two review articles assess structural variation in human genomes,” <https://www.pacb.com/blog/two-review-articles-assess-structural-variation-in-human-genomes/>, 2021, accessed: 2021-05-07. [Online]. Available: <https://www.pacb.com/blog/two-review-articles-assess-structural-variation-in-human-genomes/>



- [4] Cancer.net. (2022) Qué es la inmunoterapia. [Online]. Available: <https://www.cancer.net/es/desplazarse-por-atencion-del-cancer/como-se-trata-el-cancer/inmunoterapia/que-es-la-inmunoterapia>
- [5] NortShore, “Immunotherapy,” 2022. [Online]. Available: <https://www.northshore.org/kellogg-cancer-center/our-services/immunotherapy/>
- [6] E. S. Borden, K. H. Buetow, M. A. Wilson, and K. T. Hastings, “Cancer neoantigens: Challenges and future directions for prediction, prioritization, and validation,” *Frontiers in Oncology*, vol. 12, 2022.
- [7] I. Chen, M. Chen, P. Goedegebuure, and W. Gillanders, “Challenges targeting cancer neoantigens in 2021: a systematic literature review,” *Expert Review of Vaccines*, vol. 20, no. 7, pp. 827–837, 2021.



- [8] Q. Hao, P. Wei, Y. Shu, Y.-G. Zhang, H. Xu, and J.-N. Zhao, "Improvement of neoantigen identification through convolution neural network," *Frontiers in immunology*, vol. 12, 2021.
- [9] X. Zhang, Y. Qi, Q. Zhang, and W. Liu, "Application of mass spectrometry-based mhc immunopeptidome profiling in neoantigen identification for tumor immunotherapy," *Biomedicine & Pharmacotherapy*, vol. 120, p. 109542, 2019.
- [10] M. Peng, Y. Mo, Y. Wang, P. Wu, Y. Zhang, F. Xiong, C. Guo, X. Wu, Y. Li, X. Li *et al.*, "Neoantigen vaccine: an emerging tumor immunotherapy," *Molecular cancer*, vol. 18, no. 1, pp. 1–14, 2019.




- [11] L. Mattos, M. Vazquez, F. Finotello, R. Lepore, E. Porta, J. Hundal, P. Amengual-Rigo, C. Ng, A. Valencia, J. Carrillo *et al.*, “Neoantigen prediction and computational perspectives towards clinical benefit: recommendations from the esmo precision medicine working group,” *Annals of oncology*, vol. 31, no. 8, pp. 978–990, 2020.
- [12] N. A. Mill, C. Bogaert, W. van Criekinge, and B. Fant, “neoms: Attention-based prediction of mhc-i epitope presentation,” *bioRxiv*, 2022.
- [13] R. You, W. Qu, H. Mamitsuka, and S. Zhu, “Deepmhcii: a novel binding core-aware deep interaction model for accurate mhc-ii peptide binding affinity prediction,” *Bioinformatics*, vol. 38, no. Supplement_1, pp. i220–i228, 2022.



- [14] G. Li, B. Iyer, V. S. Prasath, Y. Ni, and N. Salomonis, “Deepimmuno: deep learning-empowered prediction and generation of immunogenic peptides for t-cell immunity,” *Briefings in bioinformatics*, vol. 22, no. 6, p. bbab160, 2021.
- [15] F. Lang, P. Riesgo-Ferreiro, M. L’ower, U. Sahin, and B. Schr’ors, “Neofox: annotating neoantigen candidates with neoantigen features,” *Bioinformatics*, vol. 37, no. 22, pp. 4246–4247, 2021.
- [16] K.-H. Lee, Y.-C. Chang, T.-F. Chen, H.-F. Juan, H.-K. Tsai, and C.-Y. Chen, “Connecting mhc-i-binding motifs with hla alleles via deep learning,” *Communications Biology*, vol. 4, no. 1, pp. 1–12, 2021.




- [17] V. Junet and X. Daura, “Cnn-peppred: an open-source tool to create convolutional nn models for the discovery of patterns in peptide sets—application to peptide–mhc class ii binding prediction,” *Bioinformatics*, vol. 37, no. 23, pp. 4567–4568, 2021.
- [18] B. Pei and Y.-H. Hsu, “Iconmhc: a deep learning convolutional neural network model to predict peptide and mhc-i binding affinity,” *Immunogenetics*, vol. 72, no. 5, pp. 295–304, 2020.
- [19] S. Saxena, S. Animesh, M. J. Fullwood, and Y. Mu, “Onionmhc: A deep learning model for peptide—hla-a* 02: 01 binding predictions using both structure and sequence feature sets,” *Journal of Micromechanics and Molecular Physics*, vol. 5, no. 03, p. 2050009, 2020.




- [20] F. S. Ng, M. Vandenberghe, G. Portella, C. Cayatte, X. Qu, S. Hanabuchi, A. Landry, R. Chaerkady, W. Yu, R. Collepardo-Guevara *et al.*, “Minerva: Learning the rules of hla class i peptide presentation in tumors with convolutional neural networks and transfer learning,” *Available at SSRN 3704016*, 2020.
- [21] T. Zhao, L. Cheng, T. Zang, and Y. Hu, “Peptide-major histocompatibility complex class i binding prediction based on deep learning with novel feature,” *Frontiers in Genetics*, vol. 10, p. 1191, 2019.
- [22] Z. Liu, Y. Cui, Z. Xiong, A. Nasiri, A. Zhang, and J. Hu, “Deepseqpan, a novel deep convolutional neural network model for pan-specific class i hla-peptide binding affinity prediction,” *Scientific reports*, vol. 9, no. 1, pp. 1–10, 2019.



- [23] Y. Han, “Deep convolutional neural networks for peptide-mhc binding predictions,” 2018.
- [24] X. Yang, L. Zhao, F. Wei, and J. Li, “Deepnetbim: deep learning model for predicting hla-epitope interactions based on network analysis by harnessing binding and immunogenicity information,” *BMC bioinformatics*, vol. 22, no. 1, pp. 1–16, 2021.
- [25] J. Jin, Z. Liu, A. Nasiri, Y. Cui, S.-Y. Louis, A. Zhang, Y. Zhao, and J. Hu, “Deep learning pan-specific model for interpretable mhc-i peptide binding prediction with improved attention mechanism,” *Proteins: Structure, Function, and Bioinformatics*, vol. 89, no. 7, pp. 866–883, 2021.



- [26] Y. Hu, Z. Wang, H. Hu, F. Wan, L. Chen, Y. Xiong, X. Wang, D. Zhao, W. Huang, and J. Zeng, “Acme: pan-specific peptide–mhc class i binding prediction through attention-based deep neural networks,” *Bioinformatics*, vol. 35, no. 23, pp. 4946–4954, 2019.
- [27] X. Xie, Y. Han, and K. Zhang, “Mhcherrypan: a novel pan-specific model for binding affinity prediction of class i hla-peptide,” *International Journal of Data Mining and Bioinformatics*, vol. 24, no. 3, pp. 201–219, 2020.
- [28] Y. Ye, J. Wang, Y. Xu, Y. Wang, Y. Pan, Q. Song, X. Liu, and J. Wan, “Mathla: a robust framework for hla-peptide binding prediction integrating bidirectional lstm and multiple head attention mechanism,” *BMC bioinformatics*, vol. 22, no. 1, pp. 1–12, 2021.




- [29] Z. Liu, J. Jin, Y. Cui, Z. Xiong, A. Nasiri, Y. Zhao, and J. Hu, “Deepseqpanii: an interpretable recurrent neural network model with attention mechanism for peptide-hla class ii binding prediction,” *IEEE/ACM Transactions on Computational Biology and Bioinformatics*, 2021.
- [30] Y. Heng, Z. Kuang, W. Xie, H. Lan, S. Huang, L. Chen, T. Shi, L. Xu, X. Pan, and H. Mei, “A simple pan-specific rnn model for predicting hla-ii binding peptides,” *Molecular Immunology*, vol. 139, pp. 177–183, 2021.
- [31] L. Jiang, H. Yu, J. Li, J. Tang, Y. Guo, and F. Guo, “Predicting mhc class i binder: existing approaches and a novel recurrent neural network solution,” *Briefings in Bioinformatics*, vol. 22, no. 6, p. bbab216, 2021.



- [32] X. M. Shao, R. Bhattacharya, J. Huang, I. Sivakumar, C. Tokheim, L. Zheng, D. Hirsch, B. Kaminow, A. Omdahl, M. Bonsack *et al.*, “High-throughput prediction of mhc class i and ii neoantigens with mhc nuggets,” *Cancer immunology research*, vol. 8, no. 3, pp. 396–408, 2020.
- [33] J. Wu, W. Wang, J. Zhang, B. Zhou, W. Zhao, Z. Su, X. Gu, J. Wu, Z. Zhou, and S. Chen, “Deephlapan: a deep learning approach for neoantigen prediction considering both hla-peptide binding and immunogenicity,” *Frontiers in Immunology*, p. 2559, 2019.
- [34] F. Wang, H. Wang, L. Wang, H. Lu, S. Qiu, T. Zang, X. Zhang, and Y. Hu, “Mhc roberta: pan-specific peptide–mhc class i binding prediction through transfer learning with label-agnostic protein sequences,” *Briefings in Bioinformatics*, vol. 23, no. 3, p. bbab595, 2022.



- [35] Y. Chu, Y. Zhang, Q. Wang, L. Zhang, X. Wang, Y. Wang, D. R. Salahub, Q. Xu, J. Wang, X. Jiang *et al.*, “A transformer-based model to predict peptide–hla class i binding and optimize mutated peptides for vaccine design,” *Nature Machine Intelligence*, vol. 4, no. 3, pp. 300–311, 2022.
- [36] J. Cheng, K. Bendjama, K. Rittner, and B. Malone, “Bertmhc: improved mhc–peptide class ii interaction prediction with transformer and multiple instance learning,” *Bioinformatics*, vol. 37, no. 22, pp. 4172–4179, 2021.
- [37] H.-C. Gasser, G. Bedran, B. Ren, D. Goodlett, J. Alfaro, and A. Rajan, “Interpreting bert architecture predictions for peptide presentation by mhc class i proteins,” *arXiv preprint arXiv:2111.07137*, 2021.



- [38] M. Shugay, D. V. Bagaev, I. V. Zvyagin, R. M. Vroomans, J. C. Crawford, G. Dolton, E. A. Komech, A. L. Sycheva, A. E. Koneva, E. S. Egorov *et al.*, “Vdjdb: a curated database of t-cell receptor sequences with known antigen specificity,” *Nucleic acids research*, vol. 46, no. D1, pp. D419–D427, 2018.
- [39] R. Vita, S. Mahajan, J. A. Overton, S. K. Dhanda, S. Martini, J. R. Cantrell, D. K. Wheeler, A. Sette, and B. Peters, “The immune epitope database (iedb): 2018 update,” *Nucleic acids research*, vol. 47, no. D1, pp. D339–D343, 2018.
- [40] J. Wu, W. Zhao, B. Zhou, Z. Su, X. Gu, Z. Zhou, and S. Chen, “Tsnadb: a database for tumor-specific neoantigens from immunogenomics data analysis,” *Genomics, proteomics & bioinformatics*, vol. 16, no. 4, pp. 276–282, 2018.



- [41] W.-J. Zhou, Z. Qu, C.-Y. Song, Y. Sun, A.-L. Lai, M.-Y. Luo, Y.-Z. Ying, H. Meng, Z. Liang, Y.-J. He *et al.*, “Neopeptide: an immunoinformatic database of t-cell-defined neoantigens,” *Database*, vol. 2019, 2019.
- [42] D. M. T. Oliveira, R. M. S. de Serpa Brandão, L. C. D. da Mata Sousa, F. d. C. A. Lima, S. J. H. do Monte, M. S. C. Marroquim, A. V. de Sousa Lima, A. G. B. Coelho, J. M. S. Costa, R. M. Ramos *et al.*, “phla3d: An online database of predicted three-dimensional structures of hla molecules,” *Human Immunology*, vol. 80, no. 10, pp. 834–841, 2019.
- [43] X. Tan, D. Li, P. Huang, X. Jian, H. Wan, G. Wang, Y. Li, J. Ouyang, Y. Lin, and L. Xie, “dbpepneo: a manually curated database for human tumor neoantigen peptides,” *Database*, vol. 2020, 2020.



- [44] M. Lu, L. Xu, X. Jian, X. Tan, J. Zhao, Z. Liu, Y. Zhang, C. Liu, L. Chen, Y. Lin *et al.*, “dbpepneo2. 0: A database for human tumor neoantigen peptides from mass spectrometry and tcr recognition,” *Frontiers in immunology*, p. 1583, 2022.
- [45] L. Zhang, G. Liu, G. Hou, H. Xiang, X. Zhang, Y. Huang, X. Zhang, B. Li, and L. J. Lee, “Introspect: Motif-guided immunopeptidome database building tool to improve the sensitivity of hla i binding peptide identification by mass spectrometry,” *Biomolecules*, vol. 12, no. 4, p. 579, 2022.
- [46] J. Robinson, D. J. Barker, X. Georgiou, M. A. Cooper, P. Flicek, and S. G. Marsh, “Ipd-imgt/hla database,” *Nucleic acids research*, vol. 48, no. D1, pp. D948–D955, 2020.



- [47] S. Kim, H. S. Kim, E. Kim, M. Lee, E.-C. Shin, and S. Paik, “Neopepsee: accurate genome-level prediction of neoantigens by harnessing sequence and amino acid immunogenicity information,” *Annals of Oncology*, vol. 29, no. 4, pp. 1030–1036, 2018.
- [48] A. Rubinsteyn, J. Kodysh, I. Hodes, S. Mondet, B. A. Aksoy, J. P. Finnigan, N. Bhardwaj, and J. Hammerbacher, “Computational pipeline for the pgv-001 neoantigen vaccine trial,” *Frontiers in immunology*, vol. 8, p. 1807, 2018.
- [49] T.-Y. Wang, L. Wang, S. K. Alam, L. H. Hoepfner, and R. Yang, “Scanneo: identifying indel-derived neoantigens using rna-seq data,” *Bioinformatics*, vol. 35, no. 20, pp. 4159–4161, 2019.



- [50] R. O. Schenck, E. Lakatos, C. Gatenbee, T. A. Graham, and A. R. Anderson, “Neopredpipe: high-throughput neoantigen prediction and recognition potential pipeline,” *BMC bioinformatics*, vol. 20, no. 1, pp. 1–6, 2019.
- [51] J. Hundal, S. Kiwala, J. McMichael, C. A. Miller, H. Xia, A. T. Wollam, C. J. Liu, S. Zhao, Y.-Y. Feng, A. P. Graubert *et al.*, “pvactools: a computational toolkit to identify and visualize cancer neoantigens,” *Cancer immunology research*, vol. 8, no. 3, pp. 409–420, 2020.
- [52] Y. Li, G. Wang, X. Tan, J. Ouyang, M. Zhang, X. Song, Q. Liu, Q. Leng, L. Chen, and L. Xie, “Progeo-neo: a customized proteogenomic workflow for neoantigen prediction and selection,” *BMC medical genomics*, vol. 13, no. 5, pp. 1–11, 2020.



- [53] M. A. Wood, A. Nguyen, A. J. Struck, K. Ellrott, A. Nellore, and R. F. Thompson, “Neoepiscopes improves neoepitope prediction with multivariant phasing,” *Bioinformatics*, vol. 36, no. 3, pp. 713–720, 2020.
- [54] A. C. M. Coelho, A. L. Fonseca, D. L. Martins, P. B. Lins, L. M. da Cunha, and S. J. de Souza, “neoant-hill: an integrated tool for identification of potential neoantigens,” *BMC Medical Genomics*, vol. 13, no. 1, pp. 1–8, 2020.
- [55] C. Wert-Carvajal, R. Sánchez-García, J. R. Macías, R. Sanz-Pamplona, A. M. Pérez, R. Alemany, E. Veiga, C. Ó. S. Sorzano, and A. Muñoz-Barrutia, “Predicting mhc i restricted t cell epitopes in mice with nap-cnb, a novel online tool,” *Scientific reports*, vol. 11, no. 1, pp. 1–10, 2021.



- [56] L. Y. Zhou, F. Zou, and W. Sun, "Prioritizing candidate peptides for cancer vaccines by peppermint: a statistical model to predict peptide presentation by hla-i proteins," *bioRxiv*, 2021.
- [57] Y. L. Terai, C. Huang, B. Wang, X. Kang, J. Han, J. Douglass, E. H.-C. Hsiue, M. Zhang, R. Purohit, T. deSilva *et al.*, "Valid-neo: A multi-omics platform for neoantigen detection and quantification from limited clinical samples," *Cancers*, vol. 14, no. 5, p. 1243, 2022.
- [58] A. Rives, J. Meier, T. Sercu, S. Goyal, Z. Lin, J. Liu, D. Guo, M. Ott, C. L. Zitnick, J. Ma *et al.*, "Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences," *Proceedings of the National Academy of Sciences*, vol. 118, no. 15, 2021.



- [59] A. V. Gopanenko, E. N. Kosobokova, and V. S. Kosorukov, "Main strategies for the identification of neoantigens," *Cancers*, vol. 12, no. 10, p. 2879, 2020.
- [60] N. Hashemi, B. Hao, M. Ignatov, I. Paschalidis, P. Vakili, S. Vajda, and D. Kozakov, "Improved predictions of mhc-peptide binding using protein language models," *bioRxiv*, 2022.

