

H.W Interpolation search

H.W :-

Binary search

### LAB-ASSIGNMENT 3 (Array and Pointer)

SUBJECT: Computer Lab. SUBJECT CODE: CS111. SEMESTER: I

1. Write a C program to take N numbers as an input in an array and print them.
2. Write a C program to insert a number in a given position in an array.
3. Write a C program to delete a number in a given position in an array.
4. Write a C program to search a number in an array and also print the position of the input number.
5. Write a C program to sort an array element. (insertion, bubble, selection)
6. Write a C program to print the address of a given input.
7. Write a C program to count the number of vowel and consonant in a character array.
8. Write a C program to take M X N matrix as an input and print the matrix properly.
9. Write a C program to addition and subtraction of two matrices.
10. Write a C program to transpose of a matrix.
11. Write a C program to multiplication of two matrices.
12. Write a C program to addition and subtraction of two matrices (using pointer and malloc() function).

if (a[i] = 'a' || 'e' || 'i' || 'o' || 'u') scanf("%d", &a)

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
int a[1000], i, n;
```

$a[100]$

```
printf("Enter size of array: ");
```

```
scanf("%d", &n);
```

```
printf("Enter %d elements in the array : ", n);
```

```
for(i=0; i < n; i++)
```

```
{
```

```
scanf("%d", &a[i]);
```

```
}
```

```
printf("\nElements in array are: ");
```

```
for(i=0; i < n; i++)
```

```
{
```

```
printf("%d ", a[i]);
```

```
}
```


```
return 0;
```

```
}
```

0	1	2	3	4		...
5	10	2	30	40		

for (i=0; i < n; i++)  
printf("%d", a[i]);

### Insert an element at a specific position in an Array



EG

1. First get the element to be inserted, say x
2. Then get the position at which this element is to be inserted, say pos
3. Then shift the array elements from this position to one position forward, and do this for all the other elements next to pos.
4. Insert the element x now at the position pos, as this is now empty.

// C Program to Insert an element  
// at a specific position in an Array

#include <stdio.h>

int main()  
{

int arr[100] = { 0 };  
int i, x, pos, n = 10;

// initial array of size 10  
for (i = 0; i < 10; i++)  
arr[i] = i + 1;

// print the original array  
for (i = 0; i < n; i++)  
printf("%d ", arr[i]);  
printf("\n");

// element to be inserted  
x = 50;



// position at which element  
// is to be inserted  
pos = 5;

// increase the size by 1  
n++;


// shift elements forward  
for (i = n-1; i >= pos; i--)  
arr[i] = arr[i - 1];

// insert x at pos  
arr[pos - 1] = x;

// print the updated array



$$a[i] = a[i-1]$$



$$a[pos-1] = x$$

$$a[3-1] =$$

$$a[2] = 10$$



```
for (i = 0; i < n; i++)  
    printf("%d ", arr[i]);  
printf("\n");  
  
return 0;
```

```
}
```

## Delete element from an array

Array



0	5	1	-3	2	7	3	6	4	2	5	1	6	8	7	3	8	0	9	4
---	---	---	----	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---



Array after deleting element at index 6

0	5	1	-3	2	7	3	6	4	2	5	1	6	3	7	0	8	4	9	4
---	---	---	----	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---



programmingsimplified.com

C program to delete an element in an array: This program deletes or removes an element from an array. A user will enter the position at which the array element deletion is required. Deleting an element does not affect the size of the array. It also checks whether deletion is possible or not, for example, if an array contains five elements and user wants to delete the element at the sixth position, it isn't possible.

Remove element from array C program

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int array[100], position, c, n;
```

```
printf("Enter number of elements in array\n");  
scanf("%d", &n);
```

```
printf("Enter %d elements\n", n);
```

```
for (c = 0; c < n; c++)  
    scanf("%d", &array[c]);
```

```
printf("Enter the location where you wish to delete element\n");  
scanf("%d", &position);
```

```
if (position >= n+1)  
    printf("Deletion not possible.\n");  
else
```

```
{  
    for (c = position - 1; c < n - 1; c++)  
        array[c] = array[c+1];
```

```
    printf("Resultant array:\n");
```

```
    for (c = 0; c < n - 1; c++)  
        printf("%d\n", array[c]);  
}
```

```
return 0;  
}
```

```
/* Linear search in an array*/
```



```

//LINEAR SEARCH
#include <stdio.h>
#define MAX 50
int main(void)
{
    int i=0,n,item,arr[MAX];
    printf("Enter the number of elements : ");
    scanf("%d",&n);
    printf("Enter the elements : \n");
    for(i=0; i<n; i++)
        scanf("%d", &arr[i]);
    printf("Enter the item to be searched : ");
    scanf("%d", &item);
    for(i=0;i<n;i++)
        if(arr[i]==item)
        {
            printf("%d is present at location %d.\n", item, i+1);
            break;
        }


    if (i == n)
        printf("%d isn't present in the array.\n", item);

    return 0;
}

```

Worst Case  
 $O(n)$

Linear searching





```

//BINARY SEARCH

#include <stdio.h>

int main()
{
    int i, low, high, mid, n, key, array[100];
    printf("Enter number of elements.....");
    scanf("%d",&n);
    printf("Enter %d integers", n);
    for(i = 0; i < n; i++)
        scanf("%d",&array[i]);
    printf("Enter value to find_____");
    scanf("%d", &key);
    low = 0;
    high = n - 1;
    mid = (low+high)/2;
    while (low <= high) {
        if(array[mid] < key)
            low = mid + 1;
        else if (array[mid] == key) {
            printf("%d found at location %d", key, mid+1);
            break;
        }
        else
            high = mid - 1;
        mid = (low + high)/2;
    }
    if(low > high)

```

```
printf("Not found! %d isn't present in the list", key);  
return 0;  
}
```

# 2D Array

int a[3][2] = { ~~{1, 2, 3}, {4, 5, 6}~~ } { {1, 2}, {3, 4}, {5, 6} } ;

no of rows no of columns

0th row  
1st row  
2nd row

1	2
3	4
5	6

0th row  
1st row  
2nd row

0th col  
1st col

a<sub>00</sub> a<sub>01</sub>  
a<sub>10</sub> a<sub>11</sub>  
a<sub>20</sub> a<sub>21</sub>

int a[5] = {10, 20, 30, 40, 50};

10	20	30	40	50
----	----	----	----	----

a[0][0] a[1][0]  
a[0][1] a[1][1]  
a[0][2] a[1][2]

{ for (i=0; i<n; i++)  
{ for (j=0; j<m; j++)  
scanf ("%d", &a[i][j]);

row major order

a<sub>00</sub> → 104

a <sub>00</sub>	a <sub>01</sub>	a <sub>02</sub>	a <sub>10</sub>	a <sub>11</sub>	a <sub>12</sub>	a <sub>20</sub>	a <sub>21</sub>	a <sub>22</sub>
100	104	108	112	116	120	124	128	

a <sub>00</sub>	a <sub>01</sub>	a <sub>02</sub>
a <sub>10</sub>	a <sub>11</sub>	a <sub>12</sub>
a <sub>20</sub>	a <sub>21</sub>	a <sub>22</sub>

Column major order

Column major order

100	104	108	112	116	120	124		
$a_{00}$	$a_{10}$	$a_{20}$	$a_{01}$	$a_{11}$	$a_{21}$	$a_{02}$	$a_{12}$	$a_{22}$

$\phi(x)$

addition

```
for (i=0; i<N; i++)  
    for (j=0; j<M; j++)  
        printf ("%d", a[i][j]);
```

$$a = \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix} \quad b = \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$$

$$c = a + b = \begin{bmatrix} 2 & 4 & 6 \\ 8 & 10 & 12 \\ 14 & 16 & 18 \end{bmatrix}$$

take 1st Matrix  $a[i][j]$   
take 2nd Matrix  $b[i][j]$

for ( $i=0; i < n; i++$ )

{ for ( $j=0; j < n; j++$ )

$c[i][j] = a[i][j] + b[i][j];$

for ( $i=0; i < n; i++$ )

{ for ( $j=0; j < n; j++$ )

printf ("%d",  $c[i][j]$ );

Transpose

$$a = \begin{bmatrix} a_{00} & a_{01} \\ a_{10} & a_{11} \\ a_{20} & a_{21} \end{bmatrix} \quad a^T = \begin{bmatrix} a_{00} & a_{10} & a_{20} \\ a_{01} & a_{11} & a_{21} \end{bmatrix}$$

$$a = \begin{bmatrix} 1 & 2 & 3 & 4 \\ 5 & 6 & 7 & 8 \\ 9 & 10 & 11 & 12 \end{bmatrix} \quad a^T = \begin{bmatrix} 1 & 5 & 9 \\ 2 & 6 & 10 \\ 3 & 7 & 11 \\ 4 & 8 & 12 \end{bmatrix}$$

## Matrix Multiplication

$$\begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix} * \begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix} = \begin{bmatrix} 1*1 + 2*3 & 1*2 + 2*4 \\ 3*1 + 4*3 & 3*2 + 4*4 \end{bmatrix} = \begin{bmatrix} 7 & 10 \\ 15 & 22 \end{bmatrix}$$



$O(n^2)$

$O(n^3)$

Strings.

array of type char

A

"deba yan"


deba yan | gan guly

gets (str)  
puts (str)


buffer:-

A temporary storage area.

buffer  
4 1



gets (str);



strlen()

debayan - ganguly/o    o/p:- 15

✓ \* Multiplication

✓ \* implement strlen() without using library function

strcpy()  
strupr()  
strrev()

↓ x  
{ while (str[i] != '\0')  
    count++;