

# Rajalakshmi Engineering College

Name: archana dhananchezhiyan  
Email: 241801026@rajalakshmi.edu.in  
Roll no: 241801026  
Phone: 6381992402  
Branch: REC  
Department: I AI & DS FA  
Batch: 2028  
Degree: B.E - AI & DS

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 7\_COD\_Question 1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Ravi is building a basic hash table to manage student roll numbers for quick lookup. He decides to use Linear Probing to handle collisions.

Implement a hash table using linear probing where:

The hash function is:  $\text{index} = \text{roll\_number} \% \text{table\_size}$  On collision, check subsequent indexes (i+1, i+2, ...) until an empty slot is found.

You need to:

Insert a list of n student roll numbers into the hash table. Print the final state of the hash table. If a slot is empty, print -1.

##### ***Input Format***

The first line of the input contains two integers n and table\_size, where n is the

number of roll numbers to be inserted, and table\_size is the size of the hash table.

The second line contains n space-separated integers — the roll numbers to insert into the hash table.

### **Output Format**

The output should print a single line with table\_size space-separated integers representing the final state of the hash table after all insertions.

If any slot remains unoccupied, it should be represented as -1.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 4 7

50 700 76 85

Output: 700 50 85 -1 -1 -1 76

### **Answer**

```
#include <stdio.h>
```

```
#define MAX 100
```

```
void initializeTable(int table[], int size) {  
    for (int i = 0; i < size; i++) {  
        table[i] = -1;  
    }  
}
```

```
int linearProbe(int table[], int size, int num) {  
    int index = num % size;  
    int start = index;  
    while (table[index] != -1) {  
        index = (index + 1) % size;  
        if (index == start) // table is full (should not happen given constraints)  
            return -1;  
    }
```

```

    }
    return index;
}

void insertIntoHashTable(int table[], int size, int arr[], int n) {
    for (int i = 0; i < n; i++) {
        int pos = linearProbe(table, size, arr[i]);
        if (pos != -1) {
            table[pos] = arr[i];
        }
    }
}

```

```

void printTable(int table[], int size) {
    for (int i = 0; i < size; i++) {
        printf("%d", table[i]);
        if (i != size - 1) printf(" ");
    }
}

```

```

int main() {
    int n, table_size;
    scanf("%d %d", &n, &table_size);

    int arr[MAX];
    int table[MAX];

    for (int i = 0; i < n; i++)
        scanf("%d", &arr[i]);

    initializeTable(table, table_size);
    insertIntoHashTable(table, table_size, arr, n);
    printTable(table, table_size);

    return 0;
}

```

**Status :** Correct

**Marks :** 10/10