

# Politecnico di Milano

# MASTER'S DEGREE IN COMPUTER SCIENCE AND ENGINEERING

SOFTWARE ENGINEERING 2

# TrackMe Requirements Analysis and Specification Document

Authors
Alberto Archetti
Fabio Carminati

Reference professor Elisabetta DI NITTO

v.0 - October 31, 2018

# Contents

1	Intr	oduction	L
	1.1	Purpose	1
		1.1.1 Project description	1
		1.1.2 Goals	1
	1.2	Scope	2
		1.2.1 World	2
		1.2.2 Shared phenomena	2
	1.3	Definitions, acronyms, abbreviations	3
		1.3.1 Definitions	3
		1.3.2 Acronyms	3
		1.3.3 Abbreviations	3
	1.4	Revision history	3
	1.5	Reference documents	3
	1.6	Document structure	3
2	Ove	rall description	5
	2.1	Product perspective	5
	2.2	Product functions	5
		2.2.1 Profile management	ŝ
		2.2.2 Data gathering	7
		2.2.3 Data sharing	7
			7
		2.2.5 Payment handling	3
			9
	2.3	User characteristics	9
	2.4	Assumptions, dependencies, constraints	9
		2.4.1 Domain assumptions	)
		2.4.2 Dependencies	)
		2.4.3 Constraints	L
3	Spe	cific requirements	2
	3.1	Scenarios	2
		3.1.1 Scenario 1	2
		3.1.2 Scenario 2	
		3.1.3 Scenario 3	2
		3.1.4 Scenario 4	

	3.2 External interface requirements			
		3.2.1	User interfaces	14
		3.2.2	Hardware interfaces	14
		3.2.3	Software interfaces	14
		3.2.4	Communication interfaces	14
	3.3	Functi	ional requirements	14
		3.3.1		16
		3.3.2		16
		3.3.3		16
	3.4	Perfor	mance requirements	16
	3.5	Design	n constraints	17
		3.5.1	Standards compliance	17
		3.5.2	Hardware limitations	17
		3.5.3	Any other constraint	17
	3.6	Softwa	are system attributes	17
		3.6.1	Reliability	17
		3.6.2	Availability	18
		3.6.3	Security	20
		3.6.4	Mantainability	21
		3.6.5	Portability	21
4	For	mal an	nalysis using Alloy	24
5	Effo	ort spe	ent	<b>25</b>
6	Gra	phics		27

### 1 Introduction

### 1.1 Purpose

### 1.1.1 Project description

TrackMe wants to develop a software-based service that allows individual users to collect health data, called Data4Help. This data can be retrived from the system and visualized according to different filters by a user interface. The system allows third parties registration. Third parties can request access to users'collected data in two ways:

**Single-person data** After the the third party makes a request to the system for a single user data sharing (providing for example the fiscal code of the user), the system asks the user for authorization; if positively provided, the third party is granted access to the user's data

Amonymous-group data Thirs parties can be interested in big amounts of data, but not in who are the people that are providing it; the system, once the request by the third party is sent, checks if the data can be effectively anonymized (it must find at least 1000 people that match the third party request) and, if positively evaluated, grants access to the anonymized data to the third party that requested it

Third parties can subscribe to new data and receive it as soon as it is collected by the system.

Another service that TrackMe wants to develop is AutomatedSOS, built on Data4Help. This service analyzes users'data and calls a SOS whenever data exceedes the basic health parameters. For this particular purpose, system performances will be a critical aspect to be taken into account, because even the slightest delay matters in critical health situations.

### 1.1.2 Goals

Here we present the goals that will be reached once the project is completed:

- G.U1 Users can collect, store and manage their health data
- G.U2 Users can choose to have their health monitored; if their health is critical, an ambulance will be dispatched

- G.T1 Third parties can ask single users for their health data sharing
- G.T2 Third parties can request access to anonymized data that comes from groups of people
- G.T3 Third parties can subscribe to new data and receive it as soon it is produced

### 1.2 Scope

### 1.2.1 World

Our world is composed of two main types of actors: users and third parties. Users are interestes in monitoring their health parameters and third parties are interested in developing services or researches that exploit the data gathered by the users. Data4Help is the service that acts as a bridge between these actors'needs.

Phenomena that occur in the world and are related to our application domain are

- physical conditions of our users
- third parties projects
- SOS system that is able to dispatch ambulances

These phenomena exist in the *world*, but cannot be observerd directly by our system.

### 1.2.2 Shared phenomena

In order to communicate with the *world*, our system needs to share some aspects with it. We will list the aspects controlled by the world, but observable by the machine:

- S.1 physical parameters of the users, gathered through sensors on wereable devices
- S.2 third parties requests to the system for the data they need
- S.3 users'location, acquired through GPS signals

On the other hand, the aspects that occur in the machine, but are observable by the world are

- S.4 interfaces that organize the gathered data that can be filtered according to time or type of data
- S.5 messages for the SOS system, that are sent in case of critical health of a user

### 1.3 Definitions, acronyms, abbreviations

### 1.3.1 Definitions

### 1.3.2 Acronyms

### 1.3.3 Abbreviations

### 1.4 Revision history

Version	Log	
v.0	First version of RASD completed	

### 1.5 Reference documents

See References for details on the consulted documents.

### 1.6 Document structure

This document uses the IEEE standards for requirement analysis documents as a guideline towards a clear and logical explanation of its contents:

- Section 1 gives a brief introduction on the project to be developed, by describing its goals and the environment in which it will be released; keeps track of the revision history
- Section 2 describes the world and the shared phenomena, by defining assumptions and constraints; it identifies the main functions of the project
- Section 3, as the main part of this document, is about requirement analysis; it has also sections about interfaces of the system and software attributes
- Section 4 contains the Alloy model that certifies correctness of goals implication by requirements and domain assumptions
- Section 5 lists the work sessions that drove this project's development, ordered by date, as the hour counter of effort spent by each group member
- Section 6 contains all the graphics that help to better understand the RASD document

# 2 Overall description

### 2.1 Product perspective

Data4Help is a service oriented to data acquisition and data sharing. Its software nature rises the necessity to combine it with another service able to directly retrive raw data from the *world*. Today we can find for sale multiple wearables that can acquire data from users and make it readable from software side. Data4Help users should already own these devices in order to exploit the data acquisition functionality (Section 1.2.2: S.1). Once the user registered to the service, its interface will gather the last data collected and organize it in a chart view, that can be filtered by data or type and rendered by the user interface (Section 1.2.2: S.4; Section 3.2.1).

It is mandatory for the user's wearable to provide a GPS signal, if the user wants to apply to the AutomatedSOS service. GPS will be used to track the user's location in case of health danger and the signal will be shared to the SOS service that already exists in the world (Section 1.2.2: S.3, S.5). This SOS service accepts messages that contain the GPS location of the person in health danger and an emergency log that AutomatedSOS generates from the acquired data. The log explains the suspected health danger and the data that passed the defined thresholds.

Third party organization are interested in data gathering. In order to allow them to make requests for specific types of data, Data4Help provides a user interface that is in charge of composing their request, to make it understendable by the software (Section 1.2.2: S.2; Section 3.2.1). The interface provides all the possible options that the third party can compose in order to provide the closest data request to its needs.

### 2.2 Product functions

Here we present the major functions that our product will offer. Some of them will entirely be handled internally by our system, but for others it will rely on external services. In the latter case, we will specify that the system will not directly provide the service and we will add example systems that already exist in the *world*, in order to guarantee the feasibility of the functions.




Figure 1: Requirement level UML class diagram

### 2.2.1 Profile management

The system will provide a registration form at which users and third parties can apply. Once registered, they will have a uniquely identifiable account, provided the requested information for its creation (see Table 1). Once the account has been successfully created, its owner can exploit the system's functionalities.

Note that accounts for users and third parties must be distinguishable from the system perspective, as it should offer different functionalities to different account types, in order to reflect the account owners' needs.

Account type	Required information	Optional information	
User	email, password, fiscal	social $status,$ $address,$	
	code, date of birth, weight,	hours of work per day,	
	height	hours of sport per week	
Third party	email, password, third	website, research interests	
party name, third party			
	description		

Table 1: Example of login form information

### 2.2.2 Data gathering

Data gathering is exploited through physical wearables that users wear and that can communicate with our software by API calls (ex. Google Fit API [6]). Data entries are identified with a timestamp and the owner user.

Collected data types depend on wearables. For example, the most common sensors for health parameters that we find on smart clothing [5] are pulse, body temperature, electrocardiogram, myocardial and blood oxygen.

### 2.2.3 Data sharing

Data4Help relies on an internal database for data storage. Once data has just been added to the system, only the user that produced it will have access. Data sharing is exploited by granting access to a copy of required data to third parties, if their requests have been accepted. Third parties can retrive these data by downloading them from their inteface.

Third party requests are encoded in the system by filling a form that contains information like Table 2. They can be accepted or rejected. In the former case the third party is granted access to the data, while in the latter it is not granted access.

### 2.2.4 Data management

Once a user collected some data, he/she can organize it by changing the view options in the user interface. These options depend on the device the user is working on, but will always provide basic filters such as time interval

Request type	Accept condition	Filters	
Single-user	Target user should ac-	fiscal code of target user,	
	cept the request through	from-date, to-date, data	
	his/her account	types (weight, heart rate,	
		$\mid$ etc.), time granular- $\mid$	
		ity  (seconds, minutes, $ $	
		hours)	
Anonymous-group	Every user should have	size, from-date, to-date,	
	accepted the automatic	data types (weight, heart	
	sharing of requested data	rate, etc.), user char-	
		acteristics (age interval,	
		weight interval, etc.)	

Table 2: Example of third party request form

or data type. Once filters have been selected by the user, the graphical interface will render a chart that organizes collected data according to them (see Section 3.2.1).

### 2.2.5 Payment handling

When third parties ask for data sharing or users apply to AutomatedSOS, they are asked for payment by the system. Payment details will be discussed by TrackMe and then the software will be updated according to their decisions.

Our system will only initialize payment requests as the effective payment operation will entirely be handled by an external software. This software should

- instanciate payment processes
- check if the payment is feasible and, if not, notify to our system
- handle the payment operation
- notify to our system if the operation has concluded correctly, otherwise notify the error occurred

There are plenty of payment handlers that exist in our *world* and can be paired to our system (ex. PayPal API [7]).

### 2.2.6 SOS handling

This function is heavily dependent on the country in which the SOS will be handled. Our system will only communicate to the external emergency service that already exists in the *world* through automatic API calls (ex. RapidSOS Emergency system for US [8]).

Calls to SOS are handled by AutomatedSOS that signals users GPS position and health status feedback. Calls occur, if the user previously subscribed to AutomatedSOS, when his/her health parameters are below certain thresholds. The time between health danger detection and emergency call must be less than 5 seconds.

### 2.3 User characteristics

The following list contains the actors that are involved in the system functions:

User Person interested in the Data4Help data management service; he/she is required to register to the Data4Help service in order to exploit its functionalities; he/she can also apply to the AutomatedSOS service; every user owns an appropriate device for Data4Help acquisition service that can monitor at least heartbeat and GPS location ex. an athlet that wants to monitor his/her physical status during sport activity, an old person that suffers from heart diseases or a sedentary worker that wants to keep track of his health parameters in the working hours

Third Party Entity interested in the Data4Help data sharing service; it is required to register to the Data4Help service in order to exploit its functionalities; according to the scope of its requests, it may be interested on the data of a particular user or in aggregated chunks of data

ex. the physician of a person that suffers from heart diseases or a statistical institute

### 2.4 Assumptions, dependencies, constraints

### 2.4.1 Domain assumptions

World

- t D.W1 Signals processed by wearables are encoded correctly and represent the status of the world
- D.W2 Given certain health parameters<sup>1</sup>, it is possible to decide if a person is in health danger just by checking wether the parameters are above or below certain thresholds

### Existing systems

- D.E1 In the *world* already exists a SOS system that is able to dispatch ambulances and accepts emergency calls through an API
- D.E2 In the *world* already exists a payment handler that is able to deliver money payments and accepts calls through an API
- D.E3 In the *world* already exist wearables that encode signals for health status; these encoded signals are accessible from the software side

### Legal constraints

D.L1 Acquired data can be sold to third parties

### 2.4.2 Dependencies

Data4Help relies on

- payment handler, to deal with payment of users and third parties, as discussed in Section 2.2.5
- wearables, to encode users'data (see Section 2.2.2)

AutomatedSOS relies on

- wearables, to encode GPS signals and users' parameters
- SOS system, for ambulance dispatching (see Section 2.2.6)

 $<sup>^{1}\</sup>mathrm{TBD}$ 

### 2.4.3 Constraints

AutomatedSOS time performances are critical: the emergency call must be delivered no more than 5 seconds after the health danger detection, in order to have an ambulance dispatched from the SOS system as soon as possible. It is important to note again that AutomatedSOS is in charge only of the emergency call.

Data4Help acquires data through external devices owned by other companies, so it must be legally authorized to sell the data it acquires. In this document we assume that there are no legal issues for the selling activity, as TrackMe will develop contracts with the wearables companies in order to solve this issue.

# 3 Specific requirements

### 3.1 Scenarios

### 3.1.1 Scenario 1

Luke is a 65 years old man that after 40 years of working at the post office finally got retired. Because of the sedentary nature of his work he is worried that he may suffer a stroke.

Therefore last week Luke downloaded the app AutomatedSOS, the system allowed him to create an account only after having filled all the required user information(see Table 1):from now on the system will check Luke's health parameters. Today Luke's health parameters exceede thresholds because of a stroke:the system recognize this critical situation and therefore within 5 seconds an emergency call to SOS System, providing the GPS location and health status feedback of the Luke, will be made by AutomatedSOS.

### 3.1.2 Scenario 2

The franchise BodySlim is opening a new gym in Milan near Parco Sempione; the most relevant aspect that characterize it, is the timetable: open 365 days, 8 hours per day. In order to maximize the revenue the management would like to know in which time of the day the potential customers make exercise. A reliable sample can be obtained from Data4Help, therefore BodySlim create a third party account filling all the required third party information (see Table 1). Then the franchise make an anonymous-group request (see Table 2) for 2000 individuals with particular characteristics: age between 20 and 60, at least once a week they are running in Parco Sempione(this can be checked with GPS position) to Data4Help. The app find in his internal database these 2000 users and therefore the system immediately shares the required information with BodySlim without asking to the users the authorization .Now looking at the most common hours chosen for running by these individuals the manager can easily identify the most profitable hours in which the gym should be opened.

### 3.1.3 Scenario 3

Rose has just discovered that is expecting a daughter. Harold, her gynecologist, needs to keep monitoring bloody ossygen, electrocardiogram and pulse

in order to understand if the pregnancy is proceeding well or not. Therefore he creates a third party account of Data4Help and after the system has checked if the required information (see Table 1) has been correctly inserted, he requires these data to the app. According to the single-user request (see Table 2) policy Data4Help asks to Rose the consensus for sharing these data. Rose, which really care about her daughter's health, immediately gave the authorization to the app that can make them available to her gynecologist. Nine months later the beautiful and healthy Marie is born.

### 3.1.4 Scenario 4

Jack is a policeman that has decided to spend his holidays in a spa called "BeautySPA" which allow him to loss 15 kg thanks to fitness activity and a healthy diet. In order to understand if this treatment is efficient over time the spa and Jack decides that user's health parameters like height, weight and body temperature must be monitored. Therefore the policeman and BeautySPA create respectively a user and a third party account of Data4Help and the system after checking that all the required information (see Table 1) are properly added, allow them to exploit all Data4Help functionalities. Indeed BeautySPA immediately apply for the three Jack's health parameters to the app. The app recognize this as a single-user request (see Table 2) so asks to Jack the authorization whether to provide them to the spa or not. Obviously he accept and therefore Data4Help make available these data. Unfortunately after just 1 month the policeman has already had a weight increase of 6 kg. So in order to better understand which may be the reasons the spa asks more health parameters such as blood oxygen and heartbeat to Data4Help which again, before sharing these data with BeautySPA, will ask the authorization of the user.

### 3.2 External interface requirements

- 3.2.1 User interfaces
- 3.2.2 Hardware interfaces
- 3.2.3 Software interfaces
- 3.2.4 Communication interfaces

### 3.3 Functional requirements

### Account handling

- R.A1 The system shall allow users registration
- R. A2 The system shall allow third party registration
- R.A3 The system shall distinguish between user and third party accounts
- R.A4 The system shall guardantee account uniqueness by not allowing two account to have the same email
- R.A6 The system shall allow users and third parties to access their account (login) only if they provide correct email and password
- R.A7 The system shall allow users and third parties to exploit Data4Help and AutomatedSOS functionalities only if they are *logged in* their account

### Data encoding

- R.D1 The system shall encode data received through wearables's ensors and store it internally<sup>2</sup>
- R.D2 The system shall be able to retrive data previously stored on request
- R.D3 The system shall not erase data once it is stored internally
- R.D4 Once the system stored data, it shall allow access to that data only to the user account that was *logged in* while the data was collected

 $<sup>^2</sup>$ for example the system can store data into an internal database or can save it using a cloud service; the important aspect is that data must be retrivable in the future

- R.D5 The system shall be able to share the stored data to more than one account
- R.D6 The system shall be able to compose groups of data entries (aggregate data) and anonymize them (every data entry in the group has no information about the providing user, such as fiscal code or email)

### Interfaces

- R.I1 The system shall provide a registration form for users and third parties
- R.I2 The system shall provide to the user an interface able to render data graphically, allowing filters like time interval or data type
- R.13 The system shall provide a request form to the third parties

### Data sharing requests

- R.R1 The system shall allow third parties to ask for data sharing of a single user
- R.R2 The system shall ask the user to accept or decline every single-user request of data sharing by third parties that has him/her as target user
- R.R3 The system shall provide access to the target user data to the third party only if the user accepted the request of the third party, otherwise the system shall notify to the third party that the user declined the request
- R.R4 The system shall allow third parties to ask for data sharing of aggregate data
- R.R5 The system shall be able to check if a request for aggregate data by a third party can be properly anonymized (there shall be at least 1000 user data entries that fit the parameters of the request)
- R.R6 The system shall provide access to the aggregate data to the third party only if the the request can be properly anonymized, otherwise the system shall notify the third party that its request cannot be properly anonymized

R.R7 The system shall provide access to a third party to newly produced data if it fits the third party request

### SOS calls

- R.S1 The system shall provide to the user an option to apply to AutomatedSOS
- R.S2 If user applied to AutomatedSOS, the system shall monitor his/her parameters in real time by checking whether they are above or below the thresholds<sup>3</sup>
- R.S3 If user applied to AutomatedSOS and his/her health parameters are critical (above or below thresholds), the system shall send an emergency call to the SOS system
- R.S4 When the system sends an emergency call, it shall provide to the SOS system API user's GPS location and user's health status through his/her critical parameters encoding
- 3.3.1
- 3.3.2
- 3.3.3

# 3.4 Performance requirements

AutomatedSOS implements a very important function:monitoring the human health; in this field having a lower time response can save a life. Therefore, when the system detects than at least one of the health parameters exceedes the thresholds (user is in health danger), it must collect all the required data(GPS location and user's health status) and send them through an emergency call to an external service(SOS System) within 5 seconds. Moreover Data4Help has to send every 1 second the required data to the subscribed third parties(both for Single-User requests and for Anonymous-Group requests) in order to grant them accurate enough data.

 $<sup>^3\</sup>mathrm{TBD}$ 

Name	Name Sign in of User in Data4Help		
Actors	User		
Entry Condition	Data4Help is downloaded on the smartphone		
Flow of Events	1.User click on "Create a new User account" button		
	in the homepage of the app.		
	2.User fills all the mandatory fields ("Age", "Name",		
	"Surname", "Email", "Sex", "Password", "Fiscal		
	Code").		
	3.User insert in the fields "Shared Data" the data		
	that he want to share with the app.		
	4.User clicks on the "Confirm" button.		
	5. The system create a DataSet for the User in his		
	internal database.		
Exit Condition	The User account has been successfully created.		
Exceptions	1. The system finds that User filled the field "Email"		
with an email that is non-existent or that has			
	been associated with another user.		
	2. The system finds that User filled the field "Fiscal		
	Code" with an expression not long 16 characters.		
	3. The system finds that User filled the field "Pass-		
	word" with an expression shorter than 8 characters.		
	All exceptions are handled notifying the issue to the		
	User and taking back the Flow of Events to the		
	point 2.		

# 3.5 Design constraints

- 3.5.1 Standards compliance
- 3.5.2 Hardware limitations
- 3.5.3 Any other constraint

# 3.6 Software system attributes

### 3.6.1 Reliability

The sofware is expected to work continuously for 24 hours a day despite small deviations are accepted.

Name	Log in of User		
Actors	User		
Entry Condition	User has already created an account		
Flow of Events	1. User opens the app on his smartphone.		
	2.User insert his email in the field "Email" in the		
	homepage of Data4Help.		
	3.User insert his password in the field "Password" in		
	the homepage of Data4Help.		
	4.User Click on "Log In" button in the homepage of		
	the app.		
Exit Condition	User is successfully Logged in and can exploit all the		
	functionalities of the app.		
Exceptions	1. The system doesn't find the email address inserted		
	in the field "Email" in his internal DataBase.		
	In this case the Flow of Events has to be executed		
	again from step 2.		
	2. The system doesn't find the password inserted in		
	the field "Password" in his internal DataBase.		
	In this case the <b>Flow of Events</b> has to be executed		
	again from step 3.		
	3. The system find both the email and the password		
	inserted by User but these refers to 2 different users.		
	In this case the Flow of Events has to be executed		
	again from step 2.		

Moreover as section 3.6.4 says, the sofware changes during time, so each time the software is modified is necessary to check the consequences on the reliability.

### 3.6.2 Availability

The system is expected to be available for 99.99 % of the time but in case of failure it must be able to recover within 1 second otherwise in case of user's health problem AutomatedSOS won't respect the constraint descibed in 2.4.3 and therefore the user will be in a critical situation.

There 2 different situations which may result in a failure:failed components or due to unexecpected increasing in the requests.

Name	Accept Single-User request		
Actors	Third party and User		
Entry Condition	Third party and User have already created respec-		
	tively a third party and a user account and they are		
	already logged in in Data4Help.		
Flow of Events	1. Third party clicks on the button "Single-User Re-		
	quest".		
	2. Third party inserts the Fiscal Code of the User in		
	the field "Fiscal Code" of the Single-User Request		
	page.		
	3. Third party lists to the system the data of the User		
	which it would like to access filling the field "DataRe-		
	quired" in the Single-User Request page.		
	4. The system asks to the User whether he accepts or		
	denies to share those specified data with the Third		
	party.		
	5.User answers clicking in the field "Yes" in his home-		
	page.		
	6. The system make available the data for the third		
E ' C 1''	party.		
Exit Condition	Third party can exploit the data		
Exceptions	1. The system doesn't find the fiscal code inserted by		
	third party in the field "Field Code" in his internal		
	database.		
	In this case the <b>Flow of Events</b> has to be executed		
	again from step 2.		
	2. The system discovers that the User has denied the		
	request therefore Data4Help notifies this information		
	to the third party which won't have access to the		
	required data.		
	The third party can make a new Single-User request		
	referred to a new User: in this case the Flow of		
	<b>Events</b> has to executed again from the first step.		

At this level of abstraction is not strickly required but in both of these cases a distributed architecture is an optimal solution:indeed in case of failure one of the redundant component can replace the one offline and in case of high

Name	Call an ambulance	
Actors	User and SOS System	
Entry Condition	User's health parameters exceedes thresholds	
Flow of Events	1.The system collects GPS location and health	
	status parameters of the User from his internal	
	database.	
	2. The system makes an emergency call to SOS	
	System by providing GPS location and health	
	status feedback of the User.	
	3. The SOS System accepts the call and dis-	
	patches the ambulance to the User location.	
	4. The SOS System notifies the system when	
	the ambulance arrives at User Location.	
Exit Condition	The ambulance is taking care of the User.	
Exceptions		
Special Requirements	1. The system has to collect the GPS loca-	
	tion, health parameters of the User and make	
	the emergency call to SOS System within five	
	seconds from the time the health parameters	
	exceedes thresholds.	

demand a load balancing between redundant component can minimize the probability of failure of the system and also improve the performances.

### 3.6.3 Security

The system requires the users(both Data4Help and AutomatedSOS) and third Parties(only in Data4Help), in order to exploit all the functionalities of the app and avoid unauthorized access, to authenticate through email and password.

These 2 credentials and all the Data collected by the system has to be securely stored in the internal database.

Moreover as requirement R.D6 says for privacy issues for all the Anonymous-Group requests the system must not allow the third parties to link data collected to the users that produced them.

Name	Accept Anonymous-Group request			
Actors	Third Party			
Entry Condition				
	and is already logged in in Data4Help.			
Flow of Events	1. Third party clicks on the button "Anonymous-			
	Group Request".			
	2. Third party lists to the system which data requires			
	filling the field "Data Required" in the Anonymous-			
	Group request page.			
	3. The system looks for, in his internal database, the			
	User's Datasets which fit with the request made by			
	the third party.			
	4. The system aggregate the data found and			
	anonymize them.			
	5. The system provides the anonymous data to the			
	third party.			
Exit Condition	Third party can exploit the data			
Exceptions	1. The data cannot be anonymized by the system			
	because it doesn't find at least 1000 User Datasets			
	which match with the third party request. Therefore			
	the system cannot grant access to the data to the			
	third party and has to notify her this information .			
	The third party can make a new Anonymous-Group			
	request asking for a new set of data: in this case the			
	Flow of Events has to be executed again from the			
	first step.			

### 3.6.4 Mantainability

Data4Help, as section 2.2.2 says, has to collect data through multiple physical wearables devices therefore Data type handling should be implemented by the system in a flexible and extensible way, because wearables technologies change rapidly and our software should adapt in the least invasive way possible.

### 3.6.5 Portability

Name	Show Data previously acquired		
Actors	User		
<b>Entry Condition</b>	User has already created a User account and is al-		
	ready logged in in Data4Help.		
Flow of Events	1. User clicks on the button "Data Management".		
	2.User decides which filter has to be applied to his		
	DataSet filling the field "Filters" in the Data Man-		
	agement page.		
	3. The system organize the User's DataSet following		
	the User's instructions.		
	4. The system show to the User these data thanks to		
	a graphical interface.		
Exit Condition	User can see his data in the specified way		
Exceptions	1 The system hasn't gathered any data yet because		
	the user has just created an account.		
	Thanks to the graphical interface the system notifies		
	the user that no data can be shown.		
	Only after having collected some data the User can		
	specified filters:the Flow of Events must be exe-		
	cuted from the first step.		

Raw ID	Goal ID	Req ID	Use Case ID
r1	G.U.1	R.A1	3.3.1
		R.A3	
		R.A4	
		R.I.2	
r2	G.U.1	R.A3	3.3.2
		R.A6	
		R.A7	
r3	G.T.1	R.A3	3.3.3
		R.I.3	
		R.R.1	
		R.R.2	
		R.R.3	
r4	G.T.1	R.A3	3.3.3
		R.I.3	
		R.R.1	
		R.R.2	
		R.R.3	

# 4 Formal analysis using Alloy

```
open util/integer
  open util/time
3 open util/boolean
5 sig User {}
  sig DataEntry {
           threshold : one Int,
           user : one User,
           value : one Int,
           location : one GPSLocation
  sig SOSSystem {
           emergencies : SOSCall -> DataEntry
  }
18 sig SOSCall {}
20 sig GPSLocation {}
23 fact CallIfAboveThreshold {
           all de : DataEntry | de.value > de.threshold
                  implies (
                   one emergency: SOSSystem.

→ emergencies | (
                            one target : SOSCall -> de
                               → target = emergency
                   )
           )
  fact OneThresholdForDataEntries {
           all disj de1, de2 : DataEntry | de1.threshold
              \hookrightarrow = de2.threshold
  }
35 pred show{}
37 run show for 4 but 2 DataEntry
```

# 5 Effort spent

### References

- [1] Mandatory Project Assignment AY 2018-2019
- [2] IEEE 830-1993 IEEE Recommended Practice for Software Requirements Specifications
- [3] ISO/IEC/IEEE 29148 Systems and software engineering Life cycle processes Requirements engineering
- [4] Collection and Processing of Data from Wrist Wearable Devices in Heterogeneous and Multiple-User Scenarios https://www.ncbi.nlm.nih.gov/pmc/articles/PMC5038811/
- [5] Wearable Devices in Medical Internet of Things: Scientific Research and Commercially Available Devices https://www.ncbi.nlm.nih.gov/pmc/articles/PMC5334130/
- [6] Google Fit API https://developers.google.com/fit/overview
- [7] PayPal API https://developer.paypal.com/docs/
- [8] RapidSOS Emergency API https://info.rapidsos.com/blog/product-spotlight-rapidsos-emergency-api
- [9] Slides of the course by Prof. Di Nitto https://beep.metid.polimi.it/
- [10] LATEX templates
  http://www.latextemplates.com/
- [11] Alloy LATEX Highlighting https://github.com/Angtrim/alloy-latex-highlighting
- [12] Draw.io https://www.draw.io/

# 6 Graphics