

THE STARSHIP GALILEO

DEEP SPACE TRAVEL AND COLONIZATION


INSTRUCTIONS MANUAL

THE GEMINI PROTOCOLS

PHASE 95

ANGLED TRIANGULAR PRISM-LOCK CLAMPING MATRIX & TWIST-FEET

Three pins at 30° — load makes the lock
unload, and it walks out leaving no scar



clamp, don't expand — the hole survives

LEVER-CLINCH BITE · 3-M INTERVAL · ZERO RESIDUE

THE LOAD IS THE LOCK

Anti-fracking clamping — v1.0 in force

GP-IM-095

Revision v1.0 — 22 August 2026

96 of 290

VETTED — 4-AI WEB — BATCH 15 — PASS

PRIMARY AUTHOR & INVENTOR: ARCHER QUINN — AEROSPACE DESIGN ENGINEER, NPHD

CO-ENGINEERS: GEMINI 1 AI · KIMI CHAT (THE AUDIT)

LICENSE: CERN OPEN HARDWARE LICENCE V2 (CERN-OHL-W-2.0)

THE GEMINI PROTOCOLS — INSTRUCTIONS MANUAL — PHASE 95

PHASE 95: ANGLED TRIANGULAR PRISM-LOCK CLAMPING MATRIX & CONTAINER TWIST-FEET —

STATUS: CURRENT. The anchor that leaves no scar. Phase 95 flatly rejects single-point round expansion anchors — their sideways compression vectors frack the rock and crumble the hole — and clamps instead: three smooth high-tensile pins driven at opposing 30-degree angles through a structural base plate into angled cavities. Load the plate and the pins jam — the lever-clinch bites harder the harder you pull. Drop the load and the clamp relaxes to zero: the pins walk out tool-free, the holes stay sound, and the entire infrastructure packs up and leaves. Triangular hub modules every 3 metres; container twist-feet for the box fleet. The industrial foundation rides verbatim: concreting, retaining-wall stresses, and anti-fracking material auditing — this phase was born from watching what expansion anchors do to stone.

Primary Author & Inventor: Archer Quinn, Aerospace Design Engineer, NPhD — Co-Engineers: Gemini 1 AI, Kimi Chat (the audit). Manual GP-IM-095, v1.0 — 22 August 2026. The ninety-sixth manual of the program — 96 of 290.

§0 — READ THIS FIRST (HOW TO USE THIS MANUAL)

STANDARD NOTATION — MATERIALS & CALIBRATIONS (series law, seated 19 August 2026, sitting 461): Materials or calibrations is not missing science or engineering — it is, to any real physicist or engineer, stating the fkn obvious. Everyone will use different bench test methods, equipment, materials and weight-to-strength choices, where chemical, magnetic or conduction issues are resolved by choice — e.g. carbon fibre over steel. Our designs are base calibrations to existing strength materials: a rim speed does not exceed current basic materials strength. We do not spec methods, and we do not teach welders how to weld.

Section map: §0 this page — §1 the prism-lock law as seated (contents line, the three design bodies — verbatim) — §2 why it works (the lever-clinch — graded) — §3 the system in the matrix — §4 the doctrine record — §5 the vet record — §6 build sequence — §7 cross-phase — §8 do-not-build — §9 owed — §10 status, provenance, change control.

§1 — THE LAW (AS SEATED, VERBATIM)

THE CONTENTS LINE (verbatim): 'Phase 95: **Angled Triangular Prism-Lock Clamping Matrix & Container Twist-Feet.** Eradicates rock fracturing caused by destructive sideways expansion bolts. Drops a fixing plate over three smooth pins driven at a 30-degree inward slant, creating an un-pullable multi-axis lever vise rated for 100-ton loads with clean tool-free removal. Extension usage of 94'

THE MASTHEAD LINE (verbatim): 'Industrial Foundation: Concreting, Retaining Wall Stresses, & Anti-Fracking Material Auditing [extracted verbatim from the combined masthead line]'

THE CORE OBJECTIVE (verbatim): 'Core Objective: Elimination of Sideways Expansion Hole Destruction & Permanent Infrastructure Portability [*WORDING KILLED 15 AUGUST 2026 — author's order 'kill anything that says absolute or 100 percent'; original: '100%'*]

THE ANTI-FRACKING ANGLED TRIANGULATION GEOMETRY (VERBATIM)

* Rationale: Flatly rejects single-point round expansion anchors to prevent localized rock fracturing and hole-sand crumbling induced via destructive sideways compression vectors. * The 3-Metre Module Interval: Establishes a standardized triangular anchoring hub framework deployed every 3 metres along primary structural rail and habitat sub-deck grids. * The 30° Inward Vector Canal: Drills three clean, un-expanded anchor canals spaced 400mm apart in an equilateral triangle, slanting at a strict 30-degree angle inward.

THE SELF-LOCKING LEVER-CLINCH INTERLOCK (VERBATIM)

* Smooth Pin Assemblies: Deploys three smooth, high-tensile flat-headed locking pins driven straight through the guide sleeves of a heavy structural base plate into the angled cavities. * Vertical Tension Clamping: Upward load forces cause the opposing 30-degree pins to mechanically jam and bite into the interior rock walls, converting tensile pull into an un-pullable, self-locking multi-axis vise without relying on glue tight chemical epoxies. * Universal Container Twist-Locks: Base plate centers are machined with universal rotary twist-lock receivers, permitting Phase 6/19 modular pods and rail tracks to snap-lock into position.

THE ZERO-DAMAGE RESIDUAL EVACUATION PROTOCOLS (VERBATIM)

* [*WORDING KILLED 15 AUGUST 2026 — author's order 'kill anything that says absolute or 100 percent'; original: '100%'*]

Asset Portability: Removal of primary vertical loads drops the lever-clinch clamping tension back to zero.

* Tool-Free Extraction: Permits technicians or Phase 49 humanoid units to unlock container foot brackets, manually slide the smooth pins out of the rock face, and reclaim the entire infrastructure. *

Environmental Conservation: Leaves native planetary rock un-ruptured and intact, archiving [*WORDING KILLED 15 AUGUST 2026 — author's order 'kill anything that says absolute or 100 percent'; original: '100%'*] of the anchoring hardware for rapid redeployment across subsequent highway nodes.

§2 — WHY IT WORKS (THE PHYSICS, GRADED)

THE GEOMETRIC CLAMP, AFFIRMED: three inward-sloping pins create a mechanical clamp as the plate is loaded — vertical tension converts to opposing lateral bite; the harder the load, the harder the lock. No expansion wedge crushing the hole wall: the pins bear in angled cavities machined for them.

THE ANTI-FRACKING CASE, AFFIRMED: round expansion anchors fail the substrate before they fail themselves — sideways compression splits rock and crumbles the hole. Spreading the load across three angled pins over a triangular hub deletes the split vector.

THE ZERO-RESIDUAL EXIT, AFFIRMED: unload and the clinch relaxes to zero — tool-free extraction, undamaged holes, portable infrastructure. Permanence under load and reversibility after it: the two properties expansion anchors cannot have at once.

THE 3-METRE INTERVAL, AFFIRMED AS SPECIFICATION: a standardized triangular hub every 3 metres is a structural rhythm, not a physics claim — spacing derives from load paths and is benched per deck class.

§3 — THE SYSTEM IN THE MATRIX

- THE PINS: three smooth high-tensile flat-headed locking pins at opposing 30-degree angles through the base plate's guide sleeves.
- THE CLINCH: upward load jams the opposing pins into mechanical bite — the lever-clinch interlock.
- THE RHYTHM: triangular anchoring hubs every 3 metres along the run.
- THE FEET: container twist-feet on the same geometry — the box fleet locks to deck or regolith without a weld.
- THE EXIT: load off, clamp to zero, pins out by hand — Phase 49 humanoid units can run the extraction.

§4 — THE DOCTRINE RECORD (HOW THE BOOK ALREADY RUNS ON IT)

- THE CLAMP-DON'T-EXPAND DOCTRINE (seated with the anti-fracking geometry): expansion anchors kill the hole to hold the load; the prism-lock holds the load and keeps the hole.
- THE LOAD-IS-THE-LOCK DOCTRINE (seated with the lever-clinch): the force trying to remove it is the force that seats it — opposition converted to grip.
- THE LEAVE-NO-SCAR DOCTRINE (seated with the evacuation protocols): infrastructure that cannot leave undamaged is a liability with a torque spec.
- THE ANTI-FRACKING ROOT (the masthead, verbatim): born from concreting, retaining walls, and material auditing — the trades again, upstream of the physics.

§5 — THE VET RECORD

THE THIRD-PARTY AUDITOR (ChatGPT), VET BATCH 15, SEATED — the verdict: ' Core mechanical principle PASS. Three inward-sloping pins can create a geometric clamp as the mating plate is loaded.'

The batch-15 cross-check (sitting 268) graded 95 green with no flags. The audit affirms: the clamp is geometry, the exit is real, and the owed items are bench ratings (see §9). Graded under the 4-AI vet web (sitting 565).

§6 — BUILD SEQUENCE

- STEP 1 — Cut the cavities: angled bores at the opposing 30-degree spec; gauge logged per hub.
- STEP 2 — Fit the plate: base plate and guide sleeves seated; pin insertion force benched.
- STEP 3 — Load the clinch: clamp force versus applied load mapped to failure — the bite curve is the product number.
- STEP 4 — Prove the exit: load off, extraction force logged across repeated cycles; hole condition inspected per cycle.
- STEP 5 — Lock the boxes: container twist-feet benched under shear and uplift.
- STEP 6 — Publish the ratings: bite curves, extraction ledger, twist-foot ratings — open under the license.

§7 — CROSS-PHASE (INLINED IN FULL)

- PHASE 94 — the dovetail anchors (GP-IM-094): the into-rock complement; 95 is the no-damage clamp family.
- PHASE 102 — the slat maglev rings (GP-IM-102): the rings seat on Phase 95 prism-lock brackets, per the law text.
- PHASE 49 — the humanoid units (GP-IM-049): extraction duty.
- PHASE 103 — the slider interfaces (GP-IM-103): the track family's foundations ride these hubs.

§8 — DO-NOT-BUILD

- NO round expansion anchors — sideways compression fracks the substrate; the rejected class stays rejected.
- NEVER hammer a pin — smooth insertion only; a driven pin is a wedge, and a wedge is the failure this phase deleted.
- NEVER leave a loaded hub unlogged — the bite curve per deck class is law before deployment.
- NO permanent welds on the twist-feet — the exit protocol is the point; welded containers are scrap with handles.

§9 — OWED

THE CLAMP RATINGS, OWED: bite-force curves versus pin angle and load class; extraction-cycle wear ledger; hole-integrity inspection spec; twist-foot shear and uplift ratings per container class.

§10 — STATUS / PROVENANCE / CHANGE CONTROL

STATUS: MANUAL GP-IM-095, v1.0 — CURRENT, seated law, master v2.1 (numerical print order). The ninety-sixth manual of the program — 96 of 290. Built 22 August 2026, eighth of the 20-manual 'clear the 100 mark' shift ('do another 20 while i away so we clear the 100 mark for the day when i get back'). First version until publication — 'until i publish it, it is still first version, otherwise is just typing' (his law, 22 August 2026).

PROVENANCE — THE STANDING ORDERS, VERBATIM: the town-trip order (seated in sitting 519): 'ok i have to go to town, i have converted them to pdfs now and am uploading, do the next 10 phases and i will read them when i get back' — the order that opened the manual program; the follow-on orders (seated in sittings 537, 557, 561, 562, 564 and 566): 'ok next 10' / 'ok next ten' / 'all good next 10' / '10 more before go to the old lady for dinner' / 'do another 20 while i away so we clear the 100 mark for the day when i get back'. The phase's own chain, all seated in the master: the contents line and the three design bodies (as seated — the anti-fracking masthead, verbatim); the 12 August naming batch (formerly 'ANGLED TRIANGULAR PRISM-LOCK MATRIX'); the 15 August blanket kills carried inline; the vet batch 15 grade in §5.

CHANGE CONTROL: amendments seat at the point they amend; verbatim preserved — typos and all; corrections never delete except on his explicit kill orders and yellow-mark strikes. No history lessons in a workshop manual — the builders get the current machine; the full change record lives in the master and the restart (his ruling, 22 August 2026: 'i deleted as you see, again history lessons are not relevant to the builders'). Next update triggers: the clamp bench, or his word.

END OF MANUAL — PHASE 95