

THE STARSHIP GALILEO

DEEP SPACE TRAVEL AND COLONIZATION

INSTRUCTIONS MANUAL

THE GEMINI PROTOCOLS

PHASE 138

DYNAMIC CRYOGENIC THERMAL IMPEDANCE OVER-SIZING

Rated for the breach at minus ninety-five, not the showroom
PVC banned fleet-wide — silicone is the floor



cold copper conducts better — record corrected

-95C CAL · COPPER MARGIN · CARBON JACKET

THE EMERGENCY IS THE RATING

Grid-materials law — v1.0 in force

GP-IM-138

Revision v1.0 — 23 August 2026

139 of 290

VETTED BATCH 18 — PASS · CORRECTED

PRIMARY AUTHOR & INVENTOR: ARCHER QUINN — AEROSPACE DESIGN ENGINEER, NPHD

CO-ENGINEERS: GEMINI 1 AI · KIMI CHAT (THE AUDIT)

LICENSE: CERN OPEN HARDWARE LICENCE V2 (CERN-OHL-W-2.0)

THE GEMINI PROTOCOLS — CHAPTER 138

PHASE 138: DYNAMIC CRYOGENIC THERMAL IMPEDANCE OVER-SIZING — STATUS: CURRENT — PASS ON THE CORRECTED RECORD. Size the wire for the cold snap, not the brochure day. Phase 138 bans the room-temperature wire gauge chart across the fleet: when a hull breach dumps a grid section into cold-sink conditions, copper contracts, insulation stiffens, and the emergency is the worst possible moment to discover the cable was rated for a showroom. The law mandates all conductive copper cross-sections over-sized for the worst-case -95°C operational calibration, with expanded mass profiles so standard and emergency grids hold unbroken current delivery under multi-G load — and it flatly prohibits PVC anywhere on the fleet: brittle below roughly -20°C, outgassing corrosive hydrogen chloride in vacuum. Aerospace-grade silicone rubber is the baseline insulation minimum, elastic to -100°C, and high-voltage buses cross-jacket with Phase 91 carbon-film membranes for on-demand inductive defrost and active EMP shielding. The phase also owns the file's neatest self-correction: an early wording blamed cold for raising copper's impedance — backwards; copper resistivity falls about 0.4% per degree, so at -95°C a bus runs roughly 40% lower resistance. The record corrected the direction, the vet recorded the correction, and the honest version of the engineering stands: the over-sizing is for mechanical contraction, micro-fissure stress, and fault-ride-through — the electricals actually get easier in the cold, and the structure is what must be sized for it.

Primary Author & Inventor: Archer Quinn, Aerospace Design Engineer, NPhD — Co-Engineers: Gemini 1 AI, Kimi Chat (the audit). Chapter GP-IM-138, v1.0 — 23 August 2026.

§0 — READ THIS FIRST (HOW TO USE THIS CHAPTER)

STANDARD NOTATION — MATERIALS & CALIBRATIONS (series law, seated 19 August 2026, sitting 461): Materials or calibrations is not missing science or engineering — it is, to any real physicist or engineer, stating the fkn obvious. Everyone will use different bench test methods, equipment, materials and weight-to-strength choices, where chemical, magnetic or conduction issues are resolved by choice — e.g. carbon fibre over steel. Our designs are base calibrations to existing strength materials: a rim speed does not exceed current basic materials strength. We do not spec methods, and we do not teach welders how to weld.

Section map: §0 this page — §1 the impedance law as seated (contents line, the two bodies, the physics note with the direction correction, verbatim) — §2 what cold actually does (graded) — §3 the system in the cross-section — §4 the doctrine record — §6 build sequence — §7 cross-phase — §8 do-not-build — §9 owed — §10 status, provenance, change control.

§1 — THE LAW (AS SEATED, VERBATIM)

THE CONTENTS LINE (verbatim): 'Phase 138: **Dynamic Cryogenic Thermal Impedance Over-Sizing.**

Rejects room-temperature-only wire gauge charts. Conductive copper cross-sections are mathematically over-sized to handle the physical contraction and electrical impedance shifts that occur during emergency hull breaches down to -95°C (-140°F), preventing sub-zero grid failures and voltage drops.'

THE CORE OBJECTIVE (verbatim): 'Core Objective: Elimination of Sub-Zero Grid Failures & Brittle Insulation Fracturing '

Industrial Electrical Base: Dynamic Thermal Impedance Splicing & Cryogenic Material Flexibility

THE DYNAMIC CRYOGENIC IMPEDANCE OVER-SIZING (VERBATIM)

- **Rationale:** Rejects room-temperature-only wire gauge charts to eliminate catastrophic voltage drops, shifting impedance curves, and copper contraction failures during emergency hull breaches.
- **Worst-Case -95C (-140F) Operational Calibration:** Mandates that all conductive copper cross-sections are structurally over-sized to handle the physical contraction and electrical impedance shifts that occur during cold-sink actions.
- **Multi-G Load Protection:** Expanded wire mass profiles ensure that standard and emergency grid systems maintain unbroken current delivery, neutralizing micro-fissure line failure vectors.

THE POLYMER PROHIBITION & SILICONE STANDARD (VERBATIM)

- **Outgassing & Embrittlement PVC Ban:** Flatly prohibits Polyvinyl Chloride (PVC) coatings across all fleet grids due to vacuum outgassing degradation and low-temperature brittle fracturing.
- **High-Durability Silicone Sheathing:** Establishes flexible, aerospace-grade silicone rubber as the baseline insulation minimum, preserving dielectric integrity and line elasticity down to -100C.
- **Carbon-Film Thermal Jacketing:** High-voltage buses are cross-jacketed with Phase 91 carbon-film membranes, providing localized, on-demand inductive defrosting capabilities and active EMP shielding.

PHYSICS NOTE — PHASE 138 (KIMI AUDIT: MATERIALS AFFIRMED — ONE IMPEDANCE DIRECTION CORRECTED) (VERBATIM)

- **The polymer call is textbook-correct.** PVC goes brittle below roughly -20C, cracks under flex, and outgasses corrosive hydrogen chloride in vacuum — banning it fleet-wide is exactly right. Aerospace-grade silicone rubber staying elastic to -100C is also accurate, and the Phase 91 carbon-film cross-jacket turns the insulation into its own de-icing system. Materials: affirmed without reservation.

- **CORRECTION — cold copper conducts better, not worse.** Copper resistivity falls roughly 0.4% per degree C, so at -95C — 115 degrees below the room-temperature rating — a copper bus carries current with roughly 46% LOWER resistance than at room temperature — the impedance curve shifts down, and voltage drop eases rather than spikes. The genuine cold hazards are mechanical, not electrical: differential thermal contraction straining terminals and solder joints (copper shrinks about 0.2% across that swing, insulation shrinks differently), solder and contact embrittlement, and insulation micro-fracture — exactly the micro-fissure vectors the markup names. The over-sizing mandate stands regardless: it buys mechanical margin and fault-current headroom, and costs only mass. Builder note: spec the cross-section for contraction stress and fault duty, not for cold resistance.

§2 — WHY IT WORKS (THE PHYSICS, GRADED)

THE POLYMER CALL, AFFIRMED AS TEXTBOOK: PVC embrittles below roughly -20°C, cracks under flex, and outgasses HCl in vacuum — the fleet-wide ban is exactly right. Silicone staying elastic to -100°C is accurate, and the Phase 91 carbon-film cross-jacket is sound practice for defrost and shielding.

THE DIRECTION CORRECTION, SEATED AS THE RECORD'S OWN: copper resistivity falls with temperature — about 0.4% per degree — so cold copper conducts better, not worse. The phase's own physics note carries the correction ('CORRECTION — cold copper conducts better, not worse'), and the vet's ledger records it as resolved: 'Corrected: cold copper lowers resistance; remaining issue is mechanical/material stress.'

THE OVER-SIZING, AFFIRMED FOR THE RIGHT REASONS: contraction stress, micro-fissure vectors, and fault-ride-through under multi-G load are mechanical and thermal-cycling problems — sizing copper mass for the cold emergency is correct engineering once the impedance direction is honest.

THE REMAINING FLAG, SEATED: mechanical and material stress under thermal cycling — conductor-to-insulation differential contraction, jacket fatigue — is the live engineering question. Not a physics objection; a test-and-rate program.

§3 — THE SYSTEM IN THE CROSS-SECTION

- THE RULE: no room-temperature-only gauge charts — every section rated at the -95°C worst case.
- THE MASS: expanded copper cross-sections — contraction and stress absorbed by design margin.
- THE BAN: PVC prohibited fleet-wide — brittleness and corrosive outgassing, named.
- THE STANDARD: aerospace silicone sheathing as the insulation minimum — elastic to -100°C.
- THE JACKET: Phase 91 carbon-film on the high-voltage buses — inductive defrost and EMP shielding

on demand.

§4 — THE DOCTRINE RECORD (HOW THE BOOK ALREADY RUNS ON IT)

- THE WORST-CASE DOCTRINE (seated with the phase): the emergency is the rating condition — the grid is sized for the breach, not the brochure.
- THE CORRECT-THE-RECORD DOCTRINE (the direction fix): the file caught its own impedance error and seated the correction — the physics note carries it in the open.
- THE BAN-THE-BAD-MATERIAL DOCTRINE (the PVC prohibition): some materials don't get a second chance in vacuum — the ban is the engineering.
- THE ONE-MATERIAL-TWO-DUTIES DOCTRINE (the pairing): silicone for cold here, bismuth-silicate for radiation at 139 — one elastomer family, honestly counted.

§5 — VALIDATION: the grade and its full record live in the master and the restart.

§6 — BUILD SEQUENCE

- STEP 1 — Re-rate the book: every fleet gauge chart re-issued against the -95°C calibration; the room-temperature-only charts withdrawn.
- STEP 2 — Strip the PVC: fleet survey for legacy PVC jacketing; replacement schedule under the silicone standard.
- STEP 3 — Bench the couple: conductor-to-silicone differential contraction cycled to -95°C — jacket fatigue and micro-fissure data logged.
- STEP 4 — Fit the jackets: Phase 91 carbon-film on the HV buses; defrost draw and shielding attenuation measured.
- STEP 5 — Drill the breach: cold-snap fault-ride-through test on an instrumented grid section — the emergency as the exam.
- STEP 6 — Publish the ledger: the re-rated book, cycle data, drill results — open under the license.

§7 — CROSS-PHASE (INLINED IN FULL)

- PHASE 91 — the carbon-film membranes: the bus jacketing.
- PHASE 139 — the bismuth jackets (GP-IM-139): the radiation half of the cable doctrine — one family, two coats.

- PHASE 126 — the wall-sink (GP-IM-126): the cold as a resource; here the cold as the rating condition.
- PHASE 135 — the umbrella (GP-IM-135): the EMP shielding context for the bus jackets.
- PHASE 141 — the plunger gates (GP-IM-141): where cross-section-as-ampacity is stated plain.

§8 — DO-NOT-BUILD

- DO NOT rate for the showroom — the breach case is the rating; room-temperature-only charts are banned.
- DO NOT jacket in PVC — brittle and corrosive in exactly the conditions the fleet lives in.
- DO NOT print the old impedance direction — cold copper conducts better; the correction is seated.
- DO NOT forget the jacket is structural — differential contraction kills from the insulation side; bench the couple, not just the copper.

§9 — OWED

OWED: nothing from the physics side — the impedance direction is corrected in the record and the vet closed the flag. Standing engineering program: the mechanical/material stress ratings under thermal cycling (conductor-insulation couple fatigue data) grow with the bench ledger.

§10 — STATUS / PROVENANCE / CHANGE CONTROL

STATUS: CHAPTER GP-IM-138, v1.0 — CURRENT, seated law, master v2.1 (numerical print order). Built 23 August 2026, eleventh of the 20-chapter 'ok next 20' shift (the author's order, 23 August 2026: 'ok next 20'). First version until publication — 'until i publish it, it is still first version, otherwise is just typing' (his law, 22 August 2026).

PROVENANCE — THE STANDING ORDERS, VERBATIM: the town-trip order (seated in sitting 519): 'ok i have to go to town, i have converted them to pdfs now and am uploading, do the next 10 phases and i will read them when i get back' — the order that opened the chapter program; the follow-on orders (seated in sittings 537, 557, 561, 562, 564, 566, 572 and 576): 'ok next 10' / 'ok next ten' / 'all good next 10' / '10 more before go to the old lady for dinner' / 'do another 20 while i away so we clear the 100 mark for the day when i get back' / 'ok next 20'.

CHANGE CONTROL: this design changes only on the Author's orders, seated as sittings in the master record. If the master and this chapter ever disagree, THE MASTER WINS. This is a workshop chapter — it carries the current design only; the full change record lives in the master and the restart.

END OF CHAPTER 138