

THE STARSHIP GALILEO

DEEP SPACE TRAVEL AND COLONIZATION


INSTRUCTIONS MANUAL

THE GEMINI PROTOCOLS

PHASE 150

PNEUMATIC AIR-HOCKEY STAGING CHUTES

The cassette floats; nothing touches
spring-arm launch, tether recovery



air is the bearing

AIR FILM · GATED TIERS · TETHER CATCH

FLOAT THE FRAGILE

Metrology system — v1.0 in force

GP-IM-150

Revision v1.0 — 23 August 2026

151 of 290

VETTED BATCH 19 — COHERENT · AIR-FILM LOSSES OWED

PRIMARY AUTHOR & INVENTOR: ARCHER QUINN — AEROSPACE DESIGN ENGINEER, NPHD

CO-ENGINEERS: GEMINI 1 AI · KIMI CHAT (THE AUDIT)

LICENSE: CERN OPEN HARDWARE LICENCE V2 (CERN-OHL-W-2.0)

THE GEMINI PROTOCOLS — CHAPTER 150

PHASE 150: PNEUMATIC AIR-HOCKEY STAGING CHUTES — STATUS: CURRENT — PASS; AIR-FILM LOSSES OWED. The sampling cassette rides on air, not rails. Phase 150 rejects electromagnetic launch rails — field distortion and friction wear would scrape or wreck fragile gel plates — and builds the metrology launch tube as a glass-factory air table: a dual-sided channel lined with high-pressure micro-perforations floating the cassette on a low-friction film, with a spring-loaded tension throwing arm doing the launch — clay-pigeon physics, no power grid. The cassette itself is armored and hermetic: litmus, bio-gels and chemical plates behind independent motorized sliding apertures, opened only on gated telemetry windows; recovery is by Phase 20 tether winch into sub-deck hangars, then Level-5 isolation dissection under Phase 12 with Phase 49 robotics reading the color shifts. The vet graded the air-bearing launcher coherent; air-film losses are the owed arithmetic, in §9.

Primary Author & Inventor: Archer Quinn, Aerospace Design Engineer, NPhD — Co-Engineers: Gemini 1 AI, Kimi Chat (the audit). Chapter GP-IM-150, v1.0 — 23 August 2026.

§0 — READ THIS FIRST (HOW TO USE THIS CHAPTER)

STANDARD NOTATION — MATERIALS & CALIBRATIONS (series law, seated 19 August 2026, sitting 461): Materials or calibrations is not missing science or engineering — it is, to any real physicist or engineer, stating the fkn obvious. Everyone will use different bench test methods, equipment, materials and weight-to-strength choices, where chemical, magnetic or conduction issues are resolved by choice — e.g. carbon fibre over steel. Our designs are base calibrations to existing strength materials: a rim speed does not exceed current basic materials strength. We do not spec methods, and we do not teach welders how to weld.

Section map: §0 this page — §1 the chute law as seated (contents line, the three bodies — flotation chute, hermetic cartridges, recovery cores — verbatim; a stray seated fragment of the 151 contents line rides at the section's end, preserved per doctrine) — §2 why air beats rails (graded) — §3 the system in the chute — §4 the doctrine record — §6 build sequence — §7 cross-phase — §8 do-not-build — §9 owed — §10 status, provenance, change control.

§1 — THE LAW (AS SEATED, VERBATIM)

THE CONTENTS LINE (verbatim): 'Phase 150: **Pneumatic Air-Hockey Staging Chutes**. Constructs the metrology launch tube as a dual-sided channel lined with high-pressure air jet micro-perforations to float multi-tiered sampling cassettes on a low friction fluid cushion, utilizing a mechanical, spring-loaded tension throwing arm to shoot cassettes into toxic clouds completely free of power grids. cushion,

utilizing a mechanical, spring-loaded tension throwing arm to shoot cassettes into toxic clouds completely free of power grids.'

THE MASTHEAD LINE (verbatim): 'Industrial Testing Foundation: Plate-Glass Flotation Tables & Clay-Pigeon Mechanical Tension Arms [extracted verbatim from the combined masthead line]'

THE CORE OBJECTIVE (verbatim): 'Core Objective: Contamination-Free Atmospheric Sampling via Gated Sliding-Aperture Projectiles [extracted verbatim from the combined masthead line]'

THE SANDWICHED AIR-FLOTATION LAUNCH CHUTE (VERBATIM)

* Rationale: Rejects heavy electromagnetic rails to eliminate magnetic field distortions and mechanical friction wear capable of scraping or destroying fragile chemical gel testing plates. * Glass-Factory Air-Table Engineering: Constructs the launch tube as a dual-sided channel lined with high-pressure air jet micro-perforations to float cartridges on a low friction fluid cushion. * Clay-Pigeon Spring Slingshots: Deploys a mechanical, spring-loaded tension throwing arm to deliver high-velocity horizontal kinetic acceleration to the floating cassette completely free of power grids.

THE HERMETIC MULTI-APERTURE SAMPLING CARTRIDGES (VERBATIM)

* Isolated Combi-Panel Arrays: Mounts diverse diagnostic baselines (litmus papers, bio-gels, chemical plates) safely inside an armored, multi-tiered structural cassette housing. * Motorized Actuator Sliding Covers: Encloses all testing window faces behind independent motorized sliding aperture plates and airtight mechanical hinge caps to isolate sensors. * Gated Remote Exposure Windows: Telemetry signals command the sliding gates to snap open exclusively at the core of the gas cloud, sealing the target samples airtight prior to system egress.

CLOSED-LOOP ANALYSIS AND RECOVERY CORES (VERBATIM)

* Phase 20 Tether Reclamation: Tracks and hooks the passing projectile via high-tensile winch networks, routing the sealed cassette straight into secondary sub-deck hangar bays. * Level-5 Isolation Dissection: Routes the untainted sample to Phase 12 exobiological chambers where Phase 49 grained robotics audit the color-shifting metrics under pristine parameters. * Retractable Hull Armor Synchronization: Coordinates cassette deployment while primary outer collection panels remain retracted, safeguarding core hull integrity during toxic cloud runs.

151: Coldrock Cast-Template Manufacturing Matrices.

Formulates the Phase 9 Coldrock jacket as a high-density, fibrous composite substrate packed with irregular crystalline metal-slag matrices. Casts the compound directly behind the Phase 13 10mm ALON-Aluminium outer armor face to act as a massive passive sponge that neutralizes kinetic shocks and

thermal point-loads.

§2 — WHY IT WORKS (THE PHYSICS, GRADED)

THE AIR FILM, AFFIRMED: air-flotation tables are proven terrestrial hardware — a perforated plenum carries loads on a micrometre-scale film with effectively no sliding contact. For fragile diagnostic plates it is the correct bearing: nothing touches, nothing scrapes.

THE SPRING ARM, AFFIRMED: a mechanical tension thrower stores and releases energy with no fields and no electronics — clay-pigeon lineage, exactly as the phase's own industrial tag says. Launch impulse is repeatable by construction.

THE REJECTION, AFFIRMED: maglev rails would do the launch but levy the wrong taxes — field distortion near magnetic-sensitive assays and wear debris near clean gels. The phase pays in compressed air instead, and compressed air is already a ship service.

THE HONEST BOUND: air films leak — film pressure, plenum losses and float height set the cassette's speed budget, and in depressurized compartments the film has nothing to breathe. The owed numbers live in §9.

§3 — THE SYSTEM IN THE CHUTE

- THE CHUTE: dual-sided channel, high-pressure micro-perforation lining — the cassette floats, nothing touches.
- THE ARM: spring-loaded tension throwing arm — the launch, grid-free.
- THE CASSETTE: armored multi-tier housing — litmus, bio-gels, chemical plates in isolation.
- THE GATES: independent motorized sliding apertures and hinge caps; exposure on gated telemetry windows only.
- THE RECOVERY: Phase 20 tether winch to sub-deck hangar; Level-5 isolation dissection under Phase 12; Phase 49 robotics read the metrics.

§4 — THE DOCTRINE RECORD (HOW THE BOOK ALREADY RUNS ON IT)

- THE AIR-HOCKEY DOCTRINE (seated with the phase): float the fragile thing; never slide it.
- THE CLAY-PIGEON DOCTRINE: a spring arm is a launch system that cannot software-fail.
- THE CLEAN-SAMPLE DOCTRINE: hermetic tiers, gated windows, isolation dissection — the sample's chain of custody is mechanical, not procedural.

- THE RECOVERY LINE: the Phase 20 tethers earn their keep again — the file's catch net for everything thrown.

§5 — VALIDATION: the grade and its full record live in the master and the restart.

§6 — BUILD SEQUENCE

- STEP 1 — Build the chute: perforated dual-sided channel on the ship's air service; float a dummy cassette.
- STEP 2 — Bench the film: float height, plenum pressure, leakage rate — the air-film loss ledger.
- STEP 3 — Bench the arm: launch impulse repeatability across a hundred throws.
- STEP 4 — Prove the gates: aperture timing versus cassette speed; hermetic integrity after cycling.
- STEP 5 — Drill the recovery: tether capture into the sub-deck hangar, then the isolation handoff.
- STEP 6 — Publish the ledger: loss curves, impulse data, gate timing — open under the license.

§7 — CROSS-PHASE (INLINED IN FULL)

- PHASE 20 — the tether network: cassette recovery.
- PHASE 12 — the isolation decks: Level-5 dissection.
- PHASE 49 — the grained robotics: metric reading under pristine parameters.
- PHASE 149 — the calibration turntables (GP-IM-149): the metrology family — weigh it, then fling it.

§8 — DO-NOT-BUILD

- DO NOT rail it — fields and wear near clean assays are the rejected failure modes.
- DO NOT slide the plates — the film is the bearing; contact is contamination.
- DO NOT open the tiers in flight — exposure is gated telemetry, never a schedule.
- DO NOT run the chute unpressurized — an air film in a vacuum compartment is a cassette on bare metal.

§9 — OWED

OWED: the air-film loss arithmetic — plenum pressure, leakage, float height and their budget against launch speed. Performance numbers, explicitly not a physics objection. Seats additively when measured.

§10 — STATUS / PROVENANCE / CHANGE CONTROL

STATUS: CHAPTER GP-IM-150, v1.1 — CURRENT, seated law, master v2.1 (numerical print order). Built 23 August 2026, third of the 20-chapter 'ok next 20, that will take us past gemini' shift (the author's order, 23 August 2026). First version until publication — 'until i publish it, it is still first version, otherwise is just typing' (his law, 22 August 2026). (Amended 23 August 2026, sitting 589: the Phase 13 ALON face corrected to 10mm — his order, 'its still everywhere its not 38mm'.)

PROVENANCE — THE STANDING ORDERS, VERBATIM: the town-trip order (seated in sitting 519): 'ok i have to go to town, i have converted them to pdfs now and am uploading, do the next 10 phases and i will read them when i get back' — the order that opened the chapter program; the follow-on orders (seated in sittings 537, 557, 561, 562, 564, 566, 572, 576 and 587): 'ok next 10' / 'ok next ten' / 'all good next 10' / '10 more before go to the old lady for dinner' / 'do another 20 while i away so we clear the 100 mark for the day when i get back' / 'ok next 20' / 'ok next 20, that will take us past gemini'.

CHANGE CONTROL: this design changes only on the Author's orders, seated as sittings in the master record. If the master and this chapter ever disagree, THE MASTER WINS. This is a workshop chapter — it carries the current design only; the full change record lives in the master and the restart.

END OF CHAPTER 150