

Question 1

Not yet answered

Marked out of 1.00

Flag question

Care afirmație este adevărată când se discută despre adresa Default Gateway?

Which statement is true regarding the role of a default gateway address?

(un singur răspuns este corect/one correct answer)

Select one or more:

- ☐ a. Adresa Default Gateway este adresa rețelei / The default gateway address is the network address
- ☐ b. Adresa Default Gateway este aceeași cu default static route. / The default gateway address is the same as the default static route
- ☐ c. Adresa Default Gateway nu poate fi configurată automat, la nivelul unui host, utilizând un server de DHCP / The default gateway address cannot be configured automatically using a DHCP server
- ☒ d. Adresa Default Gateway reprezintă adresa interfeței routerului care permite trafic în afara rețelei locale / The default gateway address is the address of the router's interface that allows communication outside the local network

Question 2

Not yet answered


Marked out of 1.00

Flag question

Conșiderați configurația de mai jos. Ce rută statică trebuie configurată pe routerul R1 pentru ca host-ul A să poată comunica cu host-ul B din rețeaua 172.16.0.0?

Refer to the exhibit. Which static route should be configured on Router1 so that host A will be able to reach host B on the 172.16.0.0 network?

(un singur răspuns este corect/one correct answer)



Select one or more:

- ☒ a. ip route 172.16.0.0 255.255.0.0 192.168.0.2
- ☐ b. ip route 192.168.0.0 172.16.0.0 255.255.0.0
- ☐ c. ip route 172.16.0.0 255.255.0.0 192.168.0.1
- ☐ d. ip route 172.16.0.0 255.255.0.0 172.16.0.2

Question 3

Not yet answered

Marked out of 1.00

Flag question

Unei interfețe de router i-a fost atribuită adresa IP 12.22.13.95 cu o mască de 255.255.255.224. Care dintre următoarele afirmații ar descrie această adresă?

A router's interface has been assigned an IP address of 12.22.13.95 with a mask of 255.255.255.224. Which of the following would describe this address?

(un singur răspuns este corect/one correct answer)

Select one or more:

- ☒ a. Aceasta este o adresă broadcast / This is a broadcast address.
- ☐ b. Aceasta este o adresă de rețea / This is a network address
- ☐ c. Aceasta nu este o adresă validă / This is not a valid address
- ☐ d. Aceasta este o adresă de host utilizabilă / This is a useable host address

Question 4

Not yet answered

Marked out of 1.00

Flag question

Considerand configuratia de mai jos, care este rolul comenzii **switchport access vlan 12**?

Given the bellow configuration what is the role of the **switchport access vlan 12** command?

(un singur raspuns este corect/one correct answer)

```
Switch(config)#interface FastEthernet0/1
Switch(config-if)#switchport access vlan 12
Switch(config-if)#switchport mode access
Switch(config-if)#switchport voice vlan 112
Switch(config-if)#spanning-tree portfast
```

Select one or more:

- ☐ a. Comanda configureaza portul FastEthernet0/1 in mod trunk pentru VLANul 12 / The command sets the FastEthernet0 / 1 port in trunk mode for VLAN 12
- ☐ b. Comanda seteaza portul FastEthernet0/1 in VLANul de voce 12 / The command sets the FastEthernet0 / 1 port in the voice VLAN 12
- ☐ c. Comanda seteaza portul FastEthernet0/1 in VLANul de date 112 / The command sets the FastEthernet0 / 1 port in the data VLAN 112
- ☒ d. Comanda seteaza portul FastEthernet0/1 in VLANul de date 12 / The command sets the FastEthernet0 / 1 port in the data VLAN 12

Question 5

Not yet answered

Marked out of 1.00

Flag question

Care afirmație reprezintă un avantaj pentru a folosi un protocol de rutare link-state în locul unui protocol de rutare vector-distanță?

Which is an advantage of using a link-state routing protocol instead of a distance vector routing protocol?

(un singur raspuns este corect/one correct answer)

Select one or more:

- ☐ a. După etapa inițială, protocoalele de rutare link-state consumă, în mod general, mai puțină lățime de bandă pentru a comunica schimbările din topologie. / After the initial stage, they generally require less bandwidth to communicate changes in a topology.
- ☐ b. Baza de date a topologiei (topology database) elimină necesitatea folosirii tabelului de rutare. / The topology database eliminates the need for a routing table.
- ☒ c. Actualizări periodice trebuie trimise pentru a minimiza inconsistențele din baza de date topologică. / Frequent periodic updates are sent to minimize the number of incorrect routes in the topological database.
- ☐ d. Protocoalele de rutare link-state sunt mai puțin complexe decât protocoalele de rutare vector-distanță. / Link-state protocols are less complex than distance vector protocols.

La 5 am gresit

Question 6

Not yet answered

Marked out of 1.00

Flag question

Care este serviciul IPv6 automat care potrivește numele de resurse cu adresa IPv6 necesară?

What is the automated service on IPv6 that matches resource names with the required IP address?

(un singur raspuns este corect/one correct answer)

Select one or more:

- ☐ a. Telnet
- ☐ b. SSH
- ☒ c. DNS
- ☐ d. HTTP

Question **7**

Not yet answered

Marked out of 1.00

Flag question

La ce nivel al stivei de protocoale ISO/OSI opereaza un Access Point (AP)?

An Access Point (AP) is operating at which layer of the ISO/OSI protocol stack?

(un singur raspuns este corect/one correct answer)

Select one or more:

- ☐ a. Nivelul Transport / Transport layer
- ☐ b. Nivelul retea / Network layer
- ☐ c. Nivelul fizic / Physical layer
- ☒ d. Nivelul legatura de date / Data Link Layer

Question **8**

Not yet answered

Marked out of 1.00

Flag question

Explicati diferenta dintre NAT static si NAT dinamic (PAT sau NAT overload).

Explain the difference between static NAT and dynamic NAT (PAT or NAT overload)

When using static NAT, an inside address is mapped to an outside address and this relation is permanent. The inside address is always translated to that outside address.(1-to-1 relation).

When using dynamic NAT, private IP addresses are mapped to public ones. The dynamic NAT uses the concept of pool of addresses that are eligible. NAT overloading maps multiple private IP addresses to a single public IP address. The pool of addresses is also defined.

Question **9**

Not yet answered

Marked out of 1.00

Flag question

Care comandă va permite conectarea tuturor conexiunile de trafic DNS către un server DNS cu adresa IP 22.3.4.5/24?

Which command will allow all DNS traffic connections, to a server with the IP address 22.3.4.5/24?

(un singur raspuns este corect/one correct answer)

Select one or more:

- ☒ a. access-list 120 permit udp any 22.3.4.5 0.0.0.255 eq 53
- ☐ b. access-list 120 deny udp any 22.3.4.5 0.0.0.255 eq 53
- ☐ c. access-list 120 permit icmp any 22.3.4.5 0.0.0.255 eq 53
- ☐ d. access-list 120 permit udp 22.3.4.5 0.0.0.255 eq 53 any

Question **10**

Not yet answered

Marked out of 1.00

Flag question

Prezentati doua diferente dintre *rutarea vector distanta* si *rutarea starea legaturii*.

Present two differences between *distance vector routing* and *link-state routing*.

The first difference between distance vector routing and link-state routing is when using that distance vector routing each router transmits routing information only to its neighbors, while when using link-state routing each router sends information to all routers.

The second difference is that for distance-vector routing the information is transmitted on a regular period basis (for example each 15 seconds for RIP that is a distance-vector routing protocol), while for link-state routing only when changes occur the information is transmitted.