Construction Chemicals

Product Datasheet
Edition: 01 | Date: Nov 2026
Accessories



Addmix HPS

Hydroxypropyl Starch Ether
Additive for Dry-Mix Mortars

Product Description

Addmix HPS is a hydroxypropyl starch ether for dry-mix mortars. Used together with cellulose ethers, it improves water retention, thickening and slip resistance, especially in tile adhesives.

Uses

- Wall putties.
- Tile adhesives.
- Plastering mortars and cement renders.
- Gypsum products.
- Joint fillers.

Advantages

- Improves slip resistance of tile adhesives.
- Supports water retention.
- Thickening effect.
- Easy to blend in dry mixes.
- Low dosage: 0.2 – 0.5 %.

Application

1. **Dosage**
   Use 0.2 – 0.5 % of the total dry-mix weight.
2. **Dry Blending**
   Pre-blend with the other dry components before adding water.
3. **Testing**
   Verify workability, water retention and adhesion in laboratory trials.

Consumption

0.2 – 0.5 %
of total dry-mix weight
Optimum dosage to be set by laboratory trials.

Packaging

20 kg and 25 kg bags; 20 ft container 12 – 14 t, 40 ft container 24 – 28 t.

Storage & Shelf Life

12 months in original, unopened bags. Store dry, protected from moisture and heat.

Technical Data

Typical values at 25 °C

Property	Typical Value	Test Method
Type	Hydroxypropyl starch ether	—
Appearance	White powder	—
Bulk density	500 – 600 g/L	—
Moisture	≤ 8 %	—
Ash content	12 ± 2 %	—
pH	8 – 10	—
Viscosity (5 % solution)	2,000 – 3,000 mPa·s	—
Shelf life	12 months	—

Consumption

Application	Typical dosage
Tile adhesives	0.2 – 0.5 %
Putties and plasters	0.2 – 0.5 %
Gypsum products	0.2 – 0.5 %
Joint fillers	0.2 – 0.5 %

Consumption is theoretical and varies with substrate porosity, profile and application method.

Application Conditions

- Add to the dry mix, not directly to water.
- Blend thoroughly for uniform distribution.
- Store dry; keep bags closed.
- Check compatibility with the full formulation.

Application Notes

- Add to the dry mix; do not dissolve directly in water.
- Use together with cellulose ethers (e.g. Addmix HPMC) as per the formulation.
- Set the dosage by laboratory trials.
- Keep bags closed.

Health & Safety

- Combustible dust: avoid dust clouds and ignition sources.
- Wear a dust mask, goggles and gloves when handling.
- Keep the work area clean of dust deposits.

First Aid & Cleaning

- Eyes: rinse with clean water and seek medical advice if irritation persists.
- Skin: wash with soap and water.
- Inhalation of dust: move to fresh air.
- Clean equipment with dry methods first, then water.

The information in this datasheet is based on laboratory tests and practical experience and is given in good faith. Users should verify product suitability for their specific application. O MIX reserves the right to update this information without prior notice.