METHOD STATEMENT

Geomat — Nonwoven Geotextile Polyester / Polypropylene

Project Name		**Document No.**	OMX-MS-GEOMAT
Main Contractor		**Revision**	01
Consultant		**Date of Issue**	Nov 2026
Product	Geomat	**Status**	For Approval

1. Purpose

This method statement defines the procedure, sequence, resources, quality checks and safety measures for the supply and application of Geomat on site. It ensures that the work is carried out safely, in line with the approved drawings and project specification, and achieves the performance stated in the O MIX Technical Data Sheet.

2. Scope of Work

This method statement covers surface preparation, laying, overlapping, fixing and covering of Geomat nonwoven geotextile for separation, filtration, drainage and protection of waterproofing layers.

- Inspection of the formation or substrate.
- Laying and overlapping of rolls.
- Temporary fixing against wind.
- Covering with the specified layer.
- Inspection and handover.

3. Definitions

Term	Meaning
Nonwoven geotextile	Fabric made of bonded fibres, not woven.
Overlap	Width by which adjacent rolls cover each other (min. 25 cm).
Separation	Preventing mixing of two soil layers.
Protection layer	Geotextile placed over a membrane to prevent damage.

4. Roles & Responsibilities

Role	Responsibility
Project Manager	Overall responsibility for planning, resources, approvals and coordination with the consultant and main contractor.
Site Engineer	Supervises the work daily; confirms substrate readiness, climate conditions, mixing, consumption and sequence; keeps daily records.

Role	Responsibility
QA/QC Inspector	Carries out inspections and tests at each stage, records results, raises inspection requests at hold points and signs the checklist.
HSE Officer	Conducts toolbox talks, checks PPE, ventilation, access and safe storage; stops work if unsafe conditions arise.
Foreman / Applicators	Carry out the work as per this method statement and report any deviation immediately.
Storekeeper	Receives, stores and issues materials in original packaging under the stated storage conditions; controls batch numbers.

5. Materials

Material	Description
Geomat	Nonwoven geotextile, weight as specified
Fixings	Pins, sandbags or adhesive

5.1 Key product data

Property	Typical Value
Material	Nonwoven polyester / polypropylene
Weights available	100 – 1200 g/m²
Roll width	1 – 6 m
Roll length	≥ 25 m
Minimum overlap	25 cm
Colours	White, black, grey, mixed

6. Tools & Equipment

- Knife
- Tape measure
- Roll bar
- Thermo-hygrometer and surface thermometer (dew point check)
- Moisture meter
- Measuring buckets and scale
- Masking tape and protective sheeting
- Lighting and extension cables

6.1 Personal protective equipment

- Gloves
- Safety shoes
- Helmet

7. Storage & Handling

- Unlimited shelf life. Store rolls dry, off the ground and protected from sunlight.
- Store on pallets, off the ground, in a dry, covered and ventilated area.
- Keep containers closed until use; use materials on a first-in, first-out basis.
- Store rolls and cartons flat, off the ground, protected from direct sunlight, heat, oil and mechanical damage.
- Handle with care to avoid damage to packaging; do not stack beyond the safe height.

8. Pre-Start Requirements

- Material submittal, this method statement and the inspection plan approved by the consultant.
- Work area handed over clean, free of other trades and with safe access.
- Adequate lighting, power supply and ventilation available.
- Climate conditions checked and recorded before work starts.
- A trial area prepared and approved where required by the project.
- Toolbox talk held with the work team covering this method statement and the safety measures.

9. Surface Preparation

1. Level the surface and remove stones, debris and sharp objects.
2. Confirm the specified weight and roll width.
3. Plan roll layout to minimise joints.
4. Obtain QA/QC approval of the prepared surface before laying.

10. Preparation of Material

1. Check roll labels (weight, width) against the specification.
2. Move rolls with a roll bar; do not drag on rough ground.

11. Laying

1. Unroll Geomat flat and without wrinkles.
2. Overlap adjacent rolls by at least 25 cm (more on soft ground).
3. Secure with pins or sandbags against wind.
4. Cut around penetrations and cover with patches overlapping 25 cm.
5. Record the area installed.

12. Covering & Protection

- Cover with the specified layer as soon as possible.
- Repair damaged areas with patches overlapping 25 cm.

- Do not allow vehicles directly on the geotextile.

13. Quality Control & Inspection

Check	Stage	Acceptance Criteria	By
Material	On receipt	Correct weight and size	Storekeeper
Surface	Before laying	Level, free of sharp objects	QA/QC
Overlaps	During laying	≥ 25 cm	QA/QC
Final	Before covering	No tears, no wrinkles	QA/QC

13.1 Inspection and test plan

Activity	Inspection / Test	Frequency	Record
Material receipt	Weight, width, condition	Each delivery	Material inspection report
Surface	Level, free of sharp objects	Each area	Inspection request
Laying	Overlaps, wrinkles	Each area	Daily report
Covering	Prompt, no damage	Each area	Handover checklist

14. Defects & Remedies

Defect	Likely Cause	Remedy
Insufficient overlap	Poor layout	Add patches overlapping 25 cm
Tears / punctures	Sharp objects; traffic	Patch with 25 cm overlap
Displacement	Wind	Re-lay and secure

15. Health, Safety & Environment

Hazard	Control Measures
Cuts from knives and tools	Cut-resistant gloves
Manual handling of rolls	Correct lifting technique
Slips and trips	Housekeeping; barricades

- Wear gloves when cutting.
- Use safety shoes and follow site rules.
- Avoid trip hazards from unrolled material.
- Cuts: clean and dress the wound.
- Eyes: rinse with clean water if fibres enter.

15.1 Waste & environment

- Collect empty containers and residues in designated bins.
- Do not discharge material or washings into drains or soil.
- Allow small quantities of leftover mixed material to cure before disposal; dispose of according to local regulations.

16. Cleaning

- Collect off-cuts in waste bins.

17. Limitations

- Minimum overlap 25 cm.
- Limit UV exposure before covering.
- Any deviation from this method statement must be approved by the Site Engineer and the consultant.

Appendix A — Inspection Checklist

Inspection Item	Result	Remarks
Weight verified	☐ Yes ☐ No	
Surface prepared	☐ Yes ☐ No	
Laid without wrinkles	☐ Yes ☐ No	
Overlaps ≥ 25 cm	☐ Yes ☐ No	
Secured against wind	☐ Yes ☐ No	
Damaged areas patched	☐ Yes ☐ No	
Covered promptly	☐ Yes ☐ No	

Inspected by	Signature	Date