Construction Chemicals

Product Datasheet
Edition: 01 | Date: Nov 2026
Accessories

Geomat

Nonwoven Geotextile
Polyester / Polypropylene



Product Description

Geomat is a nonwoven geotextile made of polyester or polypropylene fibres. It separates soil layers, filters and drains water, and protects waterproofing membranes from mechanical damage. It is also used as reinforcement in O MIX roof waterproofing systems.

Uses

- Separation of soil and aggregate layers.
- Filtration and drainage.
- Protection of waterproofing membranes.
- Reinforcement in Roofguard AC roof systems.
- Landscaping, roads and civil works.

Advantages

- Separates soil layers.
- Filters and drains water.
- Protects waterproofing layers.
- High puncture resistance.
- Unlimited shelf life.

Application

1. **Preparation**
   Level and clean the surface; remove sharp objects.
2. **Laying**
   Unroll Geomat without wrinkles; overlap adjacent rolls by at least 25 cm.
3. **Covering**
   Cover as specified promptly; do not leave exposed to sunlight for long periods.

Consumption

1 m² per m²
plus overlaps (min. 25 cm)
Allow approx. 10 – 15 % for overlaps.

Packaging

Rolls 1 – 6 m wide, min. 25 m long; weights 100 – 1200 g/m²; white, black, grey or mixed.

Storage & Shelf Life

Unlimited shelf life. Store rolls dry, off the ground and protected from sunlight.

Technical Data

Typical values at 25 °C

Property	Typical Value	Test Method
Material	Nonwoven polyester / polypropylene	—
Weights available	100 – 1200 g/m²	—
Roll width	1 – 6 m	—
Roll length	≥ 25 m	—
Minimum overlap	25 cm	—
Colours	White, black, grey, mixed	—

Consumption

Weight	Thickness	Tensile strength	Puncture (CBR)
100 g/m²	1 mm	5 – 6 kN/m	500 N
500 g/m²	3 mm	15 – 16 kN/m	2500 N

Consumption is theoretical and varies with substrate porosity, profile and application method.

Application Conditions

- Lay on a smooth surface free of sharp objects.
- Overlap adjacent rolls by at least 25 cm.
- Secure against wind during installation.
- Cover promptly to limit UV exposure.

Application Notes

- Select weight according to the function (separation, filtration or protection).
- Unroll in the direction of the slope on inclined surfaces.
- Do not drive vehicles directly on the geotextile.
- In roof systems embed in the wet Roofguard AC coat.

Health & Safety

- Wear gloves when cutting.
- Use safety shoes and follow site rules.
- Avoid trip hazards from unrolled material.

First Aid & Cleaning

- Cuts: clean and dress the wound.
- Eyes: rinse with clean water if fibres enter.
- Skin: wash with soap and water.
- Collect off-cuts in waste bins.

The information in this datasheet is based on laboratory tests and practical experience and is given in good faith. Users should verify product suitability for their specific application. O MIX reserves the right to update this information without prior notice.