Construction Chemicals

**Product Datasheet**
Edition: 01 | Date: Nov 2026
Sport Court Systems

# Acrycourt CU

Rubberised Acrylic Cushion Layer for Sport Courts




## Product Description

Acrycourt CU is a water-based acrylic cushion coating containing rubber granules. Applied in several coats over the resurfacer, it builds a resilient layer that improves player comfort and reduces fatigue on tennis, basketball and multi-purpose courts.

## Uses

- Tennis courts.
- Basketball courts.
- Multi-purpose and school courts.
- Cushion layers of the O MIX Soft Acrylic system.

## Advantages

- Resilient cushioning layer.
- Improves player comfort.
- Durable and flexible.
- Water-based, low odour.
- Suitable for outdoor courts.

## Application

1. **Surface Preparation**
   Apply over a cured, clean Acrycourt RAC resurfaced base.
2. **Mixing**
   Stir thoroughly before use; apply as supplied.
3. **Application**
   Spread with a rubber squeegee in several coats, allowing each coat to dry.

## Consumption

**1.5 – 3.0 kg/m²**
per coat
Soft Acrylic system: 3 kg/m² coarse + 3 kg/m² fine.

## Packaging

20 kg pails and 200 kg drums.

## Storage & Shelf Life

12 months in original, unopened packaging. Store at +5 °C to +35 °C; protect from frost and direct sunlight.

## Technical Data

*Typical values at 25 °C*

| Property | Typical Value | Test Method |
|---|---|---|
| **Base** | Acrylic with rubber granules | — |
| **Density** | 1.20 – 1.35 kg/L | — |
| **Solids content** | 50 – 65 % | — |
| **Viscosity** | 20,000 – 35,000 mPa·s | — |
| **Drying time** | 2 – 4 hours | — |
| **Recoat time** | 6 – 12 hours | — |
| **Full cure** | 24 – 48 hours | — |

## Consumption

| Use | Consumption |
|---|---|
| **Each cushion coat** | 1.5 – 3.0 kg/m² |
| **Soft Acrylic — coarse layers** | 3 kg/m² |
| **Soft Acrylic — fine layers** | 3 kg/m² |

*Consumption is theoretical and varies with substrate porosity, profile and application method.*

## Application Conditions

- Air and surface temperature: +10 °C to +35 °C.
- Do not apply when rain or dew is expected before the coat has dried.
- Asphalt at least 14 days old; concrete at least 28 days old.
- Surface clean, dry, sound and free of oil and loose material.

## Application Notes

- Apply over a cured resurfaced base.
- Apply several thin coats rather than one thick coat.
- Allow each coat to dry fully before the next.
- Finish with Acrycourt PAC colour coats.

## Health & Safety

- Wear gloves and safety goggles.
- Avoid contact with eyes and prolonged skin contact.
- Ensure ventilation in enclosed areas.

## First Aid & Cleaning

- Eyes: rinse with clean water for 15 minutes and seek medical advice.
- Skin: wash with soap and water.
- Inhalation: move to fresh air.
- Clean tools with water immediately after use.

*The information in this datasheet is based on laboratory tests and practical experience and is given in good faith. Users should verify product suitability for their specific application. O MIX reserves the right to update this information without prior notice.*