Construction Chemicals

Product Datasheet
Edition: 01 | Date: Nov 2026
Sport Court Systems



Acrycourt PAC

Coloured Acrylic Top Coat
for Sport Courts

Product Description

Acrycourt PAC is a water-based, coloured acrylic top coat for sport courts. It provides a colour-stable, UV-resistant and flexible playing surface over the O MIX resurfacer and cushion layers.

Uses

- Tennis and basketball courts.
- Multi-purpose courts and playgrounds.
- Final colour coats of the O MIX Hard and Soft Acrylic systems.

Advantages

- Colour stable and UV resistant.
- Flexible and durable.
- Uniform playing surface.
- Water-based, low odour.
- Wide colour range.

Application

1. **Surface Preparation**
   Apply over a clean, dry, cured resurfacer or cushion layer.
2. **Mixing**
   Stir thoroughly; add silica sand where a textured finish is specified.
3. **Application**
   Apply 2 coats by rubber squeegee or roller, the second at 90° to the first.

Consumption

0.3 – 0.5 kg/m²
per coat (2 coats)
0.5 kg/m² in the O MIX Hard / Soft Acrylic systems.

Packaging

20 kg pails and 200 kg drums.

Storage & Shelf Life

12 months in original, unopened packaging. Store at +5 °C to +35 °C; protect from frost and direct sunlight.

Technical Data

Typical values at 25 °C

Property	Typical Value	Test Method
Base	Pigmented water-based acrylic	—
Density	1.25 – 1.35 kg/L	—
Solids content	50 – 60 %	—
Drying time	1 – 2 hours	—
Recoat time	4 – 6 hours	—
Colours	Range of court colours	—

Consumption

Use	Consumption
Colour coat (each of 2 coats)	0.3 – 0.5 kg/m²
Hard / Soft Acrylic systems	0.5 kg/m²

Consumption is theoretical and varies with substrate porosity, profile and application method.

Application Conditions

- Air and surface temperature: +10 °C to +35 °C.
- Do not apply when rain or dew is expected before the coat has dried.
- Asphalt at least 14 days old; concrete at least 28 days old.
- Surface clean, dry, sound and free of oil and loose material.

Application Notes

- Apply 2 coats crosswise for a uniform colour.
- Use one batch per court to avoid shade differences.
- Apply line marking after the final coat has dried.
- Avoid application in direct midday sun on hot surfaces.

Health & Safety

- Wear gloves and safety goggles.
- Avoid contact with eyes and prolonged skin contact.
- Ensure ventilation in enclosed areas.

First Aid & Cleaning

- Eyes: rinse with clean water for 15 minutes and seek medical advice.
- Skin: wash with soap and water.
- Inhalation: move to fresh air.
- Clean tools with water immediately after use.

The information in this datasheet is based on laboratory tests and practical experience and is given in good faith. Users should verify product suitability for their specific application. O MIX reserves the right to update this information without prior notice.