Construction Chemicals

Product Datasheet
Edition: 01 | Date: Nov 2026
Protective Coating



Stone Sealer AC

Water-Based Acrylic
Wet-Look Concrete & Stone Sealer

Product Description

Stone Sealer AC is a clear, water-based acrylic sealer that gives concrete, stone and pavers a wet-look finish. It repels water, oil and stains, resists UV without yellowing, and helps prevent mould and efflorescence. Low VOC.

Uses

- Decorative and coloured concrete.
- Driveways and stamped concrete.
- Walkways, stairs and public areas.
- Exposed aggregate and interlocking pavers.
- Natural stone and building façades.

Advantages

- Repels water, oil and stains.
- UV stable even under strong Egyptian sun; non-yellowing.
- Clear wet-look gloss finish.
- Helps prevent mould and efflorescence.
- Water-based, low VOC.

Application

1. **Surface Preparation**
   Concrete ≥ 28 days, moisture < 4 %; clean, dry and dust-free.
2. **Mixing**
   Stir well; use undiluted.
3. **Application**
   Apply 2 coats by epoxy roller, 2 – 4 hours apart.

Consumption

0.15 – 0.20 kg/m²
per coat (2 coats)
Depends on substrate porosity.

Packaging

20 kg pails.

Storage & Shelf Life

12 months in original, unopened packaging. Store dry at +5 °C to +35 °C, away from direct sunlight.

Technical Data

Typical values at 25 °C

Property	Typical Value	Test Method
Base	Water-based acrylic	—
Appearance	Clear, glossy (wet look)	—
Density	1.0 ± 0.1 kg/L	—
Touch dry	30 minutes	—
Recoat	2 hours	—
Full dry	24 hours	—
VOC	Low	—

Consumption

Substrate	Consumption per coat
Dense concrete / stone	0.15 kg/m²
Porous concrete / pavers	0.20 kg/m²

Consumption is theoretical and varies with substrate porosity, profile and application method.

Application Conditions

- Ambient and substrate temperature: +10 °C to +35 °C.
- Concrete at least 28 days old, moisture < 4 %.
- Do not apply in rain or direct strong sun.

Application Notes

- Do not dilute.
- Apply thin, even coats; avoid puddles.
- Second coat 2 – 4 hours after the first.
- Allow 24 hours before foot traffic.

Health & Safety

- Wear gloves and safety goggles.
- Avoid contact with eyes and prolonged skin contact.
- Ensure ventilation in enclosed areas; use a mask for spray application.

First Aid & Cleaning

- Eyes: rinse with clean water for 15 minutes and seek medical advice.
- Skin: wash with soap and water.
- Inhalation: move to fresh air.
- Ingestion: rinse mouth and seek medical advice.
- Clean tools with water immediately after use.

The information in this datasheet is based on laboratory tests and practical experience and is given in good faith. Users should verify product suitability for their specific application. O MIX reserves the right to update this information without prior notice.