Construction Chemicals

Product Datasheet
Edition: 01 | Date: Nov 2026
Protective Coating



Stone Sealer WR

Silane / Siloxane
Non-Film-Forming Water Repellent

Product Description

Stone Sealer WR is a clear silane/siloxane water repellent that penetrates deeply into mineral substrates without forming a film. It reduces water absorption by 80 – 95 %, does not change the colour of the surface and allows the substrate to breathe.

Uses

- Natural and artificial stone.
- Concrete, precast and fair-faced concrete.
- Brick and block masonry.
- Building façades, interior and exterior.

Advantages

- Reduces water absorption by 80 – 95 %.
- No colour change; no film.
- Breathable.
- Deep penetration.
- Interior and exterior use.

Application

1. **Surface Preparation**
   Clean, dry and sound surface; repair cracks first.
2. **Preparation**
   Use as supplied; do not dilute.
3. **Application**
   Apply 2 coats by low-pressure spray, brush or roller, 2 – 4 hours apart.

Consumption

0.2 – 0.4 kg/m²
per coat (3 – 6 m²/L)
Depends on substrate porosity; confirm on a trial area.

Packaging

20 kg containers.

Storage & Shelf Life

12 months in original, unopened packaging. Store at +5 °C to +35 °C, away from direct sunlight.

Technical Data

Typical values at 25 °C

Property	Typical Value	Test Method
Base	Silane / siloxane	—
Appearance	Clear, non-film-forming	—
Reduction of water absorption	80 – 95 %	—
Coverage	3 – 6 m²/L	—
Consumption	0.2 – 0.4 kg/m² per coat	—
Number of coats	2	—
Recoat	2 – 4 hours (wet-on-dry)	—
Shelf life	12 months	—

Consumption

Substrate	Consumption per coat
Dense concrete / stone	0.2 – 0.3 kg/m²
Porous brick / block	0.3 – 0.4 kg/m²

Consumption is theoretical and varies with substrate porosity, profile and application method.

Application Conditions

- Ambient and substrate temperature: +5 °C to +35 °C.
- Substrate dry and clean; concrete at least 28 days old.
- Do not apply in rain or when rain is expected within 4 hours.
- Cracks wider than 0.3 mm must be repaired first.

Application Notes

- Apply a trial area to confirm appearance and consumption.
- Apply until saturation without run-down; work bottom to top on walls.
- Do not dilute.
- Protect glass, painted surfaces and plants from overspray.

Health & Safety

- Wear gloves and safety goggles.
- Avoid inhalation of spray mist; ensure ventilation.
- Avoid prolonged skin contact.

First Aid & Cleaning

- Eyes: rinse with clean water for 15 minutes and seek medical advice.
- Skin: wash with soap and water.
- Inhalation: move to fresh air.
- Clean tools immediately after use.

The information in this datasheet is based on laboratory tests and practical experience and is given in good faith. Users should verify product suitability for their specific application. O MIX reserves the right to update this information without prior notice.