Construction Chemicals

SUBMITTAL DOCUMENT

O MIX Safecoat

Hygienic Anti-Microbial
Wall & Ceiling System



Anti-Microbial
Bacteria & fungi

Disinfectants
Resistant

Hygienic
Easy to clean

Low VOC
Water-based

Project	
Main Contractor	
Consultant	
Submittal No. / Rev.	00
Date	Nov 2026

Construction Chemicals

Contents

1. System Method Statement 3

2. TDS — O-Filler 10

3. TDS — Carboseal 13

4. TDS — Safe Coat AC 16

5. Test Reports 19

6. Approvals & Certificates 20

METHOD STATEMENT

O MIX Safecoat — Hygienic Anti-Microbial Wall & Ceiling System

Project Name		**Document No.**	OMX-SMS-05
Main Contractor		**Revision**	01
Consultant		**Date of Issue**	Nov 2026
System	O MIX Safecoat	**Status**	For Approval

1. Purpose

This method statement defines the sequence, resources, inspection and test plan and safety measures for the installation of the O MIX Safecoat system on site. It describes how each layer of the system is prepared, mixed, applied, inspected and protected so that the completed system achieves the performance stated in the O MIX Technical Data Sheets of its components.

2. Scope of Work

O MIX Safecoat is a hygienic wall and ceiling system for clean and sensitive areas. A polymer-modified cementitious filler levels the surface, an acrylic sealer reduces absorption, and an anti-microbial water-based top coat resists bacteria, fungi and disinfectants.

- Substrate inspection, testing and acceptance.
- Surface preparation and repair of defects.
- Stage 1: Levelling / skim coat — O-Filler.
- Stage 2: Sealer — Carboseal.
- Stage 3: Anti-microbial top coat (2 coats) — Safe Coat AC.
- Curing, protection, final testing and handover.

2.1 System build-up

Stage	Product	Function	Consumption
1	O-Filler	Levelling / skim coat	0.5 – 1.0 kg/m²
2	Carboseal	Sealer	0.10 – 0.15 kg/m²
3	Safe Coat AC	Anti-microbial top coat (2 coats)	0.12 – 0.15 kg/m² per coat

2.2 Typical areas of use

- Hospitals and laboratories.
- Clean rooms.
- Pharmaceutical plants.
- Food processing areas.

3. Definitions

Term	Meaning
System	All layers of the build-up applied in the stated sequence.
Hold point	Stage at which work stops until QA/QC (and the consultant, where required) approve.
Recoat window	Minimum and maximum time between two layers for proper inter-layer bonding.
Dew point	Temperature at which moisture condenses; the substrate must be at least 3 °C above it.
Mock-up / trial area	Area applied before the main works to approve materials, method and appearance.

4. Roles & Responsibilities

Role	Responsibility
Project Manager	Planning, resources, approvals and coordination with the consultant and main contractor.
Site Engineer	Daily supervision; confirms substrate readiness, climate, mixing, consumption and recoat windows; keeps daily records.
QA/QC Inspector	Carries out tests at each hold point, records results and signs the inspection checklist.
HSE Officer	Toolbox talks, PPE, ventilation, safe access and storage; stops unsafe work.
Applicator Foreman	Leads the application team and follows this method statement; reports deviations.
O MIX Technical Representative	Technical support, site visits and advice on product use when requested.

5. Materials

Product	Description	Packaging
O-Filler	Polymer-Modified Cementitious Filler & Skim Coat	20 kg bags.
Carboseal	Acrylic Sealer Primer for Paints & Coatings	4 kg and 20 kg pails.
Safe Coat AC	Water-Based Anti-Microbial Coating for Hygienic Areas	5 kg and 20 kg pails.

5.1 Key product data

Product	Mixing ratio	Pot life / working time	Recoat / drying
O-Filler	3.5 – 4.0 L per 20 kg bag	30 – 40 min	24 h drying, then light sanding
Carboseal	Ready to use	—	30 – 60 minutes
Safe Coat AC	Ready to use	—	4 – 6 hours

6. Tools & Equipment

- Diamond grinder and/or shot blaster with dust extraction; industrial vacuum
- Slow-speed drill mixer (300 – 500 rpm) with spiral paddle
- Rollers, brushes, squeegees, notched trowels and steel trowels as required by each stage
- Scales and measuring containers for part mixing (where permitted)
- Thermo-hygrometer, surface thermometer and dew-point calculator
- Moisture meter and plastic sheets for moisture testing
- Masking tape, protective sheeting, barriers and warning signs
- Lighting and extension cables with residual current protection

6.1 Personal protective equipment

- Safety shoes, helmet and high-visibility vest
- Chemical-resistant gloves (nitrile) and safety goggles
- Coveralls with long sleeves
- Dust masks (P2) during grinding and powder mixing
- Respirators with organic vapour cartridges for solvent-containing products and confined spaces
- Knee pads for floor work

7. Storage & Handling

- Store all products in original, unopened packaging in a dry, shaded and ventilated store at the temperatures stated in each TDS.
- Keep Part A, Part B (and Part C) of each kit together; do not mix components from different batches.
- Protect liquids from frost and direct sun, and powders from moisture.
- Store solvent-containing products away from heat, sparks and ignition sources.
- Use materials on a first-in, first-out basis and record batch numbers for each area.
- Condition materials to +15 °C to +25 °C for 24 hours before use in hot or cold weather.

8. Pre-Start Requirements

- Approved material submittal, this method statement and the inspection and test plan.
- Approved drawings showing areas, joints, upstands, drains and details.
- Work area handed over clean, free of other trades, with safe access, lighting and power.
- Mock-up / trial area executed and approved for system, colour and finish.
- Toolbox talk held with the team on this method statement and HSE measures.
- Climate monitoring equipment calibrated and available.

9. Substrate Inspection & Acceptance (Hold Point)

Check	Acceptance criteria	Method
Concrete age	≥ 28 days (cement-based substrates)	Site records
Compressive strength	≥ 25 N/mm²	Rebound hammer (ASTM C805) or cores
Surface tensile (pull-off) strength	≥ 1.5 N/mm²	Pull-off test ASTM D7234
Climate	Substrate ≥ 3 °C above dew point; RH ≤ 85 %	ISO 8502-4 / thermo-hygrometer

10. Surface Preparation

1. Remove dust, loose paint, efflorescence and contaminants.
2. Repair holes and cracks; level the surface with O-Filler.
3. Ensure the substrate is sound and dry.
4. Mask and protect adjacent surfaces, drains and fixtures.
5. Record substrate test results and obtain QA/QC approval before priming (hold point).

11. Application Sequence

Apply the system stage by stage in the order below. Each stage must be inspected and approved before the next stage starts, and the next stage must be applied within the recoat window stated.

11.1 Stage 1 — Levelling / skim coat: O-Filler

Consumption: 0.5 – 1.0 kg/m². Time before next stage: 24 h drying, then light sanding.

1. Pour 3.5 – 4.0 L of clean water into a bucket.
2. Add 20 kg powder gradually while mixing at low speed.
3. Mix 3 minutes, rest 2 minutes, remix briefly.
4. Apply with a steel trowel in layers of 1 – 5 mm (fine) or 5 – 10 mm (coarse).
5. Allow each layer to set before applying the next.
6. Finish with a float or sponge as required.

11.2 Stage 2 — Sealer: Carboseal

Consumption: 0.10 – 0.15 kg/m². Time before next stage: 2 – 4 h.

1. Dilute up to 1 : 1 with water as recommended for the substrate.
2. Apply one coat by brush or roller.

11.3 Stage 3 — Anti-microbial top coat (2 coats): Safe Coat AC

Consumption: 0.12 – 0.15 kg/m² per coat. Time before next stage: 4 – 6 h between coats.

1. Stir thoroughly; use as supplied.

2. Apply the first coat by brush, roller or airless spray.
3. Apply the second coat after 4 – 6 hours.

12. Hold Points & Recoat Windows

Stage	Before starting	Waiting time before next stage	Approved by
1. O-Filler	Substrate accepted (Section 9)	24 h drying, then light sanding	QA/QC
2. Carboseal	Previous stage inspected and approved	2 – 4 h	QA/QC
3. Safe Coat AC	Previous stage inspected and approved	4 – 6 h between coats	QA/QC

13. Curing, Protection & Return to Service

- Protect each layer from rain, dew, dust, water and traffic until it has cured.
- Barricade the area and display warning signs during application and curing.
- Keep ventilation running in enclosed areas until full cure.

14. Quality Control & Inspection Test Plan

Activity	Inspection / Test	Frequency	Record
Material receipt	Product, batch, expiry, packaging condition	Each delivery	Material inspection report
Climate	Air / substrate temperature, RH, dew point (ISO 8502-4)	Start of shift and every 4 h	Daily climate log
Substrate	Strength, pull-off (ASTM D7234), moisture (ASTM D4263)	Each area (hold point)	Inspection request
Mixing	Complete kits, ratio, mixing time	Each mix	Daily record
Consumption	Material used vs area	Each stage	Daily record
Final inspection	Appearance, continuity, finish, details	Each area	Handover checklist

15. Defects & Remedies

Defect	Likely cause	Remedy
Poor adhesion / delamination	Weak, dusty or damp substrate; recoat window exceeded	Remove, re-prepare and reapply; abrade and re-prime if window exceeded
Pinholes / bubbles	Outgassing; air trapped in mixing; thick application	Seal porous areas; mix slowly; spiked roller; sand and recoat
Cracking of cementitious layers	Rapid drying; layer too thick	Protect from sun and wind; apply thinner layers
Colour / shade variation	Different batches; uneven application	Use one batch per area; apply additional coat

16. Health, Safety & Environment

Hazard	Control measures
Skin / eye contact with resins and cement	Gloves, goggles, coveralls; eye-wash station
Inhalation of dust and vapours	Dust extraction; ventilation; masks / respirators
Fire (solvent vapours)	No smoking or hot work; fire extinguisher at the work area
Slips and trips	Housekeeping; barricades and warning signs
Manual handling	Correct lifting; mechanical aids for drums and pails
Electrical equipment	Inspected tools; protected cables with RCD

- Read the Safety Data Sheet of each product before use.
- Keep first-aid kit and eye-wash on site; follow the first-aid measures in each TDS.

16.1 Waste & environment

- Collect empty containers and residues in designated bins.
- Allow small quantities of mixed resin to cure before disposal; dispose of according to local regulations.
- Do not discharge materials or washings into drains or soil.

17. Cleaning

- Clean tools of water-based and cementitious products with water immediately after use.
- Clean tools of epoxy and PU products with the recommended thinner before the material cures.
- Cured material can only be removed mechanically.

18. Limitations

- Do not apply outside the temperature and humidity limits stated in the TDS of each product.
- Do not apply on wet surfaces or when rain or dew is expected before the layer has cured.
- Do not mix or substitute products from other systems without written approval from O MIX.
- Any deviation from this method statement must be approved by the Site Engineer and the consultant.

Appendix A — Inspection Checklist

Inspection Item	Result	Remarks
Approved submittal and method statement on site	☐ Yes ☐ No	
Mock-up approved	☐ Yes ☐ No	
Substrate tests passed (strength, pull-off, moisture)	☐ Yes ☐ No	
Surface preparation approved	☐ Yes ☐ No	
Stage 1 — O-Filler applied and approved	☐ Yes ☐ No	
Stage 2 — Carboseal applied and approved	☐ Yes ☐ No	
Stage 3 — Safe Coat AC applied and approved	☐ Yes ☐ No	
Recoat windows respected	☐ Yes ☐ No	
Final tests passed	☐ Yes ☐ No	
Area protected and handed over	☐ Yes ☐ No	

Inspected by	Signature	Date

Appendix B — Daily Application Record

Date	Area / zone	Stage	Batch No.	Qty used	Air / substrate °C	RH %	Sign

Construction Chemicals

O-Filler Data Sheet

O MIX Safecoat — Submittal Document

Construction Chemicals

Product Datasheet
Edition: 01 | Date: Nov 2026
Flooring



O-Filler

Polymer-Modified Cementitious Filler & Skim Coat

Product Description

O-Filler is a high-performance, non-shrink, polymer-modified cementitious powder with a reactive resin matrix. Mixed with water, it levels and finishes exposed concrete, plaster and blockwork and fills voids and hairline cracks, inside and outside, on dry or damp surfaces.

Uses

- Levelling and finishing exposed concrete.
- Skim coating plaster and blockwork.
- Filling voids, blowholes and hairline cracks.
- Interior and exterior surfaces.
- Base layer before paints and coatings.

Advantages

- Non-shrink, smooth finish.
- Can be applied on dry or damp surfaces.
- Interior and exterior use.
- Compressive strength 30 N/mm².
- Single component — just add water.

Application

1. **Surface Preparation**
   Remove dust, oil and loose material. Pre-wet absorbent surfaces.
2. **Mixing**
   Add 20 kg powder to 3.5 – 4 L clean water and mix to a smooth paste.
3. **Application**
   Apply with a steel trowel: 0.5 – 1 cm coarse or 1 – 5 mm fine layers.

Consumption

0.5 – 1.0 kg/m²
as skim coat (approx. 0.3 – 0.5 mm)
Approx. 1.8 kg/m² per mm for thicker layers.

Packaging

20 kg bags.

Storage & Shelf Life

12 months in original, unopened bags. Store dry, off the ground, protected from moisture.

Technical Data

Typical values at 25 °C

Property	Typical Value	Test Method
Form	Grey powder	—
Mixing water	3.5 – 4.0 L per 20 kg bag	—
Specific gravity (mixed)	1.8	—
Pot life	30 – 40 min	—
Layer thickness	1 – 5 mm fine / 5 – 10 mm coarse	—
Compressive strength (28 days)	30 N/mm²	—
Bond strength	0.33 N/mm²	ASTM C321
Minimum application temperature	+5 °C	—

Consumption

Application	Thickness	Consumption
Skim coat	0.3 – 0.5 mm	0.5 – 1.0 kg/m²
Fine finish	1 – 5 mm	approx. 1.8 kg/m² per mm
Coarse levelling	5 – 10 mm	approx. 1.8 kg/m² per mm

Consumption is theoretical and varies with substrate porosity, profile and application method.

Application Conditions

- Ambient and substrate temperature: +5 °C to +35 °C.
- Do not apply on frozen surfaces or in direct strong sun.
- Protect fresh layers from rapid drying.

Application Notes

- Add the powder gradually to the water while mixing with a slow-speed mixer.
- Mix 3 minutes to a lump-free paste; rest 2 minutes and remix.
- Apply in thin layers; allow each layer to set before the next.
- Do not add extra water once mixed.

Health & Safety

- Contains cement: alkaline when wet. Wear gloves and goggles.
- Avoid dust inhalation; wear a dust mask when mixing.

First Aid & Cleaning

- Eyes: rinse with clean water for 15 minutes and seek medical advice.
- Skin: wash with soap and water.
- Clean tools with water before the material sets.

The information in this datasheet is based on laboratory tests and practical experience and is given in good faith. Users should verify product suitability for their specific application. O MIX reserves the right to update this information without prior notice.

Construction Chemicals

Carboseal Data Sheet

O MIX Safecoat — Submittal Document

Construction Chemicals

Product Datasheet
Edition: 01 | Date: Nov 2026
Decorative Paints

Carboseal

Acrylic Sealer
Primer for Paints & Coatings



Product Description

Carboseal is a water-based acrylic sealer used as a primer before paints and coatings. It reduces surface absorption and paint consumption and improves adhesion on concrete, plaster, gypsum and brick, interior and exterior.

Uses

- Primer on concrete and plaster.
- Primer on gypsum and brick.
- Sealer in the Safecoat system.
- Interior and exterior use.

Advantages

- Reduces absorption.
- Improves paint adhesion.
- Reduces paint consumption.
- Water-based; dilutable.
- Overcoat after 2 – 4 hours.

Application

1. **Surface Preparation**
   Clean, dry, dust-free substrate.
2. **Mixing**
   Dilute up to 1 : 1 with water as recommended for the substrate.
3. **Application**
   Apply one coat by brush or roller; paint after 2 – 4 hours.

Consumption

0.10 – 0.15 kg/m²
one coat

Packaging

4 kg and 20 kg pails.

Storage & Shelf Life

12 months in original, unopened packaging. Store dry at +5 °C to +35 °C, away from direct sunlight.

Technical Data

Typical values at 25 °C

Property	Typical Value	Test Method
Appearance	Milky white	—
Specific gravity	1.00 – 1.05	—
Solids content	12 – 18 %	—
pH	7 – 9	—
Touch dry	30 – 60 minutes	—
Overcoat	2 – 4 hours	—
Dilution	up to 1 : 1 with water	—
Shelf life	12 months	—

Consumption

Substrate	Consumption
Plaster / gypsum	0.10 – 0.15 kg/m²
Concrete / brick	0.10 – 0.15 kg/m²

Consumption is theoretical and varies with substrate porosity, profile and application method.

Application Conditions

- Ambient and substrate temperature: +10 °C to +35 °C.
- Substrate at least 3 °C above dew point.
- Relative humidity: max. 85 %.

Application Notes

- Dilute according to absorbency.
- Apply one uniform coat.
- Paint after 2 – 4 hours.

Health & Safety

- Wear gloves and safety goggles.
- Avoid contact with eyes and prolonged skin contact.
- Ensure ventilation in enclosed areas; use a mask for spray application.

First Aid & Cleaning

- Eyes: rinse with clean water for 15 minutes and seek medical advice.
- Skin: wash with soap and water.
- Inhalation: move to fresh air.
- Ingestion: rinse mouth and seek medical advice.
- Clean tools with water immediately after use.

The information in this datasheet is based on laboratory tests and practical experience and is given in good faith. Users should verify product suitability for their specific application. O MIX reserves the right to update this information without prior notice.

Construction Chemicals

Safe Coat AC Data Sheet

O MIX Safecoat — Submittal Document

Construction Chemicals

Product Datasheet
Edition: 01 | Date: Nov 2026
Protective Coating

Safe Coat AC

Water-Based Anti-Microbial Coating for Hygienic Areas



Product Description

Safe Coat AC is a water-based anti-microbial coating for walls and ceilings in hygienic environments. It resists bacteria, fungi, mild acids and alkalis and common disinfectants, and gives a satin, easy-to-clean finish. Low VOC.

Uses

- Clean rooms.
- Hospitals and laboratories.
- Pharmaceutical plants.
- Food processing areas.

Advantages

- Resists bacteria and fungi.
- Resists disinfectants and mild chemicals.
- Easy to clean, satin finish.
- Water-based, low VOC.
- Top coat of the O MIX Safecoat system.

Application

1. **Surface Preparation**
   Fill with O-Filler and seal with Carboseal.
2. **Mixing**
   Stir thoroughly; use as supplied.
3. **Application**
   Apply 2 coats by brush, roller or airless spray, 4 – 6 hours apart.

Consumption

0.12 – 0.15 kg/m²
per coat (8 – 10 m²/L)
Two coats recommended.

Packaging

5 kg and 20 kg pails.

Storage & Shelf Life

12 months in original, unopened packaging. Store dry at +5 °C to +35 °C, away from direct sunlight.

Technical Data

Typical values at 25 °C

Property	Typical Value	Test Method
Base	Water-based acrylic, anti-microbial	—
Finish / colour	Satin to semi-gloss, white	—
Density	1.2 – 1.4 kg/L	—
Solids content	45 – 55 %	—
Touch dry	1 – 2 hours	—
Recoat	4 – 6 hours	—
Coverage	8 – 10 m²/L	—
Shelf life	12 months	—

Consumption

Layer	Product	Consumption
Filler	O-Filler	0.25 kg/m²
Sealer	Carboseal	0.1 – 0.15 kg/m²
Top coat (2 coats)	Safe Coat AC	0.12 – 0.15 kg/m² per coat

Consumption is theoretical and varies with substrate porosity, profile and application method.

Application Conditions

- Ambient and substrate temperature: +10 °C to +35 °C.
- Substrate at least 3 °C above dew point.
- Relative humidity: max. 85 %.

Application Notes

- Apply over a sealed substrate.
- Apply 2 coats.
- Allow full drying before cleaning with disinfectants.
- Do not thin more than recommended.

Health & Safety

- Wear gloves and safety goggles.
- Avoid contact with eyes and prolonged skin contact.
- Ensure ventilation in enclosed areas; use a mask for spray application.

First Aid & Cleaning

- Eyes: rinse with clean water for 15 minutes and seek medical advice.
- Skin: wash with soap and water.
- Inhalation: move to fresh air.
- Ingestion: rinse mouth and seek medical advice.
- Clean tools with water immediately after use.

The information in this datasheet is based on laboratory tests and practical experience and is given in good faith. Users should verify product suitability for their specific application. O MIX reserves the right to update this information without prior notice.

Construction Chemicals

Test Reports

O MIX Safecoat — Submittal Document

To be attached: laboratory test reports supporting the values in the Technical Data Sheets.

Construction Chemicals

Approvals & Certificates

O MIX Safecoat — Submittal Document

To be attached: approvals and certificates, where available.