Construction Chemicals

Product Datasheet
Edition: 01 | Date: Nov 2026
Waterproofing

Waterbar

PVC Waterstop for Construction & Expansion Joints in Concrete



Product Description

Waterbar is a range of flexible PVC waterstops cast into concrete to seal construction and expansion joints against water penetration. It is supplied as centre-placed (Centerstop) and externally-placed (Outerstop) profiles, with or without a centre bulb, and is joined on site by heat welding. Prefabricated T, L and cross junctions are available.

Uses

- Water tanks and reservoirs.
- Dams, channels and culverts.
- Swimming pools.
- Basements and foundations.
- Tunnels and retaining walls.

Advantages

- Reliable watertight seal in concrete joints.
- Accommodates joint movement up to 10 mm.
- Resists water pressure up to 50 m head.
- Resistant to water, soil and mild chemicals.
- Easily heat-welded on site; prefabricated junctions.

Application

1. **Positioning**
   Fix the waterstop centrally in the joint (Centerstop) or on the formwork face (Outerstop), with half the width in each pour.
2. **Fixing & Jointing**
   Secure to reinforcement with tie wire through the edge holes or clips; heat-weld all joints and use prefabricated junctions.
3. **Concreting**
   Place and compact concrete carefully around the waterstop without displacing or folding it.

Consumption

1 m per 1 m of joint
plus overlap and welding allowance
Use prefabricated T, L and cross pieces at junctions.

Packaging

Rolls of 15 m, 20 m, 25 m or 30 m depending on profile.

Storage & Shelf Life

12 months in original packaging. Store rolls flat in a dry, shaded place away from direct sunlight, heat and oil.

Technical Data

Typical values at 25 °C

Property	Typical Value	Test Method
Material	Flexible PVC	—
Hardness	> Shore A 65	—
Tensile strength	≥ 12 MPa	—
Elongation at break	≥ 300 %	—
Brittleness temperature	< -38 °C	—
Water pressure resistance	up to 50 m head	—
Joint movement	up to 10 mm	—
Colours	Blue, black, yellow, grey	—
Shelf life	12 months	—

Consumption

Profile	Head	Width / Thickness	Roll
V-20 Centerstop — construction joint	10 m	20 cm / 3 mm	30 m
V-24 Centerstop — construction joint	15 m	24 cm / 3 mm	30 m
V-30 Centerstop — construction joint	25 m	30 cm / 4 mm	30 m
O-20 Centerstop with bulb — expansion	10 m	20 cm / 3.5 mm	15 m
O-24 Centerstop with bulb — expansion	25 m	24 cm / 3.5 mm	15 m
AR-25 / DR-25 Outerstop	—	26 cm / 5 mm	—

Consumption is theoretical and varies with substrate porosity, profile and application method.

Application Conditions

- Select bulb profiles for expansion joints and plain/ribbed profiles for construction joints.
- Embed half of the waterstop width in each concrete pour.
- Concrete cover and member thickness must allow full embedment of the profile.
- Heat-weld joints with a thermostatically controlled welding blade; do not lap or glue.
- Keep the waterstop clean and free of concrete laitance, oil and mud before the second pour.

Application Notes

- Fix at maximum 300 mm centres along both edges to prevent displacement.
- Use prefabricated T, L and cross junctions with 25 – 30 cm legs.
- Outerstop profiles: cut the notch of the bulb type to keep the barrier continuous at expansion joints.
- Inspect all welds visually before concreting.
- Protect exposed waterstop from damage and UV until the second pour.

Health & Safety

- Wear gloves and safety glasses when cutting and welding.
- Fumes from overheating PVC are irritant; avoid overheating and ensure ventilation.
- Follow site safety rules for work in excavations and on formwork.

First Aid & Cleaning

- Burns from welding blade: cool with clean water and seek medical advice.
- Eyes: rinse with clean water.
- Inhalation of welding fumes: move to fresh air.
- Clean the welding blade with a dry cloth while warm; remove concrete splashes from the waterstop with water before they set.

The information in this datasheet is based on laboratory tests and practical experience and is given in good faith. Users should verify product suitability for their specific application. O MIX reserves the right to update this information without prior notice.