Construction Chemicals

Product Datasheet
Edition: 01 | Date: Nov 2026
Protective Coating

Safe Coat AC

Water-Based Anti-Microbial Coating for Hygienic Areas



Product Description

Safe Coat AC is a water-based anti-microbial coating for walls and ceilings in hygienic environments. It resists bacteria, fungi, mild acids and alkalis and common disinfectants, and gives a satin, easy-to-clean finish. Low VOC.

Uses

- Clean rooms.
- Hospitals and laboratories.
- Pharmaceutical plants.
- Food processing areas.

Advantages

- Resists bacteria and fungi.
- Resists disinfectants and mild chemicals.
- Easy to clean, satin finish.
- Water-based, low VOC.
- Top coat of the O MIX Safecoat system.

Application

1. **Surface Preparation**
   Fill with O-Filler and seal with Carboseal.
2. **Mixing**
   Stir thoroughly; use as supplied.
3. **Application**
   Apply 2 coats by brush, roller or airless spray, 4 – 6 hours apart.

Consumption

0.12 – 0.15 kg/m²
per coat (8 – 10 m²/L)
Two coats recommended.

Packaging

5 kg and 20 kg pails.

Storage & Shelf Life

12 months in original, unopened packaging. Store dry at +5 °C to +35 °C, away from direct sunlight.

Technical Data

Typical values at 25 °C

Property	Typical Value	Test Method
Base	Water-based acrylic, anti-microbial	—
Finish / colour	Satin to semi-gloss, white	—
Density	1.2 – 1.4 kg/L	—
Solids content	45 – 55 %	—
Touch dry	1 – 2 hours	—
Recoat	4 – 6 hours	—
Coverage	8 – 10 m²/L	—
Shelf life	12 months	—

Consumption

Layer	Product	Consumption
Filler	O-Filler	0.25 kg/m²
Sealer	Carboseal	0.1 – 0.15 kg/m²
Top coat (2 coats)	Safe Coat AC	0.12 – 0.15 kg/m² per coat

Consumption is theoretical and varies with substrate porosity, profile and application method.

Application Conditions

- Ambient and substrate temperature: +10 °C to +35 °C.
- Substrate at least 3 °C above dew point.
- Relative humidity: max. 85 %.

Application Notes

- Apply over a sealed substrate.
- Apply 2 coats.
- Allow full drying before cleaning with disinfectants.
- Do not thin more than recommended.

Health & Safety

- Wear gloves and safety goggles.
- Avoid contact with eyes and prolonged skin contact.
- Ensure ventilation in enclosed areas; use a mask for spray application.

First Aid & Cleaning

- Eyes: rinse with clean water for 15 minutes and seek medical advice.
- Skin: wash with soap and water.
- Inhalation: move to fresh air.
- Ingestion: rinse mouth and seek medical advice.
- Clean tools with water immediately after use.

The information in this datasheet is based on laboratory tests and practical experience and is given in good faith. Users should verify product suitability for their specific application. O MIX reserves the right to update this information without prior notice.