Construction Chemicals

Product Datasheet
Edition: 01 | Date: Nov 2026
Decorative Paints

Carbomix AC Max

Crack-Bridging Anti-Carbonation & Anti-Chloride Coating



Product Description

Carbomix AC Max is a solvent-free acrylic copolymer coating that protects concrete against carbonation and chloride ingress and bridges cracks up to 0.5 mm. It is suitable for concrete and steel in marine and coastal structures.

Uses

- Marine and coastal structures.
- Bridges and car parks.
- Façades with fine cracks.
- Concrete and steel elements.

Advantages

- CO_2 barrier: Sd > 100 m.
- Bridges cracks up to 0.5 mm.
- Breathable (Class I).
- Protects against chlorides.
- Solvent-free.

Application

1. **Surface Preparation**
   Clean, sound concrete; repair defects.
2. **Mixing**
   Stir well before use.
3. **Application**
   Apply 2 coats by brush, roller or spray.

Consumption

0.20 – 0.30 kg/m²
per coat (2 coats)

Packaging

20 kg pails.

Storage & Shelf Life

12 months in original, unopened packaging. Store dry at +5 °C to +35 °C, away from direct sunlight.

Technical Data

Typical values at 25 °C

Property	Typical Value	Test Method
Base	Solvent-free acrylic copolymer	—
Solids content	60 – 70 %	—
Elongation	> 150 %	—
Crack bridging	up to 0.5 mm	—
CO_2 diffusion resistance (Sd)	> 100 m	—
Water vapour permeability	Class I	—

Consumption

Coat	Consumption
Each of 2 coats	0.20 – 0.30 kg/m²

Consumption is theoretical and varies with substrate porosity, profile and application method.

Application Conditions

- Ambient and substrate temperature: +10 °C to +35 °C.
- Substrate at least 3 °C above dew point.
- Relative humidity: max. 85 %.

Application Notes

- Apply 2 coats.
- Increase thickness over cracks.
- Do not apply in rain or on wet surfaces.

Health & Safety

- Wear gloves and safety goggles.
- Avoid contact with eyes and prolonged skin contact.
- Ensure ventilation in enclosed areas; use a mask for spray application.

First Aid & Cleaning

- Eyes: rinse with clean water for 15 minutes and seek medical advice.
- Skin: wash with soap and water.
- Inhalation: move to fresh air.
- Ingestion: rinse mouth and seek medical advice.
- Clean tools with water immediately after use.

The information in this datasheet is based on laboratory tests and practical experience and is given in good faith. Users should verify product suitability for their specific application. O MIX reserves the right to update this information without prior notice.