Construction Chemicals

Product Datasheet
Edition: 01 | Date: Nov 2026
Decorative Paints

Carboseal

Acrylic Sealer
Primer for Paints & Coatings



Product Description

Carboseal is a water-based acrylic sealer used as a primer before paints and coatings. It reduces surface absorption and paint consumption and improves adhesion on concrete, plaster, gypsum and brick, interior and exterior.

Uses

- Primer on concrete and plaster.
- Primer on gypsum and brick.
- Sealer in the Safecoat system.
- Interior and exterior use.

Advantages

- Reduces absorption.
- Improves paint adhesion.
- Reduces paint consumption.
- Water-based; dilutable.
- Overcoat after 2 – 4 hours.

Application

1. **Surface Preparation**
   Clean, dry, dust-free substrate.
2. **Mixing**
   Dilute up to 1 : 1 with water as recommended for the substrate.
3. **Application**
   Apply one coat by brush or roller; paint after 2 – 4 hours.

Consumption

0.10 – 0.15 kg/m²
one coat

Packaging

4 kg and 20 kg pails.

Storage & Shelf Life

12 months in original, unopened packaging. Store dry at +5 °C to +35 °C, away from direct sunlight.

Technical Data

Typical values at 25 °C

Property	Typical Value	Test Method
Appearance	Milky white	—
Specific gravity	1.00 – 1.05	—
Solids content	12 – 18 %	—
pH	7 – 9	—
Touch dry	30 – 60 minutes	—
Overcoat	2 – 4 hours	—
Dilution	up to 1 : 1 with water	—
Shelf life	12 months	—

Consumption

Substrate	Consumption
Plaster / gypsum	0.10 – 0.15 kg/m²
Concrete / brick	0.10 – 0.15 kg/m²

Consumption is theoretical and varies with substrate porosity, profile and application method.

Application Conditions

- Ambient and substrate temperature: +10 °C to +35 °C.
- Substrate at least 3 °C above dew point.
- Relative humidity: max. 85 %.

Application Notes

- Dilute according to absorbency.
- Apply one uniform coat.
- Paint after 2 – 4 hours.

Health & Safety

- Wear gloves and safety goggles.
- Avoid contact with eyes and prolonged skin contact.
- Ensure ventilation in enclosed areas; use a mask for spray application.

First Aid & Cleaning

- Eyes: rinse with clean water for 15 minutes and seek medical advice.
- Skin: wash with soap and water.
- Inhalation: move to fresh air.
- Ingestion: rinse mouth and seek medical advice.
- Clean tools with water immediately after use.

The information in this datasheet is based on laboratory tests and practical experience and is given in good faith. Users should verify product suitability for their specific application. O MIX reserves the right to update this information without prior notice.