Construction Chemicals

Product Datasheet
Edition: 01 | Date: Nov 2026
Flooring



O-Mix LH

Water-Based Copolymer
Sand Stabiliser & Dust Control

Product Description

O-Mix LH is a water-based copolymer liquid for sand stabilisation and dust control. It bonds to the pore walls of soil and sand and forms a clear, water-resistant crust. It is solvent-free, does not leach into the soil and is diluted with water.

Uses

- Dust control and sand-drift control.
- Slopes and construction sites.
- Coal and ore stockpiles.
- Oil and gas sites.
- Roads, railways, solar plants and perimeters.

Advantages

- Forms a water-resistant crust.
- Solvent-free, water-dilutable.
- Clear; keeps natural appearance.
- Stabilises sand and slopes.
- Suitable for open sites.

Application

1. **Preparation**
   Level the area and remove debris; moisten very dry sand lightly.
2. **Dilution**
   Dilute with water as recommended for the required crust.
3. **Application**
   Spray evenly at 1 – 2 L/m² for a 2 cm crust.

Consumption

1 – 2 L/m²
for an approx. 2 cm crust
Rate and dilution depend on soil type.

Packaging

230 L drums and bulk tanks.

Storage & Shelf Life

12 months in original, unopened packaging.
Store dry at +5 °C to +35 °C, away from direct sunlight.

Technical Data

Typical values at 25 °C

Property	Typical Value	Test Method
Base	Water-based copolymer	—
Appearance	White viscous liquid	—
Solids content	49 %	—
Specific gravity	1.03	—
Glass transition temperature	22 °C	—
pH	7 – 8	—
Viscosity	10,000 mPa·s	—
Shelf life	12 months	—

Consumption

Use	Application rate
Dust control (thin crust)	approx. 1 L/m²
Sand stabilisation (2 cm crust)	1 – 2 L/m²

Consumption is theoretical and varies with substrate porosity, profile and application method.

Application Conditions

- Ambient temperature: +5 °C to +40 °C.
- No rain expected within 24 hours.
- Area levelled and free of debris.

Application Notes

- Dilute with clean water as recommended.
- Spray in even passes.
- Do not apply when rain is expected within 24 hours.
- Avoid traffic until the crust has formed.

Health & Safety

- Wear gloves and safety goggles.
- Avoid contact with eyes and prolonged skin contact.
- Ensure ventilation in enclosed areas; use a mask for spray application.

First Aid & Cleaning

- Eyes: rinse with clean water for 15 minutes and seek medical advice.
- Skin: wash with soap and water.
- Inhalation: move to fresh air.
- Ingestion: rinse mouth and seek medical advice.
- Clean tools with water immediately after use.

The information in this datasheet is based on laboratory tests and practical experience and is given in good faith. Users should verify product suitability for their specific application. O MIX reserves the right to update this information without prior notice.