Construction Chemicals

Product Datasheet
Edition: 01 | Date: Nov 2026
Flooring



Road Mark WB

Water-Based Acrylic
Road Marking Paint

Product Description

Road Mark WB is a water-based acrylic road marking paint with reflective mineral content. It resists abrasion, weathering and UV, serves as a base for reflective glass beads, and is used as the first layer under anti-skid systems.

Uses

- Road and parking markings.
- Car parks and warehouses.
- Brick, concrete, stone and asphalt surfaces.
- First layer under anti-skid systems.

Advantages

- Abrasion and weather resistant.
- UV resistant.
- Base for reflective glass beads (Beadmix).
- Water-based.
- Range of colours.

Application

1. **Surface Preparation**
   Clean, dry, dust- and oil-free surface.
2. **Mixing**
   Stir well; use undiluted.
3. **Application**
   Apply 2 – 3 coats; broadcast Beadmix into the wet final coat where required.

Consumption

0.75 kg/m²
per coat (DFT 250 µm)
2 – 3 coats.

Packaging

5 kg and 25 kg pails.

Storage & Shelf Life

12 months in original, unopened packaging. Store dry at +5 °C to +35 °C, away from direct sunlight.

Technical Data

Typical values at 25 °C

Property	Typical Value	Test Method
Base	Water-based acrylic	—
Density	1.2 – 1.3 kg/L	—
Solids content	48 – 52 %	—
Touch dry	2 hours	—
Dry	24 hours	—
Full cure	3 days	—
DFT per coat	250 µm	—

Consumption

Use	Consumption
Each coat (250 µm DFT)	0.75 kg/m²

Consumption is theoretical and varies with substrate porosity, profile and application method.

Application Conditions

- Ambient and substrate temperature: +10 °C to +35 °C.
- Substrate at least 3 °C above dew point.
- Relative humidity: max. 85 %.

Application Notes

- Use undiluted.
- Apply 2 – 3 coats.
- Broadcast Beadmix glass beads into the wet coat for reflectivity.
- Allow 3 days before heavy traffic.

Health & Safety

- Wear gloves and safety goggles.
- Avoid contact with eyes and prolonged skin contact.
- Ensure ventilation in enclosed areas; use a mask for spray application.

First Aid & Cleaning

- Eyes: rinse with clean water for 15 minutes and seek medical advice.
- Skin: wash with soap and water.
- Inhalation: move to fresh air.
- Ingestion: rinse mouth and seek medical advice.
- Clean tools with water immediately after use.

The information in this datasheet is based on laboratory tests and practical experience and is given in good faith. Users should verify product suitability for their specific application. O MIX reserves the right to update this information without prior notice.