Construction Chemicals

Product Datasheet
Edition: 01 | Date: Nov 2026
Repair and Grouting Materials

Cemix Grout

High-Flow Non-Shrink
Cementitious Grout



Product Description

Cemix Grout is a high-flow, non-shrink cement-based grout for precision grouting under machine bases, column base plates and bridge bearings, and for anchoring bolts.

Uses

- Machine bases.
- Column base plates.
- Anchor bolts.
- Bridge bearings.
- Voids under steel structures.

Advantages

- High flow: 20 – 30 s.
- Non-shrink.
- 28-day strength ≥ 70 MPa.
- 1-day strength ≥ 25 MPa.
- Just add water.

Application

1. **Surface Preparation**
   Clean, roughen and pre-wet to SSD; seal formwork.
2. **Mixing**
   Add 12 – 15 % water and mix 3 – 5 minutes.
3. **Placing**
   Pour from one side continuously to avoid air entrapment.

Consumption

13 – 15 L
yield per 25 kg bag

Packaging

25 kg bags.

Storage & Shelf Life

12 months in original, unopened packaging. Store dry at +5 °C to +35 °C, away from direct sunlight.

Technical Data

Typical values at 25 °C

Property	Typical Value	Test Method
Water demand	12 – 15 %	—
Density	2.2 kg/L	—
Flow	20 – 30 seconds	—
Setting time	4 – 6 hours	—
Compressive strength, 1 day	≥ 25 MPa	—
Compressive strength, 7 days	≥ 50 MPa	—
Compressive strength, 28 days	≥ 70 MPa	—

Consumption

Item	Value
Yield per 25 kg bag	13 – 15 L
Bags per m³	approx. 70

Consumption is theoretical and varies with substrate porosity, profile and application method.

Application Conditions

- Application temperature: +5 °C to +40 °C.
- Substrate pre-wetted to SSD.

Application Notes

- Pour from one side only.
- Do not vibrate.
- Cure exposed surfaces immediately.

Health & Safety

- Wear gloves, safety goggles and a dust mask when mixing.
- Contains cement; alkaline when wet. Avoid skin and eye contact.
- Avoid inhaling dust.

First Aid & Cleaning

- Eyes: rinse immediately with plenty of clean water for at least 15 minutes and seek medical advice.
- Skin: wash with soap and water; cement is alkaline when wet.
- Inhalation of dust: move to fresh air.
- Ingestion: rinse mouth and seek medical advice.
- Clean tools and mixers with water immediately after use.

The information in this datasheet is based on laboratory tests and practical experience and is given in good faith. Users should verify product suitability for their specific application. O MIX reserves the right to update this information without prior notice.